

ACCELERATOR DESIGN EDUCATIONAL PRIMER – CONCEPTUALIZING AND OPTIMIZING THE HYBRID LHEC-LIKE ELECTRON-ION COLLIDER DESIGN*

A. Seryi[†], L. van Riesen-Haupt, Old Dominion University, A. Formenti, A. Huebl, R. Lehe,
Ch. Mitchell, Ji Qiang, J.-L. Vay, E. Zoni, Lawrence Berkeley National Laboratory, United States
C. A. Lindstrøm, University of Oslo, Oslo, Norway

T. Pieloni, L. Vanhecke, École Polytechnique Fédérale de Lausanne, Lausanne, Switzerland

Abstract

The Electron-Ion Collider (EIC) Mission Need requires $\sqrt{s} = 20\text{--}100$ GeV (upgradable to 140 GeV) and luminosity $10^{33}\text{--}10^{34}$ cm⁻² s⁻¹. The current ring-ring baseline achieves the full scope, including $\sim 10^{34}$ cm⁻² s⁻¹ across all energies. However, when the design is re-optimized for the lower boundary — accepting 10^{33} cm⁻² s⁻¹ and prioritizing cost — an alternative configuration emerges as more advantageous: a hybrid LHeC-like electron accelerator using multi-pass energy recovery linacs (ERL). This solution reduces electron-beam power by roughly an order of magnitude, yielding nearly a factor of two reduction in total project cost compared with the present baseline while still satisfying the minimum physics requirements. The study performs parametric cost and performance modeling, augmented by AI-driven optimization, to explore this design space. Serving primarily as an educational exercise for the next generation of accelerator physicists and engineers, the paper demonstrates modern design methods: rapid parametric scans, cost-driven optimization, and integration of AI tools. It examines technical feasibility, identifies critical R&D (high-current ERL operation, beam-beam effects, synchronization, etc.), and discusses how such re-optimization studies can be used to train designers in an era when artificial intelligence dramatically expands exploration of complex accelerator parameter spaces.

PREAMBLE – AI AND EDUCATION

The emergence of AI-assisted coding presents both unique challenges and unprecedented opportunities for accelerator physics education. Institutions like Fermilab (USPAS) and CERN (CAS) need to rapidly adapt their pedagogical approaches, and the Genesis program [1] in the US further encourages AI for accelerated accelerator design. A natural vehicle for developing design skills is the focused mini-project such as [2, 3], where students tackle a realistic challenge in a short intensive period. This paper rehearses what such a mini-project looks like when AI tools are available at every stage — from parameter optimization and code generation to cost estimation — serving as a draft script for a future AI-assisted USPAS course.

* Parameters of the presented concepts were developed with assistance from Grok AI and Claude AI.

[†] aseryi@odu.edu

EIC-LHEC MINI-PROJECT

The mini-project assignment is: *Given the EIC proton beam stored in the RHIC-derived Hadron Storage Ring, design the simplest and most cost-effective electron accelerator complex satisfying the EIC CD0 Mission Need lower boundary — $\sqrt{s} \approx 29\text{--}100$ GeV and $\mathcal{L} \sim 10^{33}$ cm⁻² s⁻¹ — and estimate its cost relative to the ring-ring baseline.*




Figure 1: Schematic layout of the EIC built as an LHeC-like hybrid with energy recovery.

The motivation comes from the ESPP Open Symposium [4], where it was argued that inserting a new electron ring into the LHC tunnel for LHeC would be cost-prohibitive and luminosity-limiting [5]. This prompted the question: could replacing the EIC electron storage ring with a superconducting energy-recovery linac (ERL) yield a similar cost-performance advantage? The proposed hybrid keeps the full EIC proton infrastructure intact and replaces the electron ring with a multi-pass ERL: electrons are accelerated in a superconducting RF (SRF) linac, recirculated through arcs, brought to collision, and then decelerated back through the linac for energy recovery. Key advantages over the ring-ring baseline are: electron beam power reduced by $\sim 10\times$ (each bunch used once, so large IP disruption is acceptable); no large electron storage ring, substantially reducing civil

and magnet costs; and a 6 GeV linac traversed three times covering the full 18 GeV EIC energy range.

The layout is shown in Fig. 1: the ERL linac is installed in a new tunnel in the South-West portion¹ of the RHIC inner area, with recirculation arcs routed through new arc tunnels, delivering the electron beam to the ePIC interaction region.

The mini-project proceeds through the following steps, each carried out with AI assistance (primarily Grok and Claude) and described in subsequent sections: beam parameter and luminosity modeling; beam-beam evaluation; IR optics and magnet technology assessment; energy recovery and recirculation analysis; cost estimation; and R&D identification. At each step, AI tools wrote Python scripts and draft text, while the “students” (here, the authors) formulated physically meaningful prompts and verified outputs against accelerator physics principles.

EIC-LHeC PARAMETERS

Approach and AI prompting strategy. The parameter development followed an iterative dialogue with AI tools, beginning from the two parent designs and converging on a self-consistent hybrid. The initial prompts requested Python codes to compute beam parameters, beam sizes at the IP, luminosity, and beam-beam tune shifts $\xi_{x,y}$ and RMS divergences for the standard EIC and LHeC designs separately, using published parameter tables [6, 7] as inputs. Details of prompts, outputs, and generated codes are available at [8].

Baseline EIC and LHeC reference parameters. Table 1 shows abridged parameter sets for the two parent designs; full tables are in [6, 7].

Table 1: Abridged LHeC Reference Parameters (Phase-1, 20 GeV e on 7 TeV p) and Baseline EIC (1×10^{34} Peak Luminosity, 10 GeV e on 275 GeV p) Parameters

Parameter	EIC	LHeC
e/p energy, GeV	10 / 275	20 / 7000
$\sqrt{s}$, GeV	105	749
Number of bunches	1160	2808
Collision frequency, Hz	9.1×10^7	3.2×10^7
e bunch population	1.72×10^{11}	1.19×10^{10}
p bunch population	6.9×10^{10}	2.2×10^{11}
e norm. emitt. h/v, μm	391 / 26	22 / 22
p norm. emitt. h/v μm	3.3 / 0.3	2.5 / 2.5
$e \beta_{x/y}^*$ at IP, m	0.45 / 0.06	0.2 / 0.2
$p \beta_{x/y}^*$ at IP, m	0.80 / 0.07	0.35 / 0.35
$e \sigma_{x/y}$ at IP, μm	94.8 / 8.6	10.6 / 10.6
$p \sigma_{x/y}$ at IP, μm	94.9 / 8.6	10.7 / 10.7
e/p beam current, mA	1555 / 1000	60.1 / 1110
p beam-beam $\xi_{x/y}$	0.012 / 0.012	0.001 / 0.001
Peak lumi. $\mathcal{L}$, $\text{cm}^{-2}\text{s}^{-1}$	1.05×10^{34}	5.78×10^{33}

Resolving parameter inconsistencies in the hybrid. When asked to combine EIC proton parameters with LHeC electron parameters, the AI correctly identified three fundamental conflicts before producing any code. (i) *Bunch*

rate mismatch: the EIC ring (3834 m circumference, 1160 bunches) gives a collision frequency of ~ 91 MHz, while the LHeC electron linac assumes ~ 32 MHz; naively combining the two implies ~ 1.45 A electron current, far beyond the 60 mA LHeC design value. (ii) *Beam size mismatch:* LHeC electron optics ($\beta_{x,y}^* = 0.20$ m, $\varepsilon_n = 22 \mu\text{m}$) were optimized for the $\sim 10 \mu\text{m}$ LHC proton beam, whereas EIC protons at 275 GeV give $\sigma_x \approx 173 \mu\text{m}$ at the same β^* . (iii) *Current limits:* maintaining $N_e \approx 1.19 \times 10^{10}$ at the EIC rate requires ~ 1.45 A; enforcing 60 mA instead would reduce N_e to $\sim 4 \times 10^9$. The resolution was to reduce the number of proton bunches by a factor of three (from 1160 to 386), proportionally increasing bunch population at constant 1.0 A proton current. This lowers the collision frequency to ~ 30 MHz, restoring a consistent ~ 58 mA electron current, and the IP optics were re-optimized to match beam sizes ($\beta_x^* = 1.20$ m, $\beta_y^* = 0.05$ m for electrons; $\beta_x^* = 0.12$ m, $\beta_y^* = 0.06$ m for protons). The AI also noted that ξ_e is unconstrained in a linac-ring scheme since electrons are discarded after each pass; only the proton beam-beam parameter was constrained to $\xi_p < 0.01$. A further step explored $\mathcal{L} = 10^{34} \text{ cm}^{-2}\text{s}^{-1}$ via: (i) proton emittance reduction through coherent electron cooling; and (ii) vertical electron emittance reduction by a factor of ten using a magnetized gun and Derbenev’s flat-beam transformer.

Hybrid EIC-LHeC parameter sets. Two configurations are given in Tables 2 and 3, both for $\sqrt{s} \approx 105$ GeV (10 GeV electrons, 275 GeV protons).

Table 2: Hybrid EIC-LHeC Parameters, Initial Configuration (Luminosity $\sim 2 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$)

Parameter	e	p	Unit
E	10.0	275.0	GeV
N	1.19×10^{10}	2.1×10^{11}	
n_{bunches}		386	
f_{collis}		3.0×10^7	Hz
Norm. ε h/v	22.0 / 22.0	3.3 / 0.3	μm
$\beta_{x/y}^*$ at IP	1.20 / 0.05	0.12 / 0.06	m
σ_z	3.0	70.0	mm
$\sigma_{x/y}$ at IP	36.7 / 7.5	36.8 / 7.8	μm
$\sigma'_{x/y}$ at IP	30.6 / 149.9	306.3 / 130.6	μrad
$\xi_{x/y}$	3.474 / 0.679	0.001 / 0.002	
I_{beam}	57.6	1000	mA
$\sigma_{x/y}^{\text{eff}}$ at IP	52.0 / 10.8		μm
Peak $\mathcal{L}$	2.1×10^{33}		$\text{cm}^{-2}\text{s}^{-1}$

The initial hybrid satisfies the CD0 lower boundary with unmodified EIC proton emittances; $\xi_p < 0.01$ in both configurations. The large electron ξ_e reflects severe single-pass disruption – acceptable since electrons are discarded after collision, but raising questions about ERL acceptance for the disrupted bunch (addressed in the *Energy recovery evaluations* section). The optimized case reaches $10^{34} \text{ cm}^{-2}\text{s}^{-1}$ through emittance reductions; proton divergences up to 182 μrad horizontally imply tight FD aperture requirements (see *IR optics evaluations*).

¹ Sited to avoid the Peconic River protected watershed boundary.

Table 3: Hybrid EIC-LHeC Parameters, Optimized Configuration ($1 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$, with e -cooling and flat-beam optics). Unchanged parameters as in Table 2.

Parameter	e	p	Unit
Norm. ε h/v	22.0 / 2.2	0.9 / 0.1	μm
$\beta_{x/y}^*$ at IP	0.25 / 0.10	0.09 / 0.05	m
$\sigma_{x/y}$ at IP	16.8 / 3.4	16.8 / 3.6	μm
$\sigma'_{x/y}$ at IP	66.8 / 32.7	182.4 / 77.8	μrad
$\xi_{x/y}$	3.474 / 6.789	0.003 / 0.007	
$\sigma_{x/y}^{eff}$ at IP	23.8 / 5.0		μm
Peak $\mathcal{L}$	1.0×10^{34}		$\text{cm}^{-2}\text{s}^{-1}$

BEAM-BEAM EVALUATIONS

Beam-beam collisions, highly asymmetrical for EIC hybrid, can be evaluated using existing codes, but can be also studied using vibe-coding generated code. A simplified 2D beam-beam code was written by Claude AI in a few minutes from a paragraph-long prompt – see the python code at [8] and beam-beam simulation illustration in Fig. 2.




Figure 2: Example of beam-beam collision calculated by the code produced via vibe-coding. Arbitrary units in axes.

The beam-beam simulation code was generated from a single paragraph-long prompt, reproduced here to illustrate the level of physical detail required to obtain useful AI-generated code. The prompt specified: a 2D head-on collision (longitudinal Z and vertical Y coordinates only); each bunch represented by 50 transverse slices of 21 particles, placed equidistantly along Z with spacing $dZ = 1$ and vertical particle separation $dY = 0.5$; zero initial transverse velocities; and a simplified model for the beam-beam force in which the vertical electric field acting on a particle at position Y_1 equals the number of particles of the opposing slice with $Y > Y_1$ minus those with $Y < Y_1$ – the thin-slab approximation appropriate when the horizontal extent of the bunch is much larger than its vertical size. The kick coefficient D_Y was requested to be tuned so that a particle undergoes approximately one betatron oscillation during the full collision. Visualization of the collision dynamics was requested from the outset. The AI (Claude) produced working, animated code on the first attempt. Five short follow-up prompts then corrected the kick sign, tuned D_Y , added offset collisions, and improved the visualization display. The entire exchange

– initial prompt plus five follow-up adjustments – took a few minutes and required no debugging of code syntax by the student. The prompt and the resulting python code are available at [8].

This capability suggests a transformative shift in how students learn. Rather than passively attending lectures or running decades-old legacy codes, students could actively create simplified simulation codes, then iteratively refine them through AI-assisted modifications to explore different physics phenomena.

For the specific example of EIC-LHeC hybrid mini-project, students could progressively enhance their understanding by first converting the code to use of physical units; then implementing realistic beam distributions with emittance and beta-functions; adjusting input parameters to match those of EIC-LHeC hybrid; adding luminosity calculations; investigating how luminosity depends on asymmetry of disruption parameters and beam offsets; measuring angular distribution of highly disrupted electron beam.

IR OPTICS EVALUATIONS

Describe process and prompts for generation of IR optics, beam envelopes, estimation of the collimation depth.

Text

Text

Include picture of IR optics

Text

Text

Text

Text

Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

IR MAGNETS EVALUATIONS

Describe process and prompts for evaluation of parameters and technological options for IR magnets, which will be determined need to be SC magnets, including discussion of Nb or Nb3Sn choices

Text

Text

Text

Text

Text

Text

Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

ENERGY RECOVERY EVALUATIONS

Describe process and prompts for evaluation of the energy recovery

Text

Text

Text
Text
Text
Text
Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

RECIRCULATION EVALUATIONS

Describe process and prompts for evaluation of recirculation

Text
Text
Text
Text
Text
Text
Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

INITIAL COST ESTIMATIONS

Cost estimates for the hybrid electron complex, IR, and detector were developed using AI-assisted parametric scaling from the LHeC study [9], excluding upgrades to proton infrastructure. Two linac configurations were compared: a single-pass 10 GeV SRF linac and a recirculating 6 GeV linac traversed twice (or three times for 18 GeV), analogous to CE-BAF and the LHeC design. The recirculating option halves the dominant SRF, civil, and cryo costs while adding modest arc costs (70 MCHF, 100 PY), saving ~62 MCHF and ~250 person-years (PY) overall – making it the preferred option. Estimated totals are: electron complex 278 MCHF (451 PY), IR 50 MCHF (50 PY), detector 250 MCHF (100 PY), giving a grand total of ~578 MCHF (601 PY). These figures were scaled with AI assistance and should be regarded as order-of-magnitude only; IR and detector line items were manually increased above the raw AI output.

Converting to USA DOE accounting (1 CHF = 1.25 USD; labor at 300k USD/PY; 60% contingency reflecting the preliminary nature of the estimate) yields the summary in Table 4. The total of ~1.4 B USD is approximately half the upper bound of the CD0-approved EIC cost range – a factor-of-two margin that justifies more detailed evaluation of the hybrid concept.

ADVANCED COST ESTIMATIONS

Describe process and prompts for advanced evaluation of the cost of EIC-LHeC accelerator

Will be written by Carl Andreas Lindstrøm later in April

This will be based on the cost modelling described both in the ESSPU HALHF backup document (<https://arxiv.org/pdf/2503.23489>) as well as an IPAC 2025 paper (<https://arxiv.org/pdf/2505.21654>). It will

Table 4: USA DOE Cost Accounting, EIC-LHeC Hybrid (Recirculating 6 GeV Linac)

Item	Value (MUSD)
Material costs ($578 \text{ MCHF} \times 1.25$)	722.2
Labor costs ($601 \text{ PY} \times 300\text{k USD}$)	180.5
Pre-contingency total	902.7
Contingency (60%)	541.6
Total with contingency	1444.3

also reference the code via the following link to the first, more crude cost optimization code (<https://github.com/carlandreaslindstrom/ColliderCostModel>); and to the up-to-date cost optimization code used in ABEL (https://github.com/abel-framework/ABEL/blob/main/abel/classes/cost_model.py).

Text

Text

Text

Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

REQUIRED R&D AND NEXT STEPS

The hybrid EIC-LHeC concept rests on several assumptions requiring dedicated R&D before the design can be considered credible at project-proposal level. The principal challenges, identified in dialogue with AI, are the following. *High-current ERL operation:* fractional energy loss $\lesssim 10^{-4}$ is required at 58 mA and 10 GeV; a staged program at CE-BAF (high energy, low current) and PERLE (low energy, high current) would bound the two critical parameters. *Polarized source current:* 58 mA far exceeds the state of the art (~1 mA CW); multiplexing N sources via RF mergers is a plausible path once 10 mA is demonstrated at Jefferson Lab. *IR final doublet:* small proton β^* (0.09–0.12 m) drives IP divergences of ~300 μrad , requiring large-aperture SC quadrupoles, tight collimation, and MDI compatibility with ePIC. *Intrabeam scattering:* the factor-of-three increase in proton bunch charge raises the IBS rate; electron cooling must maintain the emittances assumed in the 10^{34} configuration. *Disrupted-beam energy recovery:* with $\xi_y^e \approx 6.8$, the electron bunch is severely disrupted; whether the resulting phase space fits within ERL return-arc acceptance requires dedicated simulation.

Logical next steps are: beam-beam parameter scans with strong-strong codes; conceptual IR lattice and MDI design; ERL lattice and disrupted-beam acceptance study; IBS and cooling-power modeling; bottom-up cost re-estimation; and programmatic compatibility assessment with the EIC CD schedule. The hybrid concept illustrates how AI-assisted exploration can rapidly map an alternative design space and identify the critical questions – accelerating the early conceptual phase without replacing rigorous engineering analysis.

VERIFICATION OF AI RESULTS

Discuss how verification of AI results will be performed, and how it is connected with our believe that students will learn accelerator physics from such educational approach.

DRAFT FOR EVALUATION SECTION:

For instance, referring to the above mentioned beam-beam collision example, students could progressively enhance their understanding by making simulation more and more realistic, but most importantly...

Critically, students would develop diagnostic tests to verify that physics principles are correctly implemented – learning to validate AI-generated code against their understanding of the underlying physics.

This approach ensures that as we leverage AI tools, we continue developing human experts capable of designing and building the accelerators and colliders of tomorrow. The goal isn't to replace human expertise, but to accelerate its development while maintaining rigor and deep understanding.

Text

Text

Text

CONNECTION TO GENESIS PROGRAM

Discuss connection to Genesis program.

Text

Text

Text

Text

Text

Text

Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

SELF-ASSESSMENT AND NEXT STEPS

Discuss how we feel about the described approach, what is missing, where we are not sure, what are directions of future developments.

This section can be merged with Conclusion to save space

Text

Text

Text

(NOTE ON PAPER LENGTH: THIS IS INVITED POSTER, SO THE LIMIT IS 5 PAGES. REFERENCES CAN BE ON EXTRA PAGE.)

CONCLUSION

Write conclusion

Text

Text

Text

Text

Text

REFERENCES

- [1] Genesis – A National Mission to Accelerate Science Through Artificial Intelligence, <https://genesis.energy.gov/>
- [2] Compact Ring-Based X-Ray Source with on-Orbit and on-Energy Laser-Plasma Injection, TUA3CO03, NAPAC-2016, USPAS 2016 mini-project.
- [3] EUV FEL Light Source Based On Energy Recovery Linac With On-Orbit Laser Plasma Injection, MOPG66, IPAC 2024, USPAS 2023 mini-project.
- [4] The European Strategy for Particle Physics (ESPP) Open Symposium, July 2025 <https://agenda.infn.it/event/44943/>
- [5] Presentation of LHeC project at ESPP 2025, questions and answers: <https://youtu.be/NX1eYfol5JI?list=PLbsqUzxZ1cP5p4izedCWb7EOP-ZkSH495&t=2703>
- [6] A sample of EIC project parameters. https://eic.jlab.org/Documents/EIC-General/20250305-EIC_ParameterList.pdf
- [7] Phase-One LHeC submission to ESPP <https://indico.cern.ch/event/1439855/contributions/6461558/attachments/3045931/5381880/backup.pdf>
- [8] For EIC-LHeC vibe-coding prompts and codes, see <https://github.com/aseryi/vibe-coding/>, sub-folders EIC-LHeC and beam-beam
- [9] Bruning O., 2018 LHeC cost estimate report, CERN Geneva <https://cds.cern.ch/record/2652349/files/CERN-ACC-2018-0061.pdf>