```
     14 4.680920          128.119.245.12          192.168.1.102        HTTP      490    HTTP/1.1 200 OK  (text/html)
```

Frame 14: 490 bytes on wire (3920 bits), 490 bytes captured (3920 bits)
Ethernet II, Src: LinksysG_da:af:73 (00:06:25:da:af:73), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.102
Transmission Control Protocol, Src Port: 80, Dst Port: 4272, Seq: 4381, Ack: 502, Len: 436
[4 Reassembled TCP Segments (4816 bytes): #10(1460), #11(1460), #13(1460), #14(436)]
Hypertext Transfer Protocol
    HTTP/1.1 200 OK\r\n   14. status code and phrase
    Date: Tue, 23 Sep 2003 05:37:02 GMT\r\n
    Server: Apache/2.0.40 (Red Hat Linux)\r\n
    Last-Modified: Tue, 23 Sep 2003 05:37:01 GMT\r\n
    ETag: "1bff2-1194-96813940"\r\n
    Accept-Ranges: bytes\r\n
    Content-Length: 4500\r\n
    Keep-Alive: timeout=10, max=100\r\n
    Connection: Keep-Alive\r\n
    Content-Type: text/html; charset=ISO-8859-1\r\n
    \r\n
    [HTTP response 1/1]
    [Time since request: 0.057188000 seconds]
    [Request in frame: 8]
    File Data: 4500 bytes
Line-based text data: text/html