

Package ‘dfrr’

July 21, 2020

Type Package

Title Dichotomized Functional Response Regression

Version 0.1.0

Maintainer Fatemeh Asgari <ft.asgari@sci.ui.ac.ir>

Description Implementing Function-on-Scalar Regression model in which the response function is dichotomized and observed sparsely. This package provides smooth estimations of functional regression coefficients and principal components for the dfrr model.

License GPL-3

LazyData TRUE

Encoding UTF-8

Depends tmvtnorm,fda

Imports stats, MASS

Suggests ggplot2, plotly, car

VignetteBuilder knitr

URL <https://github.com/asgari-fatemeh/dfrr>

BugReports <https://github.com/asgari-fatemeh/dfrr/issues>

RoxygenNote 7.1.1

NeedsCompilation no

Author Fatemeh Asgari [aut, cre],
Saeed Hayati [aut, ctb]

R topics documented:

dfrr-package	2
basis	3
coef.dfrr	4
dfrr	5
fitted.dfrr	6
fpca	8
madras	9
model.matrix.dfrr	10
plot.coef.dfrr	10
plot.dfrr	11
plot.fitted.dfrr	11

plot.fPCA.dfrr	13
plot.predict.dfrr	14
plot.residuals.dfrr	15
predict.dfrr	16
residuals.dfrr	17
simulate.simple.dfrr	18

Index	20
--------------	-----------

dfrr-package	<i>dfrr: Dichotomized Functional Response Regression</i>
--------------	--

Description

Implementing Function-on-Scalar Regression model in which the response function is dichotomized and observed sparsely. This package provides smooth estimations of functional regression coefficients and principal components for the dfrr model.

Details

Implementing Function-on-Scalar Regression model in which the response function is dichotomized and observed sparsely. This package provides smooth estimations of functional regression coefficients and principal components for the dfrr model. The main function in the dfrr-package is `dfrr()`.

Author(s)

Maintainer: Fatemeh Asgari <ft.asgari@sci.ui.ac.ir>

Authors:

- Saeed Hayati <s.hayati@sci.ui.ac.ir> [contributor]

References

Fatemeh Asgari, Alamatsaz Mohammad Hossein, Hayati Saeed (2021). Dichotomized Functional Response Regression Model. <http://arxiv.org/adress_to_paper>

See Also

Useful links:

- <https://github.com/asgari-fatemeh/dfrr>
- Report bugs at <https://github.com/asgari-fatemeh/dfrr/issues>

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,M=M)

dfrr_fit<-dfrr(Y~X,yind=time)
```

```

coefs<-coef(dfrr_fit)
plot(coefs)

fitteds<-fitted(dfrr_fit)
plot(fitteds)

resids<-residuals(dfrr_fit)

eig<-fpca(dfrr_fit)
plot(eig,plot.contour=TRUE,plot.3d.surface = TRUE)

newdata<-data.frame(X=c(1,0))
preds<-predict(dfrr_fit,newdata=newdata)
plot(preds,conf.level = 0.9)

newdata<-data.frame(X=c(1,0))
preds<-predict(dfrr_fit,newdata=newdata)
plot(preds,conf.level = 0.9)

newdata<-data.frame(X=c(1,0))
newydata<-data.frame(.obs=rep(1,5),.index=c(0.0,0.1,0.2,0.3,0.7),.value=c(1,1,1,0,0))
preds<-predict(madras_dfrr,newdata=newdata,newydata = newydata)
plot(preds,conf.level = 0.9)

```

basis

*Get the basis functions from a dfrr-object***Description**

Returns the basis functions employed in fitting a dfrr-object.

Usage

```
basis(dfrr_fit)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).

Examples

```

set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
coefs<-coef(dfrr_fit,return.fourier.coefs=TRUE)

basis<-basis(dfrr_fit)
evaluated_coefs<-coefs\

```

```
#Plotting the regression coefficients
par(mfrow=c(1,2))
plot(time,evaluated_coefs[1,],l,main="Intercept")
plot(time,evaluated_coefs[2,],l,main="X")
```

coef.dfrr

Get estimated coefficients from a dfrr fit

Description

Returns estimations of the smooth functional regression coefficients $\beta(t)$. The result is a matrix of either Fourier coefficients or evaluations. See Details.

Usage

```
## S3 method for class dfrr
coef(
  dfrr_fit,
  standardized = NULL,
  unstandardized = !standardized,
  return.fourier.coefs = NULL,
  return.evaluations = !return.fourier.coefs,
  time_to_evaluate = NULL
)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).

standardized, unstandardized a boolean indicating whether stanadrized/unstandardized regression coefficients are reported. Only standardized regression coefficients are identifiable, thus the arugment is defaults to standardized=TRUE.

return.fourier.coefs, return.evaluations a boolean indicating whether the Fourier coefficients of regression coefficients are returned (return.fourier.coefs=TRUE), or evaluations of the regression coefficients (return.evaluations=TRUE). Defaults to return.fourier.coefs=TRUE.

time_to_evaluate a numeric vector indicating the set of time points for evaluating the fitted latent functions, for the case of return.evaluations=TRUE.

Details

This function will return either the Fourier coefficients or the evaluation of estimated coefficients. Fourier coefficients which are reported are based on the a set of basis which can be determined by [basis\(dfrr_fit\)](#). Thus the evaluation of regression coefficients on the set of time points specified by vector time, equals to `fitted(dfrr_fit)%*%t(eval.basis(time,basis(dfrr_fit)))`.

Consider that the unstandardized estimations are not identifiable. So, it is recommended to extract and report the standardized estimations.

See Also[plot.coef.dfrr](#)**Examples**

```

set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
coefs<-coef(dfrr_fit)
plot(coefs)

```

dfrr

*Dichotomized Functional Response Regression***Description**

Implementing Function-on-Scalar Regression model, in which the response function is dichotomized and observed sparsely.

Usage

```

dfrr(
  formula,
  yind = NULL,
  data = NULL,
  ydata = NULL,
  method = c("REML", "ML"),
  rangeval = NULL,
  basis = NULL,
  times_to_evaluate = NULL,
  ...
)

```

Arguments

formula	an object of class " formula " (or one that can be coerced to that class with as.formula : a symbolic description of the model to be fitted.
yind	a vector with length equal to the number of columns of the matrix of functional responses giving the vector of evaluation points (t_1, \dots, t_G) . If not supplied, yind is set to <code>1:ncol(<response>)</code> .
data	an (optional) <code>data.frame</code> containing the covariate data. the variable terms will be searched from the columns of data, covariates also can be read from the workspace if it is not available in data.
ydata	an (optional) <code>data.frame</code> consists of three columns <code>.obs</code> , <code>.index</code> and <code>.value</code> , supplying the functional responses that are not observed on a regular grid. ydata must be provided if the sampling design is irregular.

method	detrmines the estimation method of functional parameters. Defaults to "REML" estimation.
rangeval	an (optional) vector of length two, indicating the lower and upper limit of the domain of latent functional response. If not specified, it will set by minimum and maximum of yind or .index column of ydata.
basis	an (optional) object of class basisfd. Defaults to cubic bspline basis.
...	other arguments that can be passed to the inner function AMCEM.

Details

The output is a dfrr-object, which then can be injected into other methods/functions to postprocess the fitted model, including: `coef.dfrr`, `fitted.dfrr`, `basis`, `residuals.dfrr`, `predict.dfrr`, `fpca`, `summary.dfrr`, `model.matrix.dfrr`, `plot.coef.dfrr`, `plot.fitted.dfrr`, `plot.residuals.dfrr`, `plot.predict.dfrr`, `plot.fpca.dfrr`

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
plot(dfrr_fit)

##### Fitting dfrr model to the Madras Longitudinal Schizophrenia data
data(madras)
ydata<-data.frame(.obs=madras$id,.index=madras$month,.value=madras$y)
ids<-unique(madras$id)
q<-4
N<-length(ids)
xData<-data.frame(Age=rep(NA,N),Gender=rep(NA,N))
for(i in 1:N){
  dt<-madras[madras$id==ids[i],]
  xData[i,]<-c(dt$age[1],dt$gender[1])
}
rownames(xData)<-ids

madras_dfrr<-dfrr(Y~Age+Gender+Age*Gender, data=xData, ydata=ydata, J=11,T_E=5)
coefs<-coef(madras_dfrr)
plot(coefs)

fpcs<-fpca(madras_dfrr)
plot(fpcs)
```

Description

Fitted curves refer to the estimations of latent functional response curves. The results can be either the Fourier coefficients or evaluation of the fitted functions. See Details.

Usage

```
## S3 method for class dfrr
fitted(
  dfrr_fit,
  return.fourier.coefs = NULL,
  return.evaluations = !return.fourier.coefs,
  time_to_evaluate = NULL,
  standardized = NULL,
  unstandardized = !standardized
)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).

return.fourier.coefs, return.evaluations a boolean indicating whether the Fourier coefficients of the fitted curves are returned (`return.fourier.coefs=TRUE`), or evaluations of the fitted curves (`return.evaluations=TRUE`). Defaults to `return.fourier.coefs=TRUE`.

time_to_evaluate a numeric vector indicating the set of time points for evaluating the fitted latent functions, for the case of `return.evaluations=TRUE`.

standardized, unstandardized a boolean indicating whether stanadrdized/unstandardized fitted latent curves is reported. Only standardized fitted curves are identifiable, thus the arugment is defaults to `standardized=TRUE`.

Details

This function will return either the Fourier coefficients or the evaluation of fitted curves to the binary sequences. Fourier coefficients which are reported are based on the a set of basis which can be determined by [basis\(dfrr_fit\)](#). Thus the evaluation of fitted latent curves on the set of time points specified by vector `time`, equals to `fitted(dfrr_fit)%*%t(eval.basis(time,basis(dfrr_fit)))`.

Consider that the unstandardized estimations are not identifiable. So, it is recommended to extract and report the standardized estimations.

See Also

[plot.fitted.dfrr](#)

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
  beta1=function(t){2*t},
  X=X,time=time)
```

```
dfrr_fit<-dfrr(Y~X,yind=time)
fitteds<-fitted(dfrr_fit)
plot(fitteds)
```

fpca

Functional principal component analysis of a dfrr fit

Description

fpca() returns estimations of the smooth principal components/eigen-functions and the corresponding eigen-values of the residual function in the dfrr model. The result is a named list containing the vector of eigen-values and the matrix of Fourier coefficients. See Details.

Usage

```
fpca(dfrr_fit, standardized = NULL, unstandardized = !standardized)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).
standardized, unstandardized a boolean indicating whether stanadrized/unstandardized pricipal components/eigen-functions are reported. Only standardized pricipal components/eigen-functions are identifiable, thus the arugment is defaults to standardized=TRUE.

Details

Fourier coefficients which are reported are based on the a set of basis which can be determined by [basis\(dfrr_fit\)](#). Thus the evaluation of pricipal component/eigen-function on the set of time points specified by vector `time`, equals to `fpca(dfrr_fit)%*%t(eval.basis(time,basis(dfrr_fit)))`.

Consider that the unstandardized estimations are not identifiable. So, it is recommended to extract and report the standardized estimations.

Value

fpca(dfrr_fit) returns a list containtng the following components:

values a vector containing the eigen-values of the standaridized/unstandardized covari-
 ance operator of the residual function term in dfrr model, sorted in decreasing
 order.
vectors a matrix whose columns contain the Fourier coefficients of the principal components/eigen-
 functions of the standaridized/unstandardized covariance operator of the resid-
 ual function term in dfrr model, sorted based on the corresponding eigen-
 values.

See Also

[plot.fpca.dfrr](#)

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
fpcs<-fpca(dfrr_fit)
plot(fpcs)
```

madras

Madras Longitudinal Schizophrenia Study.

Description

Monthly records of presence/absence of psychiatric symptom 'thought disorder' of 86 patients over the first year after initial hospitalisation for disease.

Usage

madras

Format

A data frame with 1032 observations and 5 variables

id identification number of a patient

y response 'thought disorder': 0 = absent, 1 = present

month month since hospitalisation

age age indicator: 0 = less than 20 years, 1 = 20 or over

gender sex indicator: 0 = male, 1 = female

Source

Diggle PJ, Heagerty P, Liang KY, Zeger SL (2002). The analysis of Longitudinal Data, second ed., pp. 234-43. Oxford University Press, Oxford.
<http://faculty.washington.edu/heagerty/Books/AnalysisLongitudinal/datasets.html>

References

Jokinen J. Fast estimation algorithm for likelihood-based analysis of repeated categorical responses. *Computational Statistics and Data Analysis* 2006; 51:1509-1522.

model.matrix.dfrr	<i>Obtain model matrix for a dfrr fit</i>
-------------------	---

Description

Obtain model matrix for a dfrr fit

Usage

```
## S3 method for class dfrr
model.matrix(dfrr_fit)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).

plot.coef.dfrr	<i>Plot dfrr coefficients</i>
----------------	-------------------------------

Description

Plot a coef.dfrr object. The output is the plot of regression coefficients.

Usage

```
## S3 method for class coef.dfrr
plot(coefs, select = NULL, ask.hit.return = TRUE, ...)
```

Arguments

coefs	a coef.dfrr-object.
select	a vector of length one or more of indices of regression coefficients to plot.
ask.hit.return	a boolean indicating whether to wait for interaction of the user between any two plots.
...	graphical parameters passed to plot.

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
coefs<-coef(dfrr_fit)
plot(coefs)
```

plot.dfrr	<i>Plot a dfrr fit</i>
-----------	------------------------

Description

Plot the regression coefficients, principal components, kernel function and residuals of a dfrr-object.

Usage

```
## S3 method for class dfrr
plot(dfrr_fit)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function [dfrr](#).

Details

The contour plot of the kernel function is produced if the package [ggplot2](#) is installed. Plotting the 3d surface of the kernel function is also depends on the package [plotly](#). To produce the qq-plot, the package [car](#) must be installed.

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
plot(dfrr_fit)
```

plot.fitted.dfrr	<i>Plot dfrr fitted latent functions</i>
------------------	--

Description

Plot a fitted.dfrr object.

Usage

```
## S3 method for class fitted.dfrr
plot(
  fitted.dfrr,
  id = NULL,
  main = NULL,
  col = "blue",
  lwd = 2,
  lty = "solid",
  cex.circle = 1,
  col.circle = "black",
  ylim = NULL,
  ...
)
```

Arguments

<code>fitted.dfrr</code>	the output of the function fitted.dfrr
<code>id</code>	a vector of length one or more containing subject ids to plot. Must be matched with <code>rownames(<response>)</code> or the <code>.obs</code> column of <code>ydata</code> . Defaults to all subject ids.
<code>main</code>	a vector of length one or <code>length(id)</code> containing the title of plots.
<code>col, lwd, lty, ...</code>	graphical parameters passed to plot
<code>cex.circle, col.circle</code>	size and color of circles and filled circles.
<code>ylim</code>	a vector of length two indicating the range of y-axis of the plot.

Details

The output is the plot of latent curves over the observed binary sequence. The binary sequence is illustrated with circles and filled circles for the values of zero and one, respectively.

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
fitteds<-fitted(dfrr_fit)
plot(fitteds)
```

plot.fpca.dfrr	<i>Plot dfrr functional principal components</i>
----------------	--

Description

Plot a fpca.dfrr object.

Usage

```
## S3 method for class fpca.dfrr
plot(
  fpca.dfrr,
  plot.eigen.functions = TRUE,
  select = NULL,
  plot.contour = FALSE,
  plot.3dsurface = FALSE,
  plot.contour.pars = list(breaks = NULL, minor_breaks = NULL, n.breaks = NULL, labels
    = NULL, limits = NULL, colors = NULL, xlab = NULL, ylab = NULL, title = NULL),
  plot.3dsurface.pars = list(xlab = NULL, ylab = NULL, zlab = NULL, title = NULL,
    colors = NULL),
  ask.hit.return = TRUE,
  ...
)
```

Arguments

plot.eigen.functions	a boolean indicating whether to print the principal components/eigen-functions. Defaults to TRUE.
select	a vector of length one or more of indices of eigenfunctions to be plotted.
plot.contour	a boolean indicating whether to print the contour plot of the kernel function. It requires the package ggplot2 to be installed. Defaults to FALSE.
plot.3dsurface	a boolean indicating whether to print the 3d surface plot of the kernel function. It requires the package plotly to be installed. Defaults to FALSE.
plot.contour.pars	a named list of graphical parameters passed to the function ggplot .
plot.3dsurface.pars	a named list of graphical parameters passed to the function plot_ly .
ask.hit.return	a boolean indicating whether to wait for interaction of the user between any two plots.
...	graphical parameters passed to plot function in drawing 2D eigenfunctions.

Details

This function plots the functional principal components, contour plot and 3d surface of the kernel function.

If the package [ggplot2](#) is installed, the contour plot of the kernel function is produced by setting the argument `plot.contour=TRUE`. Some graphical parameters of the contour plot can be modified by setting the (optional) argument `plot.contour.pars`.

If the package `plotly` is installed, the 3d surface of the kernel function is produced by setting the argument `plot.3dsurface=TRUE`. Some graphical parameters of the 3d surface can be modified by setting the (optional) argument `plot.3dsurface.pars`.

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
fpcs<-fpca(dfrr_fit)
plot(fpcs,plot.eigen.functions=TRUE,plot.contour=TRUE,plot.3dsurface=TRUE)
```

<code>plot.predict.dfrr</code>	<i>Plot dfrr predictions</i>
--------------------------------	------------------------------

Description

Plot a `predict.dfrr` object.

Usage

```
## S3 method for class predict.dfrr
plot(
  predict.dfrr,
  id = NULL,
  conf.band.type = "BEc",
  conf.level = 0.95,
  main = id,
  col = "blue",
  lwd = 2,
  lty = "solid",
  cex.circle = 1,
  col.circle = "black",
  ylim = NULL,
  ...
)
```

Arguments

<code>predict.dfrr</code>	a <code>predict.dfrr</code> -object
<code>id</code>	a vector of length one or more containing subject ids to plot. Must be matched with <code>rownames(newdata)</code> . Defaults to all subject ids.
<code>conf.band.type</code>	a type of confidence band specified in package <code>fregion</code> . Can be either <code>NULL</code> for omitting the confidence band from the plot, <code>"BEc"</code> for modified Scheffe style band constructing from a hyper-ellipsoid region, <code>"Bs"</code> for Parametric bootstrap simultaneous confidence band, or any other <code>conf.band.type</code> acceptable to package <code>fregion</code> . Defaults to <code>NULL</code> . See References.

`conf.level` confidence levels for the bands to achieve. Defaults to 0.95.
`main` a vector of length one or `length(id)` containing the title of plots.
`col, lwd, lty, ...` graphical parameters passed to `plot`
`cex.circle, col.circle` size and color of circles and filled circles.

Details

The output is the plot of predictions of latent functions given the new covariates. For the case in which `newydata` is also given, the predictions are plotted over the observed binary sequence. The binary sequence is illustrated with circles and filled circles for the values of zero and one, respectively. Confidence bands can also be added to the plot if the package `fregion` is installed.

References

Choi, H., & Reimherr, M. A geometric approach to confidence regions and bands for functional parameters . *Journal of the Royal Statistical Society, Series B Statistical methodology* 2018; 80:239-260.

Examples

```

set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
preds<-predict(dfrr_fit)
plot(preds)
  
```

`plot.residuals.dfrr` *QQ-plot for dfrr residuals*

Description

The output gives the qq-plot of estimated measurment error.

Usage

```

## S3 method for class residuals.dfrr
plot(residuals.dfrr, ...)

## S3 method for class dfrr
qq(dfrr_fit, ...)
  
```

Arguments

residuals.dfrr a residuals.dfrr-object.
 ... graphical parameters passed to `car::qqPlot`
 dfrr_fit a fitted dfrr-object obtained from invoking the function `dfrr`.

Examples

```
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
resid<-residuals(dfrr_fit)
plot(resid)
#qq(dfrr_fit)
```

predict.dfrr

*Prediction for dichotomized function-on-scalar regression***Description**

Takes a dfrr-object created by `dfrr()` and returns predictions given a new set of values for a model covariates and an optional ydata-like data.frame of observations for the dichotomized response.

Usage

```
## S3 method for class dfrr
predict(
  dfrr_fit,
  newdata,
  newydata = NULL,
  standardized = NULL,
  unstandardized = !standardized,
  return.fourier.coefs = NULL,
  return.evaluations = !return.fourier.coefs,
  time_to_evaluate = NULL
)
```

Arguments

dfrr_fit a fitted dfrr-object obtained from invoking the function `dfrr`.
 newdata a data.frame containing the values of all of the model covariates at which the latent functional response is going to be predicted.
 newydata (optional) a ydata-like data.frame containing the values of dichotomized response sparsely observed in the domain of function.
 standardized, unstandardized a boolean indicating whether stanadrdrized/unstandardized predictions are reported. Defaults to standardized=TRUE.


```

return.fourier.coefs, return.evaluations
    a boolean indicating whether the Fourier coefficients of predictions are returned
    (return.fourier.coefs=TRUE), or evaluations of the predictions (return.evaluations=TRUE).
    Defaults to return.evaluations=TRUE.
time_to_evaluate
    a numeric vector indicating the set of time points for evaluating the predictions,
    for the case of return.evaluations=TRUE.

```

Details

This function will return either the Fourier coefficients or the evaluation of predictions. Fourier coefficients which are reported are based on the a set of basis which can be determined by `basis(dfrr_fit)`. Thus the evaluation of predictions on the set of time points specified by vector `time`, equals to `fitted(dfrr_fit, return.fourier.coefs=T)%%t(eval.basis(time, basis(dfrr_fit)))`.

See Also

`plot.predict.dfrr`

Examples

```

set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t*pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
preds<-predict(dfrr_fit)
plot(preds)

```

residuals.dfrr

Obtain residuals for a dfrr model

Description

Returns the residuals of a fitted dfrr model. A dfrr model is of the form:

$$Y_i(t) = I(W_i(t) > 0),$$

in which $I(\cdot)$ is the indicator function and $W_i(t) = Z_i(t) + \epsilon_i(t) \times \sigma^2$, where $Z_i(t)$ is the functional part of the model and $\epsilon_i(t) \times \sigma^2$ is the measurement error. The functional part of the model, consisting a location and a residual function of the form:

$$Z_i(t) = \sum_{j=1}^q \beta_j(t) * x_{ji} + \epsilon_i(t),$$

and $\epsilon_i(t)$ are iid standard normal for each i and t . The residuals reported in the output of this functions is the estimation of the measurement error of the model i.e. $\epsilon_i(t) \times \sigma^2$, which is estimated by:

$$E(W_i(t) - Z_i(t) \mid Y_i(t)).$$

Usage

```
## S3 method for class dfrr
residuals(dfrr_fit, standardized = NULL, unstandardized = !standardized)
```

Arguments

`dfrr_fit` a fitted `dfrr`-object obtained from invoking the function `dfrr`.
`standardized, unstandardized` a boolean indicating whether stanadrdized/unstandardized residuals are reported. Defaults to `standardized=TRUE`.

See Also

[plot.residuals.dfrr](#), [qq.dfrr](#)

Examples

```
set.seed(2000)
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
dfrr_fit<-dfrr(Y~X,yind=time)
resid<-residuals(dfrr_fit)
plot(resid)
#qq(dfrr_fit)
```

`simulate.simple.dfrr` *Simulating a Simple dfrr Model*

Description

Simulation from a simple `dfrr` model:

$$Y_i(t) = I(\beta_0(t) + \beta_1(t) * x_i + \varepsilon_i(t) + \epsilon_i(t) \times \sigma^2 > 0),$$

where $I(\cdot)$ is the indicator function, and $\epsilon_i(t)$ is iid standard normal for each i and t . For demonstration purpose only.

Usage

```
## S3 method for class simple.dfrr
simulate(
  beta0 = function(t) {      cos(pi * t + pi) },
  beta1 = function(t) {      2 * t },
  X = rnorm(50),
  time = seq(0, 1, length.out = 24),
  sigma2 = 0.2
)
```

Arguments

<code>beta0, beta1</code>	(optional) functional intercept and regression coefficients
<code>X</code>	an (optional) vector consists of scalar covariate
<code>time</code>	an (optional) vector of time point for which, each sample curve is observed at.

Examples

```
N<-50;M<-24
X<-rnorm(N,mean=0)
time<-seq(0,1,length.out=M)
Y<-simulate.simple.dfrr(beta0=function(t){cos(pi*t+pi)},
                        beta1=function(t){2*t},
                        X=X,time=time)
```

Index

- * **Dichotomized**
 - dfrrr-package, [2](#)
- * **FDA**,
 - dfrrr-package, [2](#)
- * **Functional**,
 - dfrrr-package, [2](#)
- * **Functional**
 - dfrrr-package, [2](#)
- * **Regression**
 - dfrrr-package, [2](#)
- * **datasets**
 - madras, [9](#)
- _PACKAGE (dfrrr-package), [2](#)
- as.formula, [5](#)
- basis, [3](#), [4](#), [6–8](#), [17](#)
- car, [11](#)
- coef.dfrr, [4](#), [6](#)
- dfrr, [2–4](#), [5](#), [7](#), [8](#), [10](#), [11](#), [16](#), [18](#)
- dfrrr-package, [2](#)
- eval.basis, [4](#), [7](#), [8](#), [17](#)
- fitted.dfrr, [6](#), [6](#), [12](#)
- formula, [5](#)
- fpca, [6](#), [8](#)
- ggplot, [13](#)
- ggplot2, [11](#), [13](#)
- madras, [9](#)
- model.matrix.dfrr, [6](#), [10](#)
- plot, [12](#), [15](#)
- plot.coef.dfrr, [4](#), [6](#), [10](#)
- plot.dfrr, [11](#)
- plot.fitted.dfrr, [6](#), [7](#), [11](#)
- plot.fpca.dfrr, [6](#), [8](#), [13](#)
- plot.predict.dfrr, [6](#), [14](#), [17](#)
- plot.residuals.dfrr, [6](#), [15](#), [18](#)
- plot_ly, [13](#)
- plotly, [11](#), [13](#), [14](#)
- predict.dfrr, [6](#), [16](#)
- qq.dfrr, [18](#)
- qq.dfrr (plot.residuals.dfrr), [15](#)
- qqPlot, [16](#)
- residuals.dfrr, [6](#), [17](#)
- simulate.simple.dfrr, [18](#)
- summary.dfrr, [6](#)