



Basic Techniques To Handle Outliers



1) Trimming: (Remove Outliers)

Temperature reading:

- 40, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 56, 89

1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5



Basic Techniques To Handle Outliers



2) Drop rows with extreme values:

Works well if outliers are **data errors**
(e.g., negative height, impossible values).

Drop this row -->

Age	Income	Position
23	40	HR
62	89	HR
53	89	HR
-12	23	IT
62	89	HR

However, it's essential to **carefully consider the percentage to be trimmed** to avoid removing too much data



Basic Techniques To Handle Outliers



3) Capping: (a.k.a. Winsorization)

- 40, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 56, 89

1, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 5, 5

Replace extreme values with nearest acceptable boundary.

Example: Cap at 5th and 95th percentile.

Best for preserving dataset size and avoiding bias.



Basic Techniques To Handle Outliers



Capping prevents the complete removal of outliers and instead modifies their values to **align them with the nearby observations**.

This approach helps **control the impact of outliers** while **retaining their presence in the dataset**



Basic Techniques To Handle Outliers



4) Imputation:

Replace outliers with a more “typical” value (mean, median, mode).

Temp: - 40, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 56, 89

Temp: M, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, M, M

Here M is median or mean value

Shoe Size: 21, 2, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 26, 89

Shoe Size: 2, 1, 2, 2, 2, 2, 2, 2, 3, 5, 4, 4, 2, 2

Here 2 is the mode.

Best for **small datasets** where every record matters.



Basic Techniques To Handle Outliers



5) Flagging Outliers:

Create a new binary column.

Example: `is_outlier = 1 if outlier else 0`

Age	Income	Position	Is_outlier
23	40	HR	0
29	89	HR	0
51	89	HR	0
98	23	IT	1
45	89	HR	0

Keeps information about outliers without deleting them.



Summary



Question

- Is it a data error?
- Is it rare but valid?
- Is it hurting model?
- Is it the target case?
- Is model sensitive?
- Is model robust?

Action

- Remove
- Keep
- Transform / cap
- Definitely keep
- Handle carefully
- Maybe ignore

Takeaway



- 1) Outliers should be detected during EDA,
- 2) handled during preprocessing, and
- 3) reconsidered during modeling — never removed blindly.



Fhdsklf
Fjdsklf
Fjsklfd

EXTRA

