

Ship Cargo Load Balancing

8 December 2025

Team Collective Solutions

Yana Padte <ypadt001@ucr.edu>

Saumya Chourasia <schou065@ucr.edu>

Anokhee Shah <ashah174@ucr.edu>

Allen Biju <abiju009@ucr.edu>

Parth Awade <pawad006@ucr.edu>

⇒ Github – <https://github.com/allenbiju30301/Ship-Balancing>

Abstract

Our client, Mr. Keogh, is the owner of a small shipping port in Long Beach, where his business ensures that each ship that passes is properly balanced and meets legal safety requirements before departing. Every incoming ship sends a manifest that lists the position and weight of up to 16 containers arranged on an 8 x 12 grid. A ship is considered legally balanced only if the total weight difference between the port and starboard sides is less than or equal to 10% of the ship's total weight. The current process is very time-consuming, as it requires operators to manually interpret ship manifests, calculate weight distribution, determine container movements, and update the manifest. Mr. Keogh has requested a reliable application that can automatically determine how to rearrange the containers in a balanced manner that meets legal safety requirements in the least time possible [1]. We developed a program that analyzes a manifest containing the container's position, description, and weight in kilograms. It then determines how to balance the ship while minimizing total move time legally, and guides the operator through each container movement.

Elicitation

1st Meeting with Dr. Keogh: November 6, 2025

Key Questions:

1. If multiple optimal solutions exist, should our program pick one randomly or use specific selection criteria?
2. What should the user see if the original manifest file is corrupted, incomplete, or includes a non-numeric weight?
3. Is there a maximum amount of time that an operator should spend balancing one ship?
4. In the event of a system crash, would you like us to update the ship's manifest continuously?

Clarifications Received: Program should select the optimal solution at random; it should be possible to recover from program crashing.

Final Understanding: The system should be able to reboot and find the previous state, so yes, the ship's manifest should be constantly updated.

2nd Meeting with Dr. Keogh: December 4, 2025

Key Questions:

1. Does the placement of comments in the log file matter, and how frequently should comments appear?
2. Should our algorithm begin at position [08, 01] or at the row directly above it?
3. In *ShipCase6.txt*, our algorithm achieves the required 10% minimum imbalance after the first move and does not require the second move shown in the test case example. Should we expect this outcome, or does this indicate that the test case assumes a different sequence of steps [2]?
4. Is *ShipCase2.txt* intended to be identical to *ShipCase1.txt*?

Clarifications Received: During our second meeting with Dr. Keogh, our team identified two inconsistencies in the provided ship case files and test examples. Both findings were discussed with Dr. Keogh, who confirmed that noting these issues in our report would be appropriate and would count toward extra credit.

1. Similarity between *ShipCase1.txt* and *ShipCase2.txt* – While reviewing the manifest files, we noticed that *ShipCase2.txt* appears to be functionally identical to *ShipCase1.txt*. After discussing this with Dr. Keogh, he confirmed that this similarity should be documented, as it may indicate an oversight in the provided test cases. Our implementation handles both files correctly, but the duplication is noted here for completeness.
2. *ShipCase6.txt* imbalance resolution requires only one move – In analyzing *ShipCase6.txt*, we found that our algorithm can reach the required 10% minimum imbalance after a single move. This differs from the example shown in the project slides, which demonstrates two moves being performed. Dr. Keogh clarified that this outcome is acceptable and that our observation should be included in the report because it highlights a discrepancy between the slide example and the actual file provided.

Final Understanding: The behavior we observed in Ship Case 6 is acceptable, but we should document this inconsistency. Additionally, upon review with Dr. Keogh, the similarity between *ShipCase1.txt* and *ShipCase2.txt* should also be noted in our report. Comments should appear in chronological order by timestamp, and some files may contain no comments. The starting location should be the space directly above the highest positive container on the far left side.

Requirement Specification

We begin with Table 1, which lists all acronyms used.

Table 1: Acronym List – Key for the acronyms referenced in this report

CLI	Command Line Interface
I/O	Input/Output
CPU	Central Processing Unit
TXT	Text File
BFS	Breadth-First Search

3.1 System Context Diagram

Figure 1 shows the system context diagram for our program. In the terminal, the Ship-Balancing CLI reads from manifest files and outputs an updated manifest for each respective input. The updated manifest includes the new container positions, and all operations are logged in a separate log file for record-keeping. This program is cyclic and terminates only when the user/operator chooses to exit.




Figure 1: Ship Balancing Planner CLI Workflow

3.2 System Functions

Figure 2 shows the core workflow of the ship-balancing system. The system first checks if the ship is legally balanced. If not, the manifest is passed through the A* search algorithm to find an effective sequence for moving the cargo to achieve legal balance [4]. The program displays the total time calculation, a colored grid of the step-by-step instructions for moving the containers, and interactive verification for the operator. Finally, the updated manifest is written to the solutions folder.




Figure 2: Ship Load Balancing Workflow

This program supports the following primary system functions:

1. Validate manifest file format, rejecting or skipping coordinate lines that are not in the proper format.
2. Parses the manifest into an 8x12 grid, a *slotExists* map, a containers list (with position, weight, description), and a *contentsMap* that preserves the original text.
3. Identifies available slots, unavailable slots (NAN), and existing containers.
4. Evaluates whether the ship is legally balanced based on port/starboard weight distribution.
5. Applying the 10% rule for three or more containers, and special-case rules for 0-2 containers (must be on opposite sides).
6. Finds a sequence of container moves to balance the ship using the A* search algorithm if rebalancing is needed.
7. Simulates step-by-step execution with user prompts between moves.
8. Allows operators to add timestamped comments during execution by pressing 'c'.
9. Provides color-coded visual feedback (green = moving container, red = destination, blue = crane position, yellow = other containers).

10. Logs each crane movement and container relocation separately with time estimates.

3.3 Operating Environment

- Standard laptop using Python.
- Local file access only.
- Dependencies limited to Python standard libraries, with Matplotlib support for visualization.
- Benchmark environment's CPU is Apple M2 Pro (12-core) at up to 3.5 GHz.

3.4 Design & Implementation Constraints

- The system must handle 8x12 ship manifests, the fixed grid size specified for the problem domain.
- The program must reject or skip malformed lines in the manifest without crashing.
- Balance validation must follow the 10% rule when the ship holds three or more containers, and apply the simplified rules for ships carrying 0-2 containers.
- A* search must complete within a practical runtime (target: under 5 minutes) for any valid manifest.
- Output files must exactly preserve original formatting except for container updates and moves.
- Only local file access is permitted; no cloud storage, remote I/O, or network-based lookups.

3.5 Assumptions and Dependencies

- All manifest files contain syntactically valid numeric weights and coordinates, along with coordinate formats.
- Containers are assumed to have integer weights.
- When movement is required, the operator will follow the printed step-by-step instructions in order, and the solver assumes perfect compliance.
- The balancing rule uses the absolute weight difference between the port and starboard sides.
- All file reading and writing uses local disk access, and no multi-threaded or distributed computation is required.
- File I/O is always local.

We have provided a short, informative README.md file with instructions for operators to follow when using the Ship-Balancing system. The guide includes directions on how to start the program, how to input a manifest, which cargo needs to be moved, how to add comments, and where to find the outbound manifest/logfile for the resulting cargo layout. This information can be found at the link below:

⇒ Operator Instructions – <https://github.com/allenbiju30301/Ship-Balancing/blob/main/README.md>

Design

4.1 Workflow Summary

Figure 3 shows the processing pipeline of the ship-balancing system. The program begins with the user providing a manifest file listing all containers, including their current positions, weights, and descriptions,

on an 8x12 grid. The program parses the manifest and immediately checks whether the ship is balanced in accordance with port regulations. For ships with three or more containers, the weight difference between the port (left) and starboard (right) sides must not exceed 10% of the total weight. For ships with two containers, they must be on opposite sides to be considered legally balanced.

If the ship is unbalanced, the program uses an A* search algorithm using BFS and Manhattan Distance to compute a sequence of crane moves to rebalance it while respecting physical constraints (containers can only be transferred from the top of their stacks, and the crane parks at [08, 01]) [4]. The program then guides the operator through each step. It displays crane movements and container relocations with time estimates in minutes. Afterwards, an updated outbound manifest is generated with the new container positions, and all operations are logged for record-keeping.




Figure 3: End-to-End Processing Pipeline for the Ship-Balancing System

Insight

Table 2 below shows how the A* algorithm distributes weight between the port and starboard sides for each test case. For every manifest, the *isBalanced.py* file compares the original difference between the two sides to the final difference after the program finishes all required moves. The $|P-S|$ value is the absolute difference between the final port and starboard totals, because it indicates how close the ship is to meeting the legal balance requirement. Any difference that is less than or equal to 10% of the ship's total weight is considered legally balanced.

Most of the test cases end with a very small final difference. Several of them have only 2 kilograms of difference between the two sides, indicating that the algorithm can place containers so the ship remains nearly even. In the cases where the ship begins heavily unbalanced, such as the *ShipCase3.txt* and *HMM_Algeciras.txt* files, the program applies the two-container exception rule. These examples show that when a perfectly even distribution is not mathematically possible, the algorithm still recognizes this and produces the best arrangement it can by placing one container on each side of the ship.

Overall, the results show that the algorithm consistently produces a legal distribution of weight. It reaches a balanced state in every case where it is achievable, and it handles special cases correctly when the 10% rule or the two-container exception must be applied.

Table 2: Ship Weight Balances

Test File	Original P weight	Original S weight	Final P weight	Final S weight	$ P-S $	Satisfies 10%?	2 Container Exception?
<i>ShipCase1.txt</i>	0	0	0	0	0	Yes	—
<i>ShipCase2.txt</i>	0	0	0	0	0	Yes	—
<i>ShipCase3.txt</i>	141	0	101	40	61	No	Yes
<i>ShipCase4.txt</i>	402	0	202	200	2	Yes	—
<i>ShipCase5.txt</i>	906	100	502	504	2	Yes	—
<i>ShipCase6.txt</i>	1101	900	1040	961	79	Yes	—
<i>HMM_Algeciras.txt</i>	423	0	123	300	177	No	Yes

Figures 4-8 show how the weight on each side of the ship shifts as the containers are moved, as per the results from *ShipCase3.txt* to *HMM_Algeciras.txt*. The green dashed line shows the ship's imbalance at each move, which eventually approaches 0, indicating that the ship is legally balanced after the respective containers are moved. In the cases of *ShipCase3.txt* and *HMM_Algeciras.txt*, the imbalance line ends at a value other than 0, as seen in Figures 4 and 8, respectively. These are still legally balanced ships since both test cases satisfy the two-container exception.




Figure 4: Port and Starboard Weight Over Time Graph for *ShipCase3.txt*




Figure 5: Port and Starboard Weight Over Time Graph for *ShipCase4.txt*




Figure 6: Port and Starboard Weight Over Time Graph for *ShipCase5.txt*




Figure 7: Port and Starboard Weight Over Time Graph for *ShipCase6.txt*




Figure 8: Port and Starboard Weight Over Time Graph for *HMM_Algeciras.txt*

Implementation

Our project was implemented in Python and organized into seven main files: *main.py*, *readManifest.py*, *AStar.py*, *isBalanced.py*, *visualize.py*, *logger.py*, and *writeManifest.py*. The *main.py* file is the program's entry point. It reads a manifest file and checks if the ship is balanced. If not, it uses the A* search algorithm to find a sequence of moves. The crane starts and ends at its parked position above [08, 01]. The program walks through each move step by step, showing crane movements and container relocations. Once done, it writes an updated manifest file with the new container positions. Users can also add comments during execution, which are recorded in the program's log files.

The *readManifest.py* file converts the input manifest file into an 8x12 grid representation. It parses each line to extract container positions and weights, distinguishing between 3 cell types: containers with weights, empty slots ("unused"), and unavailable slots ("NAN").

The *AStar.py* file finds the optimal sequence of moves by exploring different container relocations. It prioritizes moves that reduce the ship's imbalance starting from the port side. The algorithm tracks the crane position and enforces stacking rules (containers can only be picked up from the top of a stack and placed on supported spots). It uses the Manhattan Distance heuristic to guide the search toward a balanced state and searches for containers using BFS [5][6].

To guide the A* search, we designed a heuristic that combines Manhattan distance with the ship's current imbalance. The Manhattan distance helps estimate how far the crane must travel to reach and relocate a container, which keeps the search focused on physically efficient moves [5][6]. At the same time, we

compute how much each potential move reduces the port-starboard weight difference and prefer moves that push the ship closer toward legal balance. BFS is used to verify whether a path between two cells is actually reachable based on the ship layout, so the heuristic only evaluates realistic moves.

The *isBalanced.py* file checks if the ship is legally balanced by comparing port (left) and starboard (right) side weights. For ships with three or more containers, they are balanced if the weight differences are no more than 10% of the total weight. For the two-container exception, the ship is considered balanced if the containers are on opposite sides.

The *visualize.py* file displays the ship layout as an 8x12 grid, using color coding to highlight containers, empty slots, unusable positions, and active crane movements for clear operator feedback. Our program uses a 0-index grid internally but a 1-index grid for display.

The *logger.py* file records all operations and allows operators to add comments during execution. It creates timestamped log files in a “Log” folder that track the program’s activities and any user-provided notes for documentation purposes.

Finally, the *writeManifest.py* file generates the output manifest file with updated container positions after balancing is complete. It keeps the original manifest formatting while reflecting the new layout.

6.1 Naming Convention of Solution Files

→ **Outbound Manifest:** */solutions/{manifest_name}OUTBOUND.txt*

→ **Program Logfile:** */Log/{manifest_name}{MM_DD_YYYY_HHMM}.txt*

6.2 Algorithm Traces

Figures 9 through 22 show the CLI outputs for our ship-balancing algorithms on seven datasets, along with the resulting graphical visualizations and the corresponding generated logfiles. Each case shows the initial ship layout and imbalance scenario, and includes the execution trace (balance check, A* move sequence, and timing), as well as the updated outbound manifest file (**OUTBOUND.txt*).

Case 1 – *ShipCase1.txt*

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
Enter a manifest: (or press ENTER to quit): ShipCase1.txt

Ship Layout:
Row 08 | ... ..
Row 07 | ... ..
Row 06 | ... ..
Row 05 | ... ..
Row 04 | ... ..
Row 03 | ... ..
Row 02 | ... ..
Row 01 | XXX ... ..
      | 01 02 03 04 05 06 07 08 09 10 11 12

Ship is already legally balanced.

I have written an updated manifest as ShipCase1OUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

Enter a manifest: (or press ENTER to quit):

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase112_05_2025_1233.txt
Goodbye.
(base) allenbiju@Allens-MacBook-Pro-2 src %
```

Figure 9: CLI Output for Case 1 – *ShipCase1.txt*

→ Log File Contents

```
1 12 03 2025: 15:38 Program was started.
2 12 03 2025: 15:38 Manifest ShipCase1.txt is opened, there are 0 containers on the ship.
3 12 03 2025: 15:38 Ship is already balanced. No moves needed.
4 12 03 2025: 15:38 Finished a Cycle. Manifest ShipCase1OUTBOUND.txt was written to the
5   solutions folder, and a reminder pop-up to the operator to send the file was displayed.
6 12 03 2025: 15:39 Program was shut down.
7
```

Figure 10: Log File Contents (*ShipCase112_05_2025_1233.txt*)

Case 2 – *ShipCase2.txt*

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
Enter a manifest: (or press ENTER to quit): ShipCase2.txt

Ship Layout:

Row 08 | ... .. | ... ..
Row 07 | ... .. | ... ..
Row 06 | ... .. | ... ..
Row 05 | ... .. | ... ..
Row 04 | ... .. | ... ..
Row 03 | ... .. | ... ..
Row 02 | ... .. | ... ..
Row 01 | XXX ... | ... XXX
      01 02 03 04 05 06 07 08 09 10 11 12

Ship is already legally balanced.

I have written an updated manifest as ShipCase2OUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

Enter a manifest: (or press ENTER to quit):

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase212_05_2025_1234.txt
Goodbye.
(base) allenbiju@Allens-MacBook-Pro-2 src %
```

Figure 11: CLI Output for Case 2 – *ShipCase2.txt*

→ Log File Contents

```
1 12 03 2025: 15:39 Program was started.
2 12 03 2025: 15:39 Manifest ShipCase2.txt is opened, there are 0 containers on the ship.
3 12 03 2025: 15:39 Ship is already balanced. No moves needed.
4 12 03 2025: 15:39 Finished a Cycle. Manifest ShipCase2OUTBOUND.txt was written to the
5 | solutions folder, and a reminder pop-up to the operator to send the file was displayed.
6 12 03 2025: 15:39 Program was shut down.
7 |
```

Figure 12: Log File Contents (*ShipCase212_05_2025_1234.txt*)

Case 3 – *ShipCase3.txt*

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
-----
Enter a manifest: (or press ENTER to quit): ShipCase3.txt

Ship Layout:

Row 08 | ... .. | ... .. |
Row 07 | ... .. | ... .. |
Row 06 | ... .. | ... .. |
Row 05 | ... .. | ... .. |
Row 04 | ... .. | ... .. |
Row 03 | ... .. | ... .. |
Row 02 | ... .. | ... .. |
Row 01 | XXX ... 101 ... 040 | ... .. XXX
      | 01 02 03 04 05 06 | 07 08 09 10 11 12
      -----

ShipCase3.txt has 2 containers
Computing a solution...

Solution has been found, it will take
3 moves
26 minutes (including movement from/to parked position)
Hit ENTER when ready for first move:

Step 1: Move crane from park to [01,06], (12 minutes)

Ship Layout:

  1  2  3  4  5  6  7  8  9 10 11 12
-----
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN |  | 101 |  |  | 40 |  |  |  |  | NAN

Hit ENTER when done

Step 2: Move 'Bikes' from [01,06] to [01,07], (1 minutes)

Ship Layout:

  1  2  3  4  5  6  7  8  9 10 11 12
-----
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN |  | 101 |  |  | 40 |  |  |  |  | NAN
```

```
Press 'c' to add a comment, or just ENTER to continue:
Step 3: Move crane from [01,07] to park, (13 minutes)

Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
8  ┌───┴───┐
7  │       │
6  │       │
5  │       │
4  │       │
3  │       │
2  │       │
1  │NAN    │101 │   │   │40 │   │   │   │NAN
   └───┴───┘

Hit ENTER when done

I have written an updated manifest as ShipCase30UTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

-----
Enter a manifest: (or press ENTER to quit):

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase312_05_2025_1235.txt
Goodbye.
(base) allenbiju@Allens-MacBook-Pro-2 src %
```

Figure 13: CLI Output for Case 3 – *ShipCase3.txt*

→ Log File Contents

```
1  12 03 2025: 15:39 Program was started.
2  12 03 2025: 15:39 Manifest ShipCase3.txt is opened, there are 2 containers on the ship.
3  12 03 2025: 15:39 Balance solution found, it will require 3 moves/26 minutes.
4  12 03 2025: 15:39 Step 1: Move crane from park to [01,06], (12 minutes)
5  12 03 2025: 15:39 Step 2: Move 'Bikes' from [01,06] to [01,07], (1 minutes)
6  12 03 2025: 15:39 Step 3: Move crane from [01,07] to park, (13 minutes)
7  12 03 2025: 15:39 Finished a Cycle. Manifest ShipCase30UTBOUND.txt was written to the
8  |   solutions folder, and a reminder pop-up to the operator to send the file was displayed.
9  12 03 2025: 15:39 Program was shut down.
10 |
```

Figure 14: Log File Contents (*ShipCase312_05_2025_1235.txt*)

Case 4 – *ShipCase4.txt*

→ Console Output

```

• (base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
-----
Enter a manifest: (or press ENTER to quit): ShipCase4.txt

Ship Layout:

Row 08 | ... .. | ... .. |
Row 07 | ... .. | ... .. |
Row 06 | ... .. | ... .. |
Row 05 | ... .. | ... .. |
Row 04 | ... .. | ... .. |
Row 03 | ... .. | ... .. |
Row 02 | ... 999 | ... .. |
Row 01 | XXX 200 103 ... .. | ... .. XXX
      | 01 02 03 04 05 06 | 07 08 09 10 11 12

```

ShipCase4.txt has 3 containers

Computing a solution...

Solution has been found, it will take

5 moves

28 minutes (including movement from/to parked position)

Hit ENTER when ready for first move:

Step 1: Move crane from park to [02,02], (7 minutes)

Ship Layout:

Hit ENTER when done

Step 2: Move 'Tools for JD' from [02,02] to [02,03], (1 minutes)

Ship Layout:

Number of Children	Count
1	1
2	2
3	2
4	1
5	1
6	1
7	1
8	1
9	1
10	1
11	1
12	1

```
Press 'c' to add a comment, or just ENTER to continue:
Step 3: Move crane from [02,03] to [01,02], (2 minutes)

Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN 200 99  |  |  |  |  |  |  |  |  |
   | 103  |  |  |  |  |  |  |  |  |  |

Hit ENTER when done

Step 4: Move 'Carpet' from [01,02] to [01,07], (5 minutes)

Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN 200 99  |  |  |  |  |  |  |  |  |
   | 103  |  |  |  |  |  |  |  |  |  |

Press 'c' to add a comment, or just ENTER to continue:
Step 5: Move crane from [01,07] to park, (13 minutes)

Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN  |  | 99  |  | 200  |  |  |  |  |  |
   | 103  |  |  |  |  |  |  |  |  |  |

Hit ENTER when done

I have written an updated manifest as ShipCase40UTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

-----
Enter a manifest: (or press ENTER to quit):

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase412_05_2025_1237.txt
Goodbye.
(base) allenbiju@Allens-MacBook-Pro-2 src %
```

Figure 15: CLI Output for Case 4 – ShipCase4.txt

→ Log File Contents

```
1 12 03 2025: 15:40 Program was started.
2 12 03 2025: 15:40 Manifest ShipCase4.txt is opened, there are 3 containers on the ship.
3 12 03 2025: 15:40 Balance solution found, it will require 5 moves/28 minutes.
4 12 03 2025: 15:40 Step 1: Move crane from park to [02,02], (7 minutes)
5 12 03 2025: 15:40 Step 2: Move 'Tools for JD' from [02,02] to [02,03], (1 minutes)
6 12 03 2025: 15:40 Step 3: Move crane from [02,03] to [01,02], (2 minutes)
7 12 03 2025: 15:40 Step 4: Move 'Carpet' from [01,02] to [01,07], (5 minutes)
8 12 03 2025: 15:40 Step 5: Move crane from [01,07] to park, (13 minutes)
9 12 03 2025: 15:40 Finished a Cycle. Manifest ShipCase4OUTBOUND.txt was written to the
10 | solutions folder, and a reminder pop-up to the operator to send the file was displayed.
11 12 03 2025: 15:40 Program was shut down.
12
```

Figure 16: Log File Contents (ShipCase412_05_2025_1237.txt)

Case 5 – ShipCase5.txt

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
-----
Enter a manifest: (or press ENTER to quit): ShipCase5.txt
Ship Layout:

Row 08 | ... ... ... ... ... | ... ... ... ... ...
Row 07 | ... ... ... ... ... | ... ... ... ... ...
Row 06 | ... ... ... ... ... | ... ... ... ... ...
Row 05 | ... ... ... ... ... | ... ... ... ... ...
Row 04 | ... ... ... ... ... | ... ... ... ... ...
Row 03 | ... ... ... ... ... | ... ... ... ... ...
Row 02 | ... ... ... ... ... | ... ... ... ... ...
Row 01 | XXX 101 100 099 102 504 | ... 100 ... ... XXX
      | 01 02 03 04 05 06 | 07 08 09 10 11 12
      -----
```

ShipCase5.txt has 6 containers
Computing a solution...

Solution has been found, it will take
5 moves
28 minutes (including movement from/to parked position)
Hit ENTER when ready for first move:

Step 1: Move crane from park to [01,06], (12 minutes)

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	101	100	99	102	504		100				NAN

Hit ENTER when done

Step 2: Move 'B' from [01,06] to [01,07], (1 minutes)

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	101	100	99	102	504		100				NAN

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	101	100	99	102		504	100				NAN

Step 4: Move 'P' from [01,08] to [01,06], (2 minutes)

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	101	100	99	102		504	100				NAN

Step 5: Move crane from [01,06] to park, (12 minutes)

Ship Layout:

Category	Value
1	NAN
2	101
3	100
4	99
5	102
6	100
7	504
8	
9	
10	
11	
12	NAN

```
I have written an updated manifest as ShipCase50UTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.
```

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase512_05_2025_1239.txt
Goodbye.

Figure 17: CLI Output for Case 5 – *ShipCase5.txt*

→ Log File Contents

```
1 12 03 2025: 15:40 Program was started.
2 12 03 2025: 15:40 Manifest ShipCase5.txt is opened, there are 6 containers on the ship.
3 12 03 2025: 15:40 Balance solution found, it will require 5 moves/28 minutes.
4 12 03 2025: 15:40 Step 1: Move crane from park to [01,06], (12 minutes)
5 12 03 2025: 15:40 Step 2: Move 'B' from [01,06] to [01,07], (1 minutes)
6 12 03 2025: 15:40 Step 3: Move crane from [01,07] to [01,08], (1 minutes)
7 12 03 2025: 15:40 Step 4: Move 'P' from [01,08] to [01,06], (2 minutes)
8 12 03 2025: 15:40 Step 5: Move crane from [01,06] to park, (12 minutes)
9 12 03 2025: 15:40 Finished a Cycle. Manifest ShipCase5OUTBOUND.txt was written to the
10 | solutions folder, and a reminder pop-up to the operator to send the file was displayed.
11 12 03 2025: 15:40 Program was shut down.
12
```

Figure 18: Log File Contents (ShipCase512_05_2025_1239.txt)

Case 6 – *ShipCase6.txt*

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
Enter a manifest: (or press ENTER to quit): ShipCase6.txt

Ship Layout:

Row 08 | ... .. | ... ..
Row 07 | ... .. | ... ..
Row 06 | ... .. | ... ..
Row 05 | ... .. | ... ..
Row 04 | ... .. | ... ..
Row 03 | ... .. | ... ..
Row 02 | ... .. | ... ..
Row 01 | XXX 061 040 334 333 333 | ... .. 900 XXX
      | 01 02 03 04 05 06 | 07 08 09 10 11 12
```

ShipCase6.txt has 6 containers
Computing a solution...

Solution has been found, it will take
3 moves
26 minutes (including movement from/to parked position)
Hit ENTER when ready for first move:

Step 1: Move crane from park to [01,02], (8 minutes)

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	61	40	334	333	333					900	NAN

Hit ENTER when done

Step 2: Move 'Pig' from [01,02] to [01,07], (5 minutes)

Ship Layout:

	1	2	3	4	5	6	7	8	9	10	11	12
8												
7												
6												
5												
4												
3												
2												
1	NAN	61	40	334	333	333					900	NAN

```

Press 'c' to add a comment, or just ENTER to continue:
Step 3: Move crane from [01,07] to park, (13 minutes)

Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
8  [blue bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
7  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
6  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
5  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
4  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
3  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
2  [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar] [grey bar]
1  [NAN] [grey bar] [40] [334] [333] [333] [61] [grey bar] [grey bar] [grey bar] [900] [NAN]

Hit ENTER when done

I have written an updated manifest as ShipCase6OUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

-----
Enter a manifest: (or press ENTER to quit):

Log file written to: /Users/allenbiju/Desktop/Cs179/Ship-Balancing/Log/ShipCase612_05_2025_1240.txt
Goodbye.
(base) allenbiju@Allens-MacBook-Pro-2 src %

```

Figure 19: CLI Output for Case 6 – ShipCase6.txt

→ Log File Contents

```

1  12 03 2025: 15:38 Program was started.
2  12 03 2025: 15:38 Manifest ShipCase6.txt is opened, there are 6 containers on the ship.
3  12 03 2025: 15:38 Balance solution found, it will require 3 moves/26 minutes.
4  12 03 2025: 15:38 Step 1: Move crane from park to [01,02], (8 minutes)
5  12 03 2025: 15:38 Step 2: Move 'Pig' from [01,02] to [01,07], (5 minutes)
6  12 03 2025: 15:38 Step 3: Move crane from [01,07] to park, (13 minutes)
7  12 03 2025: 15:38 Finished a Cycle. Manifest ShipCase6OUTBOUND.txt was written to the
8      solutions folder, and a reminder pop-up to the operator to send the file was displayed.
9  12 03 2025: 15:38 Program was shut down.
10

```

Figure 20: Log File Contents (ShipCase612_05_2025_1240.txt)

Case 7 – HMM_Algeciras.txt

→ Console Output

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
Enter a manifest: (or press ENTER to quit): HMM_Algeciras.txt
Ship Layout:
Row 08 | ... .. | ... ..
Row 07 | ... .. | ... ..
Row 06 | ... .. | ... ..
Row 05 | ... .. | ... ..
Row 04 | ... .. | ... ..
Row 03 | ... .. | ... ..
Row 02 | ... .. | ... ..
Row 01 | XXX ... 123 300 | ... XXX
      01 02 03 04 05 06 07 08 09 10 11 12
-----

HMM_Algeciras.txt has 2 containers
Computing a solution...

Solution has been found, it will take
3 moves
26 minutes (including movement from/to parked position)
Hit ENTER when ready for first move:

Step 1: Move crane from park to [01,06], (12 minutes)
Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
-----
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN |  |  |  | 123 | 300 |  |  |  |  | NAN
   |  |  |  |  |  |  |  |  |  |  |  |

Hit ENTER when done

Step 2: Move 'Dogwood Flooring' from [01,06] to [01,07], (1 minutes)
Ship Layout:
  1  2  3  4  5  6  7  8  9 10 11 12
-----
8 |  |  |  |  |  |  |  |  |  |  |  |
7 |  |  |  |  |  |  |  |  |  |  |  |
6 |  |  |  |  |  |  |  |  |  |  |  |
5 |  |  |  |  |  |  |  |  |  |  |  |
4 |  |  |  |  |  |  |  |  |  |  |  |
3 |  |  |  |  |  |  |  |  |  |  |  |
2 |  |  |  |  |  |  |  |  |  |  |  |
1 | NAN |  |  |  | 123 | 300 |  |  |  |  | NAN
   |  |  |  |  |  |  |  |  |  |  |  |
```


Testing

7.1 Testing for Correct Program Behavior

To handle incorrect input and user errors, we added specific functionality to ensure our program could handle any issues and work as expected.

Case 1 – Empty Input

- **Condition:** User presses 'ENTER' without entering a filename.
- **Expected Behavior:** The program logs a shutdown event, saves the log, and exits.

```
filename = input("Enter a manifest: (or press ENTER to quit): ").strip()
    if filename == "":
        log_event("Program was shut down.")
        save_log()
        print("Goodbye.")
        break
```

Case 2 – File Not Found

- **Condition:** User enters a filename that does not exist in the *P3_test_cases* directory.
- **Expected Behavior:** The program displays an error message and prompts the user to try again without crashing.

```
path = f"../P3_test_cases/{filename}"

    if not os.path.exists(path):
        print("File not found. Try again.")
        continue
```

Case 3 – No Solution Found

- **Condition:** A* Search runs through all possible moves without finding a balanced configuration.
- **Expected Behavior:** Program logs failure, notifies user, and returns to the main menu instead of crashing.

```
moves, finalGrid = aStar(grid, slotMatrix, containers, balanceFunc,
    craneStart=PARK_POS)
    if moves is None:
        print("No valid solution could be found.")
        log_event("No valid balance solution could be found.")
        return None
```

Case 4 – Out-of-Bounds Coordinate Check

- **Condition:** Move instructions contain invalid coordinates or park position references.
- **Expected Behavior:** The program should validate coordinates before applying moves to the grid to prevent index errors.

```
if src != PARK_POS and 0 <= src[0] < ROWS and 0 <= src[1] < COLS:
    w = tempGrid[src[0]][src[1]]
    tempGrid[src[0]][src[1]] = "UNUSED"
    if dst != PARK_POS and 0 <= dst[0] < ROWS and 0 <= dst[1] < COLS:
        tempGrid[dst[0]][dst[1]] = w
```

Case 5 – Invalid Manifest Format

- **Condition:** Input file lines don't match expected pattern: [X, Y], {#####}, DESCRIPTION.
- **Expected Behavior:** The program should skip lines that don't match during parsing.

```
pattern = r"^\[(\d+),(\d+)\],\s*\{(\d+)\},\s*(.*)"
```

```
for line in lines:
    match = re.match(pattern, line.strip())
    if not match:
        continue
```

Case 6 – Empty Grid After Parsing

- **Condition:** Manifest file exists but contains no valid container entries.
- **Expected Behavior:** The program should handle a manifest with 0 or 1 container, and *isBalanced* returns True.

```
if count <= 1:
    return True, 0, 0
```

7.2 Quality of Solution

To verify the correctness of our ship-balancing program, we designed a series of controlled tests with known expected outcomes [3].

Test Categories:

1. **Empty/1 Container Ships** – We tested manifests such as *ShipCase1.txt* and *ShipCase9test.txt*, where ships were considered pre-balanced because they had no containers. The program correctly identified these cases immediately without attempting unnecessary moves, demonstrating proper balance validation logic. Refer to Figure 9 above to see the traces for *ShipCase1.txt* and Figure 23 below for the trace for *ShipCase9test.txt*.

```
(base) allenbiju@Allens-MacBook-Pro-2 src % python main.py
-----
Enter a manifest: (or press ENTER to quit): ShipCase9test.txt

Ship Layout:

Row 08 | ... ... ... ... ... | ... ... ... ... ...
Row 07 | ... ... ... ... ... | ... ... ... ... ...
Row 06 | ... ... ... ... ... | ... ... ... ... ...
Row 05 | ... ... ... ... ... | ... ... ... ... ...
Row 04 | ... ... ... ... ... | ... ... ... ... ...
Row 03 | ... ... ... ... ... | ... ... ... ... ...
Row 02 | ... ... ... ... ... | ... ... ... ... ...
Row 01 | XXX ... ... ... ... | 405 ... ... ... XXX
      | 01 02 03 04 05 06 | 07 08 09 10 11 12
      -----

Ship is already legally balanced.

I have written an updated manifest as ShipCase9testOUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.
```

Figure 23: Trace Output for 1 Container Ship (*ShipCase9test.txt*)

2. **Already Balanced Ships** – We created a manifest, *ShipCase7test.txt*, with four containers pre-balanced according to the 10% rule. Once again, the program correctly identified these cases immediately without attempting unnecessary moves. Figure 24 below shows the trace of this test case.

```

-----
Enter a manifest: (or press ENTER to quit): ShipCase7test.txt

Ship Layout:

Row 08 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 07 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 06 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 05 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 04 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 03 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 02 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 01 | XXX 100 100 ...  ...  ...  | 100 100 ...  ...  ...  XXX
      01  02  03  04  05  06  |  07  08  09  10  11  12
-----

Ship is already legally balanced.

I have written an updated manifest as ShipCase7testOUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

```

Figure 24: Trace Output for Pre-Balanced Ship (*ShipCase7test.txt*)

3. **2 Container Ships** – We created a manifest, called *ShipCase8test.txt*, where two containers were considered pre-balanced due to being on opposite sides of the ship. Once again, the program correctly identifies this case without attempting unnecessary moves. Figure 25 below shows the trace of this test case.

```

-----
Enter a manifest: (or press ENTER to quit): ShipCase8test.txt

Ship Layout:

Row 08 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 07 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 06 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 05 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 04 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 03 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 02 | ...  ...  ...  ...  ...  ...  |  ...  ...  ...  ...  ...  ...
Row 01 | XXX 500 ...  ...  ...  ...  | 100 ...  ...  ...  ...  XXX
      01  02  03  04  05  06  |  07  08  09  10  11  12
-----

Ship is already legally balanced.

I have written an updated manifest as ShipCase8testOUTBOUND.txt
Don't forget to email it to the captain.
Hit ENTER when done.

```

Figure 25: Trace Output for Ship with 2 Containers (*ShipCase8test.txt*)

4. **Top-Of-Stack Test** – We tested manifests, such as *ShipCase4.txt*, where the balancing method would require lifting and moving a container out of the way to access the container below it. The program correctly lifted the container in the fewest moves and outputs the best search once again. Refer to Figure 17 to see the trace for this test.

Optimality Analysis: While our imbalance heuristic with A* does not guarantee a globally optimal solution, our results demonstrate:

- All test cases converged to a legal balance according to the 10% rule
- Move counts are reasonable and minimized (typically 3-5 moves for complex cases)
- No excessive backtracking or redundant moves observed

The deterministic container selection ensures reproducible results, making the system reliable for operator use.

7.3 Algorithm Performance

The ship-balancing system uses deterministic A* search to find sequences of container moves that legally balance a ship [4]. The algorithm searches for possible moves and prioritizes those that reduce the weight imbalance between the port and starboard. A* can produce effective and efficient moves at an optimal amount of time to balance each configuration. It outputs a solution that yields a fully balanced ship with the fewest possible moves, thereby maximizing productivity.

Building upon the inherent efficiency of the A* search algorithm, our system delivers high-speed performance. The program's runtime is consistently under five minutes for all test cases. The program is designed for linear scalability, maintaining its sub-five-minute runtime even when processing significantly larger manifest datasets.

Final Test

The results in Table 3 show that the algorithm consistently reaches a legal balance while keeping the number of required moves low. Most cases are resolved with only one or two container relocations, and the total runtime remains stable at roughly half a minute per file. This indicates that the procedure scales reliably across ships of different sizes without unnecessary computation.

The container counts and movements also show that the algorithm targets only the containers that meaningfully affect the ship's balance. When the 10% rule can be met, the algorithm reaches that state directly. In the few cases where the weight distribution makes perfect balance impossible, it still satisfies the two-container exception by placing an appropriate pair of containers on opposite sides of the ship to achieve the closest feasible balance.

Overall, the data demonstrate that the algorithm efficiently and consistently corrects the imbalance, producing valid configurations with minimal moves and a predictable runtime.

Table 3: A* Ship Load Balancing Results Table

Test Cases	Number of Moves	Total Time Taken (min)	Containers on Ship	Containers Moved	P-S	Satisfies 10%?	² Container Exception?
<i>ShipCase1.txt</i>	0	0	0	0	0	Yes	——
<i>ShipCase2.txt</i>	0	0	0	0	0	Yes	——
<i>ShipCase3.txt</i>	3	26	2	1	61	No	Yes
<i>ShipCase4.txt</i>	5	28	3	2	2	Yes	——
<i>ShipCase5.txt</i>	5	28	6	2	2	Yes	——
<i>ShipCase6.txt</i>	3	26	6	1	79	Yes	——
<i>HMM_Algeci ras.txt</i>	3	26	2	1	177	No	Yes

Conclusion

In this project, we developed a ship-balancing system that Mr. Keogh can use to ensure each ship that passes his port is balanced correctly, meets legal safety requirements, and remains within the legal 10% balance requirement. When the ship is imbalanced, the program uses deterministic A* search to compute an efficient sequence of moves for the containers [4]. Those moves are translated into instructions for the operator and result in an updated outbound manifest reflecting the corrected container configuration.

We ensured that the imbalance on each ship improved with each move by calculating port-to-starboard weight differences and verifying the results using plots generated for each test case. This verification shows that our system produces the necessary ship balance with accuracy and efficiency.

References

- [1] Keogh, E. (n.d.). *Problem3_overview_by_Mr_Keogh* [Dropbox slides].
- [2] Keogh, E. (n.d.). *P3_test_cases* [Dropbox slides].
- [3] Keogh, E. (n.d.). *Binary_Test* [Dropbox slides].
- [4] GeeksforGeeks. *A Search Algorithm*. <https://www.geeksforgeeks.org/dsa/a-search-algorithm/>
- [5] DataCamp. *Manhattan Distance Tutorial*. <https://www.datacamp.com/tutorial/manhattan-distance>
- [6] GeeksforGeeks. *Maximum Manhattan Distance Between a Distinct Pair from N Coordinates*. <https://www.geeksforgeeks.org/dsa/maximum-manhattan-distance-between-a-distinct-pair-from-n-coordinates/>