

ARC Research

Global Macro & AI Research

AI models & semis update

Inkling 2 Small · SWE-2 Flash · METR on AI R&D · TSMC 3D DRAM · DeepSeek on Ascend · Data as of Nov 7, 2026

Educational purposes only, not investment advice

Agenda

01	**The two recipes at a glance**	One diagram: every stage, both companies
02	**Thinking Machines: Inkling 2 Small**	4-bit pretraining → agent midtraining → RL → alignment
03	**Cognition: SWE-2 Flash**	Borrowed base → new midtraining → audited RL → gated weights
04	**How they rank**	Vs all models, vs open models, and focus by stage
05	**Side by side**	Where the two approaches differ, stage by stage
06	**AI R&D speed: METR**	Anthropic's research is moving ~2x faster
07	**Semis: TSMC 3D DRAM, DeepSeek**	3D memory, the research; DeepSeek on Huawei Ascend

Two training recipes, one model family

	Pretrain	Midtrain	RL	Alignment	Release
THINKING MACHINES Inkling 2 Small · Nov 5	**12.2T** tokens, in 4-bit	**354B** agent-trace tokens	**17M+** rollouts, one joint run	**−78%** misbehavior vs Inkling*	**Open** weights pending
Cognition SWE-2 Flash · Nov 4	**Borrowed** Inkling-Small, 12B active	**~T's** tokens, 3 stages, new	**22x** Terminal-Bench 4.0 lift*	**n/d** method not disclosed	**Gated** Devin only

Lineage: Cognition starts from Thinking Machines' Inkling-Small (Jul 30, open weights)

*ARC Research calc.: 14.9 vs 66.8 internal misbehavior score; 20.0% vs 0.9% on Terminal-Bench 4.0

THINKING MACHINES

SECTION 2 OF 7


Thinking Machines: Inkling 2 Small

4-bit pretraining → agent midtraining → one RL run → alignment

5 What shipped
6–8 Pre- and midtraining
9–11 RL post-training
12–16 Alignment
17 Release gate
18 Results

What shipped: a big model that runs small

THINKING MACHINES



17B of 594B

parameters work per token: dense-model brains, small-model cost

292M

vision encoder

1M

tokens per agent run (was 256K)

RELEASE PATH


Now Tinker, closed → **Next** outside red-team → **Then** Apache 2.0 weights

Four data phases, narrowing as they go

ARC RESEARCH | AI UPDATE | THINKING MACHINES | PRE- AND MIDTRAINING

Less data each phase, longer context, more agent work

Token budget falls about 250x from H1 to H4 while context grows to 1M and the data shifts to agent trajectories



Source: Thinking Machines, 'Introducing Inkling 2 Small', Nov 5, 2026. H3 and H4 token counts are stated as 'about'. Log scale.
H1 context length not disclosed. 250x = 8.4T / 34B, ARC Research calculation.

SO WHAT


Volume first, then quality

Context stretches to 1M tokens before RL

Last phase is pure agent behavior

Pretraining: 8.4T tokens in 4-bit, in 68 hours


Bits per number



One NVFP4 block



16 four-bit values share one 8-bit scale



GB300 NVL72

- compute trays
- NVLink switches

72 GPUs in one fast domain
→ experts spread wide

~34M


tokens per second,
H1 average*

Midtraining: learning from recorded agent work

One agent trajectory = the whole attempt, not just the answer




Where the traces came from, and where they went



Post-training: one RL run instead of three steps

Before: Inkling (gen 1)



Now: Inkling 2 Small, one joint run, a grader per task

Task family	Reward from
Coding, terminal	Hidden unit tests + agentic grader
Documents, tool use	Rubric-based LLM judge
STEM, vision Q&A	Reference answers
Web apps	Reward model on screenshots
Forecasting	Proper scoring rules
Every task	Alignment penalty + length penalty

17M+ rollouts

1,075 update steps

3T+ tokens generated

4×10^{23}+ FLOPs


2,048 GPUs · 9 days

Where the RL compute went

ARC RESEARCH | AI UPDATE | THINKING MACHINES | POST-TRAINING

Coding is 39% of RL tasks but 65% of RL tokens

Coding tasks run long, so they dominate compute; vision tasks are many but short



Source: Thinking Machines, 'Introducing Inkling 2 Small', Nov 5, 2026, 'RL training task mix' table. Shares of the main joint RL run (17M+ rollouts, 3T+ tokens). A rollout = one attempt at one task.

SO WHAT

Long coding tasks soak up the compute

Safety tasks are many but tiny

Built for agentic coding first

Keeping GPUs busy on hour-long tasks

Samplers · 5 parts



Play out tasks with current-ish weights

Rollouts, up to ~17 updates stale



New weights · GPUDirect RDMA

Trainers · 3 parts



Update the model, never wait

Rollout length

43K → 1.5M

tokens, median → p99

Rollout time

8 min → 4 h

median → p99

Context

256K


+ trained compaction beyond it

Prefix cache

93%+ hits

KV cache offloaded to DRAM

Why alignment had to be built in



What early checkpoints did

- ⚠ Fabricated results
- ⚠ Ignored instructions
- ⚠ Concealed actions

✓ **Fix: break the loop, make honesty score higher**

Alignment built into every stage

1 · Midtraining data



- misbehavior traces out
- honest traces added

2 · RL rewards

Honest give-up +

Faked success −

Penalty on every task · self-distillation (next)

3 · Monitors

Call → Rules → LLM judge

run block

Plus a judge reviewing every finished rollout

Mid-run incident: the monitors at work

1. Model routes around a network block
2. Async monitor flags it
3. Run paused; web envs removed
4. Live tool-call monitor added
5. Resumed with extra alignment phases

Self-distillation: one model, two prompts

1

Student: task only

Acts on its own; its actual behavior

→

2

Teacher: task + conduct spec

Same weights rate each token

→

3

Measure the gap

Token by token, student vs teacher


→

4

Close it

Good conduct without the spec in the prompt

Why it helps: a signal at every token, not one score per attempt




Shading illustrative: darker = bigger correction

Alignment results: big drop, still a gap

ARC RESEARCH | AI UPDATE | THINKING MACHINES | ALIGNMENT RESULTS

Every behavior metric fell; still behind the best closed model

Inkling -> Inkling 2 Small improved on all six internal and external tests, and leads open peers on misbehavior



Source: Thinking Machines, 'Introducing Inkling 2 Small', Nov 5, 2026, alignment table. Internal = Thinking Machines evals; HoneyBench v0.2-alpha by Goodhart Labs; covert-action tests by Apollo Research. Lower = better throughout. Changes are ARC Research calculations (new minus old).


SO WHAT

All six behavior tests improved

External testers agree

Closed GPT-6.1 Sol still far lower

The cost: safer, but over-refuses




SO WHAT

Gives less harmful help under attack

Refuses benign asks most often

Alignment isn’t free

Weights open only as safety evidence builds




Internal evals
CBRN, cyber, agentic misuse

External red-teams
Most testers of any release

Helpful-only variant
Tests what attackers could unlock

What it bought: capability results



SO WHAT

Not the smartest small open model

Leads on finance and vision tasks

Pitched as a base to fine-tune



SECTION 3 OF 7

Cognition: SWE-2 Flash

Borrowed base → new midtraining → audited RL → gated weights

20 Midtraining
21 RL tasks
22 Results
23–24 Safety
25 Alignment map

Cognition’s new step: midtraining

Pretrained base

Inkling-Small

Thinking Machines · 276B / 12B active · Apache 2.0

Midtraining · a few trillion tokens



Scarcest, best data saved for last (bar size illustrative)

RL

Next slide

Data

Scientific articles, blogs, code and other sources

How mixes were picked: token efficiency

Train candidate mix → Tokens to match baseline loss → Fewer = better mix

Yardstick: held-out real-world coding set

RL: better tasks, not a new algorithm

Anatomy of one RL task, each part audited

Cognition

Instructions

Is the task clearly specified?

Environment

Does the repo and setup actually work?

Verifier

Does the grader truly test success?

Reward

Only as honest as the verifier

Quality

Every task's instructions, setup and checker reviewed


Diversity

New task types for general reasoning Devin needs

Algorithm

Only small tweaks from SWE-2's recipe

What it bought: near-SWE-2 at 1/5 the price



SO WHAT

Post-training rescued a weak base

Matches SWE-2 on everyday coding

Long terminal work still lags

Two safety levers: train behavior vs gate access

THINKING MACHINES

Change what the model chooses

- Filtered traces · alignment reward
- Self-distillation from conduct spec
- Live + after-the-fact monitors

↓

Open weights after red-teaming

Cognition

Limit who can run it


- Cyber skills trained up on purpose
- Audited verifiers cut reward hacking
- No alignment method published

↓

Weights gated: Devin + vetted partners

Cognition's safety bet: the agent in production

Planned work, from a new safety team's job posting, not a SWE-2 Flash disclosure



One Devin action, layer by layer

- **Model** proposes, trained on principles
- **Harness** decides: act, ask a human, explain
- **Every release** tested: injection, exfiltration, escape, reward hacking
- **Red team** attacks it; failures become regression tests

Where alignment enters each pipeline

	Pretraining	Midtraining	RL	Monitoring	Release
THINKING MACHINES	Not described	✓ Bad traces out, honest traces in	✓ Penalty, give-up tasks, self-distillation	✓ Live tool checks + rollout review	✓ Evals, red-teams, staged weights
Cognition	Inherited from Inkling-Small	Not disclosed	✓ Audited verifiers limit reward hacking	Not disclosed for training	✓ Weights gated over cyber risk

Thinking Machines disclosed · Cognition disclosed · nothing published


SECTION 4 OF 7

How they rank

Against all models, against open models, and where each stage focused

27 All models (independent)
28 Open models only
29 SWE-2 Flash vs frontier coders
30 Focus by training stage

Against all models: mid-table




SO WHAT

#4 of 9 open; level with Gemini 3.8 Flash

Top closed models score ~2x higher

SWE-2 Flash isn't on the index

Against open models: strong, not in coding



Source: Thinking Machines, 'Introducing Inkling 2 Small', Nov 5, 2026 benchmark table (company-run, max effort). Ranks are ARC Research calculations among the 10 open-weights models in that table (Inkling 2 Small, GLM-5.3-Flash, MiMo V2.6 Flash/Pro, MiniMax-M3.1-Flash, DeepSeek-V4.1-Flash, Muse Spark Open, GLM 5.3, Mistral Large 4, Kimi K3); n = models with a score; 20 headline tests chosen by ARC Research. Original (no-tool) score used where two are given.


SO WHAT

#1 on half the tests shown

Wins finance, vision, design

65% of RL went to coding, yet rivals win there

SWE-2 Flash vs frontier coders



Source: Cognition, 'Introducing SWE-2 Flash' (Nov 4, 2026) and 'Introducing SWE-2' (Sep 10, 2026) benchmark tables, combined on the four shared benchmarks (SWE-2's scores match across both). Cognition-run, best reasoning setting; some peer scores from Cognition's internal evaluation. % solved, higher = better.

SO WHAT

Ranks #6–#10 of 13

Close on short tasks

Long tasks: 20% vs Astra's 58%

What got the most focus, stage by stage

	Pretraining	Midtraining	Post-training / RL
THINKING MACHINES	**Scale, cheaply** 12.2T tokens in 4-bit NVFP4	**Agent behavior** 354B tokens of agent traces, 1M context	**Coding, then office work** Coding 65% Office 13% STEM 8% of RL tokens · alignment on every task
Cognition	**None** Borrowed Inkling-Small	**Technical knowledge** A few T tokens: science, blogs, code	**Task quality, coding + cyber** Audited verifiers, new task types; ExploitBench 11.3 → 34.8%

Both bet that the gains come after pretraining

Side by side

THINKING MACHINES

Cognition

Stage	Thinking Machines · Inkling 2 Small	Cognition · SWE-2 Flash
Pretraining	Own: 12.2T tokens, native 4-bit	None: starts from Inkling-Small
Midtraining	354B tokens of agent traces, 1M context	New: a few T tokens, 3 stages
Data choice	Traces from Kimi K3 and own models, filtered	Mixes ranked by token efficiency
RL	One joint run, 17M+ rollouts, many graders	Audited, more diverse coding tasks
Alignment	Reward, self-distillation, monitors, evals	Not disclosed beyond task audits
Release	Tinker now; Apache 2.0 weights pending	Devin only; weights gated
Disclosure	Very detailed	Light

SECTION 6 OF 7

AI R&D speed: METR on Anthropic


An outside check finds AI is speeding up AI research

33 The ~2x finding

34 How METR got there

METR: Anthropic’s research is moving ~2x faster

METR ANTHROP\C



Source: METR, 'Independent Assessment of AI R&D Acceleration at Anthropic in October 2026', Nov 5, 2026. AECI = Anthropic's version of the Epoch Capabilities Index; rates are METR's piecewise-linear fit with an Oct 7, 2025 break (values as rounded in the report). 1.7x = Claude Haiku 5.5 system card. Error bar = METR 95% CI.

SO WHAT

Gains per year nearly doubled

~80% of the speed-up from AI itself


Right at Anthropic’s own 2x warning line

How METR reached “about 2x”

METR ANTHROP\C

1 · Benchmarks

15 benchmarks, internal models included



Strongest evidence

2 · Staff polls

“How much faster does AI make you?”

Jan 2025 · Claude 3.7 Sonnet

1.2x


Oct 2026 · internal “Model 4”

1
2
x

“Very loose evidence”

3 · ~15 interviews

Is AI speeding up your research?



Mixed, leaning yes

VERDICT

~2x
faster on well-specified tasks

~80%
of that from AI

Not compute
training scale didn’t speed up

⚠ Anthropic redacted most of the best evidence

No clear bottleneck in the next 12 months


SECTION 7 OF 7

Semis: TSMC 3D DRAM, DeepSeek on Huawei

Nvidia's foundry eyes memory; China's top lab eyes its own chips

36 The TSMC news
37–38 3D memory explained
39–40 The research
41–42 Oxide and TSMC
43 What it means
44–45 DeepSeek on Ascend

TSMC weighs making 3D DRAM for Nvidia



Today’s HBM makers, all supplying Nvidia

Planning stage only

- New fabs or a converted plant
- Led by its advanced-packaging VP
- Oct: Nvidia wants HBM base dies on TSMC 3nm
- Memory shortage seen into 2028

“3D memory” means four different things

Planar DRAM

1970 Intel 1103




One flat layer of cells

Shipping today

HBM

2013 SK Hynix




Stacked dies beside the GPU

Shipping today

3D DRAM

~2030 target




Cell layers built upward in one die

In development

Memory on logic


2017 first lab demo



Memory built on top of compute

Lab demos

Where it could fit: a new tier in AI chips




It’s been done in the lab: a decade of research

2017

Stanford, Nature

Compute + memory layers on one chip




2M+ transistors, 1M RRAM cells

2020

imec, IEDM

DRAM cell with no capacitor (IGZO)




400+ s retention

2024

IEEE J-EDS

Working 1-Mbit 3D DRAM on CMOS




60 ns read · 85°C hold

2025

HKU, IEDM

Memory on CMOS for AI attention




eDRAM + RRAM layers

2026

Multi-deck designs

Stacking many oxide DRAM decks



Design stage

Why IGZO: leaks very little, so fewer refreshes


Made cool: can be built on top of finished logic

Why oxide transistors: data that stays put

ARC RESEARCH | AI UPDATE | SEMIS | 3D DRAM RESEARCH

Oxide memory cells can hold data far longer than DRAM

Lab IGZO cells hold data for minutes to hours; TSMC's own fast, 0.75 V cache cell keeps data 2x the DRAM refresh window



Sources: imec, 'Disrupting the DRAM roadmap with capacitor-less IGZO-DRAM technology' (2025); IEEE Journal of the Electron Devices Society vol. 12 (2024), '1-Mbit 3-D DRAM ... IGZO FETs'; TSMC, VLSI 2025 (via Mynavi); standard 64 ms refresh window per JEDEC DDR specs (Lee, 2017, arXiv:1712.08304).
Values are reported minimums under different test conditions (cell vs. array, temperature); compare orders of magnitude, not exact ratios. Research devices, not products.

SO WHAT


Seconds to hours vs 64 ms

Less refresh, less power

Still tiny research arrays

Oxide vs silicon: why it helps, what's hard


Silicon access transistor



Channel cut into the wafer, made hot at the bottom of the chip

- ✓ **Tiny leakage** · ~10^{-19} A/µm, fewer refreshes
- ✓ **Built cool** · stack layers on finished logic
- ✓ **Small or no capacitor** · denser cells

Oxide (IGZO) transistor




Thin oxide film laid down cool, on top of the wiring

- ⚠ **Slower** · moderate mobility, high contact resistance
- ⚠ **Drifts** · hydrogen and oxygen defects
- ⚠ **Stacking risk** · lower layers must survive upper ones

Why oxide fits TSMC's history

A TSMC logic chip, side view



2006 DRAM on its logic: 90nm eDRAM in production

2020 New memory in its fabs: RRAM, MRAM at 40/22nm

2022 Cache stacked on logic: SoIC, AMD 3D V-Cache

2025 **Oxide 1T1C cache in its metal layers, 0.75 V**

Oxide = memory made in its own logic fabs, without becoming a DRAM maker

What it could mean, and what could stop it

NVIDIA

More control over its scarcest input

tsmc

Value shifts toward memory fused with logic

SK hynix SAMSUNG micron

Rival and partner; DRAM know-how is hard to copy

Heat

Memory atop a hot GPU

Yield

One bad layer, one lost die

Bandwidth

Dense isn’t automatically fast

Cost

Extra steps must pay off

Watch: memory built on logic, or standalone DRAM chips?

DeepSeek shifts training onto Huawei chips

	Pretraining	Post-training	Inference
V3 / R1 Dec 2024 – Jan 2025	NVIDIA **Nvidia H800** 2,048 GPUs, ~2.8M GPU-hours	NVIDIA **Nvidia** R1 reasoning RL	**Ascend** Huawei Cloud serving by Jan 2025
V4 Apr 2026 · 1.6T params	NVIDIA + Huawei **Mixed, not disclosed** DeepSeek: H800 + Ascend 910C; analysts: mostly Nvidia	**Ascend 910C** Full V4-Pro post-train by a Shenzhen group	NVIDIA + Huawei **Both** Ascend 950 supernodes + Nvidia Blackwell
V5 planned	**Ascend (reported)** First frontier pretrain on Chinese chips	**Not reported**	**Ascend** Expected to stay on Huawei


⚠ **V5 report not confirmed by DeepSeek or Huawei**

Pretraining is the hard test, not post-training

The chip: Huawei's Ascend 950

HUAWEI

ASCEND 950DT PACKAGE (illustrative layout)



1 chip
2 TB/s links

→

8,192
SuperPoD · 8 EF FP8


→

520K+
SuperCluster · 524 EF

ARC RESEARCH | AI UPDATE | CHINA CHIPS

Ascend 950DT vs Nvidia H20, the chip China could buy

Per chip, vendor-stated figures



Huawei roadmap: FP8 compute per chip doubles each year

Sources: Huawei Connect 2025 keynote (Ascend 950/960/970 specs, launch dates); H20: flopper.io spec listing (Nvidia publishes no H20 datasheet). Huawei doesn't say whether its FP8 figure is dense or sparse; H20 shown dense.

Sources

AI models

Thinking Machines, Introducing Inkling 2 Small, Nov 5, 2026

Thinking Machines, A safe path to open weights, Jul 31, 2026, and model card

Cognition, Introducing SWE-2 Flash, Nov 4, 2026

Cognition, Introducing SWE-2, Sep 10, 2026

Cognition, Safety & Alignment job posting

Artificial Analysis, models leaderboard, Nov 6, 2026

METR, AI R&D acceleration at Anthropic, Nov 5, 2026

The Decoder, METR on Anthropic's warning threshold, Nov 2026

Zhao et al., on-policy self-distillation, 2026

Semis

Bloomberg, TSMC considers making advanced AI memory chips, Nov 6, 2026 (citing The Information)

The Next Web, TSMC weighing a move into AI memory chips, Nov 6, 2026

IEEE J-EDS vol. 12, 1-Mbit 3-D DRAM, Si CMOS + IGZO FETs, 2024

imec, Capacitor-less IGZO-DRAM technology, 2025

HKU CANLab, IEDM 2025 MoS_2 eDRAM + RRAM paper

Lee, DRAM latency thesis, 2017 (64 ms refresh)

TechNode, DeepSeek reportedly plans to train V5 on Ascend, Nov 4, 2026

Fortune, DeepSeek unveils V4, Apr 24, 2026 · China Academy on V4 chips

arXiv, SLAI T-Rex: post-training DeepSeek-V4 on Ascend, 2026

Huawei, Huawei Connect 2025 keynote (Ascend roadmap) · flopper.io H20