



University of
Nottingham

UK | CHINA | MALAYSIA

Project Proposal: Gait Recognition Using Deep Learning

Submitted 2021/10/14, in partial fulfillment of
the conditions for the award of the degree **BSc Hons Computer Science with
Artificial Intelligence.**

Shiliang Chen
20125016

Supervised by Jianfeng Ren

School of Computer Science University of Nottingham Ningbo China

Chapter 1

Aims and Objectives

The main objective of this project is to develop a deep learning based method in order to recognise people by their radar gait features. The objective method would be able to learn individuals' gait features through several well processed radar time-frequency diagrams and recognise their identity by the learned model using deep learning. Apart from the main objective, the method is hopefully to be presented in a conference. The main objective could be divided into several sub-aspects to achieve:

1. Study the micro-Doppler phenomenon and justify the possibility of applying it to recognise human gait.
2. Process the raw radar signal for clear, recognisable and regular diagrams. The raw micro-Doppler radar signal is obtained in a 2D representation, which can be fairly noisy and hard for deep learning methods to extract and learn features. Thus, this step is to investigate the signal processing techniques to obtain suitable diagrams for learning.
3. Explore and investigate possible deep learning methods existing in the industry to test and find an efficient way to classify and recognise gait features accurately.
4. Design and develop a novel method by investigating different radar signal representations and applying them to obtain better performance in gait recognition.
5. Compare and evaluate existing methods and the method I proposed.

Chapter 2

Background and Motivation

Gait, an important biological characteristic of humans, can be measured at great distances, and its recognition has become an attractive research area with many applications such as public safety monitoring [1], health screening [2] and human-computer interaction [3, 4].

Superimposed sequences of images captured by optical sensors have been commonly used to represent walking people [5, 6]. However, this approach requires the images to be captured from the side and depends heavily on the lighting conditions. The real photographs taken may also violate the privacy of individuals. Doppler radar can capture the micro-Doppler (mD) signatures of a moving target’s gait feature from the front [7], and it has been demonstrated that mD signals can reveal human dynamic features and ascertain human actions and gestures by some study [7, 8, 9]. More importantly, the radar signal is less invasive of privacy and works even in low-light conditions, making it robust in a variety of real-world situations [4]. Thus, in this project, I mainly focus on the recognition using mD signatures.

The spectrogram is a time-varying representation of mD signatures in the joint time-frequency domain [7]. As the mD effect induced by mechanical vibrating or rotating structures of a target is stable and constant, the Doppler frequency caused by that target could be well formulated by a function of dwell time [10]. Thus, the time-frequency spectrogram of mD signatures could be useful to represent a moving target and further be commonly used in gait recognition and classification [9, 11, 12, 13, 14]. However, even the same person could have slightly different gait cycles and different start location of each cycle, which would lead to degradation in classification performance. The repetition information of those frequencies is scarcely considered but is also the invariant feature of gait cycles.

The Cadence Velocity Diagram (CVD) is another form of mD signatures converted from the spectrogram by taking Fast Fourier Transform (FFT) along the time axis [15]. The CVD is less commonly used in the gait recognition [16, 17]. Although the transformation eliminates the temporal information of speed, the CVD provides another useful measure on the frequency of different velocities of body parts repeat, which is complementary to the spectrogram.

Different kinds of traditional learning paradigms, such as naive Bayes [18], SVM [2] and KNN [19] have been used to classify mD signatures. However, their nature of relying on hand-crafted features makes them lose their edge in automatically learning informative features compared to deep learning methods such as deep convolutional neural networks. Several researchers have investigated deep convolutional neural networks (CNN) to implement the classification of human gestures and human actions [20, 13]. [7] has developed temporal convolutional neural network for spectrogram, and [21] has utilised a dual-channel network to classify gait features. However, they did not exploit the latent of CVD, and their use of CNN ignored the unique physical nature of radar signal. Thus, the author will be trying to find a suitable way to address the issues in this project.

Chapter 3

Project Plan

The project is research oriented, so several research processes shall be strictly included. The first step would be necessary literature review. Since radar signal is a new field for me, relevant knowledge about different representations of radar signal and the meaning of micro-Doppler is required to be learned. Then radar signal processing techniques would be necessary to master. After figuring out how to process and represent radar signal in a proper form, feature extraction techniques are required to be studied. Since this project is closely linked to deep learning, this step would contain exploration in deep learning methods related or unrelated to the gait recognition as some research may already find ways to cope with radar gait features and some methods can be transferred to this area. After literature review, reproduction of some valuable existing ideas would be conducted to verify their availability, and new ideas might be raised in this stage by evaluating the existing ones. Experiments would be conducted to test some of the proposed ideas about the methods. According to the experimental results, there would be several sprints to evaluate and improve the proposed method. A proper deep learning based method for radar gait recognition would be proposed and evaluated at the end.

The timeline of the project is illustrated in a Gantt chart shown below. The chart could automatically present the bar of a corresponding length by entering the start date and duration. The bars in different colours denote different status. Purple means complete status, and yellow refers to beyond the plan. Beginning from October 10 to April 4, there are 28 weeks in total, and the plan would have seven stages in total. The project is deliberately most arranged in the first semester for submitting a conference paper.

1. Preliminary work
2. Literature review
3. Design & experiment
4. Interim report
5. Conference paper
6. Final report




Figure 3.1: Project Plan

References

- [1] Arunesh Roy, Nicholas Gale, and Lang Hong. Automated traffic surveillance using fusion of Doppler radar and video information. *Mathematical and Computer Modelling*, 54(1-2):531–543, 2011.
- [2] Rezaul K Begg, Marimuthu Palaniswami, and Brendan Owen. Support vector machines for automated gait classification. *IEEE Trans. Biomed. Eng.*, 52(5):828–838, 2005.
- [3] Zhenyuan Zhang, Zengshan Tian, and Mu Zhou. Latern: Dynamic continuous hand gesture recognition using FMCW radar sensor. *IEEE Sensors J.*, 18(8):3278–3289, 2018.
- [4] Zhen Meng, Song Fu, Jie Yan, Hongyuan Liang, Anfu Zhou, Shilin Zhu, Huadong Ma, Jianhua Liu, and Ning Yang. Gait recognition for co-existing multiple people using millimeter wave sensing. In *Proc. AAAI*, volume 34, pages 849–856, 2020.
- [5] Rijun Liao, Shiqi Yu, Weizhi An, and Yongzhen Huang. A model-based gait recognition method with body pose and human prior knowledge. *Pattern Recognit.*, 98:107069, 2020.
- [6] Hanqing Chao, Yiwei He, Junping Zhang, and Jianfeng Feng. Gaitset: Regarding gait as a set for cross-view gait recognition. In *Proc. AAAI*, volume 33, pages 8126–8133, 2019.
- [7] Pia Addabbo, Mario Luca Bernardi, Filippo Biondi, Marta Cimitile, Carmine Clemente, and Danilo Orlando. Temporal convolutional neural networks for radar micro-Doppler based gait recognition. *Sensors*, 21(2):381, 2021.
- [8] Xueru Bai, Ye Hui, Li Wang, and Feng Zhou. Radar-based human gait recognition using dual-channel deep convolutional neural network. *IEEE Trans. Geosci. Remote Sens.*, 57(12):9767–9778, 2019.
- [9] Hoang Thanh Le, Son Lam Phung, Abdesselam Bouzerdoum, and Fok Hing Chi Tivive. Human motion classification with micro-Doppler radar and Bayesian-optimized convolutional neural networks. In *Proc. IEEE Int. Conf. Acoustics, Speech Signal Process.*, pages 2961–2965. IEEE, 2018.
- [10] V.C. Chen. Analysis of radar micro-Doppler with time-frequency transform. In *Proc. IEEE Workshop on Statistical Signal and Array Processing*, pages 463–466, 2000.
- [11] Dave Tahmoush and Jerry Silvius. Radar micro-Doppler for long range front-view gait recognition. In *Proc. 2009 IEEE 3rd International Conference on Biometrics: Theory, Applications, and Systems*, pages 1–6. IEEE, 2009.
- [12] Zhaonian Zhang and Andreas G Andreou. Human identification experiments using acoustic micro-Doppler signatures. In *Proc. the 2008 Argentine School of Micro-Nanoelectronics, Technology and Applications*, pages 81–86. IEEE, 2008.

- [13] Xingshuai Qiao, Tao Shan, and Ran Tao. Human identification based on radar micro-Doppler signatures separation. *Electronics Letters*, 56(4):195–196, 2020.
- [14] Youngwook Kim and Taesup Moon. Human detection and activity classification based on micro-Doppler signatures using deep convolutional neural networks. *IEEE Geosci. Remote Sens. Lett.*, 13(1):8–12, 2015.
- [15] Svante Björklund, Tommy Johansson, and Henrik Petersson. Evaluation of a micro-Doppler classification method on mm-wave data. In *Proc. 2012 IEEE Radar Conf.*, pages 0934–0939. IEEE, 2012.
- [16] Ann-Kathrin Seifert, Abdelhak M Zoubir, and Moeness G Amin. Radar-based human gait recognition in cane-assisted walks. In *Proc. 2017 IEEE Radar Conf.*, pages 1428–1433. IEEE, 2017.
- [17] AW Miller, C Clemente, A Robinson, D Greig, A M Kinghorn, and J J Soraghan. Micro-Doppler based target classification using multi-feature integration. In *Proc. the IET Intelligent Signal Processing Conference 2013*, pages 1–6. IET, 2013.
- [18] Francesco Fioranelli, Matthew Ritchie, and Hugh Griffiths. Centroid features for classification of armed/unarmed multiple personnel using multistatic human micro-Doppler. *IET Radar Sonar Navig.*, 10(9):1702–1710, 2016.
- [19] WL van Rossum, L Anitori, P van Dorp, JJM de Wit, and RIA Harmanny. Classification of human gaits using interrupted radar measurements. In *Proc. 2017 IEEE Radar Conf.*, pages 0514–0519. IEEE, 2017.
- [20] Peibei Cao, Weijie Xia, Ming Ye, Jutong Zhang, and Jianjiang Zhou. Radar-ID: human identification based on radar micro-Doppler signatures using deep convolutional neural networks. *IET Radar Sonar Navig.*, 12(7):729–734, 2018.
- [21] Baptist Vandersmissen, Nicolas Knudde, Azarakhsh Jalalvand, Ivo Couckuyt, Andre Bourdoux, Wesley De Neve, and Tom Dhaene. Indoor person identification using a low-power FMCW radar. *IEEE Trans. Geosci. Remote Sens.*, 56(7):3941–3952, 2018.