

---

# libgdtl Documentation

*Release latest*

May 05, 2019



<b>1</b>	<b>libgdtl Introduction</b>	<b>1</b>
<b>2</b>	<b>libgdtl API</b>	<b>5</b>



BiDi, shaping and basic text layout for Godot Engine.

## 1.1 Dependencies

- Godot 3.1+
- C++14 compiler
- Meson build system (for gdnative module build only)
- SCons build system

## 1.2 Compiling (as builtin module)

### 1.2.1 Build options

Name	Description	Default value
<code>builtin_runtime</code>	Use the built-in libraries	true
<code>use_graphite2</code>	Enable SIL Graphite 2 complementary shaper	true

### 1.2.2 Building *libgdgl* module

Clone this repository (without `-recursive` flag) into Godot's *modules* subfolder as *godot\_tl*. Rebuild Godot engine as usual.

## 1.3 Compiling (as gdnative module)

### 1.3.1 Build options

Name	Description	Default value
godot-cpp-lib-name	godot-cpp static library name (without <i>.a</i> or <i>.lib</i> extension)	libgodot-cpp
static-runtime	Link libraries statically for better portability	false
builtin-runtime	Use the built-in libraries	false
use-graphite2	Enable SIL Graphite 2 complementary shaper	true

### 1.3.2 Building *godot-cpp* static library

See <https://github.com/GodotNativeTools/godot-cpp/blob/master/README.md#compiling-the-cpp-bindings-library>

### 1.3.3 Building *libgdtl* module

You can compile this module by executing:

```
meson {Targer-Folder} -Dgodot-cpp-lib-name={Godot-CPP-Name} --buildtype=release
ninja -C {Targer-Folder}
```

## 1.4 License

- The source code of the **libgdtl** module is released under unlicense.  
For more information, see <http://unlicense.org/> or the accompanying UNLICENSE file.
- **Godot** and **GodotNativeTools** are licensed under MIT license.  
For more information, see <https://github.com/godotengine/godot/blob/master/LICENSE.txt>.
- **HarfBuzz** is licensed under MIT-like License.  
For more information, see <https://github.com/harfbuzz/harfbuzz/blob/master/COPYING>
- **ICU4C** is licensed under Unicode, Inc. License.  
For more information, see <http://www.unicode.org/copyright.html#License>
- **FreeType** is licensed under FreeType License (BSD-like) or GNU General Public License (GPL), version 2.  
For more information, see <https://www.freetype.org/license.html>
- **SIL Graphite engine** is licensed under GNU Lesser General Public License (LGPL), version 2.1+ or GNU General Public License (GPL), version 2 or Mozilla Public License.  
For more information, see <https://github.com/silnrsi/graphite/blob/master/COPYING>

## 1.5 Demo data

Montserrat (<https://github.com/JuliettaUla/Montserrat/>), Awami Nastaliq (<https://software.sil.org/awami/download/>), Comic Neue (<http://comiconeue.com/>) and Noto (<https://www.google.com/get/noto/>) fonts are published under the SIL Open Font License, Version 1.1 ([https://scripts.sil.org/cms/scripts/page.php?site\\_id=nrsi&id=OFL](https://scripts.sil.org/cms/scripts/page.php?site_id=nrsi&id=OFL))

Material Design icons by Google (<https://github.com/google/material-design-icons>) are published under the Apache License Version 2.0 (<https://www.apache.org/licenses/LICENSE-2.0.txt>)

Noto Color Emoji font is cut down to single glyph (U+1F604) using [glyphhanger](https://github.com/filamentgroup/glyphhanger) (<https://github.com/filamentgroup/glyphhanger>).





## 2.1 TLBitmapFontFace

**Inherits:** *TLFontFace*

**Category:** Core

### 2.1.1 Brief Description

An AngelCode Bitmap Font Generator bitmap font for drawing text.

### 2.1.2 Description

TLBitmapFontFace have limited shaping support.

TLBitmapFontFace doesn't support OpenType features.

## 2.2 TLDynamicFontFace

**Inherits:** *TLFontFace*

**Category:** Core

### 2.2.1 Brief Description

A TrueType, OpenType or Graphite font for drawing text.

### 2.2.2 Properties

bool	<i>force_autohinter</i>
int	<i>hinting</i>
float	<i>oversampling</i>

## 2.2.3 Methods

bool	<i>has_graphite</i> ( ) const
------	-------------------------------

## 2.2.4 Enumerations

enum **DynamicFaceHinting**:

- **DF\_HINTING\_NONE = 0** — Disable font hinting (smoother but less crisp)
- **DF\_HINTING\_LIGHT = 1** — Use the light font hinting mode
- **DF\_HINTING\_NORMAL = 2** — Use the default font hinting mode (crisper but less smooth)

## 2.2.5 Property Descriptions

- bool **force\_autohinter**

<i>Setter</i>	set_force_autohinter(value)
<i>Getter</i>	get_force_autohinter()

If `true`, prefers FreeType auto-hinter over the font’s native hinter. Default: `false`

- int **hinting**

<i>Setter</i>	set_hinting(value)
<i>Getter</i>	get_hinting()

The font hinting mode used by FreeType auto-hinter. Default: `DF_HINTING_NONE`

- float **oversampling**

<i>Setter</i>	set_oversampling(value)
<i>Getter</i>	get_oversampling()

Font oversampling factor. Default: `1.0`

## 2.2.6 Method Descriptions

- bool **has\_graphite** ( ) const

Returns `true` if module is built with SIL Graphite 2 shaper support.

# 2.3 TLFontFace

**Inherits:**

**Inherited By:** *TLBitmapFontFace*, *TLDynamicFontFace*

**Category:** Core

## 2.3.1 Brief Description

\*Virtual class\*

A base font face class.

## 2.3.2 Properties

String	<i>font_path</i>
int	<i>texture_flags</i>

## 2.3.3 Methods

void	<i>draw_glyph</i> ( RID canvas_item, Vector2 pos, int codepoint, Color modulate, int size ) const
void	<i>draw_glyph_outline</i> ( RID canvas_item, Vector2 pos, int codepoint, Color modulate, int size ) const
float	<i>get_ascent</i> ( int size ) const
int	<i>get_base_size</i> ( ) const
float	<i>get_descent</i> ( int size ) const
Array	<i>get_glyph_outline</i> ( Vector2 pos, int codepoint, int size ) const
float	<i>get_height</i> ( int size ) const
bool	<i>load</i> ( String resource_path )
Array	<i>unicode_scripts_supported</i> ( ) const

## 2.3.4 Property Descriptions

- String **font\_path**

<i>Setter</i>	set_font_path(value)
<i>Getter</i>	get_font_path()

- int **texture\_flags**

<i>Setter</i>	set_texture_flags(value)
<i>Getter</i>	get_texture_flags()

Font texture flags. Default: FLAG\_VIDEO\_SURFACE

## 2.3.5 Method Descriptions

- void **draw\_glyph** ( RID canvas\_item, Vector2 pos, int codepoint, Color modulate, int size ) const

Draws a single glyph.

- void **draw\_glyph\_outline** ( RID canvas\_item, Vector2 pos, int codepoint, Color modulate, int size ) const

Draws single glyph outline.

- float **get\_ascent** ( int size ) const

Returns ascent (distance from the baseline to the highest position characters extend to) of the font.

- int **get\_base\_size** ( ) const

Returns default font size for bitmap fonts or 0 for dynamic fonts.

- float **get\_descent** ( int size ) const

Returns descent (distance from the base line to the lowest point characters extend to) of the font.

- Array **get\_glyph\_outline** ( Vector2 pos, int codepoint, int size ) const
- float **get\_height** ( int size ) const

Returns height (vertical distance between two consecutive baselines) of the font.

- bool **load** ( String resource\_path )

Loads font from speified file.

- Array **unicode\_scripts\_supported** ( ) const

## 2.4 TLFontFamily

**Inherits:**

**Category:** Core

### 2.4.1 Brief Description

A set of fonts that make up a font family.

### 2.4.2 Methods

void	<i>add_face</i> ( String style, <i>TLFontFace</i> ref )
void	<i>add_face_for_language</i> ( String style, <i>TLFontFace</i> ref, String lang )
void	<i>add_face_for_script</i> ( String style, <i>TLFontFace</i> ref, String script )
bool	<i>has_style</i> ( String style ) const
void	<i>remove_style</i> ( String style )

### 2.4.3 Method Descriptions

- void **add\_face** ( String style, *TLFontFace* ref )
- void **add\_face\_for\_language** ( String style, *TLFontFace* ref, String lang )
- void **add\_face\_for\_script** ( String style, *TLFontFace* ref, String script )
- bool **has\_style** ( String style ) const
- void **remove\_style** ( String style )

## 2.5 TLICUDataLoader

**Inherits:**

**Category:** Core

### 2.5.1 Brief Description

Helper class that handles ICU data loading.

### 2.5.2 Properties

String	<i>data_path</i>
--------	------------------

### 2.5.3 Methods

bool	<i>load</i> ( String resource_path )
------	--------------------------------------

## 2.5.4 Property Descriptions

- String `data_path`

<i>Setter</i>	<code>set_data_path(value)</code>
<i>Getter</i>	<code>get_data_path()</code>

## 2.5.5 Method Descriptions

- bool `load` ( String `resource_path` )

Loads ICU data file, should be done at most once in a process, before the first ICU operation. Returns `true` if function succeeds.

## 2.6 TLLabel

**Inherits:**

**Category:** Core

### 2.6.1 Brief Description

### 2.6.2 Properties

int	<i>align</i>
bool	<i>autowrap</i>
<i>TLFontFamily</i>	<i>base_font</i>
int	<i>base_font_size</i>
String	<i>base_font_style</i>
bool	<i>clip_text</i>
String	<i>language</i>
String	<i>ot_features</i>
String	<i>text</i>
int	<i>text_direction</i>
bool	<i>uppercase</i>
int	<i>valign</i>

### 2.6.3 Methods

int	<i>get_line_count</i> ( ) const
int	<i>get_line_height</i> ( ) const
int	<i>get_lines_skipped</i> ( ) const
int	<i>get_max_lines_visible</i> ( ) const
float	<i>get_percent_visible</i> ( ) const
int	<i>get_total_character_count</i> ( ) const
int	<i>get_visible_characters</i> ( ) const
int	<i>get_visible_line_count</i> ( ) const
void	<i>set_lines_skipped</i> ( int <i>lines_skipped</i> )
void	<i>set_max_lines_visible</i> ( int <i>lines_visible</i> )
void	<i>set_percent_visible</i> ( float <i>percent_visible</i> )
void	<i>set_visible_characters</i> ( int <i>amount</i> )

## 2.6.4 Enumerations

enum **Align**:

- **ALIGN\_LEFT** = 0
- **ALIGN\_CENTER** = 1
- **ALIGN\_RIGHT** = 2
- **ALIGN\_FILL** = 3

enum **VAlign**:

- **VALIGN\_TOP** = 0
- **VALIGN\_CENTER** = 1
- **VALIGN\_BOTTOM** = 2
- **VALIGN\_FILL** = 3

## 2.6.5 Property Descriptions

- int **align**

<i>Setter</i>	set_align(value)
<i>Getter</i>	get_align()

- bool **autowrap**

<i>Setter</i>	set_autowrap(value)
<i>Getter</i>	has_autowrap()

- *TLFontFamily* **base\_font**

<i>Setter</i>	set_base_font(value)
<i>Getter</i>	get_base_font()

- int **base\_font\_size**

<i>Setter</i>	set_base_font_size(value)
<i>Getter</i>	get_base_font_size()

- String **base\_font\_style**

<i>Setter</i>	set_base_font_style(value)
<i>Getter</i>	get_base_font_style()

- bool **clip\_text**

<i>Setter</i>	set_clip_text(value)
<i>Getter</i>	is_clipping_text()

- String **language**

<i>Setter</i>	set_language(value)
<i>Getter</i>	get_language()

- String **ot\_features**

<i>Setter</i>	set_ot_features(value)
<i>Getter</i>	get_ot_features()

- String **text**

<i>Setter</i>	set_text(value)
<i>Getter</i>	get_text()

- int **text\_direction**

<i>Setter</i>	set_text_direction(value)
<i>Getter</i>	get_text_direction()

- bool **uppercase**

<i>Setter</i>	set_uppercase(value)
<i>Getter</i>	is_uppercase()

- int **valign**

<i>Setter</i>	set_valign(value)
<i>Getter</i>	get_valign()

## 2.6.6 Method Descriptions

- int **get\_line\_count** ( ) const
- int **get\_line\_height** ( ) const
- int **get\_lines\_skipped** ( ) const
- int **get\_max\_lines\_visible** ( ) const
- float **get\_percent\_visible** ( ) const
- int **get\_total\_character\_count** ( ) const
- int **get\_visible\_characters** ( ) const
- int **get\_visible\_line\_count** ( ) const
- void **set\_lines\_skipped** ( int lines\_skipped )
- void **set\_max\_lines\_visible** ( int lines\_visible )
- void **set\_percent\_visible** ( float percent\_visible )
- void **set\_visible\_characters** ( int amount )

## 2.7 TLLineEdit

**Inherits:**

**Category:** Core

### 2.7.1 Brief Description

### 2.7.2 Properties

int	<i>align</i>
<i>TLFontFamily</i>	<i>base_font</i>
int	<i>base_font_size</i>
String	<i>base_font_style</i>
bool	<i>caret_blink</i>
float	<i>caret_blink_speed</i>
int	<i>caret_position</i>
bool	<i>clear_button_enabled</i>
bool	<i>context_menu_enabled</i>
bool	<i>editable</i>
bool	<i>expand_to_text_length</i>
Control.FocusMode	<i>focus_mode</i>
String	<i>language</i>
int	<i>max_length</i>
String	<i>ot_features</i>
float	<i>placeholder_alpha</i>
String	<i>placeholder_text</i>
bool	<i>secret</i>
String	<i>secret_character</i>
String	<i>text</i>
int	<i>text_direction</i>

### 2.7.3 Methods

void	<i>append_at_cursor</i> ( String text )
void	<i>clear</i> ( )
void	<i>deselect</i> ( )
PopupMenu	<i>get_menu</i> ( ) const
void	<i>menu_option</i> ( int option )
void	<i>select</i> ( int from=0, int to=-1 )
void	<i>select_all</i> ( )

### 2.7.4 Signals

- **text\_changed** ( String new\_text )
- **text\_entered** ( String new\_text )

### 2.7.5 Enumerations

enum **Align**:

- **ALIGN\_LEFT** = 0



- **ALIGN\_CENTER = 1**
- **ALIGN\_RIGHT = 2**
- **ALIGN\_FILL = 3**

enum **MenuItems**:

- **MENU\_CUT = 0**
- **MENU\_COPY = 1**
- **MENU\_PASTE = 2**
- **MENU\_CLEAR = 3**
- **MENU\_SELECT\_ALL = 4**
- **MENU\_UNDO = 5**
- **MENU\_REDO = 6**
- **MENU\_MAX = 7**

## 2.7.6 Property Descriptions

- int **align**

<i>Setter</i>	set_align(value)
<i>Getter</i>	get_align()

- *TLFontFamily* **base\_font**

<i>Setter</i>	set_base_font(value)
<i>Getter</i>	get_base_font()

- int **base\_font\_size**

<i>Setter</i>	set_base_font_size(value)
<i>Getter</i>	get_base_font_size()

- String **base\_font\_style**

<i>Setter</i>	set_base_font_style(value)
<i>Getter</i>	get_base_font_style()

- bool **caret\_blink**

<i>Setter</i>	cursor_set_blink_enabled(value)
<i>Getter</i>	cursor_get_blink_enabled()

- float **caret\_blink\_speed**

<i>Setter</i>	cursor_set_blink_speed(value)
<i>Getter</i>	cursor_get_blink_speed()

- int **caret\_position**

<i>Setter</i>	set_cursor_position(value)
<i>Getter</i>	get_cursor_position()

- bool **clear\_button\_enabled**

<i>Setter</i>	set_clear_button_enabled(value)
<i>Getter</i>	is_clear_button_enabled()

- bool **context\_menu\_enabled**

<i>Setter</i>	set_context_menu_enabled(value)
<i>Getter</i>	is_context_menu_enabled()

- bool **editable**

<i>Setter</i>	set_editable(value)
<i>Getter</i>	is_editable()

- bool **expand\_to\_text\_length**

<i>Setter</i>	set_expand_to_text_length(value)
<i>Getter</i>	get_expand_to_text_length()

- Control.FocusMode **focus\_mode**

<i>Setter</i>	set_focus_mode(value)
<i>Getter</i>	get_focus_mode()

- String **language**

<i>Setter</i>	set_language(value)
<i>Getter</i>	get_language()

- int **max\_length**

<i>Setter</i>	set_max_length(value)
<i>Getter</i>	get_max_length()

- String **ot\_features**

<i>Setter</i>	set_ot_features(value)
<i>Getter</i>	get_ot_features()

- float **placeholder\_alpha**

<i>Setter</i>	set_placeholder_alpha(value)
<i>Getter</i>	get_placeholder_alpha()

- String **placeholder\_text**

<i>Setter</i>	set_placeholder(value)
<i>Getter</i>	get_placeholder()

- bool **secret**

<i>Setter</i>	set_secret(value)
<i>Getter</i>	is_secret()

- String **secret\_character**

<i>Setter</i>	set_secret_character(value)
<i>Getter</i>	get_secret_character()

- String **text**

<i>Setter</i>	set_text(value)
<i>Getter</i>	get_text()

- int **text\_direction**

<i>Setter</i>	set_text_direction(value)
<i>Getter</i>	get_text_direction()

## 2.7.7 Method Descriptions

- void **append\_at\_cursor** ( String text )
- void **clear** ( )
- void **deselect** ( )
- PopupMenu **get\_menu** ( ) const
- void **menu\_option** ( int option )
- void **select** ( int from=0, int to=-1 )
- void **select\_all** ( )

## 2.8 TLProtoControl

**Inherits:**

**Category:** Core

### 2.8.1 Brief Description

Rich text input control prototype.

## 2.8.2 Properties

Color	<i>back_color</i>
float	<i>paragraph_spacing</i>
bool	<i>readonly</i>
bool	<i>selectable</i>

## 2.8.3 Methods

void	<i>add_attribute</i> ( <i>TLProtoControlSelection</i> selection, int attribute, Variant value )
void	<i>clear</i> ( )
void	<i>debug_draw</i> ( RID rid, Vector2 position, Vector2 hit_position, bool draw_brk_ops, bool draw_jst_ops )
void	<i>debug_draw_as_hex</i> ( RID rid, Vector2 position, Vector2 hit_position, bool draw_brk_ops, bool draw_jst_ops )
void	<i>debug_draw_logical_as_hex</i> ( RID rid, Vector2 position, Vector2 hit_position, bool draw_brk_ops, bool draw_jst_ops )
Vector2	<i>get_caret_position</i> ( )
String	<i>get_cluster_debug_info_hit_test</i> ( Vector2 position )
Array	<i>get_cluster_glyphs_hit_test</i> ( Vector2 position )
Rect2	<i>get_cluster_rect_hit_test</i> ( Vector2 position )
<i>TLShapedParagraph</i>	<i>get_paragraph</i> ( int index ) const
int	<i>get_paragraphs</i> ( )
<i>TLProtoControlSelection</i>	<i>get_selection</i> ( ) const
int	<i>insert_paragraph</i> ( <i>TLShapedParagraph</i> para, int index )
void	<i>remove_attribute</i> ( <i>TLProtoControlSelection</i> selection, int attribute )
void	<i>remove_attributes</i> ( <i>TLProtoControlSelection</i> selection )
void	<i>remove_paragraph</i> ( int index )
void	<i>replace_sstring</i> ( <i>TLProtoControlSelection</i> selection, <i>TLShapedString</i> text )
void	<i>replace_text</i> ( <i>TLProtoControlSelection</i> selection, String text )
void	<i>replace_utf16</i> ( <i>TLProtoControlSelection</i> selection, PoolByteArray text )
void	<i>replace_utf32</i> ( <i>TLProtoControlSelection</i> selection, PoolByteArray text )
void	<i>replace_utf8</i> ( <i>TLProtoControlSelection</i> selection, PoolByteArray text )
void	<i>set_paragraph</i> ( <i>TLShapedParagraph</i> para, int index )
void	<i>set_paragraph_back_color</i> ( <i>TLProtoControlSelection</i> selection, Color bcolor )
void	<i>set_paragraph_brk_flags</i> ( <i>TLProtoControlSelection</i> selection, int flags )
void	<i>set_paragraph_halign</i> ( <i>TLProtoControlSelection</i> selection, int halign )
void	<i>set_paragraph_indent</i> ( <i>TLProtoControlSelection</i> selection, float indent )
void	<i>set_paragraph_jst_flags</i> ( <i>TLProtoControlSelection</i> selection, int flags )
void	<i>set_paragraph_line_spacing</i> ( <i>TLProtoControlSelection</i> selection, float line_spacing )
void	<i>set_paragraph_width</i> ( <i>TLProtoControlSelection</i> selection, float width )
void	<i>set_selection</i> ( <i>TLProtoControlSelection</i> selection )

## 2.8.4 Signals

- *cursor\_changed* ( )
- *paragraph\_changed* ( )

## 2.8.5 Property Descriptions

- Color **back\_color**

<i>Setter</i>	set_back_color(value)
<i>Getter</i>	get_back_color()

- float **paragraph\_spacing**

<i>Setter</i>	set_paragraph_spacing(value)
<i>Getter</i>	get_paragraph_spacing()

- bool **readonly**

<i>Setter</i>	set_readonly(value)
<i>Getter</i>	get_readonly()

- bool **selectable**

<i>Setter</i>	set_selectable(value)
<i>Getter</i>	get_selectable()

## 2.8.6 Method Descriptions

- void **add\_attribute** ( *TLProtoControlSelection* selection, int attribute, Variant value )
- void **clear** ( )
- void **debug\_draw** ( RID rid, Vector2 position, Vector2 hit\_position, bool draw\_brk\_ops, bool draw\_jst\_ops )
- void **debug\_draw\_as\_hex** ( RID rid, Vector2 position, Vector2 hit\_position, bool draw\_brk\_ops, bool draw\_jst\_ops )
- void **debug\_draw\_logical\_as\_hex** ( RID rid, Vector2 position, Vector2 hit\_position, bool draw\_brk\_ops, bool draw\_jst\_ops )
- Vector2 **get\_caret\_position** ( )
- String **get\_cluster\_debug\_info\_hit\_test** ( Vector2 position )
- Array **get\_cluster\_glyphs\_hit\_test** ( Vector2 position )
- Rect2 **get\_cluster\_rect\_hit\_test** ( Vector2 position )
- *TLShapedParagraph* **get\_paragraph** ( int index ) const
- int **get\_paragraphs** ( )
- *TLProtoControlSelection* **get\_selection** ( ) const
- int **insert\_paragraph** ( *TLShapedParagraph* para, int index )
- void **remove\_attribute** ( *TLProtoControlSelection* selection, int attribute )
- void **remove\_attributes** ( *TLProtoControlSelection* selection )
- void **remove\_paragraph** ( int index )
- void **replace\_sstring** ( *TLProtoControlSelection* selection, *TLShapedString* text )
- void **replace\_text** ( *TLProtoControlSelection* selection, String text )

- void **replace\_utf16** ( *TLProtoControlSelection* selection, PoolByteArray text )
- void **replace\_utf32** ( *TLProtoControlSelection* selection, PoolByteArray text )
- void **replace\_utf8** ( *TLProtoControlSelection* selection, PoolByteArray text )
- void **set\_paragraph** ( *TLShapedParagraph* para, int index )
- void **set\_paragraph\_back\_color** ( *TLProtoControlSelection* selection, Color bcolor )
- void **set\_paragraph\_brk\_flags** ( *TLProtoControlSelection* selection, int flags )
- void **set\_paragraph\_halign** ( *TLProtoControlSelection* selection, int halign )
- void **set\_paragraph\_indent** ( *TLProtoControlSelection* selection, float indent )
- void **set\_paragraph\_jst\_flags** ( *TLProtoControlSelection* selection, int flags )
- void **set\_paragraph\_line\_spacing** ( *TLProtoControlSelection* selection, float line\_spacing )
- void **set\_paragraph\_width** ( *TLProtoControlSelection* selection, float width )
- void **set\_selection** ( *TLProtoControlSelection* selection )

## 2.9 TLProtoControlSelection

**Inherits:**

**Category:** Core

### 2.9.1 Brief Description

### 2.9.2 Properties

int	<i>caret_offset</i>
int	<i>caret_para</i>
int	<i>end_offset</i>
int	<i>end_para</i>
int	<i>start_offset</i>
int	<i>start_para</i>

### 2.9.3 Signals

- **selection\_changed** ( )

### 2.9.4 Property Descriptions

- int **caret\_offset**

<i>Setter</i>	set_caret_offset(value)
<i>Getter</i>	get_caret_offset()

- int **caret\_para**

<i>Setter</i>	set_caret_para(value)
<i>Getter</i>	get_caret_para()

- int **end\_offset**

<i>Setter</i>	set_end_offset(value)
<i>Getter</i>	get_end_offset()

- int **end\_para**

<i>Setter</i>	set_end_para(value)
<i>Getter</i>	get_end_para()

- int **start\_offset**

<i>Setter</i>	set_start_offset(value)
<i>Getter</i>	get_start_offset()

- int **start\_para**

<i>Setter</i>	set_start_para(value)
<i>Getter</i>	get_start_para()

## 2.10 TLShapedAttributedString

**Inherits:** *TLShapedString*

**Category:** Core

### 2.10.1 Brief Description

Gold's shaped line of text with associated attributes.

### 2.10.2 Methods

void	<i>add_attribute</i> ( int attribute, Variant value, int start, int end )
void	<i>clear_attributes</i> ( )
Variant	<i>get_attribute</i> ( int attribute, int index ) const
int	<i>get_attribute_end</i> ( int attribute, int index ) const
int	<i>get_attribute_start</i> ( int attribute, int index ) const
Array	<i>get_embedded_rects</i> ( )
bool	<i>has_attribute</i> ( int attribute, int index ) const
void	<i>load_attributes_dict</i> ( Array array )
void	<i>remove_attribute</i> ( int attribute, int start, int end )
void	<i>remove_attributes</i> ( int start, int end )
Array	<i>save_attributes_dict</i> ( ) const

### 2.10.3 Enumerations

enum **TextAttribute**:

- **TEXT\_ATTRIBUTE\_FONT = 1** — Font family. Attribute type: *TLFontFamily*
- **TEXT\_ATTRIBUTE\_FONT\_STYLE = 2** — Font style (Regular, Bold, Italic, Oblique etc.). Attribute type: String
- **TEXT\_ATTRIBUTE\_FONT\_SIZE = 3** — Font size. Attribute type: int

- **TEXT\_ATTRIBUTE\_FONT\_FEATURES = 4** — Comma separated list of OpenType feature tags. More info: <https://docs.microsoft.com/en-us/typography/opentype/spec/featuretags>. Attribute type: String
- **TEXT\_ATTRIBUTE\_LANGUAGE = 5** — Language code. Attribute type: String
- **TEXT\_ATTRIBUTE\_REPLACEMENT\_IMAGE = 6** — Embedded image. Attribute type: Texture
- **TEXT\_ATTRIBUTE\_REPLACEMENT\_RECT = 7** — Reserved space for custom embedded object. Attribute type: Vector2
- **TEXT\_ATTRIBUTE\_REPLACEMENT\_ID = 8** — Embedded object id key. Attribute type: Variant
- **TEXT\_ATTRIBUTE\_REPLACEMENT\_VALIGN = 9** — Embedded image/object inline alignment. Attribute type: TEXT\_VALIGN\_\*
- **TEXT\_ATTRIBUTE\_COLOR = 31** — Text color. Attribute type: Color
- **TEXT\_ATTRIBUTE\_OUTLINE\_COLOR = 32** — Text outline color. Attribute type: Color
- **TEXT\_ATTRIBUTE\_UNDERLINE\_COLOR = 41** — Underline color. Attribute type: Color
- **TEXT\_ATTRIBUTE\_UNDERLINE\_WIDTH = 42** — Underline width. Attribute type: int
- **TEXT\_ATTRIBUTE\_STRIKETHROUGH\_COLOR = 51** — Strikethrough line color. Attribute type: Color
- **TEXT\_ATTRIBUTE\_STRIKETHROUGH\_WIDTH = 52** — Strikethrough line width. Attribute type: int
- **TEXT\_ATTRIBUTE\_OVERLINE\_COLOR = 61** — Overline color/ Attribute type: Color
- **TEXT\_ATTRIBUTE\_OVERLINE\_WIDTH = 62** — Overline width. Attribute type: int
- **TEXT\_ATTRIBUTE\_HIGHLIGHT\_COLOR = 71** — Highlight color. Attribute type: Color
- **TEXT\_ATTRIBUTE\_META = 100** — User defined data, use TEXT\_ATTRIBUTE\_META + x to define multiple user attributes. Attribute type: Variant

enum **TextValign**:

- **TEXT\_VALIGN\_TOP = 0** — Inline vertical top alignment
- **TEXT\_VALIGN\_CENTER = 1** — Inline vertical center alignment
- **TEXT\_VALIGN\_BOTTOM = 2** — Inline vertical bottom alignment

## 2.10.4 Method Descriptions

- void **add\_attribute** ( int attribute, Variant value, int start, int end )

Sets *attribute* attribute to *value* for specified text range.

- void **clear\_attributes** ( )

Removes all attributes.

- Variant **get\_attribute** ( int attribute, int index ) const

Returns *attribute* attribute value for specified text position.

- int **get\_attribute\_end** ( int attribute, int index ) const

Returns last position of *attribute* attribute run enclosing specified position.

- int **get\_attribute\_start** ( int attribute, int index ) const

Returns first position of *attribute* attribute run enclosing specified position.

- Array **get\_embedded\_rects** ( )

Returns bounding rects of embedded objects (TEXT\_ATTRIBUTE\_REPLACEMENT\_RECT attributes).



- bool **has\_attribute** ( int attribute, int index ) const

Returns `true` if specified position has `attribute` attribute set.

- void **load\_attributes\_dict** ( Array array )

Loads attributes from Array of Dictionary.

- void **remove\_attribute** ( int attribute, int start, int end )

Removes `attribute` attribute for specified text range.

- void **remove\_attributes** ( int start, int end )

Removes all attributes for specified text range.

- Array **save\_attributes\_dict** ( ) const

Stores string attributes into Array of Dictionary.

## 2.11 TLShapedParagraph

**Inherits:**

**Category:** Core

### 2.11.1 Brief Description

### 2.11.2 Properties

Color	<i>back_color</i>
int	<i>brk_flags</i>
int	<i>halign</i>
float	<i>indent</i>
int	<i>jst_flags</i>
float	<i>line_spacing</i>
<i>TLShapedAttributedString</i>	<i>string</i>
float	<i>width</i>

### 2.11.3 Methods

void	<i>copy_properties</i> ( <i>TLShapedParagraph</i> source )
<i>TLShapedAttributedString</i>	<i>get_line</i> ( int index ) const
Array	<i>get_line_bounds</i> ( ) const
int	<i>get_lines</i> ( ) const
Vector2	<i>get_size</i> ( ) const
Array	<i>get_word_bounds</i> ( ) const

### 2.11.4 Signals

- **paragraph\_changed** ( )

### 2.11.5 Enumerations

enum **ParaHAlign**:

- **PARA\_HALIGN\_LEFT** = 0

- `PARA_HALIGN_CENTER = 1`
- `PARA_HALIGN_RIGHT = 2`
- `PARA_HALIGN_FILL = 3`

### 2.11.6 Property Descriptions

- Color **back\_color**

<i>Setter</i>	<code>set_back_color(value)</code>
<i>Getter</i>	<code>get_back_color()</code>

- int **brk\_flags**

<i>Setter</i>	<code>set_brk_flags(value)</code>
<i>Getter</i>	<code>get_brk_flags()</code>

- int **halign**

<i>Setter</i>	<code>set_halign(value)</code>
<i>Getter</i>	<code>get_halign()</code>

- float **indent**

<i>Setter</i>	<code>set_indent(value)</code>
<i>Getter</i>	<code>get_indent()</code>

- int **jst\_flags**

<i>Setter</i>	<code>set_jst_flags(value)</code>
<i>Getter</i>	<code>get_jst_flags()</code>

- float **line\_spacing**

<i>Setter</i>	<code>set_line_spacing(value)</code>
<i>Getter</i>	<code>get_line_spacing()</code>

- *TLShapedAttributedString* **string**

<i>Setter</i>	<code>set_string(value)</code>
<i>Getter</i>	<code>get_string()</code>

- float **width**

<i>Setter</i>	<code>set_width(value)</code>
<i>Getter</i>	<code>get_width()</code>

## 2.11.7 Method Descriptions

- void **copy\_properties** ( *TLShapedParagraph* source )
- *TLShapedAttributedString* **get\_line** ( int index ) const
- Array **get\_line\_bounds** ( ) const
- int **get\_lines** ( ) const
- Vector2 **get\_size** ( ) const
- Array **get\_word\_bounds** ( ) const

## 2.12 TLShapedString

**Inherits:**

**Inherited By:** *TLShapedAttributedString*

**Category:** Core

### 2.12.1 Brief Description

Holds shaped line of plain text.

### 2.12.2 Properties

int	<i>base_direction</i>
<i>TLFontFamily</i>	<i>base_font</i>
int	<i>base_font_size</i>
String	<i>base_font_style</i>
String	<i>features</i>
String	<i>language</i>
bool	<i>preserve_control</i>
String	<i>text</i>

### 2.12.3 Methods

void	<i>add_sstring</i> ( <i>TLShapedString</i> text )
void	<i>add_text</i> ( String text )
void	<i>add_utf16</i> ( PoolByteArray text )
void	<i>add_utf32</i> ( PoolByteArray text )
void	<i>add_utf8</i> ( PoolByteArray text )
Array	<i>break_jst</i> ( ) const
Array	<i>break_lines</i> ( float width, int flags ) const
Array	<i>break_words</i> ( ) const
int	<i>char_count</i> ( ) const
int	<i>clusters</i> ( ) const
void	<i>copy_properties</i> ( <i>TLShapedString</i> source )
void	<i>draw</i> ( RID canvas_item, Vector2 position, Color modulate )
void	<i>draw_as_hex</i> ( RID canvas_item, Vector2 position, Color modulate, bool draw_brk_ops, bool draw_jst_ops )
Vector2	<i>draw_cluster</i> ( RID canvas_item, Vector2 position, int index, Color modulate )
void	<i>draw_dbg</i> ( RID canvas_item, Vector2 position, Color modulate, bool draw_brk_ops, bool draw_jst_ops )

Continued on next page

Table 1 – continued from previous page

void	<i>draw_logical_as_hex</i> ( RID canvas_item, Vector2 position, Color modulate, bool draw_brk_ops, bool draw_jst_op
bool	<i>empty</i> ( ) const
float	<i>extend_to_width</i> ( float width, int flags )
float	<i>get_ascent</i> ( ) const
<i>TextDirection</i>	<i>get_char_direction</i> ( int position ) const
float	<i>get_cluster_ascent</i> ( int index ) const
String	<i>get_cluster_debug_info</i> ( int index ) const
float	<i>get_cluster_descent</i> ( int index ) const
int	<i>get_cluster_end</i> ( int index ) const
<i>TLFontFace</i>	<i>get_cluster_face</i> ( int position ) const
float	<i>get_cluster_face_size</i> ( int position ) const
int	<i>get_cluster_glyph</i> ( int index, int glyph ) const
Vector2	<i>get_cluster_glyph_advance</i> ( int index, int glyph ) const
Vector2	<i>get_cluster_glyph_offset</i> ( int index, int glyph ) const
int	<i>get_cluster_glyphs</i> ( int index ) const
float	<i>get_cluster_height</i> ( int index ) const
int	<i>get_cluster_index</i> ( int position ) const
float	<i>get_cluster_leading_edge</i> ( int index ) const
Rect2	<i>get_cluster_rect</i> ( int index ) const
int	<i>get_cluster_start</i> ( int index ) const
float	<i>get_cluster_trailing_edge</i> ( int index ) const
float	<i>get_cluster_width</i> ( int index ) const
Array	<i>get_cursor_positions</i> ( int position, int primary_dir ) const
float	<i>get_descent</i> ( ) const
float	<i>get_height</i> ( ) const
Array	<i>get_highlight_shapes</i> ( int start, int end ) const
int	<i>get_para_direction</i> ( ) const
PoolByteArray	<i>get_utf16</i> ( ) const
PoolByteArray	<i>get_utf32</i> ( ) const
PoolByteArray	<i>get_utf8</i> ( ) const
float	<i>get_width</i> ( ) const
int	<i>hit_test</i> ( float position ) const
int	<i>hit_test_cluster</i> ( float position ) const
bool	<i>is_valid</i> ( ) const
int	<i>length</i> ( ) const
int	<i>next_safe_bound</i> ( int position ) const
int	<i>pos_u16_to_wcs</i> ( int position ) const
int	<i>pos_wcs_to_u16</i> ( int position ) const
int	<i>prev_safe_bound</i> ( int position ) const
void	<i>replace_sstring</i> ( int start, int end, <i>TLShapedString</i> text )
void	<i>replace_text</i> ( int start, int end, String text )
void	<i>replace_utf16</i> ( int start, int end, PoolByteArray text )
void	<i>replace_utf32</i> ( int start, int end, PoolByteArray text )
void	<i>replace_utf8</i> ( int start, int end, PoolByteArray text )
void	<i>set_utf16</i> ( PoolByteArray data )
void	<i>set_utf32</i> ( PoolByteArray data )
void	<i>set_utf8</i> ( PoolByteArray data )
bool	<i>shape</i> ( )
<i>TLShapedString</i>	<i>substr</i> ( int start, int end, int trim ) const

## 2.12.4 Signals

- `string_changed ( )`
- `string_shaped ( )`

## 2.12.5 Enumerations

enum **TextDirection**:

- **TEXT\_DIRECTION\_LTR = 0** — Left-to-right text writing direction
- **TEXT\_DIRECTION\_RTL = 1** — Right-to-left text writing direction
- **TEXT\_DIRECTION\_LOCALE = 2** — Text writing direction is derived from the locale's script according to the CLDR metadata
- **TEXT\_DIRECTION\_AUTO = 3** — Text writing direction is derived from the first character in the string with BiDi class L, R, or AL or locale's script if text is not strongly directional
- **TEXT\_DIRECTION\_INVALID = 4**

enum **TextJustification**:

- **TEXT\_JUSTIFICATION\_NONE = 0** — No text justification
- **TEXT\_JUSTIFICATION\_KASHIDA\_AND\_WHITESPACE = 1** — Use kashida and whitespace elongation to justify text
- **TEXT\_JUSTIFICATION\_KASHIDA\_ONLY = 2** — Use kashida elongation to justify text
- **TEXT\_JUSTIFICATION\_WHITESPACE\_ONLY = 3** — Use whitespace elongation to justify text
- **TEXT\_JUSTIFICATION\_KASHIDA\_AND\_WHITESPACE\_AND\_INTERCHAR = 4**
- **TEXT\_JUSTIFICATION\_KASHIDA\_AND\_INTERCHAR = 5**
- **TEXT\_JUSTIFICATION\_WHITESPACE\_AND\_INTERCHAR = 6**
- **TEXT\_JUSTIFICATION\_INTERCHAR\_ONLY = 7**

enum **TextBreak**:

- **TEXT\_BREAK\_NONE = 0** — No line breaking
- **TEXT\_BREAK\_MANDATORY = 1** — Break lines only at mandatory break points
- **TEXT\_BREAK\_MANDATORY\_AND\_WORD\_BOUND = 2** — Break lines at mandatory break points and word boundaries
- **TEXT\_BREAK\_MANDATORY\_AND\_ANYWHERE = 3** — Break lines at mandatory break points and grapheme cluster boundaries

enum **TextTrimMode**:

- **TEXT\_TRIM\_NONE = 0** — No substring trimming
- **TEXT\_TRIM\_BREAK = 1** — Trim line break characters for substring ends
- **TEXT\_TRIM\_BREAK\_AND\_WHITESPACE = 2** — Trim line break and whitespace characters for substring ends

## 2.12.6 Description

Note 1: Code points, Characters, Clusters and Glyphs

- A code point is a single encoding UTF-16 unit (Unicode character or half of the surrogate pair).
- A character is a full Unicode character.
- A grapheme cluster is the abstract unit of a writing system (a letter, a digit, or punctuation).
- A glyph is a shape used to render a character or a sequence of characters.

In general, code point, characters, clusters and glyphs do not have one-to-one correspondence.

Note 2: Encoding

TLShapedString uses UTF-16 encoding, all positions accepted and returned by TLShapedString function are measured in UTF-16 code points.

## 2.12.7 Property Descriptions

- int **base\_direction**

<i>Setter</i>	set_base_direction(value)
<i>Getter</i>	get_base_direction()

Base text writing direction. Default: TEXT\_DIRECTION\_AUTO

- *TLFontFamily* **base\_font**

<i>Setter</i>	set_base_font(value)
<i>Getter</i>	get_base_font()

Base font family reference. Default: null

- int **base\_font\_size**

<i>Setter</i>	set_base_font_size(value)
<i>Getter</i>	get_base_font_size()

Font size. Default: 12

- String **base\_font\_style**

<i>Setter</i>	set_base_font_style(value)
<i>Getter</i>	get_base_font_style()

Style name (Regular, Bold, Italic, Oblique etc.). Default: "Regular"

- String **features**

<i>Setter</i>	set_features(value)
<i>Getter</i>	get_features()

Comma separated list of OpenType feature tags. More info: <https://docs.microsoft.com/en-us/typography/opentype/spec/featuretags>. Default: ""

- String **language**

<i>Setter</i>	set_language(value)
<i>Getter</i>	get_language()

Language code. Default: ""

- bool **preserve\_control**

<i>Setter</i>	set_preserve_control(value)
<i>Getter</i>	get_preserve_control()

If `true` displays control character. Default: `false`

- String **text**

<i>Setter</i>	set_text(value)
<i>Getter</i>	get_text()

Text string. Default: ""

## 2.12.8 Method Descriptions

- void **add\_sstring** ( *TLShapedString* text )
- void **add\_text** ( String text )

Appends plain text string.

- void **add\_utf16** ( PoolByteArray text )
- void **add\_utf32** ( PoolByteArray text )
- void **add\_utf8** ( PoolByteArray text )
- Array **break\_jst** ( ) const
- Array **break\_lines** ( float width, int flags ) const

Breaks text into lines that fit within a specified width.

Returns Array of line boundaries.

- Array **break\_words** ( ) const

Breaks text into words.

Returns Array of word boundaries.

- int **char\_count** ( ) const

Returns number of characters in the string.

- int **clusters** ( ) const

Returns number of grapheme clusters, clusters are indexed in visual order.

- void **copy\_properties** ( *TLShapedString* source )
- void **draw** ( RID canvas\_item, Vector2 position, Color modulate )

Draws a string.

- void **draw\_as\_hex** ( RID canvas\_item, Vector2 position, Color modulate, bool draw\_brk\_ops, bool draw\_jst\_ops )

- Vector2 **draw\_cluster** ( RID canvas\_item, Vector2 position, int index, Color modulate )

Draws single grapheme cluster. Returns advance.

- void **draw\_dbg** ( RID canvas\_item, Vector2 position, Color modulate, bool draw\_brk\_ops, bool draw\_jst\_ops )
- void **draw\_logical\_as\_hex** ( RID canvas\_item, Vector2 position, Color modulate, bool draw\_brk\_ops, bool draw\_jst\_ops )
- bool **empty** ( ) const

Returns `true` if the string is empty.

- float **extend\_to\_width** ( float width, int flags )

Increase text width to the specified. Returns new line width.

- float **get\_ascent** ( ) const

Returns ascent of the line.

- *TextDirection* **get\_char\_direction** ( int position ) const

Return writing direction of a character writing direction.

- float **get\_cluster\_ascent** ( int index ) const

Returns cluster ascent.

- String **get\_cluster\_debug\_info** ( int index ) const
- float **get\_cluster\_descent** ( int index ) const

Returns cluster descent.

- int **get\_cluster\_end** ( int index ) const

Returns last character position corresponding cluster.

- *TLFontFace* **get\_cluster\_face** ( int position ) const
- float **get\_cluster\_face\_size** ( int position ) const
- int **get\_cluster\_glyph** ( int index, int glyph ) const

Returns glyph ID.

- Vector2 **get\_cluster\_glyph\_advance** ( int index, int glyph ) const

Returns glyph advance.

- Vector2 **get\_cluster\_glyph\_offset** ( int index, int glyph ) const

Returns glyph offset.

- int **get\_cluster\_glyphs** ( int index ) const

Returns number of glyphs in cluster.

- float **get\_cluster\_height** ( int index ) const

Returns cluster height.

- int **get\_cluster\_index** ( int position ) const

Returns cluster index corresponding to a specific character position in string.

- float **get\_cluster\_leading\_edge** ( int index ) const

Returns cluster leading edge offset in pixels.



- Rect2 **get\_cluster\_rect** ( int index ) const

Returns cluster bounding rectangle.

- int **get\_cluster\_start** ( int index ) const

Returns first character position corresponding cluster.

- float **get\_cluster\_trailing\_edge** ( int index ) const

Returns cluster trailing edge offset in pixels.

- float **get\_cluster\_width** ( int index ) const

Returns cluster width.

- Array **get\_cursor\_positions** ( int position, int primary\_dir ) const

Returns an Array of float (up to two elements) offsets corresponding to the strong and weak cursor, at the specified character position.

- float **get\_descent** ( ) const

Returns descent of the line.

- float **get\_height** ( ) const

Returns height of the line.

- Array **get\_highlight\_shapes** ( int start, int end ) const

Returns an Array of Rect2 enclosing the selection/highlight in the specified range.

- int **get\_para\_direction** ( ) const

- PoolByteArray **get\_utf16** ( ) const

Returns raw text string in UTF-16 encoding.

- PoolByteArray **get\_utf32** ( ) const

Returns raw text string in UTF-32 encoding.

- PoolByteArray **get\_utf8** ( ) const

Returns raw text string in UTF-8 encoding.

- float **get\_width** ( ) const

Returns width of the line.

- int **hit\_test** ( float position ) const

Returns a cursor position corresponding to the specified pixel offset.

- int **hit\_test\_cluster** ( float position ) const

- bool **is\_valid** ( ) const

Returns true if the string is shaped successfully.

- int **length** ( ) const

Returns number of UTF-16 codepoints in the string.

- int **next\_safe\_bound** ( int position ) const

Returns next whole character position in the string.

- int **pos\_u16\_to\_wcs** ( int position ) const

Returns character position (Characters)

- `int pos_wcs_to_u16 ( int position ) const`

Retruns character position (UTF-16 codepoints)

- `int prev_safe_bound ( int position ) const`

Returns previous whole character position in the string.

- `void replace_sstring ( int start, int end, TLShapedString text )`
- `void replace_text ( int start, int end, String text )`

Replaces substring.

- `void replace_utf16 ( int start, int end, PoolByteArray text )`
- `void replace_utf32 ( int start, int end, PoolByteArray text )`
- `void replace_utf8 ( int start, int end, PoolByteArray text )`
- `void set_utf16 ( PoolByteArray data )`

Sets taw text string in UTF-16 encoding

- `void set_utf32 ( PoolByteArray data )`

Sets taw text string in UTF-32 encoding

- `void set_utf8 ( PoolByteArray data )`

Sets taw text string in UTF-8 encoding

- `bool shape ( )`

Shapes string and returns `true` if the string is shaped successfully.

- `TLShapedString substr ( int start, int end, int trim ) const`