


Binary Search Trees

- A Binary Search Tree (BST) is a special type of binary tree
 - it represents information in an ordered format
 - A binary tree is a binary search tree if for every node w , all keys in the left subtree of w have values less than the key of w and all keys in the right subtree have values greater than the key of w .

Binary Search Trees

- Definition: A binary search tree T is a binary tree; either it is empty or each node in the tree contains an identifier and:
 - all keys in the left subtree of T are less (numerically or alphabetically) than the identifier in the root node T ;
 - all identifiers in the right subtree of T are greater than the identifier in the root node T ;
 - The left and right subtrees of T are also binary search trees.

Binary Search Trees




Binary Search Trees

- The main point to notice about such a tree is that, if traversed inorder, the keys of the tree (*i.e.* its data elements) will be encountered in a sorted fashion.
- Furthermore, efficient searching is possible using the binary search technique
 - search time is $O(\log_2 n)$.


Binary Search Trees

- It should be noted that several binary search trees are possible for a given data set, e.g, consider the following tree:

Binary Search Trees



Binary Search Trees



Binary Search Trees

- Let us consider how such a situation might arise. To do so, we need to address how a binary search tree is constructed.
 - Assume we are building a binary search tree of words.
 - Initially, the tree is null, i.e. there are no nodes in the tree.
 - The first word is inserted as a node in the tree as the root, with no children.

Binary Search Trees

- On insertion of the second word, we check to see if it is the same as the key in the root, less than it, or greater than it.
 - » If it is the same, no further action is required (duplicates are not allowed).
 - » If it is less than the key in the current node, move to the left subtree and *compare again*.
 - » If the left subtree does not exist, then the word does not exist and it is inserted as a new node on the left.

Binary Search Trees

- » If, on the other hand, the word was greater than the key in the current node, move to the right subtree and compare again.
- » If the right subtree does not exist, then the word does not exist and it is inserted as a new node on the right.
- This insertion can most easily be effected in a recursive manner

Binary Search Trees

- The point here is that the structure of the tree depends on the order in which the data is inserted in the list.
- If the words are entered in sorted order, then the tree will degenerate to a 1-D list.

BST Operations

- *Insert*: $E \times \text{BST} \rightarrow \text{BST}$:

The function value $\text{Insert}(e, T)$ is the BST T with the element e inserted as a leaf node; if the element already exists, no action is taken.

BST Operations

- *Delete*: $E \times \text{BST} \rightarrow \text{BST}$:

The function value $Delete(e, T)$ is the BST T with the element e deleted; if the element is not in the BST exists, no action is taken.

Implementation of *Insert*(*e*, *T*)

- If *T* is empty (i.e. *T* is NULL)
 - create a new node for *e*
 - make *T* point to it
- If *T* is not empty
 - if $e < \text{element at root of } T$
 - » Insert *e* in left child of *T*: *Insert*(*e*, *T*(1))
 - if $e > \text{element at root of } T$
 - » Insert *e* in right child of *T*: *Insert*(*e*, *T*(2))

Implementation of *Insert*(e, T)

Implementation of *Delete*(e , T)

- First, we must locate the element e to be deleted in the tree
 - if e is at a leaf node
 - » we can delete that node and be done
 - if e is at an interior node at w
 - » we can't simply delete the node at w as that would disconnect its children
 - if the node at w has only one child
 - » we can replace that node with its child

Implementation of *Delete*(e , T)

- if the node at w has two children
 - » we replace the node at w with the lowest-valued element among the descendants of its right child
 - » this is the left-most node of the right tree
 - » It is useful to have a function DeleteMin with removes the smallest element from a non-empty tree and returns the value of the element removed


Implementation of *Delete(e, T)*

- If T is not empty
 - if $e <$ element at root of T
 - » Delete e from left child of T : $Delete(e, T(1))$
 - if $e >$ element at root of T
 - » Delete e from right child of T : $Delete(e, T(2))$
 - if $e =$ element at root of T and both children are empty
 - » Remove T
 - if $e =$ element at root of T and left child is empty
 - » Replace T with $T(2)$


Implementation of *Delete*(e , T)

- if e = element at root of T and right child is empty
 - » Replace T with $T(1)$
- if e = element at root of T and neither child is empty
 - » Replace T with left-most node of $T(2)$

Implementation of *Delete(e, T)*



Implementation of *Delete(e, T)*



BST Implementation

```
/* implementation of BST ADT */
```

```
#include <stdio.h>
```

```
#include <math.h>
```

```
#include <string.h>
```

```
#define FALSE 0
```

```
#define TRUE 1
```

```
typedef struct {  
    int number;  
    char *string;  
} ELEMENT_TYPE;
```

BST Implementation

```
typedef struct node *NODE_TYPE;
```

```
typedef struct node{  
    ELEMENT_TYPE element;  
    NODE_TYPE left, right;  
} NODE;
```

```
typedef NODE_TYPE BST_TYPE;
```

```
typedef NODE_TYPE WINDOW_TYPE;
```

BST Implementation

```
/** insert an element in a BST */

BST_TYPE *insert(ELEMENT_TYPE e, BST_TYPE *tree) {
    WINDOW_TYPE temp;
    if (*tree == NULL) {
        /* we are at an external node: create a new node */
        /* and insert it */
        if ((temp = (NODE_TYPE) malloc(sizeof(NODE))) == NULL)
            error("insert: unable to allocate memory");
        else {
            temp->element = e;
            temp->left = NULL;
            temp->right = NULL;
            *tree = temp;
        }
    }
}
```


BST Implementation

```
}  
else if (e.number < (*tree)->element.number) {  
    /* assume number field is the key */  
    insert(e, &((*tree)->left));  
}  
else if (e.number > (*tree)->element.number) {  
    insert(e, &((*tree)->right));  
}  
  
/* if e.number == (*tree)->element.number, e is */  
/* already in the tree so do nothing */  
  
return(tree);  
}
```

BST Implementation

```
/** return and delete the smallest node in a tree */
/** i.e. return and delete the left-most node */

ELEMENT_TYPE delete_min(BST_TYPE *tree) {
    ELEMENT_TYPE e;
    BST_TYPE p;
    if ((*tree)->left == NULL) {

        /* (*tree) points to the smallest element */

        e = (*tree)->element;

        /* replace the node pointed to by tree */
        /* by its right child */
    }
}
```

BST Implementation

```
p = *tree;  
*tree = (*tree)->right;  
free(p);
```

```
return (e);
```

```
}
```

```
else {
```

```
    /* the node pointed to by *tree has a left child */
```

```
    return(delete_min(&((*tree)->left)));
```

```
}
```

```
}
```

BST Implementation

```
/** delete an element from a BST */

BST_TYPE *delete(ELEMENT_TYPE e, BST_TYPE *tree) {
    BST_TYPE p;
    if (*tree != NULL) {
        if (e.number < (*tree)->element.number)
            delete(e, &((*tree)->left));
        else if (e.number > (*tree)->element.number)
            delete(e, &((*tree)->right));
        else if (((*tree)->left == NULL) &&
                ((*tree)->right == NULL)) {

            /* leaf node containing e: delete it */
        }
    }
}
```

BST Implementation

```
    /* leaf node containing e: delete it */

    p = *tree;
    free(p);
    *tree = NULL;
}
else if ((*tree)->left == NULL) {
    /* internal node containing e and it has only */
    /* a right child; delete it and make tree */
    /* point to the right child */

    p = *tree;
    *tree = (*tree)->right;
    free(p);
}
```

BST Implementation

```
else if ((*tree)->right == NULL) {  
  
    /* internal node containing e and it has only */  
    /* a left child; delete it and make tree      */  
    /* point to the left child                     */  
  
    p = *tree;  
    *tree = (*tree)->left;  
    free(p);  
}
```

BST Implementation

```
else {
    /* internal node containing e and it has both */
    /* left and right children; replace it with */
    /* the leftmost node of the right child */

    (*tree)->element = delete_min(&((*tree)->right));
}
}
```

BST Implementation

```
/** inorder traversal of a tree,          */
/** printing node elements                */
/** parameter n is the current level in the tree */

int inorder(BST_TYPE *tree, int n) {
    int i;
    if (*tree != NULL) {
        inorder(tree->left, n+1);
        for (i=0; i<n; i++) printf(" ");
        printf("%d %s\n", tree->element.number,
                tree->element.string);
        inorder(tree->right, n+1);
    }
}
```


BST Implementation

```
/** print all elements in a tree by traversing    */
/** inorder                                         */

int print(BST_TYPE *tree) {

    printf("Contents of tree by inorder traversal: \n");

    inorder(tree, 0);

    printf("-----");
}
```

BST Implementation

```
/** error handler: print message passed as argument and
    take appropriate action                                     */
int error(char *s); {
    printf("Error: %s\n", s);
    exit(0);
}

/** assign values to an element */

int assign_element_values(ELEMENT_TYPE *e, int number,
    char s[]) {
    e->string = (char *) malloc(sizeof(char) * strlen(s));
    strcpy(e->string, s);
    e->number = number;
}
```

BST Implementation

```
/** main driver routine */

ELEMENT_TYPE e;
BST_TYPE list;
int i;

print(tree);

assign_element_values(&e, 3, "...");
insert(e, &tree);
print(tree);

assign_element_values(&e, 1, "+++");
insert(e, &tree);
print(tree);
```

BST Implementation

```
assign_element_values(&e, 5, "---");  
insert(e, &tree);  
print(tree);
```

```
assign_element_values(&e, 2, ",,,");  
insert(e, &tree);  
print(tree);
```


```
assign_element_values(&e, 4, "***");  
insert(e, &tree);  
print(tree);
```

```
assign_element_values(&e, 6, "000");  
insert(e, &tree);  
print(tree);
```


BST Implementation

```
assign_element_values(&e, 3, "...");  
insert(e, &tree);  
print(tree);  
}
```


BINARY_TREE Implementation




BINARY_TREE Implementation




BINARY_TREE Implementation




BINARY_TREE Implementation




BINARY_TREE Implementation



BINARY_TREE Implementation



BINARY_TREE Implementation




Tree Traversals

- To perform a traversal of a data structure, we use a method of visiting every node in some predetermined order
- Traversals can be used
 - to test data structures for equality
 - to display a data structure
 - to construct a data structure of a give size
 - to copy a data structure

Depth-First Traversals

- There are 3 depth-first traversals
 - inorder
 - postorder
 - preorder
- For example, consider the expression tree:

Example: Expression Tree



Depth-First Traversals

- Inorder traversal

$A - B + C \times D + E \times F - G$

- Postorder traversal

$A B - C + D E + F G - \times \times$

- Preorder traversal

$\times + - A B C \times + D E - F G$

Depth-First Traversals

- The parenthesised Inorder traversal

$$((A - B) + C) \times ((D + E) \times (F - G))$$

This is the **infix** expression corresponding to the expression tree

- Postorder traversal gives a **postfix** expression
- Preorder traversal gives a prefix expression

Depth-First Traversals

- Recursive definition of inorder traversal

Given a binary tree T

if T is empty

visit the external node


otherwise

perform an inorder traversal of $Left(T)$


visit the root of T

perform an inorder traversal of $Right(T)$

Example: Inorder Traversal



Example: Inorder Traversal



Depth-First Traversals

- Recursive definition of postorder traversal

Given a binary tree T

if T is empty

visit the external node


otherwise

perform an postorder traversal of $Left(T)$


perform an postorder traversal of $Right(T)$

visit the root of T

Example: Postorder Traversal



Example: Postorder Traversal



Depth-First Traversals

- Recursive definition of preorder traversal

Given a binary tree T


if T is not an external node

visit the root of T

perform an inorder traversal of $Left(T)$

perform an inorder traversal of $Right(T)$

Example: Preorder Traversal



Example: Preorder Traversal

