RESEARCH STATEMENT

Md Ashikul Haque

My areas of interest and expertise include the Internet of Things (IoT), wireless networked systems, real-time and embedded systems, cyber-physical systems (CPS), and their integration with artificial intelligence (AI). My research addresses the challenges of security, reliability, scalability, timeliness, and energy efficiency in these areas through theory and system design, with applications in autonomous and connected vehicles, smart cities, industrial control, and disaster response. Defense against jamming and coexistence with other networks are very challenging in low-power wide-area networks (LPWANs). Solutions designed for Wi-Fi, cellular, and other wireless networks cannot be adopted directly, because LPWAN devices have limited computation, low transmission power, and small batteries. My major research initiatives and future plans are summarized as follows.

1 Anti-Jamming for Low-Power Wide-Area Networks (LPWANs)

LPWANs such as LoRa let battery-powered devices send data over several kilometers for years. LPWAN signals are weak and easy to jam. A jammer is a transmitter that deliberately corrupts legitimate packets. In 2020, 85% of cargo truck thefts in Mexico involved wireless jamming, and Starlink terminals were jammed in 2022. I first modeled jamming as a game between a jammer and the base station of Sensor Network Over White spaces (SNOW), our laboratory's LPWAN (EWSN 2023).[1] The nodes counter the jammer by hopping across frequencies and adjusting their transmission power. The base station learns this strategy with multi-agent reinforcement learning (RL) on behalf of the nodes, which do none of the computation. This defense improved the packet reception rate (PRR) by up to 31.83× and the energy efficiency by up to 34× in simulations with 50 to 240 nodes, and the joint game converges in 10 to 15 minutes where either lever alone does not. It achieved a PRR of 94% on an indoor testbed of Universal Software Radio Peripheral (USRP) B200 radios and Texas Instruments CC1310 nodes, against 5.4% for SNOW without it.

Multi-Gateway Decoding. A packet and a jamming signal reach each gateway with a different relative delay, because the gateways sit at different distances from the node and from the jammer. Exploiting this variation, I have designed an anti-jamming technique for LoRa that decodes packets at signal-to-noise ratios below −35 dB, where seven existing LoRa decoders have a 100% symbol error rate (IoTDI 2024). Three gateways in a line with equal spacing leave a clean fragment for almost every jammer position. The exceptions are a jammer at the node's mirror position or at one specific distance, and a fourth gateway off the line removes both. The LoRa Network Server (LNS) aligns the copies of a packet from the gateways and stitches their jammer-free fragments into one packet. It finds clean fragments by a threshold on signal power, and a convolutional neural network classifies the fragments near the threshold. The technique is link layer-agnostic and imposes no overhead on the nodes. I evaluated it outdoors with USRP gateways and commercial off-the-shelf LoRa nodes. It improved PRR by 83.91× and cut the energy per delivered packet by 115.65×.

Single-Gateway Decoding. Placing several gateways around every node is not always possible, so I have also developed decoders for a single gateway. The first handles multiple jammers that transmit LoRa packets (MobiHoc 2025). After recovering every symbol boundary, the decoder estimates the legitimate signal power from the preamble, which usually reaches the gateway before the jamming signals. It then zeroes every frequency bin that exceeds this power by a margin. The decoder adds about 3 ms per 32-byte packet, where one LoRa symbol often lasts over 50 ms. It improved PRR from 0.32% to 34.14%, a gain of 106.56× over the best existing LoRa defense, published at INFOCOM 2021, which collapses beyond one jammer.

[1] Each tag (e.g., SenSys 2026) cites one of my peer-reviewed papers and links to it. My CV lists all of them in full.

The second decoder handles collaborative jammers that need not transmit chirps (EWSN 2026). A special node transmits a known signal that stays orthogonal to the LoRa signal but collides with the jamming signals. It listens for uplinks with the carrier activity detection feature of LoRa chips, which Long Range Wide Area Network (LoRaWAN) does not use, and transmits the known signal as soon as it detects activity. The gateway uses the known signal to disentangle the combined jamming signal and cancel it. A lightweight generative model at the gateway maps the jamming energy from one spreading factor to another when the known signal and the packet use different spreading factors. With three jammers at 50 m, PRR rose from 0.4% to 40.7%. The decoder kept 40 to 70% PRR under channel-switching, proactive, and random jammers, while the three-gateway design fell to about 1%. Decoding takes about 12 ms per 32-byte packet, against 11 ms for a standard receiver. In the harshest three-jammer case, the decoder cut the energy per packet by 136×.

To our knowledge, my game-theoretic defense (EWSN 2023) is **the first anti-jamming work for LPWANs**, and my multi-gateway technique (IoTDI 2024) is the first to mitigate jamming in LoRa. None of my decoders needs a change to the 125 million deployed LoRa end devices.

2 Coexistence and Cross-Technology Communication

Learning-Based Coexistence. As LPWANs grow, several LoRaWAN operators in a city share the same unlicensed channels, and their nodes transmit without carrier sensing. Hence the frames of one network collide with those of its neighbors, and no operator sees the traffic of the others. Existing learning-based schemes run tabular Q-learning at each node, so they spend scarce energy and see only a local view. I have moved the learning to the LNS, which observes every packet and acknowledgment in its network (INFOCOM 2025). A deep Q-network selects the transmission parameters of each node for both the uplink and the acknowledgments, so nodes stop retransmitting packets that already arrived. The LNS sends these parameters through the existing downlink. I evaluated this approach through physical experiments and NS-3 simulations. Compared to the decentralized state of the art, this approach improved PRR by up to 70.97% and reduced energy consumption by up to 62.91%.

I identified a new failure mode: when neighboring operators each run such an agent, the agents can converge on the same choices and collide. I have developed a coordination service that shares only model-level information, never traffic (ICLR 2026 workshop). A hypernetwork maps this information to an update for each agent, so that the agents make complementary choices. Over independent agents, this coordination improved PRR by 20% with two networks and 10% with four.

Cross-Technology Communication. Long Range Frequency Hopping Spread Spectrum (LR-FHSS) is a LoRa physical layer for long-range and direct-to-satellite uplinks. However, LR-FHSS devices receive only LoRa, so the downlink to an LR-FHSS device must use LoRa. Because LoRa has a shorter range, a gateway can hear a far LR-FHSS device but cannot reply to it. A LoRa receiver cannot decode an LR-FHSS transmission, because LoRa requires chirps with linear frequency modulation, whereas LR-FHSS sends narrowband hops. I enabled an LR-FHSS transmitter to produce a waveform that a LoRa receiver can decode with baseband access at the gateway and in-phase and quadrature (I/Q) access at the receiver, but no change to the radio frequency (RF) front end (SenSys 2026). By controlling its hop sequence, the transmitter synthesizes a pseudo-chirp from narrowband hops. A Chirp Reconstruction Module at the receiver aligns the fragments, corrects carrier and timing offsets, and passes a LoRa-compatible chirp to the standard demodulator. With Aakriti Jain and Venkata Prashant Modekurthy, I implemented this cross-technology communication (CTC) link on USRP B200 with GNU Radio and deployed it with one gateway and five nodes in a suburban area. It improved long-range reliability by up to 79% over LoRa, and the resulting link tracks native LR-FHSS range to within a few percentage points. Acknowledgments sent over the link raised end-to-end LR-FHSS PRR from 79.04% to 94.57%.

To our knowledge, my CTC technique (SenSys 2026) is **the first to enable communication from LR-FHSS to LoRa**. It lets a gateway acknowledge a far device, change its reporting rate, or trigger an emergency transmission. My network-server learning (INFOCOM 2025) is cited by a 2026 paper in IEEE Transactions on Green Communications and Networking that schedules satellite LoRa uplinks with deep RL. I developed both coexistence designs with Prof. Haibo Zhang at the University of New South Wales, and we still collaborate.

3 Real-Time Guarantees for Wireless Networks and AI Agents

Real-Time Wireless Networks. A forest fire or a volcanic eruption makes every LoRa node report at once. Under LoRaWAN's random access, many of these reports collide when they matter most. *Burst-MAC*, which Aakriti Jain led with my help on the protocol design and the physical experiments, switches the nodes to time slots only during a burst (RTSS 2024). Each node derives its slots from a hash function, so the gateway sends no schedule. Gateway acknowledgments resolve slot collisions and keep every packet's latency bounded. On LoRa devices and in NS-3, Burst-MAC improved PRR by 4.5×, cut energy use by up to 6×, and reduced latency by up to 2.5×.

Industrial wireless sensor-actuator networks (WSANs) run control loops of different criticality over one network. When a plant enters a critical condition, high-criticality (HC) loops need more airtime, but low-criticality (LC) loops must not be starved. I have designed *ReMix*, which keeps a stable base schedule and a contingency pool of preinstalled cells (ICCCN 2026). A short broadcast bitmap selects which cells of the pool to activate, and a duplicated-payload frame layout lets the receiver rebuild a corrupted packet in software on stock radios. In HC mode, ReMix reclaims redundancy from LC traffic, while a service budget bounds the service loss of each LC loop. On a 15-node Tmote Sky testbed, ReMix raised HC deadline satisfaction from 32.9% to 85.9% under the heaviest stress. It kept LC delivery at 63.4% during HC intervals. At a representative stress point, it cut the trace-derived radio energy per delivered HC packet by 31.9%.

With Dali Ismail, I have also studied scalable real-time control over WSANs (SDN-CPS 2024). Earlier co-designs of control and scheduling were offline and centralized, so they could not respond to the current behavior of the control loops. This work proposes to co-design model predictive control with the transmission schedule online, with an anytime local search that would return a feasible schedule immediately.

Real-Time AI Systems. A large language model (LLM) agent that drives an actuator has a deadline on its first useful action, not on its last token. Existing LLM serving systems improve throughput and tail latency, but they do not reserve capacity for the part of a response that makes an action usable. I have developed *Deadline-Aware Token Scheduling*, which splits each request into prefill, a validator-backed mandatory prefix, and an optional suffix (RTSS 2026). It admits a critical request only when its mandatory work passes a deadline guard and its key-value cache reservation fits in memory. It dispatches admitted mandatory work in earliest-deadline-first order and runs optional tokens only when slack remains. I have proved a sufficient schedulability condition for the mandatory mode under bounded service and blocking, and the scheduler held zero admitted-critical misses under arrival jitter and service noise, without per-workload tuning. A multi-mode variant gives each critical request three certified service modes, so that it can fall back to a compact or safe response when its full response is infeasible. On deterministic workloads, this variant reduced the share of critical requests that are rejected or miss their deadline from 39.9% under guarded segmentation without fallback to 11.9%. On a vLLM stress test of 5,760 requests, it reduced this share from 92.5% under first-come first-served scheduling to 23.8%.

The artifact of Deadline-Aware Token Scheduling passed the RTSS 2026 Artifact Evaluation. Burst-MAC is cited by LoRaHART at ECRTS 2025. My workshop paper on real-time control in industrial CPS is cited at IEEE RTAS 2025 and RTSS 2025.

4 Future Research Direction

My goal is to establish a leading research group that makes IoT and physical AI dependable by combining AI with next-generation wireless and real-time systems. Physical AI refers to AI that senses the physical world and acts on it through machines such as vehicles, robots, and drones. My doctoral research asked how a wireless network stays reliable and on time when jammers, neighboring networks, and competing deadlines contend for its resources. Physical AI and IoT beyond cellular coverage raise this question, with fundamental challenges that the state of the art cannot handle. In the next five years, I am excited to address them in multiple new projects.

4.1 Real-Time Physical AI

OpenVLA, a vision-language-action model for robot manipulation, runs at about 6 Hz on a desktop graphics processing unit (GPU). Existing serving systems do not guarantee that each action reaches its robot before its deadline when robots share an edge server.

This project treats each action as a real-time task that spans a shared GPU and a wireless link, with ground robots as the testbed. I will schedule inference and transmission together to bound the probability that an action misses its end-to-end deadline. Agents that call tools or other models pause but keep their GPU memory. I will treat these pauses as self-suspensions in a response-time analysis for chains of calls. Because timing assumptions can still fail, I will build monitors that switch a machine to a verified safe controller. Per-agent budgets will stop a looping or attacked agent from delaying others.

4.2 Secure Direct-to-Satellite IoT for Remote Areas

Direct-to-satellite (DtS) IoT lets remote LoRa sensors reach a satellite in low Earth orbit. These sensors can warn of floods, wildfires, and other hazards, which leave little time to act. In July 2025, the Guadalupe River in Texas rose 32.5 feet in 1.5 hours. Jamming raises four challenges that are new or harder with satellites. A satellite at 550 km passes over in 10 minutes or less, so a lost warning may wait hours. One ground jammer can disrupt reception across the whole area that a satellite covers. Because satellites are hard to update in orbit, a defense should need no change on the satellite. Acknowledgments are rare, so a device cannot tell jamming from collisions with unseen networks. Prior designs handle intermittent contact or jamming, not both.

To close this gap, each device will derive its transmission times and channels from its LoRaWAN session key and frame counter. The network server will know where each packet should appear, but a jammer will not. I will certify delivery deadlines against a jammer with bounded power that knows everything except the key. I will also develop AI models that tell whether each missing packet was jammed, collided, or faded. They will tighten the certificate, but its correctness will not depend on them. Experiments will use a campus ground station and a drone-mounted gateway.

4.3 Beyond-Line-of-Sight Perception for Connected Autonomous Vehicles

Any obstacle, such as a building or a truck, can hide an oncoming car or a crossing child from a vehicle's cameras and lidars. Cooperative perception lets vehicles share detections, but only timely detections help. Current standards and systems do not bound the probability of a late arrival under fading, contention, and interference.

On the road, links can change within a single maneuver. I will bound this probability over whole maneuvers, so a vehicle yields when shared data may be late. In dense traffic, many vehicles contend for one channel. I will shape the delay tail through standard cellular vehicle-to-everything (C-V2X) settings and split one risk budget among vehicles. Attackers can forge shared detections and jam channels. I will authenticate detections, reject physically implausible ones, and fall back to onboard sensors under jamming. Prototypes will run on software-defined radios and small vehicles.