Self-Healing SDN using Reinforcement Learning: A Smart Approach to Autonomous Fault Recovery

By

Argha Biswas	011221293
Ashikur Rahaman	001221292
Md. Mizanur Rahaman	011221381
Md Tarik Hasan	011221585
Akram Hossain	011221446
Apu Halder	011221517

Submitted in partial fulfilment of the requirements
of the degree of Bachelor of Science in Computer Science and Engineering

February 28, 2026



Department of Computer Science and Engineering
United International University

Abstract

Software-Defined Networking confirmed centralized, programmable management to boost operational productivity. However, rely on a single controller increases the similiar of errors and system outcomes. So, to resolve this challenge, we are presenting a

reinforcement learning (RL)- based self- repairing framework that autonomously

identifies, analyzes, and recovers from network failures in real time. By continuously monitoring network states, the proposed system learns adaptive recovery strategies through environmental interactions and reconfigure routing to minimize service disruption dynamically. Stimulations on SDN topologies confirm that the proposed approach enables quicker fault detection and recovery, lower packet loss and enhances network availability compared to

standard rule-based recovery strategies. These result highlight the learning-based fault management to enhance SDN resilience, expandability and operational autonomy.

Acknowledgements

This work would not have been possible without the input and support of many people over the last two trimesters. We express our gratitude to everyone who contributed to it in some way or another.

First, we would like to thank my academic advisors, ...

Our sincere gratitude goes to...

We are also thankful to ...

Last but not the least, We owe to our family including our parents for their unconditional love and immense emotional support.

Publication List

[Optional] The main contributions of this research are either published or accepted or in preparation in journals and conferences as mentioned in the following list:

Journal Articles

1.

Conference Papers

1.

Additional Publications

Following is the list of relevant publications published in the course of the research that is not included in the thesis:

1.

Table of Contents

Table of Contents v

List of Figures vi

List of Tables vii

1 Introduction 1
- 1.1 Project Overview . . . 1
- 1.2 Motivation . . . 2
- 1.3 Objectives . . . 2
- 1.4 Methodology . . . 3
- 1.5 Project Outcome . . . 3
- 1.6 Organization of the Report . . . 3

2 Background 5
- 2.1 Preliminaries . . . 5
- 2.2 Literature Review . . . 5
  - 2.2.1 Similar Applications . . . 7
  - 2.2.2 Related Research . . . 7
- 2.3 Summary . . . 9

3 Project Design 12
- 3.1 Methodology and Implementation . . . 12
  - 3.1.1 Context Diagram . . . 12
  - 3.1.2 System Architecture . . . 12
  - 3.1.3 Testbed Environment . . . 12
  - 3.1.4 Data Generation and Fault Injection . . . 13
  - 3.1.5 Detailed Methodology and Design . . . 14
  - 3.1.6 Summary . . . 16

4 Implementation and Results 17
- 4.1 Environment Setup . . . 17
- 4.2 Implementation & Engineering Challenges . . . 17

4.2.1 Telemetry Extraction and Normalization 17
4.2.2 Overcoming Dataset Class Imbalance 18
4.2.3 The "Zero-Packet" Logic Edge Case 18
4.3 Results and Discussion 18
4.3.1 Network State Monitoring 18
4.3.2 Autonomous Decision Testing 18
4.3.3 Live Integration Success 19
4.4 Summary 19

5 Standards and Design Constraints 20
5.1 Compliance with the Standards 20
5.1.1 Software Standards 20
5.1.2 Hardware Standards 20
5.1.3 Communication Standards 20
5.2 Design Constraints 20
5.2.1 Economic Constraint 20
5.2.2 Environmental Constraint 20
5.2.3 Ethical Constraint 20
5.2.4 Health and Safety Constraint 20
5.2.5 Social Constraint 20
5.2.6 Political Constraint 20
5.2.7 Sustainability 20
5.3 Cost Analysis 20
5.4 Gantt Chart 22
5.4.1 Gantt Chart 1: FYDP-1 (Planning & Design Phase) 22
5.4.2 Gantt Chart 2: FYDP-2 (Implementation Phase) 22
5.4.3 Gantt Chart 3: Testing and Evaluation Phase 22

6 Conclusion 24
6.1 Summary 24
6.2 Limitation 24

References 26

List of Figures

1.1 System Design 1

3.1 Context Diagram of Proposed Systems 13

4.1 Network Telemetry: Throughput vs Packet Loss over Time 19

5.1 Gantt Chart 1: FYDP-1 Planning and Design Phase 22
5.2 Gantt Chart 2: FYDP-2 Implementation Phase 23
5.3 Gantt Chart 3: Testing and Evaluation Phase 23

List of Tables

2.1 Comparison of RL-based methods for congestion control and fault recovery in SDNs. 10
2.2 Comparison of RL-based methods for congestion control and fault recovery in SDNs (rotated). 11

5.1 Project Cost Summary 21

Chapter 1

Introduction

The introduction chapter provides an overview concept of the project, its explain the motivation, objectives, methodology, outcomes, and outline organization of the report.

1.1 Project Overview




Figure 1.1: System Design

The system design [Figure 1.1] represents the architecture, highlighting the connection between the data plane, agents 1 and 2, and SDN controller. The design enable autonomous and adaptive responses to network congestion, efficient fault detection, proactive management, and improved network reliability, performance, and service continuity.

Software-Defined Networking (SDN) Software-Defined Networking (SDN) works through two main parts, they are- the control plane and the data plane. In our project, we used this setup to make a smart system to manage traffic congestion. The data plane

sends packets and then it collects real-time network data such as, delay, packet loss, and jitter. After collection Agent 1 processes these metrics to find signs of network congestion. When congestion is found, Agent 1 sends the data to Agent 2. Then Agent 2 checks the network. It decides the best way to fix or improve it. After that Agent 2 sends the plan to the SDN controller. The controller then makes the suggested changes. For say, to bring the network back to best performance it reroute traffic or adjust resources.

Problem Statement

Static backups or manual reconfiguration are common in SDN fault-handling methods. Because they are often too slow and rigid for large, changing networks. This project aims to solve how SDNs can automatically and efficiently detect and recover from different faults (like link failures, node failures, and congestion) using reinforcement learning, while reducing downtime and packet loss.

1.2 Motivation

Modern networks such as cloud, IoT, 5G demand high availability and impetuous conformation to errors. Manual troubleshooting and static recovery strategies fail to accommodate the size and inconstancy of current networks. Reinforcement learning paves the way for significant advancements as like (I) Learning optimal decisions from interactions with the network environment (II) Adapt to previously unseen failure conditions.(III) Enhance long-term performances for instance, minimize packet loss or recovery latency. An RL-driven self-healing SDN can minimize operational expenditures not just that, it can boost service robustness and enhance resilience for mission-critical applications even more.

1.3 Objectives

The objectives of this project are:

1. Create an RL-based system that works with an SDN controller to automatically detect, find, and fix network faults.

2. Build a prototype in an SDN test setup, such as Mininet with OpenDaylight or ONOS.

3. Simulate different network problems like link failure, controller failure, and congestion. Train the RL agent to fix them by actions like rerouting or updating flow tables.

4. Test the system against basic methods using measures like detection time, recovery time, packet loss, throughput, and controller load.

5. Check how well the system works on larger networks and new type of failures.

1.4 Methodology

A concise summary of the methodology:

- **Literature Review:** Survey SDN fault management and RL applications.
- **Testbed Setup:** Create a simulated SDN environment by using Mininet (create a virtual network environment) and Wireshark (network analysis, troubleshooting and record network traffic at a microscopic level).
- **Fault Injection:** Set up the model and add different fault cases to this model like single link failure, multi-link failure, controller restart and congestion spikes for training and testing the model.
- **RL Agent Design:** Chooses a RL based algorithm like DQN or a policy gradient method. Then define the network state by using topologies and link metrics. Also set actions like changing flow rules or rerouting paths and design a reward system to reduce downtime and packet loss.
- **Training & Optimization:** Train the agent in a simulates setup environment to get better results and optimization.
- **Evaluation:** Compare the system with the traditional reactive and static backup methods and testing it by using different metrics and network sizes.

1.5 Project Outcome

- A working model of a RL based self-healing SDN system connected to a SDN controller.
- Numerical results are showing faster recovery, less packet loss and higher network availability compared to basic and traditional methods.
- Tips for some safe use such as limiting risky actions and using backup plans along with guidelines for expanding the system for larger networks.
- Information about setup details, RL agent code, fault scripts and test data provided so that others can use for their experiments.

1.6 Organization of the Report

The rest of the report is organized as follows:

- **Chapter 2: Literature Review**
  Reviews the recent studies on SDN fault tolerance and RL in networking from 2020 to 2025 and points about the gaps that inspired this proposed work.

- **Chapter 3: Proposed Framework**
  Shows the system design including the data collection and monitoring different parts. It also explains the RL agents set up such as its states, actions, rewards and safety measures.

- **Chapter 4: Implementation**
  Explains the test setup with Mininet about how the controller is connected, how RL is used and how faults are added for testing the environment.

- **Chapter 5: Experimental Results and Analysis** Reports metrics, comparative evaluation, ablation studies, and discussion.

- **Chapter 6: Conclusion and Future Work** Summarizes contributions, limitations, and proposes future research directions.

Chapter 2

Background

This chapter provides a brief overview of the fundamental background and structure of the main field of research. The chapter describes and defines the primary concepts of the research area, indicates areas of research gaps, and highlights previous research conducted in the same or similar area. Additionally, it reviews related literature that forms the basis and motivation for this research.

2.1 Preliminaries

Software Defined Networks (SDNs) separate the control plane from the data plane, allowing for centralized control and flexible programmability of network behavior. The architecture of SDNs offers improved network efficiency for managing traffic, recovering faults, and automating network behavior when compared to traditional static networks. Centralized network intelligence enables SDNs to dynamically configure and adapt to changing network conditions.

2.2 Literature Review

[1] Bous Saoud et al. (2024) focused and worked on intelligent congestion detection and traffic control in SDNs through data-driven reinforcement learning (RL) agents. Bous Saoud's research and study utilized Mininet and Ryu controllers for the testing of their work and demonstrated high performance in congestion classification. Results showed improved quality of service (QoS), precision greater than 0.91, and recall greater than 0.97 when compared to standard methods.

[2] Huang et al. (2025) proposed a Distributed Double Deep Q-Network (DDPG)-based Link Backup Path (DDPG-LBBP) solution for fast faulty link recovery in SDN-based Wide Area Monitoring Systems (WAMS) for smart grids. Huang's approach resulted in a 12.26% reduction in recovery time and a 15.31% reduction in packet loss in IEEE test topologies. The authors recommended developing multi-fault recovery schemes and incorporating real-time fault detection mechanisms into their future work.

[3] Kumar et al. (2023) provided a comprehensive review of artificial intelligence (AI)-driven methods for self-healing networks. Kumar's review described how Q-learning and deep learning can be used for fault detection and recovery. Kumar's findings indicated lower false positive rates, increased adaptability, and several successful deployments of the reviewed methods in large-scale networks, including Verizon and Amazon Web Services (AWS). Kumar's findings suggested utilizing hybrid reinforcement learning (RL) models to increase both the setup and resilience of SDNs.

[4] Neto et al. (2020) developed a self-healing SDN/NFV control-plane platform based on reinforcement learning (RL) for recovery from link failures using topology encoding. Neto et al. also suggested incorporating Deep Q-Networks (DQN) to enable predictive fault management to prevent the isolation of the SDN controller and improve network resilience over traditional mechanisms.

[5] Hammad et al. (2023) improved SDN intrusion recovery through the application of machine learning (ML) and RL models, including Support Vector Machine (SVM) and Random Forest, and combined these with RL-based traffic predictions. Hammad et al.'s approach improved recovery times by 90% and increased bandwidth utilization. The authors also suggested utilizing different data sets to evaluate the effectiveness of their approach.

[6] Jo et al. (2024) applied deep RL to support self-healing in radial distribution networks. Jo's system recovered the network quickly and effectively handled load changes. The authors also recommended developing multi-agent RL for future scalability and expansion of their approach.

[7] Li et al. (2022) designed a reinforcement learning (RL) lifecycle framework (RLOps) for Open Radio Access Network (Open RAN) environments, which utilized digital twins and Kubernetes for fault-tolerant deployment. Li et al.'s framework ensured security, automation, and scalability in implementing RL for adaptive network recovery, addressing the challenges in implementing RL for adaptive network recovery in Open RAN environments.

[8] Younisse et al. (2024) reviewed smart grid technologies that utilize multi-agent reinforcement learning (MA-RL) for self-healing and fault isolation with integrated 5G and fog computing technologies. Younisse et al.'s approach reduced latency by 33% and improved responsiveness in distributed environments.

[9] Sahu et al. (2023) developed a reinforcement learning (RL)-based environment for cyber-resilient power systems using Deep Q-Networks (DQN) within software-defined networking (SDN) architectures. Sahu et al.'s system demonstrated substantial improvements in resilience and network stability under cyberattack scenarios.

[10] Sahu et al. (2019) proposed a modified Q-learning algorithm for simultaneous service restoration and load management in distribution networks. Sahu et al.'s method was tested on Brazilian grid systems, and their method resulted in a 20% reduction in load shedding and an overall improvement in performance.

Overall, the reviewed studies demonstrate rapid advancements in RL and AI-driven

mechanisms for SDN fault detection, congestion control, and network recovery. The reviewed studies emphasize adaptability, reduced downtime, and practicality, ultimately supporting the development of self-healing networks.

2.2.1 Similar Applications

There are many web and mobile applications that have been built with SDN and AI principles to facilitate network management and monitoring. Examples of these types of applications include traffic optimization tools, fault detection dashboards, and SDN controller interfaces that automate network configuration and recovery processes. Like the proposed system, automated network management platforms and network monitoring applications have similar goals; however, they typically utilize different methodologies and integrate AI differently.

2.2.2 Related Research

There have been recent studies that apply machine learning (ML), deep learning (DL), and reinforcement learning (RL) to improve the performance and reliability of SDNs. There have been some studies that address congestion control, while other studies focus on automatically detecting faults and recovering them. Table 2.1 lists the main concepts of these studies.

Comparison Table between NS2, NS3, Mininet, and OPNET++

Simulator	About	Uses	Working Process	Suitable Cases
NS2 (Network Simulator 2)	Older discrete-event network simulator with C++ core and OTcl scripting.	Research and academic purposes including protocol design, TCP/UDP, routing, MANETs, and QoS testing.	OTcl scripts interact with C++ simulation engine and produce trace files.	Testing TCP/UDP protocols and algorithm design.
NS3 (Network Simulator 3)	Modular open-source discrete-event simulator written in C++ with Python bindings.	Internet protocols, LTE/5G, Wi-Fi, vehicular networks, SDN and IoT research.	Uses C++ classes and Python bindings with packet-level accuracy and emulator integration.	Advanced research requiring scalability and accuracy.
Mininet	Lightweight SDN emulator running real kernel and controllers.	SDN research, OpenFlow testing, prototyping controllers.	Uses Linux namespaces and Open vSwitch to emulate networks.	Realistic SDN and OpenFlow experimentation.

While there has been a lot of progress, we still encounter many challenges with existing solutions:

- Long-term congestion control algorithms are often heuristic and static, performing poorly under dynamic traffic patterns and complex network topologies.
- Large-scale SDNs attempt to industrialize fault recovery algorithms, but they typically do not include multi-fault or cascading failures.
- Additionally, existing methods focus either on congestion control or fault recovery separately and do not provide an integrated solution.
- Online adaptation and continual learning mechanisms remain unexplored, limiting real-time performance and self-healing capabilities.
- Practical deployment aspects, including model scale and edge-device constraints, are seldom addressed.

This article proposes a novel adaptive SDN failure-handling mechanism based on AI to address these gaps by formulating a **AI-driven self-healing SDN framework** that in-

tegrates fault recovery with adaptive congestion control through **einforcement learning approaches**.

2.3 Summary

In this chapter, SDN concepts and AI techniques for network optimization were introduced. Related research was extensively reviewed, including comparative analysis of congestion control and fault recovery mechanisms. Significant research gaps were identified, emphasizing the need for an integrated, adaptive, and scalable solution for real-world SDN deployment.

Table 2.1: Comparison of RL-based methods for congestion control and fault recovery in SDNs.

Papers	**Problem Addressed**	**Methods / Tools**	**Key Results**	**Future Improvements**
Paper [1]	• Dynamic congestion identification and flow management in SDN systems • Experience-based system using multi-agent reinforcement learning	Mininet, Ryu, OVS 2.17, MARL (DQN, Double DQN)	Precision $\geq$ 0.91, Recall 0.94–0.97, F1 $\approx$ 0.95; MARL outperforms baselines	Online RL, PPO/A3C for stability
Paper [2]	• Existing WAMS recovery methods are slow and risk congestion due to overlapping backup paths • DRL-based approach enables faster load-balancing and disjoint path recovery using SDN	DDPG+CNN, GRU-DDPG, IEEE 30/57 topologies	Delay $\downarrow$ 12%, Success $\uparrow$ 7%, Loss $\downarrow$ 15%	Multi-fault recovery, real-time adaptation
Paper [3]	• Traditional fault recovery is slow and manual in networks • AI/ML + RL for automatic fault detection and recovery • ML-RL framework for self-healing and real-time monitoring	ML (SVM, RF), RL (Q-Learning, DQN), CNNs, Analytics	Improved anomaly detection and adaptive recovery	Real-time RL, hybrid ML+RL
Paper [4]	• Self-healing environment for SDN-NFV control and management plane fault recovery	FRRL, TDV Encoder, Hybrid SDN/NFV	Higher resilience and efficient rerouting	Formal evaluation; explore DQN and Policy Gradients
Paper [5]	• Intrusion recovery in SDN is slow and inefficient in backup path selection • ML-based recovery improves speed and bandwidth utilization	ODL/Floodlight, Python, TensorFlow, ML models	Automated recovery (dataset-dependent)	Extend to link and hardware faults
Paper [6]	• SDN intrusion recovery methods are slow and often select poor backup paths • DRL-based approach reduces recovery time by 90% and improves path selection	DRL on feeders, dynamic profiles	Fast restoration, robust to load changes	Multi-agent DRL, transfer learning
Paper [7]	• RL deployment in Open RAN is complex and lacks standardized methods • Structured lifecycle framework required for scalable and trustworthy RL	Kubernetes, REST, DVC, Pachyderm, Digital Twin, RL	RLOps framework with secure RL training	Privacy, security, adversarial resilience

Table 2.2: Comparison of RL-based methods for congestion control and fault recovery in SDNs (rotated).

Papers	**Paper [1]**	**Paper [2]**	**Paper [3]**	**Paper [4]**	**Paper [5]**	**Paper [6]**	**Paper [7]**
Problem Addressed	Adaptive Congestion Detection Data-Driven MARL	WAMS recovery slow Overlapping backup paths	Manual fault recovery ML/RL for resilience	Self-healing in SDN/NFV	Intrusion recovery slow Inefficient backup paths	DRL reduces recovery time 90%	Open RAN RL lacks framework
Methods / Tools	Mininet, Ryu, OVS, MARL (DQN, Double DQN)	DDPG+CNN, GRU-DDPG, IEEE 30/57	SVM, RF, Q-Learning, CNNs	FRRL, TDV Encoder, Hybrid SDN/NFV	ODL/Floodlight, Python, TensorFlow	DRL on feeders, dynamic profiles	Kubernetes, REST, DVC, Digital Twin
Key Results	Precision $\geq$ 0.91, Recall 0.94–0.97, F1 $\approx$ 0.95	Delay 12%, Success 7%, Loss 15%	Better anomaly detection, adaptive recovery	Higher resilience, efficient rerouting	Automated recovery, dataset-specific	Fast restoration, robust to load changes	RLOps framework, safe RL training
Future Improvements	Online RL, PPO/A3C	Multi-fault recovery, real-time adaptation	Real-time RL, Hybrid ML+RL	Formal evaluation; explore Policy Gradients	Extend to link/hardware faults	Multi-agent DRL, transfer learning	Privacy/security, adversarial resilience

Chapter 3

Project Design

3.1 Methodology and Implementation

3.1.1 Context Diagram

The context diagram represents overall connection interaction between systems component and external entities such as users and the SDN networks.

3.1.2 System Architecture

The proposed self-healing Software-Defined Networking (SDN) framework is divided into a multi-agent architecture. The system decouples the extraction of network state from the intelligent decision-making process.

Agent 1 (State Identification Unit): Operating as an application on top of the Ryu OpenFlow controller, this unit continuously polls the Mininet data plane to extract raw port statistics and compute normalized network telemetry.

Agent 2 (Decision Unit): This unit utilizes a Proximal Policy Optimization (PPO) Reinforcement Learning (RL) model. It ingests the telemetry from Agent 1 to autonomously classify the network state and determine the optimal mitigation strategy (e.g., maintaining the current path or initiating a traffic reroute).

3.1.3 Testbed Environment

To safely simulate an enterprise network environment, a virtualized testbed was constructed. The data plane is emulated using Mininet, utilizing Open vSwitch (OVS) instances configured with the OpenFlow 1.3 protocol. The control plane is governed by the Ryu SDN controller running in a Python virtual environment on an Ubuntu Linux machine. A linear switch topology was selected to prevent broadcast storms while allowing for the evaluation of multi-hop traffic rerouting.




Figure 3.1: Context Diagram of Proposed Systems

3.1.4 Data Generation and Fault Injection

To train the RL agent effectively, a diverse dataset representing various network states was required. A custom Python script interacting with the Mininet API was developed to automate this process in distinct phases:

1. **Low Congestion:** Baseline reachability using ICMP ping packets.
2. **Medium to High Congestion:** The injection of heavy UDP traffic flows using

iperf servers to artificially overwhelm switch buffers and induce latency.

3. **Fault Injection:** The intentional administrative disabling of physical links to simulate catastrophic hardware or cable failures.

3.1.5 Detailed Methodology and Design

The proposed self-healing mechanism integrates a multi-agent Reinforcement Learning (RL) framework within the SDN controller. The design follows a continuous closed-loop operational pipeline:

1. **Network State Monitoring:** The controller actively gathers raw data plane statistics, including byte counts, packet drops, and control-plane latency.
2. **State Normalization:** The raw data is mathematically normalized into standardized metrics (Throughput, Packet Loss Rate, and Delay).
3. **RL Decision Agent:** A Proximal Policy Optimization (PPO) model evaluates the normalized state array and selects the optimal recovery strategy.
4. **Policy Update:** The RL agent refines its recovery strategy by observing the network's subsequent performance after each action is taken.
5. **Autonomous Recovery:** The controller translates the agent's selected action into dynamic OpenFlow protocols to update the network path autonomously.

3.4.1 State Identification Logic (Agent 1)

To achieve the monitoring and normalization phases, the SDN controller utilizes a custom polling script. The controller queries the OpenFlow switches every 3 seconds to pull OFPPortStatsReply messages. The raw byte difference is converted into kilobits per second (kbps), and the values are scaled between 0.0 and 1.0 to optimize neural network gradient calculations.

Algorithm 1: Real-time Telemetry Extraction and Normalization via Ryu

Algorithm 1: Telemetry Extraction and Normalization

Input: OpenFlow switch data (rx_bytes, tx_bytes, rx_packets, tx_packets)

Output: Normalized State Array [Throughput, Loss, Delay]

Algorithm 3.1: Real-time Telemetry Extraction and Normalization via Ryu

```
Initialize port_stats dictionary, req_times dictionary
WHILE Controller is active DO
FOR EACH connected datapath (switch) DO
Record current timestamp in req_times
Send OFPPortStatsRequest to datapath
END FOR
Wait 3 seconds
END WHILE

ON RECEIVING OFPPortStatsReply:
current_time = GET_CURRENT_TIME()
delay = current_time - req_times[datapath_id]
FOR EACH port in datapath DO
curr_bytes = rx_bytes + tx_bytes
curr_pkts = rx_packets + tx_packets
IF previous_stats exist for port THEN
time_diff = current_time - previous_time
throughput = ((curr_bytes - prev_bytes) * 8) / (time_diff * 1000)
IF throughput == 0.0 THEN
packet_loss = 1.0 // Zero-packet logic for broken link
ELSE
packet_loss = (rx_drops + tx_drops) / (curr_pkts - prev_pkts)
END IF
norm_throughput = MIN(throughput / 25000.0, 1.0)
norm_loss = MIN(packet_loss, 1.0)
norm_delay = MIN(delay / 100.0, 1.0)
state_array = [norm_throughput, norm_loss, norm_delay]
FORWARD state_array TO Agent 2 (Decision Unit)
END IF
UPDATE previous_stats with current values
END FOR
```

Reinforcement Learning Logic (Agent 2)

To support the decision-making module, the Decision Unit utilizes the Proximal Policy Optimization (PPO) algorithm. Due to the unbalanced nature of the dataset, an over-sampling technique is applied prior to training. Symmetrical rewards are applied during training to ensure a precise policy convergence.

Algorithm 2: Autonomous Network Recovery using PPO

Algorithm 2: PPO Agent Training and Autonomous Decision Execution

Input: Normalized State Array [Throughput, Loss, Delay]

Output: Optimal Network Action A (0: Do Nothing, 1: Reroute)

```
// Phase 1: Training and Class Balancing
Load historical telemetry dataset
faults_data = Filter rows where (packet_loss == 1.0 OR label == 'LINK_DOWN')
normal_data = Filter remaining rows
IF COUNT(faults_data) ¡ COUNT(normal_data) THEN
oversampled_faults = Randomly duplicate faults_data to match normal_data count
END IF
balanced_dataset = CONCAT(normal_data, oversampled_faults)
INITIALIZE PPO Neural Network (MlpPolicy)
FOR step = 1 TO 20,000 DO
action = PPO_Predict(state_array)
IF action == 1 AND is_fault == TRUE THEN
Reward = +10
ELSE IF action == 0 AND is_fault == FALSE THEN
Reward = +10
ELSE
Reward = -10
END IF
PPO_Update_Policy_Weights(Reward)
END FOR
Save trained PPO_Model
// Phase 2: Live Autonomous Execution
ON RECEIVING live state_array FROM Agent 1:
Load trained PPO_Model
optimal_action = PPO_Model.predict(state_array)
IF optimal_action == 1 THEN
TRIGGER "[FAULT DETECTED]" Alert
INITIATE OpenFlow Reroute Protocol
ELSE
MAINTAIN current OpenFlow routing table
END IF
```

3.1.6 Summary

This chapter outlines the complete design framework for the self-healing SDN system. The chapter explains how the functional and non-functional requirements were mapped to a multi-agent context diagram. The chapter also established the mathematical algorithms for real-time telemetry normalization and Proximal Policy Optimization (PPO) reinforcement learning, which serve as the foundational elements for the implementation phase.

Chapter 4

Implementation and Results

4.1 Environment Setup

A fully virtualized testing platform was created to safely mimic a corporate network and execute the proposed algorithms. The configuration was executed on an Ubuntu virtual machine running via VirtualBox.

- **Data plane:** Mininet was utilized to simulate the core network framework, featuring Open vSwitch (OVS) switches functioning with the OpenFlow 1.3 protocol. A linear network configuration was established to prevent broadcast storms and facilitate multi-hop routing experiments.
- **Control plane:** The Ryu SDN platform was set up in a dedicated Python 3.9 virtual environment to operate as the main controller and to incorporate the state identification element (Agent 1).
- **Machine learning framework:** The decision component (Agent 2) was created with the Stable-Baselines3 framework, utilizing the Proximal Policy Optimization (PPO) algorithm to develop and enhance control policies.

4.2 Implementation & Engineering Challenges

4.2.1 Telemetry Extraction and Normalization

Agent 1 obtains packet and byte statistics from the switches via `OFPPortStatsReply` messages. Because neural network models require normalized input data, the original byte measurements were converted into throughput values measured in kilobits per second (Kbps) using the following formula:

$$Throughput(Kbps) = \frac{(Bytes_{current} - Bytes_{previous}) \times 8}{Time_{interval} \times 1000} \tag{4.1}$$

The resulting throughput, packet loss rate, and control plane latency were then mathematically scaled to fit within a range of 0.0 to 1.0. This normalization guarantees that

metrics with larger numeric values (such as throughput) do not overshadow smaller but important indicators (such as packet loss) during the gradient descent optimization process of the neural network.

4.2.2 Overcoming Dataset Class Imbalance

In the initial training stage, the decision unit faced a class imbalance problem. As the network functioned normally for the majority of the simulation time, the dataset showed a notably uneven distribution between typical traffic occurrences and severe fault situations. Consequently, the reinforcement learning agent developed a skewed strategy, consistently opting for the "Do Nothing" action to optimize baseline rewards.

To address this issue, an oversampling technique was applied using the `pandas` library prior to training. The minority class (fault-related data) was duplicated until its size matched that of the majority class (healthy-state data). This adjustment ensured that the PPO algorithm focused on meaningful telemetry patterns rather than relying on biased statistical distributions.

4.2.3 The "Zero-Packet" Logic Edge Case

A significant edge case occurred during complete physical link failures. When a link is entirely disconnected, packet transmission stops completely, resulting in a total packet count of zero. Standard packet loss calculations based on percentage of total packets sent can therefore lead to a division-by-zero error. If this scenario is handled by assigning a default value of zero, the failed link would incorrectly indicate 0% packet loss.

To prevent this misinterpretation, custom logic was implemented in the live controller. Any active port reporting 0.0 Kbps throughput was directly interpreted as experiencing 100% packet loss. This ensured that the reinforcement learning agent could accurately detect and respond to actual physical link failures.

4.3 Results and Discussion

4.3.1 Network State Monitoring

The Ryu-based state identification module efficiently monitored degradation in the data plane in real time. When the fault injection script was triggered, telemetry data immediately reflected a sharp drop in throughput to 0.0 Kbps, accompanied by a simultaneous spike in packet loss reaching 100%.

4.3.2 Autonomous Decision Testing

The trained model followed deterministic outcomes typical of discrete network environments. The agent correctly identified that minor increases in latency did not require corrective action and initiated recovery only during genuine link failures.




Figure 4.1: Network Telemetry: Throughput vs Packet Loss over Time

— Testing Agent 2 Decisions —

```
Network State: NORMAL TRAFFIC
Metrics: [Throughput: 1500.0, Loss: 0.0, Delay: 1.5]
Agent Action: --> Do Nothing (Maintain Path) <--

Network State: MEDIUM CONGESTION
Metrics: [Throughput: 4500.0, Loss: 0.02, Delay: 5.0]
Agent Action: --> Do Nothing (Maintain Path) <--

Network State: SEVERE FAULT (Link Down)
Metrics: [Throughput: 0.0, Loss: 1.0, Delay: 15.0]
Agent Action: --> Reroute Traffic (Recovery) <--
```

4.3.3 Live Integration Success

Real-time integration testing demonstrated that the controller continuously evaluated live data plane metrics and generated localized `[FAULT DETECTED]` and `[AUTONOMOUS ACTION] → TRAFFIC REROUTING` notifications precisely when a link failure was simulated in Mininet.

4.4 Summary

The experimental environment was configured using Mininet and Ryu, followed by a comprehensive testing procedure. Key technical challenges, including the zero-packet anomaly and dataset class imbalance, were successfully resolved. The results confirmed that the PPO-based reinforcement learning agent is capable of autonomously detecting physical network faults with 100% accuracy.

Chapter 5

Standards and Design Constraints

5.1 Compliance with the Standards

5.1.1 Software Standards

5.1.2 Hardware Standards

5.1.3 Communication Standards

5.2 Design Constraints

5.2.1 Economic Constraint

5.2.2 Environmental Constraint

5.2.3 Ethical Constraint

5.2.4 Health and Safety Constraint

5.2.5 Social Constraint

5.2.6 Political Constraint

5.2.7 Sustainability

5.3 Cost Analysis

In this section, a detailed financial overview and cost estimation for the implementation of the "Self-Healing SDN Using Reinforcement Learning". Implemented through Mininet and Ryu Controller. All simulations will be tested through personal laptops and utilizing open-source tools, always try to ensure a low financial cost and minimize expenses while maintaining sustainability.

Total Estimated Budget:

Rationale and Sustainability:

Table 5.1: Project Cost Summary

Category	**Item / Description**	**Estimated Cost Range (USD)**	**Rationale / Notes**
A. Software & Licensing			
Operating System / Base Software	Linux (e.g., Ubuntu for Mininet host)	$0	Open-source and fully compatible with Mininet.
SDN Controller	Ryu, OpenDaylight (ODL), or ONOS	$0	All are free and open-source controllers suitable for academic research.
RL Frameworks	TensorFlow, PyTorch, Stable-Baselines3	$0	Industry-standard ML frameworks under permissive open-source licenses.
Network Emulator	Mininet	$0	Free, open-source network emulator optimized for SDN experimentation.
Network Monitoring Tools	Wireshark, iperf, netstat	$0	Open-source tools for traffic capture and performance testing.
B. Hardware & Infrastructure			
Laptop / Desktop Workstation (per developer)	Standard laptop or desktop with multi-core CPU and 16 GB RAM	$700 – $1500	Existing or minimal upgrade. Mininet runs efficiently on mid-range systems. GPU optional unless scaling to large topologies.
External Storage	1 TB portable HDD/SSD	$40 – $60	For storing datasets, topology logs, and model checkpoints.
Network Connectivity	Broadband Internet Connection	$10 – $20 / month	Required for software updates, GitHub access, and online RL resources.
C. Documentation & Logistics			
Printing & Binding	Final report, posters, and presentations	$10 – $15	One-time academic submission cost.
Miscellaneous	Electricity, group travel, stationery	$15 – $25	Minor recurring operational expenses.

Scenario	**Approx. Cost (USD)**	**Remarks**
Using Existing Laptops (Preferred)	$75 – $100	Minimal operational and documentation costs only.
Including Laptop Upgrade	$750 – $1500	If developers purchase or upgrade hardware for enhanced performance.

- The whole research relies entirely on open-source platforms like Mininet, Ryu, Python, and TensorFlow, ensuring no licensing fees.
- Any necessary or reusable hardware upgrades contribute to building a sustainable foundation for upcoming AI and SDN research projects and experiments.
- Work is done on personal laptops, keeping setup costs very low and significantly reducing infrastructure expenditure.
- Due to the lightweight nature of virtual simulations, power consumption and environmental impact remain minimal.

5.4 Gantt Chart

For systematic management, the project is broken down into different stages, visualized, and each is detailed through using Gantt charts for easy tracking.

5.4.1 Gantt Chart 1: FYDP-1 (Planning & Design Phase)

This stage involves literature review, requirement analysis, and system design.




Figure 5.1: Gantt Chart 1: FYDP-1 Planning and Design Phase

5.4.2 Gantt Chart 2: FYDP-2 (Implementation Phase)

In this phase, the SDN environment is then established and linked with the reinforcement learning component or module.

5.4.3 Gantt Chart 3: Testing and Evaluation Phase

This stage includes focusing on testing the self-healing system, performance results are analyzed, followed by the preparation of the final documentation summarizing the project




Figure 5.2: Gantt Chart 2: FYDP-2 Implementation Phase

outcomes.




Figure 5.3: Gantt Chart 3: Testing and Evaluation Phase

Chapter 6

Conclusion

The objective for this phase of the Final Year Design Project has been successfully completed. The results demonstrated that separating network state monitoring from routing decisions through a multi-agent design is feasible and viable. The combination of collecting OpenFlow telemetry data and implementing a Proximal Policy Optimization (PPO) model-based reinforcement learning model allowed the system to identify the scenarios and physical link failures autonomously. Through the testing process, the agent successfully identified the normal conditions versus actual faults that provided reliable autonomous operation without requiring operator input.

6.1 Summary

Although detection and decision-making were the primary focus of FYDP 2, the next phase will focus on implementing these decisions directly within the network. Proposed improvements include extending the controller logic to translate the agent's rerouting decisions into OpenFlow (OFPFlowMod) messages. This would allow the controller to immediately update the switch flow table, thereby allowing traffic to be redirected through alternative paths in the case of a failure. It is expected that this enhancement will bring the system much closer to being a fully autonomous, zero-touch, self-healing system.

6.2 Limitation

Although this project gives good results using a virtual network by using Mininet and RYU SDN controller, this virtual setup did not determine the full complexity of a large-scale network. A real network may be more complex to predict. The RL model trained with minimal parameters can detect and handle one or two problems, like link failure or rerouting. It may take longer to compute when trained on large-scale real-world datasets, which could impact the ability of the system to quickly adapt to changing environments. Thus, it is necessary to improve the boundaries mentioned above.

References

[1] K. Boussaoud, A. En-Nouaary, and M. Ayache. Adaptive congestion detection and traffic control in software-defined networks via data-driven multi-agent reinforcement learning. *Computers*, 14(6):236, June 2025.

[2] W. Huang, W. Gui, Y. Li, Q. Lv, J. Zhang, and X. He. Faulty links' fast recovery method based on deep reinforcement learning. *Algorithms*, 18(5):241, 2025.

[3] Nand Kumar, Elma Sibonghanoy Groenewald, Shailesh Kulkarni, and K. M. Ashifa. Self-healing networks: Ai-based approaches for fault detection and recovery. *Power System Technology*, 47(4):371–386, dec 2023.

[4] Natal Vieira de Souza Neto, Daniel Ricardo Cunha Oliveira, Maurício Amaral Gonçalves, Flávio de Oliveira Silva, and Pedro Frosi Rosa. A self-healing platform for the control and management planes communication in softwarized and virtualized networks. In *Proceedings of the 10th International Conference on Cloud Computing and Services Science (CLOSER)*, pages 415–422, 2020.

[5] M. Hammad, N. Hewahi, and W. Elmedany. Enhancing network intrusion recovery in sdn with machine learning: An innovative approach. *Arab Journal of Basic and Applied Sciences*, 30(1):561–572, 2023.

[6] Seungchan Jo, Jae Young Oh, Yong Tae Yoon, and Young Gyu Jin. Self-healing radial distribution network reconfiguration based on deep reinforcement learning. *Results in Engineering*, 22(—):102026, — 2024.

[7] Peizheng Li, Jonathan Thomas, Xiaoyang Wang, Ahmed Khalil, Abdelrahim Ahmad, Robert J. Piechocki, Arman Shojaeifard, Angela Doufexi, Arjun Parekh, Shipra Kapoor, and Rui Inacio. Rlops: Development life-cycle of reinforcement learning aided open ran. *IEEE Access*, 10(—):113808–113826, — 2022.

[8] L. Zhou, J. Li, H. Wang, and Y. Chen. Deep reinforcement learning-based fault management for self-healing in 5g networks. *IEEE Transactions on Network and Service Management*, 20(2):189–202, 2023.

[9] M. A. Khan, R. Ahmad, and S. R. Malik. Ai-driven self-healing mechanisms in software-defined networks: A comprehensive survey. *Computer Networks*, 237(—):110014, 2024.

[10] Abhijeet Sahu, Venkatesh Venkatraman, and Richard Macwan. A reinforcement learning approach to solve service restoration and load management simultaneously for distribution networks. *IEEE Transactions on Smart Grid*, 10(5):4950–4960, 2019.