

DAY-5:

TERRAFORM:

Terraform is an **Infrastructure as Code (IaC)** tool developed by **HashiCorp** that allows users to define and provision infrastructure using a **declarative configuration language**. It supports various cloud providers like **AWS, Azure, GCP, and on-premises** environments.

```
terraform {
  required_providers {
    aws = {
      source = "hashicorp/aws"
      version = "5.92.0"
    }
  }
}

provider "aws" {
  region = "us-east-1"
}

resource "aws_vpc" "myvpc" {
  cidr_block = "10.0.0.0/16"

  tags = {
    Name = "demovpc"
  }
}

resource "aws_subnet" "pubsub" {
  vpc_id = aws_vpc.myvpc.id
  cidr_block = "10.0.1.0/24"
  availability_zone = "us-east-1a"

  tags = {
    Name = "sn1"
  }
}

resource "aws_subnet" "pubsub" {
  vpc_id = aws_vpc.myvpc.id
  cidr_block = "10.0.2.0/24"
  availability_zone = "us-east-1b"

  tags = {
    Name = "sn2"
  }
}

resource "aws_subnet" "prisub" {
  vpc_id = aws_vpc.myvpc.id
  cidr_block = "10.0.3.0/24"
  availability_zone = "us-east-1b"
}
```

```

tags = {
  Name = "sn3"
}
}

resource "aws_subnet" "prisub" {
  vpc_id    = aws_vpc.myvpc.id
  cidr_block = "10.0.4.0/24"
  availability_zone = "us-east-1b"

  tags = {
    Name = "sn4"
  }
}

resource "aws_internet_gateway" "tfigw" {
  vpc_id = aws_vpc.myvpc.id

  tags = {
    Name = "tfigw"
  }
}

resource "aws_route_table" "tfpubrt" {
  vpc_id = aws_vpc.myvpc.id

  route {
    cidr_block = "0.0.0.0/0"
    gateway_id = aws_internet_gateway.tfigw.id
  }

  tags = {
    Name = "tfpublicroute"
  }
}

resource "aws_route_table_association" "pubsn1" {
  subnet_id    = aws_subnet.pubsub.id
  route_table_id = aws_route_table.tfpubrt.id
}

resource "aws_route_table_association" "pubsn2" {
  subnet_id    = aws_subnet.pub_sub.id
  route_table_id = aws_route_table.tfpubrt.id
}

resource "aws_eip" "tfeip" {
  domain = "vpc"
}

resource "aws_nat_gateway" "tfnat" {
  allocation_id = aws_eip.tfeip.id
  subnet_id    = aws_subnet.pub_sub.id

  tags = {
    Name = "gw NAT"
  }
}

```

```

    }
  }
  resource "aws_route_table" "tfprirt" {
    vpc_id = aws_vpc.myvpc.id

    route {
      cidr_block = "0.0.0.0/0"
      gateway_id = aws_nat_gateway.tfnat.id
    }

    tags = {
      Name = "tfprivateroute"
    }
  }
  resource "aws_route_table_association" "prisn3" {
    subnet_id    = aws_subnet.prisub.id
    route_table_id = aws_route_table.tfprirt.id
  }
  resource "aws_route_table_association" "prisn4" {
    subnet_id    = aws_subnet.pri_sub.id
    route_table_id = aws_route_table.tfprirt.id
  }
  resource "aws_security_group" "allow_tfsg" {
    name        = "allow_tfsg"
    description = "Allow TLS inbound traffic"
    vpc_id      = aws_vpc.myvpc.id

    ingress {
      description = "HTTPS "
      from_port   = 443
      to_port     = 443
      protocol    = "tcp"
      cidr_blocks = ["0.0.0.0/0"]
    }
    ingress {
      description = "HTTP "
      from_port   = 80
      to_port     = 80
      protocol    = "tcp"
      cidr_blocks = ["0.0.0.0/0"]
    }
    ingress {
      description = "SSH"
      from_port   = 22
      to_port     = 22
      protocol    = "tcp"
      cidr_blocks = ["0.0.0.0/0"]
    }
  }
  egress {

```

```

    from_port    = 0
    to_port      = 0
    protocol     = "-1"
    cidr_blocks  = ["0.0.0.0/0"]
  }

  tags = {
    Name = "TfsecurityGroup"
  }
}

resource "aws_instance" "pub_ins" {
  ami            = "ami-0fc5d935ebf8bc3bc"
  instance_type  = "t2.micro"
  subnet_id      = aws_subnet.pub_sub.id
  vpc_security_group_ids = [aws_security_group.allow_tfsg.id]
  key_name       = "David"
  associate_public_ip_address = "true"
}

resource "aws_instance" "pri_ins" {
  ami            = "ami-0fc5d935ebf8bc3bc"
  instance_type  = "t2.micro"
  subnet_id      = aws_subnet.prisub.id
  vpc_security_group_ids = [aws_security_group.allow_tfsg.id]
  key_name       = "ashilin"
}

```