

Carrier Ethernet Service Specification v2.1

Revision History

Version	Date	Author	Change
1.0	2023-01-15	J. Smith	Initial release
2.0	2024-03-02	A. Lee	Added UNI section
2.1	2025-06-30	A. Lee	Editorial fixes

1 Introduction

This document specifies the service attributes of an Ethernet Virtual Connection (EVC) delivered by a Service Provider to a Subscriber. The EVC is an association of two or more UNIs that limits the exchange of Service Frames.

Figure 2 – Reference model

4 Service Attributes

4.3 EVC Service Attributes

Attribute	Type	Units	M/O/C	Range	Default	Description
CIR	Integer	Mbps	M	10–1000	100	Committed Information Rate for the EVC
EIR	Integer	Mbps	O	0–1000	0	Excess Information Rate for the EVC
EVC ID	String		M			Unique identifier for the EVC assigned by the Service Provider
Service Type	Enum		M	Point-to-Point, Multipoint-to-Multipoint	Point-to-Point	Connectivity type of the EVC
CoS Name	String		O		Standard	Class of Service name applied to the EVC

Table 3 – EVC Service Attributes

5 UNI

The UNI has a port speed of 1 Gbps. Each UNI SHALL have a physical medium and a MAC address. There are 12 such UNIs in the reference deployment.

5.1 UNI Attributes

Attribute	Type	Units	M/O/C	Range	Default	Description
Port Speed	Integer	Mbps	M	10, 100, 1000, 10000	1000	Physical port speed of the UNI
Physical Medium	Enum		M	Copper, Fibre	Fibre	Physical medium of the UNI
MAC Address	String		M			MAC address of the UNI port

6 Subscriber

Each Subscriber SHALL have an IMSI and an MSISDN. The Subscriber's MSISDN is an E.164 number such as +447700900123. The Order is created, submitted and terminated by the operator. Provisioning of the service takes up to 5 working days.

7 Service Provider

The Service Provider allocates the EVC ID and maintains the Ethernet Virtual Connection for the duration of the contract.

Page 3 of 3