

# Practical-9

## Performing basics commands to interact with kubernetes

The objective of this lab is to familiarize yourself with basic commands to interact with a Kubernetes cluster. You will learn how to perform essential operations such as deploying pods,

### Lab Steps:

Step 1: Verify 'kubectl' Configuration

```
PS D:\Desktop\stream> kubectl config current-context  
docker-desktop
```

Step 2: List Nodes To view the nodes in your Kubernetes cluster, use the following command

```
PS D:\Desktop\stream> kubectl get nodes  
NAME                STATUS    ROLES    AGE     VERSION  
docker-desktop      Ready    control-plane  2m30s  v1.27.2
```

Step 3: Create a Deployment Create a simple NGINX deployment using the 'kubectl create' command

```
PS D:\Desktop\stream> kubectl create deployment nginx-deployment --image=nginx  
deployment.apps/nginx-deployment created
```

### Verify the deployment

```
PS D:\Desktop\stream> kubectl get deployments  
NAME                READY    UP-TO-DATE    AVAILABLE    AGE  
nginx-deployment    1/1      1             1            27s
```

Step 4: List Pods To list the pods in your cluster, run

```
PS D:\Desktop\stream> kubectl get pods  
NAME                                READY    STATUS    RESTARTS    AGE  
nginx-deployment-66fb7f764c-8jv7g  1/1      Running    0            3m9s
```

Step 5: Access Pod Logs Access the logs of one of the NGINX pods to check its activity

```
PS D:\Desktop\stream> kubectl logs nginx-deployment-66fb7f764c-8jv7g
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Sourcing /docker-entrypoint.d/15-local-resolvers.envsh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/11/23 13:05:43 [notice] 1#1: using the "epoll" event method
2023/11/23 13:05:43 [notice] 1#1: nginx/1.25.3
2023/11/23 13:05:43 [notice] 1#1: built by gcc 12.2.0 (Debian 12.2.0-14)
2023/11/23 13:05:43 [notice] 1#1: OS: Linux 5.15.90.1-microsoft-standard-WSL2
2023/11/23 13:05:43 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2023/11/23 13:05:43 [notice] 1#1: start worker processes
2023/11/23 13:05:43 [notice] 1#1: start worker process 29
2023/11/23 13:05:43 [notice] 1#1: start worker process 30
2023/11/23 13:05:43 [notice] 1#1: start worker process 31
2023/11/23 13:05:43 [notice] 1#1: start worker process 32
2023/11/23 13:05:43 [notice] 1#1: start worker process 33
2023/11/23 13:05:43 [notice] 1#1: start worker process 34
2023/11/23 13:05:43 [notice] 1#1: start worker process 35
2023/11/23 13:05:43 [notice] 1#1: start worker process 36
```

Step 6: Expose Deployment as a Service Expose the NGINX deployment as a service to make it accessible externally

```
PS D:\Desktop\stream> kubectl expose deployment nginx-deployment --port=80 --type=NodePort --name=nginx-service
service/nginx-service exposed
```

Step 7: List Services To list the services in your cluster

```
PS D:\Desktop\stream> kubectl get services
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
kubernetes	ClusterIP	10.96.0.1	<none>	443/TCP	10m
nginx-deployment	ClusterIP	10.96.11.106	<none>	80/TCP	2m31s
nginx-service	NodePort	10.99.103.113	<none>	80:32031/TCP	91s

Step 8: Access the NGINX Service Determine the NodePort assigned to the NGINX service

```

PS D:\Desktop\stream> kubectl describe service nginx-deployment
Name: nginx-deployment
Namespace: default
Labels: app=nginx-deployment
Annotations: <none>
Selector: app=nginx-deployment
Type: ClusterIP
IP Family Policy: SingleStack
IP Families: IPv4
IP: 10.96.11.106
IPs: 10.96.11.106
Port: <unset> 80/TCP
TargetPort: 80/TCP
Endpoints: 10.1.0.6:80
Session Affinity: None
Events: <none>

```

Step 9: Delete Resources Clean up by deleting the deployment and service

```

PS D:\Desktop\stream> kubectl delete deployment nginx-deployment
deployment.apps "nginx-deployment" deleted
PS D:\Desktop\stream> kubectl delete service nginx-deployment
service "nginx-deployment" deleted
PS D:\Desktop\stream>

```

Step 10: Scale Deployment Scale the NGINX deployment to run multiple replicas

```

PS D:\Desktop\stream> kubectl scale deployment nginx-deployment --replicas=3
error: no objects passed to scale

```

Step 11: Update Deployment

```

PS D:\Desktop\stream> kubectl create deployment nginx-deployment --image=nginx:1.21
deployment.apps/nginx-deployment created
PS D:\Desktop\stream> kubectl scale deployment nginx-deployment --replicas=3
deployment.apps/nginx-deployment scaled
PS D:\Desktop\stream> kubectl set image deployment/nginx-deployment nginx=nginx:1.21
PS D:\Desktop\stream> kubectl set image deployment/nginx-deployment nginx=nginx:1.21

```

Verify the rollout status :

```

PS D:\Desktop\stream> kubectl rollout status deployment/nginx-deployment
deployment "nginx-deployment" successfully rolled out

```



Step 12: Rollback Deployment If needed, you can rollback to the previous deployment version

```
PS D:\Desktop\stream> kubectl rollout history deployment/nginx-deployment
deployment.apps/nginx-deployment
REVISION  CHANGE-CAUSE
1          <none>

PS D:\Desktop\stream> kubectl set image deployment/nginx-deployment nginx=nginx:1.22
deployment.apps/nginx-deployment image updated
PS D:\Desktop\stream> 
```