

API Endpoints

Base URL: `http://98.86.63.69`

Header (all requests): X-API-Key:

`f379241418da1092837aaa6b7138e850e4b99b1b2f88ba90d527e6a0b4b4a600`

Method Endpoint Purpose

POST `/cases` Create new case → returns `case_id`

POST `/cases/{case_id}/files` Upload audio/video file → returns `job_id`

GET `/jobs/{job_id}` Poll job status + progress

GET `/jobs/{job_id}/result` Full result (transcript, speakers, conversation table)

GET `/cases/{case_id}/files/{file_id}/result` Same result by case+file

GET `/cases/{case_id}` List all files + latest job per file in case

POST `/jobs/{job_id}/rerun` Re-process same file with new job

POST `/cases/{case_id}/files/{file_id}/certify` Mark transcript certified

Test from Laptop (curl)

Variables

`BASE=http://98.86.63.69`

`KEY=f379241418da1092837aaa6b7138e850e4b99b1b2f88ba90d527e6a0b4b4a600`

`AUDIO=/path/to/your/file.mp4` # change this

1. Create case

```
CASE=$(curl -s -X POST "$BASE/cases" -H "X-API-Key: $KEY" | python3 -c "import json,sys;
print(json.load(sys.stdin)['case_id'])")
echo "case_id: $CASE"
```

2. Upload file

```
RESP=$(curl -s -X POST "$BASE/cases/$CASE/files"
-H "X-API-Key: $KEY"
-F "audio=@$AUDIO")
JOB=$(echo $RESP | python3 -c "import json,sys; print(json.load(sys.stdin)['job_id'])")
echo "job_id: $JOB"
```

3. Poll status

```
curl -s "$BASE/jobs/$JOB" -H "X-API-Key: $KEY" | python3 -m json.tool
```

4. Get result (once status = completed)

```
curl -s "$BASE/jobs/$JOB/result" -H "X-API-Key: $KEY" | python3 -m json.tool
```

5. Pretty-print conversation table only

```
curl -s "$BASE/jobs/$JOB/result" -H "X-API-Key: $KEY" |  
python3 -c "  
import json,sys  
d=json.load(sys.stdin)  
for r in d['conversation_table']['rows']:  
print(f'{{r['sl']:>3}}. [{{r['time']}}] {{r['person']:>15}}: {{r['conversation']}}")"
```

6. Save full result to file

```
curl -s "$BASE/jobs/$JOB/result" -H "X-API-Key: $KEY" > result.json
```

Poll Until Done (one-liner)

```
JOB=<your_job_id>  
while true; do  
S=$(curl -s "http://98.86.63.69/jobs/$JOB" -H "X-API-Key:  
f379241418da1092837aaa6b7138e850e4b99b1b2f88ba90d527e6a0b4b4a600" | python3 -c "import  
json,sys; d=json.load(sys.stdin); print(d['status'], d['stage'], str(d['progress'])+'%")")  
echo $S  
echo $S | grep -q "completed|failed" && break  
sleep 15  
done
```

Store in Your App

```
BASE_URL = http://98.86.63.69
```

```
API_KEY = f379241418da1092837aaa6b7138e850e4b99b1b2f88ba90d527e6a0b4b4a600
```

Webhook: pass `callback_url=https://yourapp.com/webhook` on file upload — server POSTs job status on every stage transition, so you don't need to poll.