

Certificates Used in ACE-Platform

Advanced Conversational Engagement

Exported on 06/06/2025

Table of Contents

1	Required tools	4
2	Steps to create SSL certificate.....	5
2.1	Config file with SAN.....	5
2.2	CSR file using Config	6
2.3	Upload the CSR	6
2.4	Convert OU Signed CER to PEM.....	7
2.5	Upload certificate and Key to secure files.....	8
2.6	Upload to Azure Key Vault.....	8

In ACE Platform we use 3 different certificates as below

- Infra CA G3 certificate (self-signed)
- Chained Certificate (Signed by trusted CA)
- Root Certificate

Infra CA G3 certificate:

We use Infra CA G3 certificate for

- Ingress in AKS
- To connect to other third-party applications by third-party service application used by Integration team
- Private Appgw certificates used for Advisor Assist

Procedure to deploy Infra CA G3 certificate:

There are 2 methods to deploy Infra CA G3 certificate:

1. Manually
2. Through Release Pipeline
3. Through Automated Pipeline

Steps to create Infra CA G3 certificate manually:

1 Required tools

- [OpenSsl](https://www.openssl.org/)¹
- [KeyStore](https://keystore-explorer.org/)²
- Bash

¹ <https://www.openssl.org/>

² <https://keystore-explorer.org/>

2 Steps to create SSL certificate

2.1 Config file with SAN

For the current project, approach to connect to the services is through alternate names on the same certificate. That is the Common Name (CN) says the same `ace-<env>.nl.eu.abnamro.com`³

Subject Alternate Names (SAN) values are provided during the certificate generation.

Create a supporting config file with required parameters:

```
## input config file
## filename: ace-csr-config.txt

default_bits      = 2048 # may also be 4096
distinguished_name = req_distinguished_name
req_extensions    = req_ext
prompt = no
[ req_distinguished_name ]
countryName       = NL
stateOrProvinceName = Noord-Holland
organizationName  = ABN AMRO Bank N.V.
commonName        = ace-d.nl.eu.abnamro.com
[ req_ext ]
subjectAltName = @alt_names
[alt_names]
DNS.1   = ace-d.nl.eu.abnamro.com
DNS.2   = pvt-dev-ace-d.nl.eu.abnamro.com
DNS.3   = labelstudio-ace-d.nl.eu.abnamro.com
DNS.4   = botstudio-ace-d.nl.eu.abnamro.com
DNS.5   = ml-model-simple-1-ace-d.nl.eu.abnamro.com
DNS.6   = botium-anna-ace-d.nl.eu.abnamro.com
DNS.7   = conversation-selector-ace-d.nl.eu.abnamro.com
DNS.8   = autolabelling-1-ace-d.nl.eu.abnamro.com
DNS.9   = airflow.ace-d.nl.eu.abnamro.com
DNS.10  = airflow-test-ace-d.nl.eu.abnamro.com
```

³ <http://nl.eu.abnamro.com>

```

DNS.11 = airflow-annacb-ace-d.nl.eu.abnamro.com
DNS.12 = hasura-ace-d.nl.eu.abnamro.com
DNS.13 = temporal-ace-d.nl.eu.abnamro.com
DNS.14 = ace-be-fe-d.nl.eu.abnamro.com

```

2.2 CSR file using Config


Now that we have the config, using openssl, generate `*.csr` file along with the private key in pem format `key.pem`.

Use the following to generate the certificate (`ace.csr`) with private key (`ace-key.pem`):

```
openssl req -out ace.csr -newkey rsa:2048 -nodes -keyout ace-key.pem -config
ace-csr-config.txt
```

2.3 Upload the CSR

- Browse Security services from MYIT ([IT Security Services \(CISO\) - MyIT Portal \(service-now.com\)](#)⁴) to select the Block and OAR. In our case it is ACE Azure Platform



- Once you choose the OAR you will get the list of created certificates under the specific OAR
- To request new Certificate you have to click on plus icon as below and select **New Digital Certificate**

⁴ https://aabsiampr.service-now.com/esc?id=emp_taxonomy_topic_rff&topic_id=21f0f7761b93ddd0ee0ca68ee54bcb7c

Actions

Select the application (OAR) you want to target

ACE Azure Platform

Certificate overview - Active only

Name	Serial No	Env.	Status	Expiration Date	Source
aab-sys-021582.acep-					

- Open `.csr` in a text editor and copy the content (exclude the empty line at the end of the file). Content starts and ends as below

-----BEGIN CERTIFICATE REQUEST-----

```
MIIEjDCCA3QCAQAwZDELMAkGA1UEBhMCTkwxFjAUBgNVBAgMDU5vb3JkLUhvbGxhbmQxGzAZBgNVBAoMEkFCTiBBTVJPIEJhbm90TjE5WLjEgMB4GA1UEAwwXYWw1LLWQu
```

...

...

-----END CERTIFICATE REQUEST-----

- Redirected to upload the certificate, fill the form and select **Order Now**

- Common Name should match Hostname
- Do not copy empty line at the end
- Upon ordering ServiceNow ticket is created it takes around 5mins to provision the certificate and to be visible in MYIT.

2.4 Convert OU Signed CER to PEM

As the process completes, the certificate should be available for download. Click on the settings icon as below to download the .cer or .pem file of the cert

ace03-p.nl.eu.abnamro.com

49db49bdba772684

Production

Active

16-10-2024 15:42:57

MyIT



Certificate

ace03-p.nl.eu.abnamr o.com

Actions

Renew

Revoke

Download

.cer

.pem

Download the .pem , resulting in certificate.pem

2.5 Upload certificate and Key to secure files

Upload both downloaded pem certificate and certificate key to secure files like below



2.6 Upload to Azure Key Vault

Using the stage : [push_aks_certificate_kv from pre-infra-pipeline.yaml - Repos \(azure.com\)](#)⁵ deploy the certificate into KV and using

[deploy_ingressTLS_certificate from post-aks-pipeline.yaml - Repos \(azure.com\)](#)⁶ create ace-ingress-tls-secret secret in AKS cluster

How to renew the aks ingress certificate:

- Use the config file aks cert of specific environment for which the cert is going to expire and generate CSR and private key using the below command

```
openssl req -out ace.csr -newkey rsa:2048 -nodes -keyout ace-key.pem -config ace-csr-config.txt
```


replace the values with your existing config file name

Navigate to myIT

Click on the settings icon of certificate which needs to be renewed as below

⁵ https://dev.azure.com/cbsp-abnamro/GRD0001014/_git/acep-platform-infrastructure?path=/pipelines/pre-infra-pipeline.yaml&version=GBdevelop&a=contents

⁶ https://dev.azure.com/cbsp-abnamro/GRD0001014/_git/acep-platform-infrastructure?path=/pipelines/post-aks-pipeline.yaml&version=GBdevelop&a=contents

ace03-p.nl.eu.abnamr o.com	49db49bdba772684	Production	Active	16-10-2024 15:42:57	MyIT	
-------------------------------	------------------	------------	--------	---------------------	------	---

once you click on settings icon you should see two options RENEW OR REVOKE

Certificate

ace03-p.nl.eu.abnamr o.com

Actions

Renew

Revoke

Download

.cer

.pem

Click on Renew for renewal ,
it navigates to renewal page provide the above generated CSR in the CSR field



and click on request now

It takes around 5 mins for the renewed certificate to be visible in myit , once it is visible download the .pem file and upload the .pem and private key in secure files and to push the certificate to keyvault from secure files and download the certificate from keyvault and upload it into aks namespaces.

Once the pipeline is successful you can verify the latest certificate by hitting any of the SAN values of the certificate and checking the expiry as below



you should see renewed expiry date as per myIT

Note: Currently we are using Manual method to deploy ingress certificate

Through Release Pipeline:

To deploy the certificate using release navigate to [Releases - Pipelines \(azure.com\)](https://dev.azure.com/cbsp-abnamro/GRD0001014/_release?_a=releases&view=all&definitionId=915)⁷, the link takes you to the devops release pipeline where we have created release to deploy infra CA G3 certificate.

Click on edit release pipeline and choose the environment displayed on the stage to which env you want to create the Cert

- After you open the stage click on plus symbol on the agent job to add the required task
- Search for Infra CA G3 and select the task

⁷ https://dev.azure.com/cbsp-abnamro/GRD0001014/_release?_a=releases&view=all&definitionId=915

Add tasks | Refresh

INFRA CA G3



InfraCA G3 certificate request task

Request certificate from InfraCA G3 via Azure Cloud RA

- The infra CA G3 task contains different fields like below

- To request a new certificate you can choose the action as new request and provide the details for RG, KV, OAR , Certifiacte Name , format , requied SAN values and environment to which you want to deploy and save the release and deploy the certificate
- Once you create the release it takes around 1min for the certificate to provision and once the release is successful the certificate will be available in the keyvault , you can verify the certificate by navigating into certifiactes section in KV as below [acep03-a-kv - Microsoft Azure](#)⁸

+ Generate/Import Refresh Restore Backup Manage deleted certificates Certificate Contacts ...

Name	Thumbprint	Status	Expiration date
Completed			
ace03-a-appgw-private-cert	01D6854AF16C87361F75FBFE25C...	✓ Enabled	3/27/2025
acep03-a-appgw-public-signer...	D11A14DB5C8F3D5743C28D1CC...	✓ Enabled	7/4/2024
aceplatform-thirdpartycertific...	56F687D63C641CD82377005619...	✓ Enabled	9/21/2024
aceplatform-thirdpartyservice	66BBB1021A3E777F882606FEB42...	✓ Enabled	8/1/2024

- To renew or revoke the certificate you can use action as renew or revoke and provide the same details as you have mentioned earlier and deploy the release and requested action will be provisioned

Through Automated Pipeline:

⁸<https://portal.azure.com/#@abnamro.onmicrosoft.com/resource/subscriptions/bb5fe5fb-0b33-4cce-9d15-4397f5ab7487/resourceGroups/acep03-a-rg/providers/Microsoft.KeyVault/vaults/acep03-a-kv/certificates>

There are 2 token types for automated pipeline approach

Token type: abn_amro_infra_ca_g3_ssl


Reference automated Pipeline : [Pipelines - Runs for acep-certificate-pipeline](#)⁹

Automated Pipeline has 3 actions


1. New (To create new certificate)
2. Renew (To renew existing cert)
3. Revoke (To delete unused certificate)

Action : NEW

1. To create new certificate we need to choose new action with abnamro token type as mentioned in screenshot



2. Provide the common DNS Name , certificate name to save in key vault and SAN values if any
3. After providing step 2 details select the format of cert to be deployed , except for application gateway all other certificate formats are PEM



for application gateway it should be pkcs12 format

4. During creation of certificate provide random value for certificate revoke version parameter because it is a required param to provide
5. After all above details are updated trigger the pipeline and the certificate will be deployed to key vault with the mentioned name provided in the parameters during run time

Action : Renew

⁹ https://dev.azure.com/cbsp-abnamro/GRD0001014/_build?definitionId=87478&a=summary


1. For renew action follow the steps same as the process followed for Action : NEW, but select the action as renew as below

Run pipeline ×
Select parameters below and manually run the pipeline

Branch/tag
 ▼
Select the branch, commit, or tag

Deployment Environment
 ▼

Choose Action to Perform on Certificate

☐ new
☒ **renew** 
☐ revoke

Action: Revoke


1. For Revoke , provide all the details as provided for renew/new actions and additional to that we have to provide certificate version from keyvault which we want to remove as below

Run pipeline ×
Select parameters below and manually run the pipeline

Subject Alternatives names (DNS Name)

Certificate Format to deploy

☐ none
☐ pem-file
☒ **pkcs12**

Certificate Version To Revoke from KeyVault
 
Version in case of major change(only fill in case of major change)

2. We can get certificate version from key vault as below

Home > Key vaults > acep03-a-kv | Certificates >

ace03-a-appgw-private-cert ...
Versions

[+ New Version](#)
[Refresh](#)
[Delete](#)
[Download Backup](#)
[Issuance Policy](#)
[Certificate Operation](#)

Version	Thumbprint	Status	Activation date
CURRENT VERSION			
03acb31b46074edeb2fe2cb1b88ccb31	AF58BF9C81D1C53F08DC1D32D...	✓ Enabled	3/4/2025
OLDER VERSIONS			
de3a492d785b485b3e211b077da8760	01D6854AF16C87361F75FBFE25...	✓ Enabled	3/27/2024


Token type : service_token

For service_token , updation of all the parameters is same as abn amro token type except token selected is service_token

Deployment Environment
 ▼

Choose Action to Perform on Certificate

☐ new
☒ **renew**
☐ revoke

Choose the Type of tokenType
 ▼ 

Common DNS Name for Certificate

Note : We are using service token type only for Third party certificate "aceplatform-thirdpartyservice" in DTAP

Chained Certificate:


Procedure to deploy the Chained certificate is documented in the following wiki page [Create Entrust Chained SSL Certificate - Overview \(azure.com\)](https://dev.azure.com/cbsp-abnamro/GRD0001014/_wiki/wikis/GRD0001014.wiki/71494/Create-Entrust-Chained-SSL-Certificate)¹⁰

Root Certificate :


We use root certificate as a SSL certificate in application gateway to identify the AKS as backend server since AKS uses Ingress certificate which also has the same root .

Procedure to deploy root cert :


- Go to MyIT and click on the AKS certificate for the env to which you are creating the root cert
- Click on settings icon and download the .cer file of the certificate
- Once you download the .cer and open it it looks something as below



- Open .cer file of new certificate and click on certification path and open the root certificate by clicking on view certificate as below and it opens the root certificate




- after you click on view certificate of root you will see the root cert as below




¹⁰ https://dev.azure.com/cbsp-abnamro/GRD0001014/_wiki/wikis/GRD0001014.wiki/71494/Create-Entrust-Chained-SSL-Certificate


- Now click on details and click on copy to file




- After clicking on copy to file click on next and choose the base-64 format of certificate




- Give the name of the file and choose the folder



- Click on next and click on finish



- After you click on finish you should message as export was successful



- Repeat the above steps for intermediate certificate



- Export the intermediate certificate
- After two certs are imported open the root and intermediate certificates with notepad
- Append the content of intermediate certificate after the content of root certificate as attached file [acep03-t-aks-cert.cer](#)¹¹
- Upload the combined .cer file in secure files


cbasp-abnamro / GRD0001014 / Pipelines / Library			Search
acep03-p-aks-cert.cer	10/17/2023	KW	Kishita Wahane
acep03-p-aks-cert.pem	10/17/2023	KW	Kishita Wahane
acep03-p-appgw-public-signed-including-chain.pfx	10/12/2023	PS	Prudvi Saraseshwari Sane
acep03-p-privatekey.pem	10/17/2023	KW	Kishita Wahane
acep03-t-aks-cert(old).cer	3 hours ago	PS	Prudvi Saraseshwari Sane
acep03-t-aks-cert.cer	3 hours ago	PS	Prudvi Saraseshwari Sane

- After it is uploaded provide the permission to block and run the pre-infrastructure-pipeline by choosing only [push_aks_certificate_kv](#) from [pre-infra-pipeline.yaml](#) - [Repos \(azure.com\)](#)¹²
- After the pipeline is successful check the version in kv if the secret is uploaded

¹¹ <https://confluence.int.abnamro.com/download/attachments/635450707/acep03-t-aks-cert.cer?api=v2&modificationDate=1709816331067&version=1>

¹² https://dev.azure.com/cbsp-abnamro/GRD0001014/_git/acep-platform-infrastructure?path=/pipelines/pre-infra-pipeline.yaml

Home > acep03-t-kv | Secrets >

 **aks-tls-certificate-cer** ...
Versions

+ New Version Refresh Delete Download Backup

Version	Status	Activation date	Expiration date
CURRENT VERSION			
a7f01cb7c05644f4be8c1c0ff4ccb5ef	✓ Enabled		3/7/2025
OLDER VERSIONS			


- With the above process Root certificate upload to kv is done


Validation of certificate with appgw:

- Appgw automatically checks if any new version of cert exists in Key vault for every 4hrs and pulls the latest updated cert so you can use below KQL query in key vault logs

▶ Run

Time range : Last 4 hours

 Save

 Share

+ New

```

1 AzureDiagnostics
2 | where CallerIpAddress contains "4.210.194.59"

```

- Check when does the latest pull happened , check the time at which you have uploaded the cert in KV and Revalidate the public URL(ace-t.abnamro.nl/message-hub/ping¹³) access after the appgw has pull the updated cert from kv.
- We don't need to wait for 4hours for application gateway to pull the latest certificate , to mitigate the above error you can manually update the latest version of kv secret using below command

az network application-gateway root-cert update --gateway-name acep03-d-appgw --name chatbot-trustedCert --resource-group acep-d-rg --keyvault-secret <https://acep03-d-kv.vault.azure.net/secrets/aks-tls-certificate-cer/0952af44bca34fc8b9129029d412f466>

Note: The root and sub root of infra ca g3 certificate expiry is not similar to other certificate expiries which we request through MYIT , since these are managed through crypto team they provide us the update on when the certificates are going to expire till then we don't need to update the root or sub root if we are using latest ca g3 certificates. In our case we don't need to update the secure file ace03-env-aks-cer.cer from library until crypto notifies us if there is any change for the root or sub root

Note: We use Chained Certificate and Root Certificate for application Gateway

¹³ <https://ace-t.abnamro.nl/message-hub/ping>