

## Unit Test -6

Topic: JSP,EL and JSTL

max marks:40

1. Which of the following are not jsp implicit objects.

- A exception
- B session
- C request
- D application
- E servletcontext

2 Which of the following are not valid expression tags?

- A `<%= 13+4 %>`
- B `<%= new java.util.Date() %>`
- C `<%= 12 < 3; %>`
- D `<%= 12>3 && 9<2 %>`
- E `<%= 10 %>`

3

`<%! int x=10; %>` -----1

`<% ++x; %>` -----2

`<%= x%>` -----3

Which of the following statements are true about the above code.

- A The above code prints 11 11 11 when executed thrice
- B The above code prints 11 12 13 when executed thrice
- C x is created as an instance variable inside the jspServlet.
- C x is not accessible in statements 2 and 3
- D Statement 3 has error, there should be a semicolon.

4

`<% int x=12; %>`

```
<%! int f1(){  
    out.println(x);  
%>
```

What is the output: ?

- A     12
- B     error because x is not accessible
- C     error because out is not accessible
- D     error because out not declared

5.

Mark the following in order of lifecycle of a jsp program

6 marks

- A     Translate The JSP into java source code
- B     compile source code and create a servlet
- C     call `_jspService()`
- D     Instantiate the servlet class
- E     call `jspInit()`
- F     call `jspDestroy()`

6.

```
<% int x=12;  
out.println(x);  
%>
```

gets translated to.

- A     

```
public void _jspService(some code){  
    int x=12;  
    PrintWriter out=response.getWriter();  
    out.print(x);}

```

B     `int x=12;`  
  
      `public void _jspService(some code){`  
      `PrintWriter out=response.getWriter();`  
      `out.print(x);}`

C

```
int x=12;

public void jspInit(){

    PrintWriter out=response.getWriter();

    out.print(x);}

}
```

7     Which of the following attributes are mandatory for action tag `jsp:useBean`.

- A     scope and id.
- B     id and class
- C     name and class
- D     name and scope

8

Which JSP expression tag will print the context initialization parameter named “`javax.sql.DataSource`”?

- A     `<%= application.getAttribute("javax.sql.DataSource") %>`
- B     `<%= application.getInitParameter("javax.sql.DataSource") %>`
- C     `<%= request.getParameter("javax.sql.DataSource") %>`
- D     `<%= contextParam.getAttribute("javax.sql.DataSource") %>`

9

Which of the following statements prints the value passed through request parameter called username.

A     <%= request.getParameter("username") %>

B     \${request.username}

C     \${param.username}

D     \${param["username"]}

10

If in a servlet I have

```
String names[] = {"sam","smith","Johnson","james"};
```

```
request.setAttribute("names",names);
```

through requestdispatcher I am moving to Jsp1.jsp.then inside

what would be output for the following statements inside Jsp1.jsp

```
    ${names[1]}
```

```
    ${names["1"]}
```

A     sam

B     sam smith

C     sam sam

D     smith smith

11

```
Java.util.Map elements=new java.util.HashMap();
```

```
Elements.put("one","two");
```

```
Elements.put("two","one");
```

```
Elements.put("three","two");
```

What statements are valid so that it prints two.

A     \${elements.one}

B     \${elements["one"]}

C     \${elements.three}

D     `${elements["three"]}`

12

Which of these are EL implicit objects

A     `initparam`

B     `cookie`

C     `request`

D     `session`

13

In jstl.

```
<c:forEach _____="x" _____="${myList}">
    ${x}
</c:forEach>
```

What should come in place of blanks.

A     `var` and `list`

B     `varStatus` and `items`

C     `var` and `items`

D     `counter` and `items`

14

```
<% Cookie ck[]=request.getCookies();
    for(Cookie c:ck)
    {
        If(c.getName().equals("username"))
            out.print(c.getValue());
    }
%>
```

Corresponding EL Expression for the above is:

- A    `${cookie[username].value}`
- B    `${cookie.username.value}`
- C    `${cookies.username}`
- D    `${cookie.username}`

15

What would be the output of the following expressions.

`${35/0}` and `${35%0}`

- A    NullPointerException and NAN
- B    infinity and Exception
- C    Exception and 35
- D    None of the above

16

2 marks

What is the difference between `<jsp:include..>` and `<%@ include file="demo.jsp"...>`

17

Which of the following are valid attributes for a page directive.

- A    `isThreadSafe`, `import`, `ErrorPage`, `uri`
- B    `isThreadSafe`, `isErrorPage`, `session`, `import`
- C    `isThreadSafe`, `isErrorPage`, `isSession`, `import`
- D    `language`, `import`, `isErrorPage`, `file`

18

```
<% java.util.ArrayList list=new java.util.ArrayList();  
list.add("1");  
list.add("2");  
list.add("3");  
request.setAttribute("list",list);  
%>
```

5 marks

What would be the output of the following statements.

- I     `${list[1] eq 1}`
- II    `${list[0] le 1}`
- III   `${list[1] >=2}`
- IV    `${list[2] % 0}`
- V     `${list[1] and true }`

19

7 marks

Which of the following statements are true regarding JSTL.

- 1     JSTL are template libraries.
- 2     JSTL uses EL.
- 3     JSTL has `<c:out>`, `<c:catch>`, `<c:url>` elements.
- 4     In JSTL `<c:dispatch>` redirects to a new resource.
- 5     `<c:if >` and `<c:else>` are valid elements in jstl.
- 6     `<sql:query>` and `<sql:update>` are elements to interact with database.
- 7     Jstl has core, xml, formatting, sql libraries.

20

5 marks

Which are the different types of tags in JSP.

Give one Example for each. (Please don't explain).