

Plagiarism Detection, Feature Engineering

In this project, you will be tasked with building a plagiarism detector that examines an answer text file and performs binary classification; labeling that file as either plagiarized or not, depending on how similar that text file is to a provided, source text.

Your first task will be to create some features that can then be used to train a classification model. This task will be broken down into a few discrete steps:

- Clean and pre-process the data.
- Define features for comparing the similarity of an answer text and a source text, and extract similarity features.
- Select "good" features, by analyzing the correlations between different features.
- Create train/test .csv files that hold the relevant features and class labels for train/test data points.

In the *next* notebook, Notebook 3, you'll use the features and .csv files you create in *this* notebook to train a binary classification model in a SageMaker notebook instance.

You'll be defining a few different similarity features, as outlined in [this paper](#) (https://s3.amazonaws.com/video.udacity-data.com/topher/2019/January/5c412841_developing-a-corpus-of-plagiarised-short-answers/developing-a-corpus-of-plagiarised-short-answers.pdf), which should help you build a robust plagiarism detector!

To complete this notebook, you'll have to complete all given exercises and answer all the questions in this notebook.

All your tasks will be clearly labeled **EXERCISE** and questions as **QUESTION**.

It will be up to you to decide on the features to include in your final training and test data.

Read in the Data

The cell below will download the necessary, project data and extract the files into the folder `data/`.

This data is a slightly modified version of a dataset created by Paul Clough (Information Studies) and Mark Stevenson (Computer Science), at the University of Sheffield. You can read all about the data collection and corpus, at [their university webpage](#) (https://ir.shef.ac.uk/cloughie/resources/plagiarism_corpus.html).

Citation for data: Clough, P. and Stevenson, M. Developing A Corpus of Plagiarised Short Answers, Language Resources and Evaluation: Special Issue on Plagiarism and Authorship Analysis, In Press. [Download]

```
In [1]: # NOTE:  
# you only need to run this cell if you have not yet downloaded the data  
# otherwise you may skip this cell or comment it out  
import os  
if not (os.path.exists("data/")):  
    !wget https://s3.amazonaws.com/video.udacity-data.com/topher/2019/January/  
5c4147f9_data/data.zip  
    !unzip data
```

```
In [2]: # import libraries  
import pandas as pd  
import numpy as np  
import os
```

This plagiarism dataset is made of multiple text files; each of these files has characteristics that are summarized in a .csv file named `file_information.csv`, which we can read in using `pandas`.

```
In [3]: csv_file = 'data/file_information.csv'  
plagiarism_df = pd.read_csv(csv_file)  
  
# print out the first few rows of data info  
plagiarism_df.head()
```

Out[3]:

	File	Task	Category
0	g0pA_taska.txt	a	non
1	g0pA_taskb.txt	b	cut
2	g0pA_taskc.txt	c	light
3	g0pA_taskd.txt	d	heavy
4	g0pA_taske.txt	e	non

Types of Plagiarism

Each text file is associated with one **Task** (task A-E) and one **Category** of plagiarism, which you can see in the above DataFrame.

Tasks, A-E

Each text file contains an answer to one short question; these questions are labeled as tasks A-E. For example, Task A asks the question: "What is inheritance in object oriented programming?"

Categories of plagiarism

Each text file has an associated plagiarism label/category:

1. Plagiarized categories: `cut` , `light` , and `heavy` .

- These categories represent different levels of plagiarized answer texts. `cut` answers copy directly from a source text, `light` answers are based on the source text but include some light rephrasing, and `heavy` answers are based on the source text, but *heavily* rephrased (and will likely be the most challenging kind of plagiarism to detect).

2. Non-plagiarized category: `non` .

- `non` indicates that an answer is not plagiarized; the Wikipedia source text is not used to create this answer.

3. Special, source text category: `orig` .

- This is a specific category for the original, Wikipedia source text. We will use these files only for comparison purposes.

Pre-Process the Data

In the next few cells, you'll be tasked with creating a new DataFrame of desired information about all of the files in the `data/` directory. This will prepare the data for feature extraction and for training a binary, plagiarism classifier.

EXERCISE: Convert categorical to numerical data

You'll notice that the `Category` column in the data, contains string or categorical values, and to prepare these for feature extraction, we'll want to convert these into numerical values. Additionally, our goal is to create a binary classifier and so we'll need a binary class label that indicates whether an answer text is plagiarized (1) or not (0). Complete the below function `numerical_dataframe` that reads in a `file_information.csv` file by name, and returns a new DataFrame with a numerical `Category` column and a new `Class` column that labels each answer as plagiarized or not.

Your function should return a new DataFrame with the following properties:

- 4 columns: `File` , `Task` , `Category` , `Class` . The `File` and `Task` columns can remain unchanged from the original `.csv` file.
- Convert all `Category` labels to numerical labels according to the following rules (a higher value indicates a higher degree of plagiarism):
 - 0 = non
 - 1 = heavy
 - 2 = light
 - 3 = cut
 - -1 = orig , this is a special value that indicates an original file.
- For the new `Class` column
 - Any answer text that is not plagiarized (`non`) should have the class label `0` .
 - Any plagiarized answer texts should have the class label `1` .
 - And any `orig` texts will have a special label `-1` .

Expected output

After running your function, you should get a DataFrame with rows that looks like the following:

	File	Task	Category	Class
0	g0pA_taska.txt	a	0	0
1	g0pA_taskb.txt	b	3	1
2	g0pA_taskc.txt	c	2	1
3	g0pA_taskd.txt	d	1	1
4	g0pA_taske.txt	e	0	0
...				
...				
99	orig_taske.txt	e	-1	-1

```
In [4]: # Read in a csv file and return a transformed dataframe
def numerical_dataframe(csv_file='data/file_information.csv'):
    '''Reads in a csv file which is assumed to have `File`, `Category` and `Task` columns.
    This function does two things:
    1) converts `Category` column values to numerical values
    2) Adds a new, numerical `Class` Label column.
    The `Class` column will Label plagiarized answers as 1 and non-plagiarized as 0.
    Source texts have a special Label, -1.
    :param csv_file: The directory for the file_information.csv file
    :return: A dataframe with numerical categories and a new `Class` Label column'''
    # your code here
    num_df = pd.read_csv(csv_file)

    #define maps for conversion
    category_numerical_map = {'orig': -1, 'non' : 0, 'heavy' : 1, 'light' : 2,
    'cut' : 3 }

    num_df['Category'] = num_df.Category.map(category_numerical_map)
    num_df['Class'] = num_df.Category.apply(lambda x: x if x < 1 else 1)

    return num_df
```

Test cells

Below are a couple of test cells. The first is an informal test where you can check that your code is working as expected by calling your function and printing out the returned result.

The **second** cell below is a more rigorous test cell. The goal of a cell like this is to ensure that your code is working as expected, and to form any variables that might be used in *later* tests/code, in this case, the data frame, `transformed_df`.

The cells in this notebook should be run in chronological order (the order they appear in the notebook). This is especially important for test cells.

Often, later cells rely on the functions, imports, or variables defined in earlier cells. For example, some tests rely on previous tests to work.

These tests do not test all cases, but they are a great way to check that you are on the right track!

```
In [5]: # informal testing, print out the results of a called function
# create new `transformed_df`
transformed_df = numerical_dataframe(csv_file ='data/file_information.csv')

# check work
# check that all categories of plagiarism have a class label = 1
transformed_df.head(10)
```

Out[5]:

	File	Task	Category	Class
0	g0pA_taska.txt	a	0	0
1	g0pA_taskb.txt	b	3	1
2	g0pA_taskc.txt	c	2	1
3	g0pA_taskd.txt	d	1	1
4	g0pA_taske.txt	e	0	0
5	g0pB_taska.txt	a	0	0
6	g0pB_taskb.txt	b	0	0
7	g0pB_taskc.txt	c	3	1
8	g0pB_taskd.txt	d	2	1
9	g0pB_taske.txt	e	1	1

```
In [6]: # test cell that creates `transformed_df`, if tests are passed
```

```
"""
```

```
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
```

```
"""
```

```
# importing tests
```

```
import problem_unittests as tests
```

```
# test numerical_dataframe function
```

```
tests.test_numerical_df(numerical_dataframe)
```

```
# if above test is passed, create NEW `transformed_df`
```

```
transformed_df = numerical_dataframe(csv_file ='data/file_information.csv')
```

```
# check work
```

```
print('\nExample data: ')
```

```
transformed_df.head()
```

Tests Passed!

Example data:

Out[6]:

	File	Task	Category	Class
0	g0pA_taska.txt	a	0	0
1	g0pA_taskb.txt	b	3	1
2	g0pA_taskc.txt	c	2	1
3	g0pA_taskd.txt	d	1	1
4	g0pA_taske.txt	e	0	0

Text Processing & Splitting Data

Recall that the goal of this project is to build a plagiarism classifier. At its heart, this task is a comparison text; one that looks at a given answer and a source text, compares them and predicts whether an answer has plagiarized from the source. To effectively do this comparison, and train a classifier we'll need to do a few more things: pre-process all of our text data and prepare the text files (in this case, the 95 answer files and 5 original source files) to be easily compared, and split our data into a `train` and `test` set that can be used to train a classifier and evaluate it, respectively.

To this end, you've been provided code that adds additional information to your `transformed_df` from above. The next two cells need not be changed; they add two additional columns to the `transformed_df`:

1. A `Text` column; this holds all the lowercase text for a `File`, with extraneous punctuation removed.
2. A `Datatype` column; this is a string value `train`, `test`, or `orig` that labels a data point as part of our `train` or `test` set

The details of how these additional columns are created can be found in the `helpers.py` file in the project directory. You're encouraged to read through that file to see exactly how text is processed and how data is split.

Run the cells below to get a `complete_df` that has all the information you need to proceed with plagiarism detection and feature engineering.

In [7]:

```
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

import helpers

# create a text column
text_df = helpers.create_text_column(transformed_df)
text_df.head()
```

Out[7]:

	File	Task	Category	Class	Text
0	g0pA_taska.txt	a	0	0	inheritance is a basic concept of object orient...
1	g0pA_taskb.txt	b	3	1	pagerank is a link analysis algorithm used by ...
2	g0pA_taskc.txt	c	2	1	the vector space model also called term vector...
3	g0pA_taskd.txt	d	1	1	bayes theorem was named after rev thomas bayes...
4	g0pA_taske.txt	e	0	0	dynamic programming is an algorithm design tec...

```
In [8]: # after running the cell above
# check out the processed text for a single file, by row index
row_idx = 0 # feel free to change this index

sample_text = text_df.iloc[0]['Text']

print('Sample processed text:\n\n', sample_text)
```

Sample processed text:

inheritance is a basic concept of object oriented programming where the basic idea is to create new classes that add extra detail to existing classes this is done by allowing the new classes to reuse the methods and variables of the existing classes and new methods and classes are added to specialise the new class inheritance models this kind of relationship between entities or objects for example postgraduates and undergraduates are both kinds of student this kind of relationship can be visualised as a tree structure where student would be the more general root node and both postgraduate and undergraduate would be more specialised extensions of the student node or the child nodes in this relationship student would be known as the superclass or parent class whereas postgraduate would be known as the subclass or child class because the postgraduate class extends the student class inheritance can occur on several layers where if visualised would display a larger tree structure for example we could further extend the postgraduate node by adding two extra extended classes to it called msc student and phd student as both these types of student are kinds of postgraduate student this would mean that both the msc student and phd student classes would inherit methods and variables from both the postgraduate and student classes

Split data into training and test sets

The next cell will add a `Datatype` column to a given DataFrame to indicate if the record is:

- `train` - Training data, for model training.
- `test` - Testing data, for model evaluation.
- `orig` - The task's original answer from wikipedia.

Stratified sampling

The given code uses a helper function which you can view in the `helpers.py` file in the main project directory. This implements [stratified random sampling](https://en.wikipedia.org/wiki/Stratified_sampling) (https://en.wikipedia.org/wiki/Stratified_sampling) to randomly split data by task & plagiarism amount. Stratified sampling ensures that we get training and test data that is fairly evenly distributed across task & plagiarism combinations. Approximately 26% of the data is held out for testing and 74% of the data is used for training.

The function `train_test_dataframe` takes in a DataFrame that it assumes has `Task` and `Category` columns, and, returns a modified frame that indicates which `Datatype` (train, test, or orig) a file falls into. This sampling will change slightly based on a passed in `random_seed`. Due to a small sample size, this stratified random sampling will provide more stable results for a binary plagiarism classifier. Stability here is smaller variance in the accuracy of classifier, given a random seed.

```
In [9]: random_seed = 1 # can change; set for reproducibility

"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

import helpers

# create new df with Datatype (train, test, orig) column
# pass in `text_df` from above to create a complete dataframe, with all the information you need
complete_df = helpers.train_test_dataframe(text_df, random_seed=random_seed)

# check results
complete_df.head(10)
```

Out[9]:

	File	Task	Category	Class	Text	Datatype
0	g0pA_taska.txt	a	0	0	inheritance is a basic concept of object orient... ation	train
1	g0pA_taskb.txt	b	3	1	pagerank is a link analysis algorithm used by ... several search engines to rank web pages in their ...	test
2	g0pA_taskc.txt	c	2	1	the vector space model also called term vector... model	train
3	g0pA_taskd.txt	d	1	1	bayes theorem was named after rev thomas bayes... and is a fundamental concept in machine learning.	train
4	g0pA_taske.txt	e	0	0	dynamic programming is an algorithm design tec... nique that solves problems by breaking them down ...	train
5	g0pB_taska.txt	a	0	0	inheritance is a basic concept in object orient... ation	train
6	g0pB_taskb.txt	b	0	0	pagerank pr refers to both the concept and the ... algorithm used by search engines to rank web pages.	train
7	g0pB_taskc.txt	c	3	1	vector space model is an algebraic model for r... epresenting text documents and objects in a vector ...	test
8	g0pB_taskd.txt	d	2	1	bayes theorem relates the conditional and marg... inal probabilities of variables in a joint probabi...	train
9	g0pB_taske.txt	e	1	1	dynamic programming is a method for solving ma... thematical optimization problems by decomposing t...	test

Determining Plagiarism

Now that you've prepared this data and created a `complete_df` of information, including the text and class associated with each file, you can move on to the task of extracting similarity features that will be useful for plagiarism classification.

Note: The following code exercises, assume that the `complete_df` as it exists now, will **not** have its existing columns modified.

The `complete_df` should always include the columns: `['File', 'Task', 'Category', 'Class', 'Text', 'Datatype']`. You can add additional columns, and you can create any new DataFrames you need by copying the parts of the `complete_df` as long as you do not modify the existing values, directly.

Similarity Features

One of the ways we might go about detecting plagiarism, is by computing **similarity features** that measure how similar a given answer text is as compared to the original wikipedia source text (for a specific task, a-e). The similarity features you will use are informed by [this paper on plagiarism detection \(\[https://s3.amazonaws.com/video.udacity-data.com/topher/2019/January/5c412841_developing-a-corpus-of-plagiarised-short-answers/developing-a-corpus-of-plagiarised-short-answers.pdf\]\(https://s3.amazonaws.com/video.udacity-data.com/topher/2019/January/5c412841_developing-a-corpus-of-plagiarised-short-answers/developing-a-corpus-of-plagiarised-short-answers.pdf\)\).](https://s3.amazonaws.com/video.udacity-data.com/topher/2019/January/5c412841_developing-a-corpus-of-plagiarised-short-answers/developing-a-corpus-of-plagiarised-short-answers.pdf)

In this paper, researchers created features called **containment** and **longest common subsequence**.

Using these features as input, you will train a model to distinguish between plagiarized and not-plagiarized text files.

Feature Engineering

Let's talk a bit more about the features we want to include in a plagiarism detection model and how to calculate such features. In the following explanations, I'll refer to a submitted text file as a **Student Answer Text (A)** and the original, wikipedia source file (that we want to compare that answer to) as the **Wikipedia Source Text (S)**.

Containment

Your first task will be to create **containment features**. To understand containment, let's first revisit a definition of [n-grams](https://en.wikipedia.org/wiki/N-gram) (<https://en.wikipedia.org/wiki/N-gram>). An *n*-gram is a sequential word grouping. For example, in a line like "bayes rule gives us a way to combine prior knowledge with new information," a 1-gram is just one word, like "bayes." A 2-gram might be "bayes rule" and a 3-gram might be "combine prior knowledge."

Containment is defined as the **intersection** of the n-gram word count of the Wikipedia Source Text (S) with the n-gram word count of the Student Answer Text (S) divided by the n-gram word count of the Student Answer Text.

$$\frac{\sum \text{count}(\text{ngram}_A) \cap \text{count}(\text{ngram}_S)}{\sum \text{count}(\text{ngram}_A)}$$

If the two texts have no n-grams in common, the containment will be 0, but if *all* their n-grams intersect then the containment will be 1. Intuitively, you can see how having longer n-gram's in common, might be an indication of cut-and-paste plagiarism. In this project, it will be up to you to decide on the appropriate *n* or several *n*'s to use in your final model.

EXERCISE: Create containment features

Given the `complete_df` that you've created, you should have all the information you need to compare any Student Answer Text (A) with its appropriate Wikipedia Source Text (S). An answer for task A should be compared to the source text for task A, just as answers to tasks B, C, D, and E should be compared to the corresponding original source text.

In this exercise, you'll complete the function, `calculate_containment` which calculates containment based upon the following parameters:

- A given DataFrame, `df` (which is assumed to be the `complete_df` from above)
- An `answer_filename`, such as 'g0pB_taskd.txt'
- An n-gram length, `n`

Containment calculation

The general steps to complete this function are as follows:

1. From *all* of the text files in given `df`, create an array of n-gram counts; it is suggested that you use a [CountVectorizer](https://scikit-learn.org/stable/modules/generated/sklearn.feature_extraction.text.CountVectorizer.html) (https://scikit-learn.org/stable/modules/generated/sklearn.feature_extraction.text.CountVectorizer.html) for this purpose.
2. Get the processed answer and source texts for the given `answer_filename`.
3. Calculate the containment between an answer and source text according to the following equation.

$$\frac{\sum \text{count}(\text{ngram}_A) \cap \text{count}(\text{ngram}_S)}{\sum \text{count}(\text{ngram}_A)}$$

4. Return that containment value.

You are encouraged to write any helper functions that you need to complete the function below.

```
In [10]: from sklearn.feature_extraction.text import CountVectorizer
```

```
In [11]: # Calculate the ngram containment for one answer file/source file pair in a df
def calculateContainment(df, n, answer_filename):
    '''Calculates the containment between a given answer text and its associated source text.
    This function creates a count of ngrams (of a size, n) for each text file in our data.
    Then calculates the containment by finding the ngram count for a given answer text,
    and its associated source text, and calculating the normalized intersection of those counts.
    :param df: A dataframe with columns,
        'File', 'Task', 'Category', 'Class', 'Text', and 'Datatype'
    :param n: An integer that defines the ngram size
    :param answer_filename: A filename for an answer text in the df, ex. 'g0pB_taskd.txt'
    :return: A single containment value that represents the similarity
            between an answer text and its source text.
    ...
    # your code here
    # instantiate an ngram counter
    count_vec = CountVectorizer(analyzer='word', ngram_range=(n,n))

    answer_text, task = df[df['File'] == answer_filename][['Text', 'Task']].iloc[0]

    src_filter = (df['Class'] == -1) & (df['Task'] == task)
    source_text = df[src_filter]['Text'].iloc[0]

    ngrams_array = count_vec.fit_transform([answer_text, source_text]).toarray()
()

## Calculate containment
intersection_count = sum(min(ans, source) for (ans, source) in zip(*ngrams_array))
count_ngrams_answer = ngrams_array[0].sum()
containment_val = intersection_count / count_ngrams_answer

return containment_val
```

Test cells

After you've implemented the containment function, you can test out its behavior.

The cell below iterates through the first few files, and calculates the original category *and* containment values for a specified n and file.

If you've implemented this correctly, you should see that the non-plagiarized have low or close to 0 containment values and that plagiarized examples have higher containment values, closer to 1.

Note what happens when you change the value of n. I recommend applying your code to multiple files and comparing the resultant containment values. You should see that the highest containment values correspond to files with the highest category (`cut`) of plagiarism level.

```
In [12]: # select a value for n
n = 3

# indices for first few files
test_indices = range(5)

# iterate through files and calculate containment
category_vals = []
containment_vals = []
for i in test_indices:
    # get level of plagiarism for a given file index
    category_vals.append(complete_df.loc[i, 'Category'])
    # calculate containment for given file and n
    filename = complete_df.loc[i, 'File']
    c = calculateContainment(complete_df, n, filename)
    containment_vals.append(c)

# print out result, does it make sense?
print('Original category values: \n', category_vals)
print()
print(str(n) + '-gram containment values: \n', containment_vals)
```

Original category values:
[0, 3, 2, 1, 0]

3-gram containment values:
[0.009345794392523364, 0.9641025641025641, 0.6136363636363636, 0.15675675675
675677, 0.031746031746031744]

```
In [13]: # run this test cell
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""
# test containment calculation
# params: complete_df from before, and containment function
tests.testContainment(complete_df, calculateContainment)
```

Tests Passed!

QUESTION 1: Why can we calculate containment features across *all* data (training & test), prior to splitting the DataFrame for modeling? That is, what about the containment calculation means that the test and training data do not influence each other?

Answer: Computing the containment is a feature engineering step. The objective is to identify the similarity(words overlap) between 2 pair of documents answer and source only in a numerical way so that this feature can be used for modeling later. Since containment value is only dependent on the pair of document and not the whole set of data(training and test), there will not be any influence on test and train data.

Longest Common Subsequence

Containment a good way to find overlap in word usage between two documents; it may help identify cases of cut-and-paste as well as paraphrased levels of plagiarism. Since plagiarism is a fairly complex task with varying levels, it's often useful to include other measures of similarity. The paper also discusses a feature called **longest common subsequence**.

The longest common subsequence is the longest string of words (or letters) that are *the same* between the Wikipedia Source Text (S) and the Student Answer Text (A). This value is also normalized by dividing by the total number of words (or letters) in the Student Answer Text.

In this exercise, we'll ask you to calculate the longest common subsequence of words between two texts.

EXERCISE: Calculate the longest common subsequence

Complete the function `lcs_norm_word`; this should calculate the *longest common subsequence* of words between a Student Answer Text and corresponding Wikipedia Source Text.

It may be helpful to think of this in a concrete example. A Longest Common Subsequence (LCS) problem may look as follows:

- Given two texts: text A (answer text) of length n, and string S (original source text) of length m. Our goal is to produce their longest common subsequence of words: the longest sequence of words that appear left-to-right in both texts (though the words don't have to be in continuous order).
- Consider:
 - A = "i think pagerank is a link analysis algorithm used by google that uses a system of weights attached to each element of a hyperlinked set of documents"
 - S = "pagerank is a link analysis algorithm used by the google internet search engine that assigns a numerical weighting to each element of a hyperlinked set of documents"
- In this case, we can see that the start of each sentence is fairly similar, having overlap in the sequence of words, "pagerank is a link analysis algorithm used by" before diverging slightly. Then we **continue moving left-to-right along both texts** until we see the next common sequence; in this case it is only one word, "google". Next we find "that" and "a" and finally the same ending "to each element of a hyperlinked set of documents".
- Below, is a clear visual of how these sequences were found, sequentially, in each text.

A =
 "i think pagerank is a link analysis algorithm used by google
 that uses a system of weights attached to each element of a
 hyperlinked set of documents"

S =
 "pagerank is a link analysis algorithm used by the google
 internet search engine that assigns a numerical weighting to
 each element of a hyperlinked set of documents"

- Now, those words appear in left-to-right order in each document, sequentially, and even though there are some words in between, we count this as the longest common subsequence between the two texts.
- If I count up each word that I found in common I get the value 20. **So, LCS has length 20.**

- Next, to normalize this value, divide by the total length of the student answer; in this example that length is only 27. **So, the function `lcs_norm_word` should return the value `20/27` or about `0.7408`.**

In this way, LCS is a great indicator of cut-and-paste plagiarism or if someone has referenced the same source text multiple times in an answer.

LCS, dynamic programming

If you read through the scenario above, you can see that this algorithm depends on looking at two texts and comparing them word by word. You can solve this problem in multiple ways. First, it may be useful to `.split()` each text into lists of comma separated words to compare. Then, you can iterate through each word in the texts and compare them, adding to your value for LCS as you go.

The method I recommend for implementing an efficient LCS algorithm is: using a matrix and dynamic programming. **Dynamic programming** is all about breaking a larger problem into a smaller set of subproblems, and building up a complete result without having to repeat any subproblems.

This approach assumes that you can split up a large LCS task into a combination of smaller LCS tasks. Let's look at a simple example that compares letters:

- A = "ABCD"
- S = "BD"

We can see right away that the longest subsequence of *letters* here is 2 (B and D are in sequence in both strings). And we can calculate this by looking at relationships between each letter in the two strings, A and S.

Here, I have a matrix with the letters of A on top and the letters of S on the left side:

	A	B	C	D
A	0	0	0	0
B	0			
S	0			

This starts out as a matrix that has as many columns and rows as letters in the strings S and O **+1** additional row and column, filled with zeros on the top and left sides. So, in this case, instead of a 2x4 matrix it is a 3x5.

Now, we can fill this matrix up by breaking it into smaller LCS problems. For example, let's first look at the shortest substrings: the starting letter of A and S. We'll first ask, what is the Longest Common Subsequence between these two letters "A" and "B"?

Here, the answer is zero and we fill in the corresponding grid cell with that value.

	A	B	C	D
A	0	0	0	0
B	0	0		
D	0			

Then, we ask the next question, what is the LCS between "AB" and "B"?

Here, we have a match, and can fill in the appropriate value 1.

	A	B	C	D
A	0	0	0	0
B	0	0	1	
D	0			

If we continue, we get to a final matrix that looks as follows, with a **2** in the bottom right corner.

	A	B	C	D
A	0	0	0	0
B	0	0	1	-1
D	0	0	1	2

The final LCS will be that value **2** *normalized* by the number of n-grams in A. So, our normalized value is $2/4 = 0.5$.

The matrix rules

One thing to notice here is that, you can efficiently fill up this matrix one cell at a time. Each grid cell only depends on the values in the grid cells that are directly on top and to the left of it, or on the diagonal/top-left. The rules are as follows:

- Start with a matrix that has one extra row and column of zeros.
- As you traverse your string:
 - If there is a match, fill that grid cell with the value to the top-left of that cell *plus* one. So, in our case, when we found a matching B-B, we added +1 to the value in the top-left of the matching cell, 0.
 - If there is not a match, take the *maximum* value from either directly to the left or the top cell, and carry that value over to the non-match cell.

	A	B	C	D
A	0	0	0	0
B	0	0	1	1
D	0	0	1	2

|

	A	B	C	D
A	0	0	0	0
B	0	0	1	1
D	0	0	1	2

no match: max of top/left values
match: diagonal addition

After completely filling the matrix, **the bottom-right cell will hold the non-normalized LCS value**.

This matrix treatment can be applied to a set of words instead of letters. Your function should apply this to the

```
In [14]: # Compute the normalized LCS given an answer text and a source text
def lcs_norm_word(answer_text, source_text):
    '''Computes the Longest common subsequence of words in two texts; returns
    a normalized value.
    :param answer_text: The pre-processed text for an answer text
    :param source_text: The pre-processed text for an answer's associated s
ource text
    :return: A normalized LCS value'''

    # your code here
    answer = answer_text.split()
    source = source_text.split()

    answer_word_count = len(answer)
    source_word_count = len(source)

    matrix = np.zeros((source_word_count + 1, answer_word_count + 1), dtype=in
t)

    for i, src_word in enumerate(source, 1):
        for j, ans_word in enumerate(answer, 1):
            if src_word == ans_word: # match -> Diagonal addition
                matrix[i][j] = matrix[i-1][j-1] + 1
            else: # no-match -> Max of top/left value
                matrix[i][j] = max(matrix[i][j-1], matrix[i-1][j] )

    lcs = matrix[source_word_count][answer_word_count]
    lcs_norm = lcs/answer_word_count

    return lcs_norm
```

Test cells

Let's start by testing out your code on the example given in the initial description.

In the below cell, we have specified strings A (answer text) and S (original source text). We know that these texts have 20 words in common and the submitted answer is 27 words long, so the normalized, longest common subsequence should be 20/27.

```
In [15]: # Run the test scenario from above
# does your function return the expected value?

A = "i think pagerank is a link analysis algorithm used by google that uses a
    system of weights attached to each element of a hyperlinked set of documents"
S = "pagerank is a link analysis algorithm used by the google internet search
    engine that assigns a numerical weighting to each element of a hyperlinked se
t of documents"

# calculate LCS
lcs = lcs_norm_word(A, S)
print('LCS = ', lcs)

# expected value test
assert lcs==20/27., "Incorrect LCS value, expected about 0.7408, got "+str(lcs
)

print('Test passed!')
```

LCS = 0.7407407407407407
Test passed!

This next cell runs a more rigorous test.

```
In [16]: # run test cell
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""
# test lcs implementation
# params: complete_df from before, and lcs_norm_word function
tests.test_lcs(complete_df, lcs_norm_word)
```

Tests Passed!

Finally, take a look at a few resultant values for `lcs_norm_word`. Just like before, you should see that higher values correspond to higher levels of plagiarism.

```
In [17]: # test on your own
test_indices = range(5) # Look at first few files

category_vals = []
lcs_norm_vals = []
# iterate through first few docs and calculate LCS
for i in test_indices:
    category_vals.append(complete_df.loc[i, 'Category'])
    # get texts to compare
    answer_text = complete_df.loc[i, 'Text']
    task = complete_df.loc[i, 'Task']
    # we know that source texts have Class = -1
    orig_rows = complete_df[(complete_df['Class'] == -1)]
    orig_row = orig_rows[(orig_rows['Task'] == task)]
    source_text = orig_row['Text'].values[0]

    # calculate lcs
    lcs_val = lcs_norm_word(answer_text, source_text)
    lcs_norm_vals.append(lcs_val)

# print out result, does it make sense?
print('Original category values: \n', category_vals)
print()
print('Normalized LCS values: \n', lcs_norm_vals)
```

Original category values:

```
[0, 3, 2, 1, 0]
```

Normalized LCS values:

```
[0.1917808219178082, 0.8207547169811321, 0.8464912280701754, 0.3160621761658
031, 0.24257425742574257]
```

Create All Features

Now that you've completed the feature calculation functions, it's time to actually create multiple features and decide on which ones to use in your final model! In the below cells, you're provided two helper functions to help you create multiple features and store those in a DataFrame, `features_df`.

Creating multiple containment features

Your completed `calculate_containment` function will be called in the next cell, which defines the helper function `create_containment_features`.

This function returns a list of containment features, calculated for a given `n` and for *all* files in a `df` (assumed to be the `complete_df`).

For our original files, the containment value is set to a special value, `-1`.

This function gives you the ability to easily create several containment features, of different n-gram lengths, for each of our text files.

```
In [18]: """
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

# Function returns a list of containment features, calculated for a given n
# Should return a list of length 100 for all files in a complete_df
def create_containment_features(df, n, column_name=None):

    containment_values = []

    if(column_name==None):
        column_name = 'c_'+str(n) # c_1, c_2, .. c_n

    # iterates through dataframe rows
    for i in df.index:
        file = df.loc[i, 'File']
        # Computes features using calculate_containment function
        if df.loc[i,'Category'] > -1:
            c = calculate_containment(df, n, file)
            containment_values.append(c)
        # Sets value to -1 for original tasks
        else:
            containment_values.append(-1)

    print(str(n)+'-gram containment features created!')
    return containment_values
```

Creating LCS features

Below, your complete `lcs_norm_word` function is used to create a list of LCS features for all the answer files in a given DataFrame (again, this assumes you are passing in the `complete_df`. It assigns a special value for our original, source files, -1.

```
In [19]: """
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

# Function creates lcs feature and add it to the dataframe
def create_lcs_features(df, column_name='lcs_word'):

    lcs_values = []

    # iterate through files in dataframe
    for i in df.index:
        # Computes LCS_norm words feature using function above for answer task
        if df.loc[i, 'Category'] > -1:
            # get texts to compare
            answer_text = df.loc[i, 'Text']
            task = df.loc[i, 'Task']
            # we know that source texts have Class = -1
            orig_rows = df[(df['Class'] == -1)]
            orig_row = orig_rows[(orig_rows['Task'] == task)]
            source_text = orig_row['Text'].values[0]

            # calculate lcs
            lcs = lcs_norm_word(answer_text, source_text)
            lcs_values.append(lcs)
        # Sets to -1 for original tasks
        else:
            lcs_values.append(-1)

    print('LCS features created!')
    return lcs_values
```

EXERCISE: Create a features DataFrame by selecting an ngram_range

The paper suggests calculating the following features: containment *1-gram to 5-gram* and *longest common subsequence*.

In this exercise, you can choose to create even more features, for example from *1-gram to 7-gram* containment features and *longest common subsequence*.

You'll want to create at least 6 features to choose from as you think about which to give to your final, classification model. Defining and comparing at least 6 different features allows you to discard any features that seem redundant, and choose to use the best features for your final model!

In the below cell **define an n-gram range**; these will be the n's you use to create n-gram containment features. The rest of the feature creation code is provided.

```
In [20]: # Define an ngram range
ngram_range = range(1,9)

# The following code may take a minute to run, depending on your ngram_range
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""
features_list = []

# Create features in a features_df
all_features = np.zeros((len(ngram_range)+1, len(complete_df)))

# Calculate features for containment for ngrams in range
i=0
for n in ngram_range:
    column_name = 'c_'+str(n)
    features_list.append(column_name)
    # create containment features
    all_features[i]=np.squeeze(create_containment_features(complete_df, n))
    i+=1

# Calculate features for LCS_Norm Words
features_list.append('lcs_word')
all_features[i]= np.squeeze(create_lcs_features(complete_df))

# create a features dataframe
features_df = pd.DataFrame(np.transpose(all_features), columns=features_list)

# Print all features/columns
print()
print('Features: ', features_list)
print()
```

```
1-gram containment features created!
2-gram containment features created!
3-gram containment features created!
4-gram containment features created!
5-gram containment features created!
6-gram containment features created!
7-gram containment features created!
8-gram containment features created!
LCS features created!
```

```
Features:  ['c_1', 'c_2', 'c_3', 'c_4', 'c_5', 'c_6', 'c_7', 'c_8', 'lcs_word']
```

```
In [21]: # print some results
features_df.head(10)
```

Out[21]:

	c_1	c_2	c_3	c_4	c_5	c_6	c_7	c_8	lcs_word
0	0.398148	0.079070	0.009346	0.000000	0.000000	0.000000	0.000000	0.000000	0.191781
1	1.000000	0.984694	0.964103	0.943299	0.922280	0.901042	0.879581	0.857895	0.820755
2	0.869369	0.719457	0.613636	0.515982	0.449541	0.382488	0.319444	0.265116	0.846491
3	0.593583	0.268817	0.156757	0.108696	0.081967	0.060440	0.044199	0.027778	0.316062
4	0.544503	0.115789	0.031746	0.005319	0.000000	0.000000	0.000000	0.000000	0.242574
5	0.329502	0.053846	0.007722	0.003876	0.000000	0.000000	0.000000	0.000000	0.161172
6	0.590308	0.150442	0.035556	0.004464	0.000000	0.000000	0.000000	0.000000	0.301653
7	0.765306	0.709898	0.664384	0.625430	0.589655	0.553633	0.520833	0.487805	0.621711
8	0.759777	0.505618	0.395480	0.306818	0.245714	0.195402	0.150289	0.110465	0.484305
9	0.884444	0.526786	0.340807	0.247748	0.180995	0.150000	0.118721	0.091743	0.597458

Correlated Features

You should use feature correlation across the *entire* dataset to determine which features are **too highly-correlated** with each other to include both features in a single model. For this analysis, you can use the *entire* dataset due to the small sample size we have.

All of our features try to measure the similarity between two texts. Since our features are designed to measure similarity, it is expected that these features will be highly-correlated. Many classification models, for example a Naive Bayes classifier, rely on the assumption that features are *not* highly correlated; highly-correlated features may over-inflate the importance of a single feature.

So, you'll want to choose your features based on which pairings have the lowest correlation. These correlation values range between 0 and 1; from low to high correlation, and are displayed in a [correlation matrix](https://www.displayr.com/what-is-a-correlation-matrix/) (<https://www.displayr.com/what-is-a-correlation-matrix/>), below.

In [22]:

```
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

# Create correlation matrix for just Features to determine different models to
# test
corr_matrix = features_df.corr().abs().round(2)

# display shows all of a dataframe
display(corr_matrix)
```

	c_1	c_2	c_3	c_4	c_5	c_6	c_7	c_8	lcs_word
c_1	1.00	0.94	0.90	0.89	0.88	0.87	0.87	0.87	0.97
c_2	0.94	1.00	0.99	0.98	0.97	0.96	0.95	0.94	0.98
c_3	0.90	0.99	1.00	1.00	0.99	0.98	0.98	0.97	0.97
c_4	0.89	0.98	1.00	1.00	1.00	0.99	0.99	0.98	0.95
c_5	0.88	0.97	0.99	1.00	1.00	1.00	1.00	0.99	0.95
c_6	0.87	0.96	0.98	0.99	1.00	1.00	1.00	1.00	0.94
c_7	0.87	0.95	0.98	0.99	1.00	1.00	1.00	1.00	0.93
c_8	0.87	0.94	0.97	0.98	0.99	1.00	1.00	1.00	0.92
lcs_word	0.97	0.98	0.97	0.95	0.95	0.94	0.93	0.92	1.00

EXERCISE: Create selected train/test data

Complete the `train_test_data` function below. This function should take in the following parameters:

- `complete_df` : A DataFrame that contains all of our processed text data, file info, datatypes, and class labels
- `features_df` : A DataFrame of all calculated features, such as containment for ngrams, n= 1-5, and lcs values for each text file listed in the `complete_df` (this was created in the above cells)
- `selected_features` : A list of feature column names, ex. `['c_1', 'lcs_word']`, which will be used to select the final features in creating train/test sets of data.

It should return two tuples:

- `(train_x, train_y)` , selected training features and their corresponding class labels (0/1)
- `(test_x, test_y)` , selected training features and their corresponding class labels (0/1)

Note: x and y should be arrays of feature values and numerical class labels, respectively; not DataFrames.

Looking at the above correlation matrix, you should decide on a **cutoff** correlation value, less than 1.0, to determine which sets of features are *too* highly-correlated to be included in the final training and test data. If you cannot find features that are less correlated than some cutoff value, it is suggested that you increase the number of features (longer n-grams) to choose from or use *only one or two* features in your final model to avoid introducing highly-correlated features.

Recall that the `complete_df` has a `Datatype` column that indicates whether data should be `train` or `test` data; this should help you split the data appropriately.

```
In [23]: # Takes in dataframes and a List of selected features (column names)
# and returns (train_x, train_y), (test_x, test_y)
def train_test_data(complete_df, features_df, selected_features):
    '''Gets selected training and test features from given dataframes, and
       returns tuples for training and test features and their corresponding c
lass Labels.
    :param complete_df: A dataframe with all of our processed text data, da
tatypes, and Labels
    :param features_df: A dataframe of all computed, similarity features
    :param selected_features: An array of selected features that correspond
to certain columns in `features_df`
    :return: training and test features and Labels: (train_x, train_y), (te
st_x, test_y)'''

    df = pd.concat([complete_df, features_df], axis=1)

    # get the training features
    train_x = df[df['Datatype'] == 'train'][selected_features].values
    # And training class Labels (0 or 1)
    train_y = df[df['Datatype'] == 'train']['Class'].values

    # get the test features and Labels
    test_x = df[df['Datatype'] == 'test'][selected_features].values
    test_y = df[df['Datatype'] == 'test']['Class'].values

    return (train_x, train_y), (test_x, test_y)
```

Test cells

Below, test out your implementation and create the final train/test data.

```
In [24]: """
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

test_selection = list(features_df)[:2] # first couple columns as a test
# test that the correct train/test data is created
(train_x, train_y), (test_x, test_y) = train_test_data(complete_df, features_d
f, test_selection)

# params: generated train/test data
tests.test_data_split(train_x, train_y, test_x, test_y)
```

Tests Passed!

EXERCISE: Select "good" features

If you passed the test above, you can create your own train/test data, below.

Define a list of features you'd like to include in your final mode, `selected_features` ; this is a list of the features names you want to include.

```
In [25]: # Select your list of features, this should be column names from features_df
# ex. ['c_1', 'lcs_word']
selected_features = ['c_1', 'c_7', 'lcs_word']

"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

(train_x, train_y), (test_x, test_y) = train_test_data(complete_df, features_df,
selected_features)

# check that division of samples seems correct
# these should add up to 95 (100 - 5 original files)
print('Training size: ', len(train_x))
print('Test size: ', len(test_x))
print()
print('Training df sample: \n', train_x[:10])
```

Training size: 70

Test size: 25

Training df sample:

```
[[0.39814815 0.          0.19178082]
[0.86936937 0.31944444 0.84649123]
[0.59358289 0.0441989  0.31606218]
[0.54450262 0.          0.24257426]
[0.32950192 0.          0.16117216]
[0.59030837 0.          0.30165289]
[0.75977654 0.15028902 0.48430493]
[0.51612903 0.          0.27083333]
[0.44086022 0.          0.22395833]
[0.97945205 0.7         0.9         ]]
```

Question 2: How did you decide on which features to include in your final model?

Answer: The features are chosen having lowest correlation amongst containment features - c_1 and c_7 = 0.87 and the highest lcs_norm (c_1, lcs_word) = 0.97 and (c_7, lcs_word) = 0.93

Creating Final Data Files

Now, you are almost ready to move on to training a model in SageMaker!

You'll want to access your train and test data in SageMaker and upload it to S3. In this project, SageMaker will expect the following format for your train/test data:

- Training and test data should be saved in one `.csv` file each, ex `train.csv` and `test.csv`
- These files should have class labels in the first column and features in the rest of the columns

This format follows the practice, outlined in the [SageMaker documentation](#)

(<https://docs.aws.amazon.com/sagemaker/latest/dg/cdf-training.html>), which reads: "Amazon SageMaker requires that a CSV file doesn't have a header record and that the target variable [class label] is in the first column."

EXERCISE: Create csv files

Define a function that takes in `x` (features) and `y` (labels) and saves them to one `.csv` file at the path `data_dir/filename`.

It may be useful to use pandas to merge your features and labels into one DataFrame and then convert that into a csv file. You can make sure to get rid of any incomplete rows, in a DataFrame, by using `dropna`.

```
In [26]: def make_csv(x, y, filename, data_dir):
    '''Merges features and Labels and converts them into one csv file with Labels in the first column.
    :param x: Data features
    :param y: Data labels
    :param file_name: Name of csv file, ex. 'train.csv'
    :param data_dir: The directory where files will be saved
    '''

    # make data dir, if it does not exist
    if not os.path.exists(data_dir):
        os.makedirs(data_dir)

    # your code here
    pd.concat([pd.DataFrame(y), pd.DataFrame(x)], axis=1).to_csv(os.path.join(
        data_dir, filename), header=False, index=False)

    # nothing is returned, but a print statement indicates that the function has run
    print('Path created: '+str(data_dir)+'/'+str(filename))
```

Test cells

Test that your code produces the correct format for a `.csv` file, given some text features and labels.

In [27]:

```
"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

fake_x = [ [0.39814815, 0.0001, 0.19178082],
            [0.86936937, 0.44954128, 0.84649123],
            [0.44086022, 0., 0.22395833] ]

fake_y = [0, 1, 1]

make_csv(fake_x, fake_y, filename='to_delete.csv', data_dir='test_csv')

# read in and test dimensions
fake_df = pd.read_csv('test_csv/to_delete.csv', header=None)

# check shape
assert fake_df.shape==(3, 4), \
    'The file should have as many rows as data_points and as many columns as \
features+1 (for indices).'
# check that first column = labels
assert np.all(fake_df.iloc[:,0].values==fake_y), 'First column is not equal to \
the labels, fake_y.'
print('Tests passed!')
```

Path created: `test_csv/to_delete.csv`
 Tests passed!

In [28]:

```
# delete the test csv file, generated above
! rm -rf test_csv
```

If you've passed the tests above, run the following cell to create `train.csv` and `test.csv` files in a directory that you specify! This will save the data in a local directory. Remember the name of this directory because you will reference it again when uploading this data to S3.

In [29]:

```
# can change directory, if you want
data_dir = 'plagiarism_data'

"""
DON'T MODIFY ANYTHING IN THIS CELL THAT IS BELOW THIS LINE
"""

make_csv(train_x, train_y, filename='train.csv', data_dir=data_dir)
make_csv(test_x, test_y, filename='test.csv', data_dir=data_dir)
```

Path created: `plagiarism_data/train.csv`
 Path created: `plagiarism_data/test.csv`

Up Next

Now that you've done some feature engineering and created some training and test data, you are ready to train and deploy a plagiarism classification model. The next notebook will utilize SageMaker resources to train and test a model that you design.