## **PROGRAM 1b**

- ASHISH KUMAR
- 2K18/SE/041

**<u>Aim:-</u>** Write a C++ program to implement data link layer - Character Stuffing.

**Theory:-** In byte stuffing(or character stuffing), a special byte called the escape character (ESC) is stuffed before data section of the frame when there is a character with the same pattern as the flag byte. If the ESC sequence is found in the message byte, then another ESC byte is stuffed before it. Whenever the receiver encounters the ESC character, it deletes it from the data section and treats the next character as data, not a delimiting flag.

## **CODE:-**

```
cin>>a;
cout<<"\n Enter a character that represents starting delimiter:";
cin>>sd;
cout<<"\n Enter a character that represents ending delimiter:";
cin>>ed;
x[0] = s[0] = s[1] = sd;
x[1] = s[2] = '\0';
y[0] = d[0] = d[1] = ed;
d[2] = y[1] = '\0';
strcat(fs, x);
for(i = 0; i < strlen(a); i++)
{
  t[0] = a[i];
  t[1] = '\ 0';
  if(t[0] == 'F') //if we see a flag byte, then insert E before F
     strcat(fs, "EF");
  else if(t[0] == 'E') //if we see a ESC byte, then insert E before E
     strcat(fs, "EE");
  else
     strcat(fs, "D"); //if we see data, then nothing will be done
}
strcat(fs, y);
cout<<"\n After character stuffing:"<< fs;</pre>
return 0;
```

}

## **OUTPUT:-**

```
Enter characters to be stuffed:DDEDFFDE

Enter a character that represents starting delimiter:F

Enter a character that represents ending delimiter:F

After character stuffing: FDDEEDEFEFDEEF

Process exited after 36.37 seconds with return value 0

Press any key to continue . . .
```

<u>Learning Outcome:-</u> We have successfully implemented Character stuffing and we learnt its application in computer network.