

Chapter 7

Domain-Specific Architectures- TPU ONLY

Introduction

- Moore's Law enabled:
  - Deep memory hierarchy
  - Wide SIMD units
  - Deep pipelines
  - Branch prediction
  - Out-of-order execution
  - Speculative prefetching
  - Multithreading
  - Multiprocessing

- Objective:
  - Extract performance from software that is oblivious to architecture

Introduction

- Need factor of 100 improvements in number of operations per instruction
  - Requires domain specific architectures
  - For ASICs, NRE cannot be amoratized over large volumes
  - FPGAs are less efficient than ASICs

Guidelines for DSAs

- Use dedicated memories to minimize data movement
- Invest resources into more arithmetic units or bigger memories
- Use the easiest form of parallelism that matches the domain
- Reduce data size and type to the simplest needed for the domain
- Use a domain-specific programming language

Guidelines for DSAs

Guideline	TPU	Catapult	Crest	Pixel Visual Core
Design target	Data center ASIC	Data center FPGA	Data center ASIC	PMD ASIC/SOC IP
1. Dedicated memories	24 MiB Unified Buffer, 4 MiB Accumulators	Varies	N.A.	Per core: 128 KiB line buffer, 64 KiB P.E. memory
2. Larger arithmetic unit	65,536 Multiply-accumulators	Varies	N.A.	Per core: 256 Multiply-accumulators (512 ALUs)
3. Easy parallelism	Single-threaded, SIMD, in-order	SIMD, MISD	N.A.	MPMD, SIMD, VLIW
4. Smaller data size	8-Bit, 16-bit integer	8-Bit, 16-bit integer 32-bit Fl. Pt.	21-bit Fl. Pt.	8-bit, 16-bit, 32-bit integer
5. Domain-specific lang.	TensorFlow	Verilog	TensorFlow	Halide/TensorFlow

Example: Deep Neural Networks

- Inpired by neuron of the brain
- Computes non-linear “activiation” function of the weighted sum of input values
- Neurons arranged in layers

Name	DNN layers	Weights	Operations/Weight
MLP0	5	20M	200
MLP1	4	5M	168
LSTM0	58	52M	64
LSTM1	56	34M	96
CNN0	16	8M	2888
CNN1	89	100M	1750

Example: Deep Neural Networks

- Most practioners will choose an existing design
  - Topology
  - Data type
- Training (learning):
  - Calculate weights using backpropagation algorithm
  - Supervised learning: stocastic graduate descent

Type of data	Problem area	Size of benchmark's training set	DNN architecture	Hardware	Training time
text [1]	Word prediction (word2vec)	100 billion words (Wikipedia)	2-layer skip gram	1 NVIDIA Titan X GPU	6.2 hours
audio [2]	Speech recognition	2000 hours (Fisher Corpus)	11-layer RNN	1 NVIDIA K1200 GPU	3.5 days
images [3]	Image classification	1 million images (ImageNet)	22-layer CNN	1 NVIDIA K20 GPU	3 weeks
video [4]	activity recognition	1 million videos (Sports-1M)	8-layer CNN	10 NVIDIA GPUs	1 month

- Inferrence: use neural network for classification

Multi-Layer Perceptrons

- Parameters:
  - Dim[i]: number of neurons
  - Dim[i-1]: dimension of input vector
  - Number of weights: Dim[i-1] x Dim[i]
  - Operations: 2 x Dim[i-1] x Dim[i]
  - Operations/weight: 2



Convolutional Neural Network

- Computer vision
- Each layer raises the level of abstraction
  - First layer recognizes horizontal and vertical lines
  - Second layer recognizes corners
  - Third layer recognizes shapes
  - Fourth layer recognizes features, such as ears of a dog
  - Higher layers recognizes different breeds of dogs



Convolutional Neural Network



- Parameters:
  - DimFM[i-1]: Dimension of the (square) input Feature Map
  - DimFM[i]: Dimension of the (square) output Feature Map
  - DimSten[i]: Dimension of the (square) stencil
  - NumFM[i-1]: Number of input Feature Maps
  - NumFM[i]: Number of output Feature Maps
  - Number of neurons: NumFM[i] x DimFM[i]^2
  - Number of weights per output Feature Map: NumFM[i-1] x DimSten[i]^2
  - Total number of weights per layer: NumFM[i] x Number of weights per output Feature Map
  - Number of operations per output Feature Map: 2 x DimFM[i]^2 x Number of weights per output Feature Map
  - Total number of operations per layer: NumFM[i] x Number of operations per output Feature Map = 2 x DimFM[i]^2 x NumFM[i] x Number of weights per output Feature Map = 2 x DimFM[i]^2 x Total number of weights per layer
  - Operations/Weight: 2 x DimFM[i]^2

Recurrent Neural Network

- Speech recognition and language translation
- Long short-term memory (LSTM) network



Recurrent Neural Network



- Parameters:
  - Number of weights per cell: 3 x (3 x Dim x Dim)+(2 x Dim x Dim) + (1 x Dim x Dim) = 12 x Dim^2
  - Number of operations for the 5 vector-matrix multiplies per cell: 2 x Number of weights per cell = 24 x Dim^2
  - Number of operations for the 3 element-wise multiplies and 1 addition (vectors are all the size of the output): 4 x Dim
  - Total number of operations per cell (5 vector-matrix multiplies and the 4 element-wise operations): 24 x Dim^2 + 4 x Dim
  - Operations/Weight: ~2

Convolutional Neural Network

- Batches:
  - Reuse weights once fetched from memory across multiple inputs
  - Increases operational intensity
- Quantization
  - Use 8- or 16-bit fixed point
- Summary:
  - Need the following kernels:
    - Matrix-vector multiply
    - Matrix-matrix multiply
    - Stencil
    - ReLU
    - Sigmoid
    - Hyperbolic tangeant

Tensor Processing Unit

- Google's DNN ASIC
- 256 x 256 8-bit matrix multiply unit
- Large software-managed scratchpad
- Coprocessor on the PCIe bus

Tensor Processing Unit



TPU ISA

- Read_Host_Memory
  - Reads memory from the CPU memory into the unified buffer
- Read_Weights
  - Reads weights from the Weight Memory into the Weight FIFO as input to the Matrix Unit
- MatrixMatrixMultiply/Convolve
  - Perform a matrix-matrix multiply, a vector-matrix multiply, an element-wise matrix multiply, an element-wise vector multiply, or a convolution from the Unified Buffer into the accumulators
  - takes a variable-sized B*256 input, multiplies it by a 256x256 constant input, and produces a B*256 output, taking B pipelined cycles to complete
- Activate
  - Computes activation function
- Write_Host_Memory
  - Writes data from unified buffer into host memory

TPU ISA





TPU ISA





TPU ISA

- Read_Host_Memory
  - Reads memory from the CPU memory into the unified buffer
- Read_Weights
  - Reads weights from the Weight Memory into the Weight FIFO as input to the Matrix Unit
- MatrixMatrixMultiply/Convolve
  - Perform a matrix-matrix multiply, a vector-matrix multiply, an element-wise matrix multiply, an element-wise vector multiply, or a convolution from the Unified Buffer into the accumulators
  - takes a variable-sized B*256 input, multiplies it by a 256x256 constant input, and produces a B*256 output, taking B pipelined cycles to complete
- Activate
  - Computes activation function
- Write_Host_Memory
  - Writes data from unified buffer into host memory

Improving the TPU



The TPU and the Guidelines

- Use dedicated memories
  - 24 MiB dedicated buffer, 4 MiB accumulator buffers
- Invest resources in arithmetic units and dedicated memories
  - 60% of the memory and 250X the arithmetic units of a server-class CPU
- Use the easiest form of parallelism that matches the domain
  - Exploits 2D SIMD parallelism
- Reduce the data size and type needed for the domain
  - Primarily uses 8-bit integers
- Use a domain-specific programming language
  - Uses TensorFlow

Fallacies and Pitfalls

- It costs $100 million to design a custom chip
- Performance counters added as an afterthought
- Architects are tackling the right DNN tasks
- For DNN hardware, inferences per second (IPS) is a fair summary performance metric
- Being ignorant of architecture history when designing an DSA