

C2_04 Module Test - Protected Review RC4

Open only after a saved genuine attempt. Diagnose the weak competency, close this review, then perform a changed retry.

DAX1

A measure is evaluated inside the active filter context supplied by visual coordinates, slicers, page/report filters, relationships and DAX filters. Different cells ask different filtered questions.

DAX2

Row context identifies the current row for row-by-row expressions; filter context is the set of allowed values/tables for measure evaluation. Iterators create row context; measures primarily respond to filter context.

DAX3

CALCULATE evaluates an expression after changing filter context. Describe starting filters, each added/replaced/removed filter, then the re-evaluated expression.

DAX4

Use an iterator when the expression must be evaluated per row before aggregation, such as Quantity * UnitPrice. Validate the iterator input table/grain first or it will multiply an already duplicated grain.

DAX5

Context transition converts current-row values into filters when CALCULATE is invoked; measure references can invoke CALCULATE behavior implicitly. Trace which row columns become filters.

DAX6

Use a trustworthy Date table with unique continuous dates, correct active relationship/role and a base measure that already reconciles. Then shift the date context and re-evaluate.

DAX7

Define the window anchor, included dates, complete/partial-period policy and comparison period. Boundary months can contain unequal days/data completeness and silently distort a percentage.

DAX8

Variables label intermediate results and let you temporarily RETURN each piece while debugging. A variable stores the result from the context where it is defined; later code does not re-evaluate it like a live cell reference.

DAX9

Define eligible population, numerator, denominator, exception/blank-zero treatment and expected total behavior. Then reconcile numerator/denominator independently.

DAX10

Freeze a failing cell/context; test base measures; expose variables/intermediate tables; compare row/subtotal/grand total and slicer states; identify the first divergence before rewriting the final formula.

DAX11

A decision-first page establishes one message and evidence hierarchy: headline, trend, drivers, exceptions, recommendation. Remove visuals that do not change a decision or explain a material exception.

DAX12

Test starting context, navigation trigger, target context/filter state, back/reset route and repeated use. Essential conclusions must not live only in hover tooltips.

DAX13

Use sufficient contrast, visible labels/text, meaningful alt text, logical keyboard/tab order, non-color encodings and accessible navigation. Verify critical information remains available without hover.

DAX14

Test each identity against the mapping table/role, including a multi-mapped user, an unmapped user and cross-region/team records. Confirm allowed union and denied rows in View as and, where available, real Service identity.

DAX15

Record workspace/access owner, distribution method, semantic model/report ownership, refresh/gateway credentials and failure owner, RLS membership, deployment/change impact, rollback and monitoring. Publish alone is not release.

Repair routing

Weak evidence	Repair route
context / calculate / iterator	DAX1-DAX5 + changed detail/total context case
time / business measure / debugging	DAX6-DAX10 + changed date/denominator/semi-additive case
report / accessibility / RLS / lifecycle	DAX11-DAX15 + changed UX/identity/release test

Close this review and prove the weak skill on changed evidence. This diagnostic remains non-gating; Gate A eligibility is unchanged.