

C2-03 Mini-Lab - Parcel Delivery Model

Integrated semantic-model practice after PBM-A1 to PBM-A10

SCENARIO

Operations needs a reusable Power BI model for parcel shipments, delivery charges, shipment events and monthly hub targets. The data includes multiple process grains, an intentionally duplicated HubID on the supposed one-side, one unknown HubID in the fact, and separate Order Date / Delivery Date roles.

YOUR JOB

Build the model contract first. Then create an understandable star design, clean or quarantine the duplicated one-side key, preserve the unknown-fact exception, model higher-grain targets deliberately, choose the date-role strategy, organize Power Query into source/staging/model-ready layers, and validate relationship/filter/total behavior in Power BI Desktop.

PASS SIGNAL

A second analyst can explain every fact grain, one-side key, relationship direction and date role. Tiny filter tests behave as predicted. Material totals reconcile. No many-to-many or bidirectional relationship is used merely to make an error disappear.

Mini-Lab - Release defense

Mastery requires Desktop evidence where relationship behavior matters

REQUIRED EVIDENCE

Model contract; model screenshot; table-role/grain register; duplicate/unknown-key evidence; relationship log; OrderDate and DeliveryDate filter test; target-grain test; source-to-model reconciliation; Power Query dependency notes; one measured performance observation if available; handoff/release note.

90-SECOND DEFENSE

Answer: What does one row in each fact mean? Which table is allowed on the one-side and why? Why are monthly targets not joined directly to shipment rows? How do Order Date and Delivery Date work? Which filter test proves propagation? What would make you block model release?

CHANGED RETRY

After protected review, close it and redesign a service-operations model with Ticket, TicketEvent, Agent, Customer, StaffingTarget and Created/Resolved date roles. Do not reuse the parcel table names or relationship sketch.