

[Home](#)

[DAA](#)

[DS](#)

[DBMS](#)

[Aptitude](#)

[Selenium](#)

[Kotlin](#)

[C#](#)

[HTML](#)

[CSS](#)


[JavaScript](#)

## Example of Matrix Chain Multiplication

**Example:** We are given the sequence {4, 10, 3, 12, 20, and 7}. The matrices have size 4 x 10, 10 x 3, 3 x 12, 12 x 20, 20 x 7. We need to compute  $M[i, j]$ ,  $0 \leq i, j \leq 5$ . We know  $M[i, i] = 0$  for all  $i$ .

1	2	3	4	5	
0					1
	0				2
		0			3
			0		4
				0	5

Let us proceed with working away from the diagonal. We compute the optimal solution for the product of 2 matrices.



Here  $P_0$  to  $P_5$  are Position and  $M_1$  to  $M_5$  are matrix of size  $(p_i \text{ to } p_{i-1})$

On the basis of sequence, we make a formula

For  $M_i \longrightarrow p[i]$  as column

$p[i-1]$  as row

In Dynamic Programming, initialization of every method done by '0'. So we initialize it by '0'. It will sort out diagonally.

We have to sort out all the combination but the minimum output combination is taken into consideration.

#### Calculation of Product of 2 matrices:

1.  $m(1, 2) = m_1 \times m_2$   
 $= 4 \times 10 \times 10 \times 3$   
 $= 4 \times 10 \times 3 = 120$
2.  $m(2, 3) = m_2 \times m_3$   
 $= 10 \times 3 \times 3 \times 12$   
 $= 10 \times 3 \times 12 = 360$
3.  $m(3, 4) = m_3 \times m_4$   
 $= 3 \times 12 \times 12 \times 20$   
 $= 3 \times 12 \times 20 = 720$
4.  $m(4, 5) = m_4 \times m_5$   
 $= 12 \times 20 \times 20 \times 7$   
 $= 12 \times 20 \times 7 = 1680$

1	2	3	4	5	
0	120				1
	0	360			2
		0	720		3
			0	1680	4
				0	5

- We initialize the diagonal element with equal i,j value with '0'.
- After that second diagonal is sorted out and we get all the values corresponded to it

Now the third diagonal will be solved out in the same way.

**Now product of 3 matrices:**

$$M [1, 3] = M_1 M_2 M_3$$

1. There are two cases by which we can solve this multiplication: (  $M_1 \times M_2$  ) +  $M_3$ ,  $M_1 + (M_2 \times M_3)$
2. After solving both cases we choose the case in which minimum output is there.

$$M [1, 3] = \min \left\{ \begin{array}{l} M [1,2] + M [3,3] + p_0 p_2 p_3 = 120 + 0 + 4.3.12 = 264 \\ M [1,1] + M [2,3] + p_0 p_1 p_3 = 0 + 360 + 4.10.12 = 840 \end{array} \right\}$$

$$M [1, 3] = 264$$

As Comparing both output **264** is minimum in both cases so we insert **264** in table and (  $M_1 \times M_2$  ) +  $M_3$  this combination is chosen for the output making.

$$M [2, 4] = M_2 M_3 M_4$$

1. There are two cases by which we can solve this multiplication: (  $M_2 \times M_3$  ) +  $M_4$ ,  $M_2 + (M_3 \times M_4)$
2. After solving both cases we choose the case in which minimum output is there.

$$M [2, 4] = \min \left\{ \begin{array}{l} M [2,3] + M [4,4] + p_1 p_3 p_4 = 360 + 0 + 10.12.20 = 2760 \\ M [2,2] + M [3,4] + p_1 p_2 p_4 = 0 + 720 + 10.3.20 = 1320 \end{array} \right\}$$

$$M [2, 4] = 1320$$

As Comparing both output **1320** is minimum in both cases so we insert **1320** in table and  $M_2 + (M_3 \times M_4)$  this combination is chosen for the output making.

$$M[3, 5] = M_3 \times M_4 \times M_5$$

1. There are two cases by which we can solve this multiplication:  $(M_3 \times M_4) \times M_5$ ,  $M_3 \times (M_4 \times M_5)$
2. After solving both cases we choose the case in which minimum output is there.

$$M[3, 5] = \min \begin{cases} M[3,4] + M[5,5] + p_2 p_4 p_5 = 720 + 0 + 3 \cdot 20 \cdot 7 = 1140 \\ M[3,3] + M[4,5] + p_2 p_3 p_5 = 0 + 1680 + 3 \cdot 12 \cdot 7 = 1932 \end{cases}$$

$$M[3, 5] = 1140$$

As Comparing both output **1140** is minimum in both cases so we insert **1140** in table and  $(M_3 \times M_4) \times M_5$  this combination is chosen for the output making.

1	2	3	4	5	
0	120				1
	0	360			2
		0	720		3
			0	1680	4
				0	5

→

1	2	3	4	5	
0	120	264			1
	0	360	1320		2
		0	720	1140	3
			0	1680	4
				0	5

Now Product of 4 matrices:

$$M[1, 4] = M_1 \times M_2 \times M_3 \times M_4$$

There are three cases by which we can solve this multiplication:

1.  $(M_1 \times M_2 \times M_3) \times M_4$
2.  $M_1 \times (M_2 \times M_3 \times M_4)$
3.  $(M_1 \times M_2) \times (M_3 \times M_4)$

After solving these cases we choose the case in which minimum output is there

$$(M[1,3] + M[4,4] + p_1 p_3 p_4 = 264 + 0 + 4 \cdot 12 \cdot 20 = 1224)$$

$$M[1, 4] = 1080$$

As comparing the output of different cases then '**1080**' is minimum output, so we insert 1080 in the table and  $(M_1 \times M_2) \times (M_3 \times M_4)$  combination is taken out in output making,

$$M[2, 5] = M_2 M_3 M_4 M_5$$

There are three cases by which we can solve this multiplication:

1.  $(M_2 \times M_3 \times M_4) \times M_5$
2.  $M_2 \times (M_3 \times M_4 \times M_5)$
3.  $(M_2 \times M_3) \times (M_4 \times M_5)$

After solving these cases we choose the case in which minimum output is there

$$M[2, 5] = \min \left( M[2, 4] + M[5, 5] + p_1 p_4 p_5 = 1320 + 0 + 10 \cdot 20 \cdot 7 = 2720 \right)$$

$$M[2, 5] = 1350$$

As comparing the output of different cases then '**1350**' is minimum output, so we insert 1350 in the table and  $M_2 \times (M_3 \times M_4 \times M_5)$  combination is taken out in output making.

1	2	3	4	5		1	2	3	4	5	

### Now Product of 5 matrices:

$$M[1, 5] = M_1 \times M_2 \times M_3 \times M_4 \times M_5$$

There are five cases by which we can solve this multiplication:

1.  $(M_1 \times M_2 \times M_3 \times M_4) \times M_5$
2.  $M_1 \times (M_2 \times M_3 \times M_4 \times M_5)$
3.  $(M_1 \times M_2 \times M_3) \times M_4 \times M_5$
4.  $M_1 \times M_2 \times (M_3 \times M_4 \times M_5)$

After solving these cases we choose the case in which minimum output is there

$$M[1, 5] = 1344$$

As comparing the output of different cases then '**1344**' is minimum output, so we insert 1344 in the table and  $M_1 \times M_2 \times (M_3 \times M_4 \times M_5)$  combination is taken out in output making.

### Final Output is:

1	2	3	4	5		1	2	3	4	5	
0	120	264	1080		1	0	120	264	1080	1344	1

**Step 3: Computing Optimal Costs:** let us assume that matrix  $A_i$  has dimension  $p_{i-1} \times p_i$  for  $i=1, 2, 3, \dots, n$ . The input is a sequence  $(p_0, p_1, \dots, p_n)$  where  $\text{length}[p] = n+1$ . The procedure uses an auxiliary table  $m[1 \dots n, 1 \dots n]$  for storing  $m[i, j]$  costs an auxiliary table  $s[1 \dots n, 1 \dots n]$  that record which index

of  $k$  achieved the optimal costs in computing  $m[i, j]$ .

The algorithm first computes  $m[i, j] \leftarrow 0$  for  $i=1, 2, 3, \dots, n$ , the minimum costs for the chain of length 1.

[< Prev](#)[Next >](#)

 Youtube For Videos Join Our Youtube Channel: [Join Now](#)

## Feedback


- Send your Feedback to [feedback@javatpoint.com](mailto:feedback@javatpoint.com)


## Help Others, Please Share







## Learn Latest Tutorials


 **Splunk tutorial**  
Splunk


 **SPSS tutorial**  
SPSS

 **Swagger tutorial**  
Swagger


 **T-SQL tutorial**  
Transact-SQL

 **Tumblr tutorial**  
Tumblr


 **React tutorial**  
ReactJS

 **Regex tutorial**  
Regex

 **Reinforcement learning tutorial**  
Reinforcement Learning


 **R Programming tutorial**  
R Programming

 **RxJS tutorial**  
RxJS

 **React Native tutorial**  
React Native

 **Python Design Patterns**  
Python Design Patterns


 **Python Pillow tutorial**  
Python Pillow


 **Python Turtle tutorial**  
Python Turtle

 **Keras tutorial**  
Keras


## Preparation

 **Aptitude**  
Aptitude

 **Logical Reasoning**  
Reasoning

 **Verbal Ability**  
Verbal Ability


 **Interview Questions**  
Interview Questions



Company Interview Questions


Company Questions

Trending Technologies




Artificial Intelligence

Artificial Intelligence




AWS Tutorial

AWS




Selenium tutorial

Selenium




Cloud Computing

Cloud Computing




Hadoop tutorial

Hadoop




ReactJS Tutorial

ReactJS




Data Science Tutorial

Data Science




Angular 7 Tutorial

Angular 7




Blockchain Tutorial

Blockchain




Git Tutorial

Git




Machine Learning Tutorial

Machine Learning




DevOps Tutorial


DevOps




DBMS tutorial  
DBMS




Data Structures  
tutorial  
Data Structures



DAA tutorial  
DAA




Operating  
System  
Operating System




Computer  
Network tutorial  
Computer Network




Compiler  
Design tutorial  
Compiler Design




Computer  
Organization and  
Architecture  
Computer  
Organization




Discrete  
Mathematics  
Tutorial  
Discrete  
Mathematics




Ethical Hacking  
Ethical Hacking



Computer  
Graphics Tutorial  
Computer Graphics



Software  
Engineering  
Software  
Engineering




html tutorial  
Web Technology




Cyber Security  
tutorial  
Cyber Security




Automata  
Tutorial  
Automata



C Language  
tutorial  
C Programming




C++ tutorial  
C++




Java tutorial  
Java




.Net  
Framework  
tutorial  
.Net



Python tutorial  
Python



List of  
Programs  
Programs



Control  
Systems tutorial  
Control System



Data Mining  
Tutorial  
Data Mining



Data  
Warehouse  
Tutorial  
Data Warehouse

