

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

Search tutorials & examples



(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)

www.domain-name.com

Binary Search

In this tutorial, you will learn how Binary Search sort works. Also, you will find working examples of Binary Search in C, C++, Java and Python.

Binary Search is a searching algorithm for finding an element's position in a sorted array.

In this approach, the element is always searched in the middle of a portion of an array.

Binary search can be implemented only on a sorted list of items. If the elements are not sorted already, we need to sort them first.

Binary Search Working

Binary Search Algorithm can be implemented in two ways which are discussed below.

1. Iterative Method
2. Recursive Method

The recursive method follows [the divide and conquer \(/dsa/divide-and-conquer\)](/dsa/divide-and-conquer) approach.

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

Search tutorials & examples

(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)



www.domain-name.com

Let $x = 4$ be the element to be searched.

- Set two pointers low and high at the lowest and the highest positions respectively.



Setting pointers

- Find the middle element mid of the array ie. $arr[(low + high)/2] = 6$.



Mid element

- If $x == mid$, then return mid. Else, compare the element to be searched with m .

[Get 50%](#)

[FLASH SALE](#)

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)



Search tutorials & examples

www.domain-name.com



Finding mid element

7. Repeat steps 3 to 6 until low meets high.



Mid element

8. `x = 4` is found.



Found

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

Search tutorials & examples



(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)

www.domain-name.com

```
high = mid - 1
```

Recursive Method

```
binarySearch(arr, x, low, high)
    if low > high
        return False
    else
        mid = (low + high) / 2
        if x == arr[mid]
            return mid
        else if x > arr[mid]           // x is on the right side
            return binarySearch(arr, x, mid + 1, high)
        else                          // x is on the left side
            return binarySearch(arr, x, low, mid - 1)
```

Python, Java, C/C++ Examples (Iterative Method)

Python

Java

C

C++

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

OFF all

PRO

courses!

Claim

Your

Discount

Search tutorials & examples



(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)

www.domain-name.com

```
if array[mid] == x:
    return mid

elif array[mid] < x:
    low = mid + 1

else:
    high = mid - 1

return -1

array = [3, 4, 5, 6, 7, 8, 9]
x = 4

result = binarySearch(array, x, 0, len(array)-1)

if result != -1:
```

Python, Java, C/C++ Examples (Recursive Method)

Python

Java

C

C++

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

Search tutorials & examples



(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)

www.domain-name.com

```
if array[mid] == x:
    return mid

# Search the left half
elif array[mid] > x:
    return binarySearch(array, x, low, mid-1)

# Search the right half
else:
    return binarySearch(array, x, mid + 1, high)

else:
    return -1

array = [3, 4, 5, 6, 7, 8, 9]
x = 4
```

Binary Search Complexity

Time Complexities

Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all](#)

[PRO](#)

[courses!](#)

[Claim](#)

[Your](#)

[Discount](#)

Search tutorials & examples



(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50)

www.domain-name.com

Binary Search Applications

- In libraries of Java, .Net, C++ STL
- While debugging, the binary search is used to pinpoint the place where the error happens.

Next Tutorial:

Greedy Algorithm

(</dsa/greedy-algorithm>)

Previous Tutorial:

Linear Search

(</dsa/linear-search>)

Share on:



(<https://www.facebook.com/sharer/sharer.php?u=https://www.programiz.com/dsa/binary-search>)



(<https://twitter.com/intent/tweet?text=Check%20this%20amazing%20search>)

Did you find this article helpful?



Thank you for printing our content at www.domain-name.com. Please check back soon for new contents.

[Get 50%](#)

**FLASH
SALE**

[OFF all
PRO
courses!
Claim
Your
Discount](#)

(https://programiz.pro/offer/pro-sales?utm_source=top-banner-programiz-web&utm_medium=banner&utm_campaign=3-day-sale_top-banner-programiz-web_may_50).



Search tutorials & examples

www.domain-name.com

Related Tutorials

[DS & Algorithms](#)

[Linear Search](#)

(</dsa/linear-search>)

[DS & Algorithms](#)

[Quicksort Algorithm](#)

(</dsa/quick-sort>)

[DS & Algorithms](#)

[Insertion Sort Algorithm](#)

(</dsa/insertion-sort>)

[DS & Algorithms](#)

[Hashing](#)

(</dsa/hashing>)