



Optimal Storage on Tapes



Sagnik Chaudhuri

Read

Discuss

Courses

Practice

Video

Given n programs stored on a computer tape and length of each program i is L_i where $1 \leq i \leq n$, find the order in which the programs should be stored in the tape for which the Mean Retrieval Time (MRT given as $\frac{1}{n} \sum_{i=1}^n \sum_{j=1}^i L_j$) is minimized.

The greedy algorithm finds the MRT as following:

Algorithm MRT_SINGLE_TAPE(L)

// Description: Find storage order of n programs to such that mean retrieval time is minimum

//Input: L is array of program length sorted in ascending order

// Output: Minimum Mean Retrieval Time

$T_j \leftarrow 0$

for $i \leftarrow 1$ to n do

for $j \leftarrow 1$ to i do

$T_j \leftarrow T_j + L[j]$

end

end

$MRT \leftarrow \text{sum}(T) / n$

Complexity analysis:

Primitive operation in the above algorithm is the addition of program length, which is enclosed within two loops. The running time of algorithm is given by,

$$T(n) = O(1)$$

$$= \sum \sum L$$

$$= \sum_{i=1}^n i = 1 + 2 + 3 + \dots + n$$

$$= n(n+1)/2$$

$$= n^2/2 + n/2$$

$$T(n) = O(n^2)$$

This algorithm runs in $O(n^2)$ time.

Example:

Input : $n = 3$

$L[] = \{ 5, 3, 10 \}$

Output : Order should be $\{ 3, 5, 10 \}$ with $MRT = 29/3$

Prerequisites: [Magnetic Tapes Data Storage](#)

Recommended: Please try your approach on [{IDE}](#) first, before moving on to the solution.

Let us first break down the problem and understand what needs to be done.

A magnetic tape provides only sequential access of data. In an audio tape/cassette, unlike a CD, a fifth song from the tape can't be just directly played. The length of the first four songs must be traversed to play the fifth song. So in order to access certain data, head of the tape should be positioned accordingly.

Now suppose there are 4 songs in a tape of audio lengths 5, 7, 3 and 2 mins respectively. In order to play the fourth song, we need to traverse an audio length of $5 + 7 + 3 = 15$ mins and then position the tape head.

Retrieval time of the data is the time taken to retrieve/access that data in its entirety. Hence retrieval time of the fourth song is $15 + 2 = 17$ mins.

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

tape head points to the front of the tape every time, a new term can be defined called the Mean Retrieval Time (MRT).

Let's suppose that the retrieval time of program i is T_i . Therefore, $T_i = \sum_{j=1}^i L_j$

MRT is the average of all such T_i . Therefore $MRT = \frac{1}{n} \sum_{i=1}^n T_i$, or $MRT = \frac{1}{n} \sum_{i=1}^n \sum_{j=1}^i L_j$

The sequential access of data in a tape has some limitations. Order must be defined in which the data/programs in a tape are stored so that least MRT can be obtained. Hence the order of storing becomes very important to reduce the data retrieval/access time.

Thus, the task gets reduced – to define the correct order and hence minimize the MRT, i.e. to minimize the term $\sum_{i=1}^n \sum_{j=1}^i L_j$

For e.g. Suppose there are 3 programs of lengths 2, 5 and 4 respectively. So there are total $3! = 6$ possible orders of storage.

	Order	Total Retrieval Time	Mean Retrieval Time
1	1 2 3	$2 + (2 + 5) + (2 + 5 + 4) = 20$	$20/3$
2	1 3 2	$2 + (2 + 4) + (2 + 4 + 5) = 19$	$19/3$
3	2 1 3	$5 + (5 + 2) + (5 + 2 + 4) = 23$	$23/3$
4	2 3 1	$5 + (5 + 4) + (5 + 4 + 2) = 25$	$25/3$
5	3 1 2	$4 + (4 + 2) + (4 + 2 + 5) = 21$	$21/3$
6	3 2 1	$4 + (4 + 5) + (4 + 5 + 2) = 24$	$24/3$

It's clear that by following the second order in storing the programs, the mean retrieval time is least.

In above example, the first program's length is added 'n' times, the second 'n-1' times... and so on till the last program is added only once. So, careful analysis suggests that in order to minimize the MRT, programs having greater lengths should be put towards the end so that the summation is reduced. Or, the lengths of the programs should be sorted

immediate choice of putting the program having the least time first, in order to build up the ultimate optimized solution to the problem piece by piece.

Below is the implementation:

C++

```
// CPP Program to find the order
// of programs for which MRT is
// minimized
#include <bits/stdc++.h>

using namespace std;

// This functions outputs the required
// order and Minimum Retrieval Time
void findOrderMRT(int L[], int n)
{
    // Here length of i'th program is L[i]
    sort(L, L + n);

    // Lengths of programs sorted according to increasing
    // lengths. This is the order in which the programs
    // have to be stored on tape for minimum MRT
    cout << "Optimal order in which programs are to be"
          "stored is: ";
    for (int i = 0; i < n; i++)
        cout << L[i] << " ";
    cout << endl;

    // MRT - Minimum Retrieval Time
    double MRT = 0;
    for (int i = 0; i < n; i++) {
        int sum = 0;
        for (int j = 0; j <= i; j++)
            sum += L[j];
        MRT += sum;
    }
    MRT /= n;
    cout << "Minimum Retrieval Time of this"
          " order is " << MRT;
}

// Driver Code to test above function
int main()
{
    int L[] = { 2, 5, 4 };
    int n = sizeof(L) / sizeof(L[0]);
    findOrderMRT(L, n);
    return 0;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

// Java Program to find the order
// of programs for which MRT is
// minimized
import java.io.*;
import java .util.*;

class GFG
{
    // This functions outputs
    // the required order and
    // Minimum Retrieval Time
    static void findOrderMRT(int []L,
                             int n)
    {
        // Here length of
        // i'th program is L[i]
        Arrays.sort(L);

        // Lengths of programs sorted
        // according to increasing lengths.
        // This is the order in which
        // the programs have to be stored
        // on tape for minimum MRT
        System.out.print("Optimal order in which " +
            "programs are to be stored is: ");
        for (int i = 0; i < n; i++)
            System.out.print(L[i] + " ");
        System.out.println();

        // MRT - Minimum Retrieval Time
        double MRT = 0;
        for (int i = 0; i < n; i++)
        {
            int sum = 0;
            for (int j = 0; j <= i; j++)
                sum += L[j];
            MRT += sum;
        }
        MRT /= n;
        System.out.print( "Minimum Retrieval Time" +
            " of this order is " + MRT);
    }

    // Driver Code
    public static void main (String[] args)
    {
        int []L = { 2, 5, 4 };
        int n = L.length;
        findOrderMRT(L, n);
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Python3

```
# Python program to find the order of programs for which MRT is minimized

# This function outputs the required order and Minimum Retrieval Time
def findOrderMRT(L, n):

    # Here length of i'th program is L[i]
    L.sort()

    # Lengths of programs sorted according to increasing lengths.
    # This is the order in which the programs have to be stored on tape for minimum MR
    print("Optimal order in which programs are to be stored is:", end=" ")
    for i in range(0, n):
        print(L[i], end=" ")
    print()

    # MRT - Minimum Retrieval Time
    MRT = 0
    for i in range(0, n):
        sum = 0
        for j in range(0, i+1):
            sum += L[j]
        MRT += sum

    MRT /= n
    print("Minimum Retrieval Time of this order is", "{0:.5f}".format(MRT))

L = [2, 5, 4]
n = len(L)
findOrderMRT(L, n)

# This code is contributed by lokesh (lokeshmvs21).
```

C#

```
// C# Program to find the
// order of programs for
// which MRT is minimized
using System;

class GFG
{
    // This functions outputs
    // the required order and
    // Minimum Retrieval Time
    static void findOrderMRT(int []L,
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

// i'th program is L[i]
Array.Sort(L);

// Lengths of programs sorted
// according to increasing lengths.
// This is the order in which
// the programs have to be stored
// on tape for minimum MRT
Console.Write("Optimal order in " +
              "which programs are" +
              " to be stored is: ");
for (int i = 0; i < n; i++)
    Console.Write(L[i] + " ");
    Console.WriteLine();

// MRT - Minimum Retrieval Time
double MRT = 0;
for (int i = 0; i < n; i++)
{
    int sum = 0;
    for (int j = 0; j <= i; j++)
        sum += L[j];
    MRT += sum;
}
MRT /= n;
Console.WriteLine("Minimum Retrieval " +
                  "Time of this order is " +
                  MRT);
}

// Driver Code
public static void Main ()
{
    int []L = { 2, 5, 4 };
    int n = L.Length;
    findOrderMRT(L, n);
}
}

// This code is contributed
// by anuj_67.

```

Javascript

```

// Javascript Program to find the order
// of programs for which MRT is
// minimized

// This functions outputs
// the required order and
// Minimum Retrieval Time
function findOrderMRT(L, n)

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

// i'th program is L[i]
L.sort();

// Lengths of programs sorted
// according to increasing lengths.
// This is the order in which
// the programs have to be stored
// on tape for minimum MRT
document.write("Optimal order in which " +
               "programs are to be stored is: ");
for (let i = 0; i < n; i++)
    document.write(L[i] + " ");
document.write("<br/>");

// MRT - Minimum Retrieval Time
let MRT = 0;
for (let i = 0; i < n; i++)
{
    let sum = 0;
    for (let j = 0; j <= i; j++)
        sum += L[j];
    MRT += sum;
}
MRT /= n;
document.write( "Minimum Retrieval Time" +
               " of this order is " + MRT);
}

// driver code

let L = [ 2, 5, 4 ];
let n = L.length;
findOrderMRT(L, n);

```

Output

```

Optimal order in which programs are to bestored is: 2 4 5
Minimum Retrieval Time of this order is 6.33333

```

Time complexity of the above program is the time complexity for sorting, that is $O(n \lg n)$ (Since `std::sort()` operates in $O(n \lg n)$) If you use bubble sort instead of `std::sort()`, it will take $O(n^2)$

You may think that the time complexity for this particular above code should be due to both the loops in 'mrt' calculation, that is, $O(n^2)$, but do remember that intuitively, the for loops used can also be coded in this manner to avoid two loops :

```

for (int i = 0; i < n; i++)
    MRT += (n - i) * L[i];

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Last Updated : 25 Apr, 2023

5

Similar Reads

1. Sorting with Tapes : Balanced Merge

2. Vertical and Horizontal retrieval (MRT) on Tapes

3. Secretary Problem (A Optimal Stopping Problem)

4. Optimal partition of an array into four parts

5. Optimal sequence for AVL tree insertion (without any rotations)

6. Find optimal weights which can be used to weigh all the weights in the range $[1, X]$

7. Optimal Strategy for a Game | Set 3

8. Optimal strategy for a Game with modifications

9. Optimal Strategy for a Game | DP-31

10. Finding optimal move in Tic-Tac-Toe using Minimax Algorithm in Game Theory

Related Tutorials

1. Learn Data Structures with Javascript | DSA Tutorial

2. Introduction to Max-Heap – Data Structure and Algorithm Tutorials

3. Introduction to Set – Data Structure and Algorithm Tutorials

4. Introduction to Map – Data Structure and Algorithm Tutorials

5. What is Dijkstra's Algorithm? | Introduction to Dijkstra's Shortest Path Algorithm

Next

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Article Contributed By :

**Sagnik Chaudhuri**

Sagnik Chaudhuri

Vote for difficulty

Current difficulty : [Easy](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [vt_m](#), [Sagnik Chaudhuri](#), [chinmoy1997pal](#), [lokeshmvs21](#), [hardikkoriintern](#), [phasing17](#), [laxmishinde5t82](#)

Article Tags : [programming-puzzle](#), [Arrays](#), [DSA](#), [Greedy](#)

Practice Tags : [Arrays](#), [Greedy](#)

[Improve Article](#)[Report Issue](#)**GeeksforGeeks**

A-143, 9th Floor, Sovereign Corporate
Tower, Sector-136, Noida, Uttar Pradesh -
201305

feedback@geeksforgeeks.org

Company

[About Us](#)[Careers](#)[In Media](#)[Contact Us](#)[Terms and Conditions](#)[Privacy Policy](#)[Copyright Policy](#)[Third-Party Copyright Notices](#)

Explore

[Job Fair For Students](#)[POTD: Revamped](#)[Python Backend LIVE](#)[Android App Development](#)[DevOps LIVE](#)[DSA in JavaScript](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Languages

Python
Java
C++
GoLang
SQL
R Language
Android Tutorial

Data Structures

Array
String
Linked List
Stack
Queue
Tree
Graph

Algorithms

Sorting
Searching
Greedy
Dynamic Programming
Pattern Searching
Recursion
Backtracking

Web Development

HTML
CSS
JavaScript
Bootstrap
ReactJS
AngularJS
NodeJS

Data Science & ML

Data Science With Python
Data Science For Beginner
Machine Learning Tutorial
Maths For Machine Learning
Pandas Tutorial
NumPy Tutorial
NLP Tutorial

Interview Corner

Company Preparation
Preparation for SDE
Company Interview Corner
Experienced Interview
Internship Interview
Competitive Programming
Aptitude

Python

Python Tutorial
Python Programming Examples
Django Tutorial
Python Projects
Python Tkinter
OpenCV Python Tutorial

GfG School

CBSE Notes for Class 8
CBSE Notes for Class 9
CBSE Notes for Class 10
CBSE Notes for Class 11
CBSE Notes for Class 12
English Grammar

IIPSC/SSC/BANKING

Write & Earn

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

SBI PO Syllabus	Improve an Article
IBPS PO Syllabus	Pick Topics to Write
UPSC Ethics Notes	Write Interview Experience
UPSC Economics Notes	Internships
UPSC History Notes	Video Internship

@geeksforgeeks , Some rights reserved