

SPECIFICATIONS



Model	S70	S450	S510	S590
Loader Series	K-Series	M3-Series	M3-Series	M3-Series
Rated Operating Capacity (ROC) (35% of tipping load)	—	—	—	—
ROC (50% of tipping load)	760 lb. (344 kg)	1370 lb. (621 kg)	1790 lb. (812 kg)	2000 lb. (907 kg)
ROC With (optional 200 lb., 90 kg) Counterweight	—	1430 lb. (649 kg)	2023 lb. (917 kg)	2150 lb. (975 kg)
Tipping Load	1520 lb. (689 kg)	2740 lb. (1243 kg)	3754 lb. (1702 kg)	4202 lb. (1906 kg)
Height to Bucket Hinge Pin	94.5 in. (2400 mm)	109.5 in. (2781 mm)	114.5 in. (2908 mm)	119.0 in. (3023 mm)
Lift Arm Path	Radius	Radius	Radius	Vertical
Size and Speed				
Operating Weight	2892 lb. (1312 kg)	5370 lb. (2436 kg)	6208 lb. (2816 kg)	6765 lb. (3069 kg)
Width With Bucket	36.0 in. (914 mm)	62.0 in. (1575 mm)	68.0 in. (1727 mm)	68.0 in. (1727 mm)
Height With Cab	71.4 in. (1814 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)
Travel Speed - Low Range	6.3 mph (10.1 km/hr.)	7.6 mph (12.3 km/hr.)	7.6 mph (12.3 km/hr.)	6.9 mph (11.2 km/hr.)
Travel Speed - High Range (optional 2-Speed travel)	—	9.2 mph (14.8 km/hr.)	—	11.4 mph (18.4 km/hr.)
Engine				
Horsepower	23.5 hp (17.5 kW)	49.0 hp (36.5 kW)	55.0 hp (41.0 kW)	68.0 hp (50.7 kW)
Type	Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel
Fuel Tank Capacity	6.5 gal. (24.6 L)	14.2 gal. (53.8 L)	24.8 gal. (93.7 L)	24.8 gal. (93.7 L)
Horsepower Management	—	Included with SJC Option	Included with SJC Option	Included with SJC Option
Tires				
Bobcat Heavy Duty	—	Std	Std	—
Bobcat Standard Duty	Std	—	—	—
Bobcat Superfloat Duty	—	—	—	Std
Tracks/Undercarriage				
Track Width - Standard	—	—	—	—
Track Width - Optional	—	—	—	—
Ground Pressure (with standard tracks)	—	—	—	—
Ground Pressure (with optional tracks)	—	—	—	—
Length of Track on Ground	—	—	—	—
5-Link Torsion Suspension Undercarriage	—	—	—	—
Grease Cylinder Track Tensioning	—	—	—	—
Control Options				
Bobcat Standard (foot pedals/steering levers)	Std	Std	Std	Std
Selectable Joystick Controls (SJC)	—	Opt	Opt	Opt
Radio Remote Control (SJC required)	—	Opt	Opt	Opt
Machine Features				
2-Speed Travel	—	Opt	—	Opt
Automatic Ride Control	—	—	—*	Opt
Back-Up Alarm and Horn	Std	Std	Std	Std
Bobcat Interlock Control System (BICS™)	Std	Std	Std	Std
Cab With Heat	—*	—*	—	—
Cab With Heat and Air Conditioning	—	Opt	Opt	Opt
Heated Cloth Air-Ride Seat	—	—*	—*	—*
Hydraulic Bucket Positioning	—	—*	—*	Opt
Front and Rear Work Lights	Std	Std	Std	Std
Mechanical Suspension Seat	Std	Std	Std	Std
Radio	—	—*	—*	—*
Reversing Fan	—	—	—*	—*
ROPS/FOPS Approved Cab Structure	Std	Std	Std	Std
Deluxe Panel	—	Opt	—*	—*
Side Lighting Kit	—	—	—*	—*
Sound Reduction Package	Opt	Opt	—*	—*
Features for Attachments				
Attachment Control	—*	—*	—*	Opt
Bob-Tach Mounting System	Std	Std	Std	Std
Power Bob-Tach System	—	Opt	—*	Opt
Fingertip Auxiliary Hydraulics Control	—	Std	Std	Std
Hydraulic System Pressure	3000 psi (20.6 MPa)	3300 psi (22.7 MPa)	3550 psi (24.4 MPa)	3550 psi (24.4 MPa)
Hydraulic Standard Flow	9.8 gpm (37.1 L/min.)	16.7 gpm (63.2 L/min.)	17.1 gpm (64.7 L/min.)	17.1 gpm (64.7 L/min.)
Hydraulic High Flow	—	—	—	—
Pressure Release Hydraulic Quick Couplers	—	Std	Std	Std
Speed Management	—	Included with SJC Option	Included with SJC Option	Included with SJC Option

*Ask your Bobcat dealer about installing this option. | **Optional

						
S650	S770	T450	T550	T595	T650	T770
M3-Series	M3-Series	M3-Series	M3-Series	M3-Series	M3-Series	M3-Series
–	–	1490 lb. (676 kg)	1995 lb. (905 kg)	2200 lb. (998 kg)	2570 lb. (1165 kg)	3475 lb. (1576 kg)
2690 lb. (1220 kg)	3350 lb. (1520 kg)	2120 lb. (962 kg)	2850 lb. (1293 kg)	3142 lb. (1425 kg)	3670 lb. (1664 kg)	4960 lb. (2250 kg)
2840 lb. (1288 kg)	3500 lb. (1588 kg)	1656 lb. (745 kg)	2095 lb. (950 kg)	–	2670 lb. (1211 kg)	3575 lb. (1622 kg)
5380 lb. (2440 kg)	6700 lb. (3039 kg)	4257 lb. (1931 kg)	5792 lb. (2627 kg)	6517 lb. (2956 kg)	7343 lb. (3330 kg)	9929 lb. (4504 kg)
124.0 in. (3149 mm)	131.4 in. (3338 mm)	109.5 in. (2781 mm)	114.5 in. (2908 mm)	119.0 in. (3023 mm)	124.0 in. (3149 mm)	131.4 in. (3338 mm)
Vertical	Vertical	Radius	Radius	Vertical	Vertical	Vertical
8061 lb. (3656 kg)	9314 lb. (4225 kg)	6424 lb. (2914 kg)	7557 lb. (3428 kg)	8022 lb. (3638 kg)	9113 lb. (4133 kg)	10,515 lb. (4770 kg)
74.0 in. (1880 mm)	74.0 in. (1880 mm)	56.0 in. (1422 mm)	68.0 in. (1727 mm)	68.0 in. (1727 mm)	74.0 in. (1880 mm)	80.0 in. (2032 mm)
81.3 in. (2065 mm)	81.3 in. (2065 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)	77.8 in. (1976 mm)	81.3 in. (2065 kg)	81.3 in. (2065 mm)
7.1 mph (11.4 km/hr.)	7.1 mph (11.4 km/hr.)	6.9 mph (11.2 km/hr.)	7.1 mph (11.4 km/hr.)	7.1 mph (11.4 km/hr.)	6.2 mph (9.9 km/hr.)	6.6 mph (10.6 km/hr.)
12.3 mph (19.7 km/hr.)	12.3 mph (19.8 km/hr.)	11.0 mph (17.7 km/hr.)	–	–	10.0 mph (16.0 km/hr.)	10.7 mph (17.2 km/hr.)
Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
74.0 hp (55.1 kW)	92.0 hp (68.6 kW)	55.0 hp (41.0 kW)	68.0 hp (50.7 kW)	70.0 hp (52.2 kW)	74.0 hp (55.1 kW)	92.0 hp (68.6 kW)
Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel	Turbo Diesel
23.9 gal. (90.5 L)	23.9 gal. (90.5 L)	16.7 gal. (63.2 L)	36.5 gal. (138.2 L)	36.5 gal. (138.2 L)	23.9 gal. (90.5 L)	43.8 gal. (165.8 L)
Included with SJC Option	Included with SJC Option	Included with SJC Option	Included with SJC Option	Included	Included with SJC Option	Included with SJC Option
Std	Std	–	–	–	–	–
Opt (Parts)	–	–	–	–	–	–
Opt (Parts)	–	–	–	–	–	–
–	–	11.8 in. (300 mm)	12.6 in. (320 mm)	12.6 in. (320 mm)	12.6 in. (320 mm)	17.7 in. (450 mm)
–	–	–	15.7 in. (400 mm)	15.7 in. (400 mm)	17.7 in. (447 mm) (Parts)	15.7 in. (398 mm) (Parts)
–	–	4.8 psi (0.33 bar)	4.9 psi (0.34 bar)	5.1 psi (0.35 bar)	5.7 psi (0.39 bar)	4.2 psi (0.29 bar)
–	–	–	4.0 psi (0.27 bar)	4.1 psi (0.28 bar)	4.1 psi (0.28 bar)	–
–	–	50.2 in. (1275 mm)	54.1 in. (1374 mm)	54.1 in. (1374 mm)	58.5 in. (1485 mm)	63.7 in. (1618 mm)
–	–	–	–	–	–	Solid Mount/Roller Suspension
–	–	Std	Std	Std	Std	Std
Std	Std	Std	Std	–	Std	Std
Opt	Opt	Opt	Opt	Std	Opt	Opt
Opt	Opt	Opt	Opt	Opt	Opt	Opt
Opt	Opt	Opt	–	–	Opt	Opt
Opt	Opt	–	–*	Opt	Opt (Parts)	Opt
Std	Std	Std	Std	Std	Std	Std
Std	Std	Std	Std	Std	Std	Std
–	Opt	–	–	–	–	–
Opt	Opt	Opt	Opt	Opt	Opt	Opt
Opt (Parts)	Opt	–*	–*	–*	Opt (Parts)	Opt
Opt	Opt	–*	–*	Opt	Opt	Opt
Std	Std	Std	Std	Std	Std	Std
Std	Std	Std	Std	Std	Std	Std
Opt (Parts)	Opt	–*	–*	–*	Opt (Parts)	Opt
Opt (Parts)	Opt	–	–*	–*	Opt (Parts)	Opt
Std	Std	Std	Std	Std	Std	Std
–	Opt	–*	–*	–*	–	Opt
Opt	Opt	–	–*	–*	Opt	Opt
Opt	Opt	–*	–*	–*	Opt	Opt
Opt	Opt	–*	–*	Opt	Opt	Opt
Opt	Opt	–*	–*	Std	Std	Std
Opt	Opt	–*	–*	Std	Std	Std
Opt	Opt	Opt	–*	Opt	Opt	Opt
Std	Std	Std	Std	Std	Std	Std
3500 psi (24.1 MPa)	3500 psi (24.1 MPa)	3300 psi (22.7 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)	3500 psi (24.1 MPa)
23.0 gpm (87.0 L/min.)	23.0 gpm (87.1 L/min.)	16.7 gpm (63.2 L/min.)	17.1 gpm (64.7 L/min.)	17.1 gpm (64.7 L/min.)	23.0 gpm (87.0 L/min.)	23.0 gpm (87.1 L/min.)
–	36.6 gpm (138.5 L/min.)**	–	–	–	–	36.6 gpm (138.5 L/min.)**
Std	Std	Std	Std	Std	Std	Std
Included with SJC Option	Included with SJC Option	Included with SJC Option	Included with SJC Option	Included	Included with SJC Option	Included with SJC Option