

MLOPS

By: Ashish Pal




MODEL DEPLOYMENT

When designing an ML system architecture, the following should be borne in mind.

- **Modularity:** the code used in preprocessing/feature engineering should be arranged in comprehensive pipelines.
- **Reproducibility:** the output of each component must be replicable for any version in time.
- **Scalability:** the model must be serveable to a large number of customers with minimal response time.
- **Extensibility:** it should be easy to modify for future tasks.
- **Testing:** the ability to test variation between model versions.
- **Automation:** eliminating manual steps wherever possible to reduce error chances.


DEPLOYMENT PIPELINES

Deployment Type	Training Approach	Prediction Approach - Batch	Prediction Approach - Live 
On-Premises	Training is done locally on dedicated hardware or servers.	Batch predictions are run periodically on the same infrastructure.	Live predictions are served from the on-premises infrastructure.
Cloud	Training is performed on cloud-based resources.	Batch predictions can be scheduled using cloud services (e.g., AWS Batch).	Live predictions are served via cloud-based APIs or services (e.g., AWS Lambda).
Hybrid	A combination of local and cloud training resources.	Batch predictions can use cloud services for scalability (e.g., Azure Data Factory).	Live predictions can be a mix of on-premises and cloud APIs.
Edge	Training can occur on edge devices or remote servers.	Batch predictions might not be common due to limited resources.	Live predictions are executed directly on edge devices with optimized models.
Serverless	Training might involve serverless functions for specific tasks.	Batch predictions can be triggered by events using serverless functions.	Live predictions are served through serverless functions or APIs.
Containerized	Training is done within Docker containers for consistency.	Batch predictions can be executed within containerized environments.	Live predictions are served using containerized applications or microservices.

Model as a Service

- Model-as-Service is a common pattern for wrapping an ML model as an independent service. We can wrap the ML model and the interpreter within a dedicated web service that applications can request through a REST API or consume as a gRPC service.
- This pattern can be used for various ML workflows, such as Forecast, Web Service, Online Learning.

MODEL-as-SERVICE




Model as a Dependency

Model-as-Dependency is probably the most straightforward way to package an ML model. A packaged ML model is considered as a dependency within the software application.

For example, the application consumes the ML model like a conventional jar dependency by invoking the prediction method and passing the values. The return value of such method execution is some prediction that is performed by the previously trained ML model.

The Model-as-Dependency approach is mostly used for implementing the Forecast pattern.


MODEL-as-DEPENDENCY



Precompute Serving Pattern

This type of ML model serving is tightly related to the Forecast ML workflow. With the Precompute serving pattern, we use an already trained ML model and precompute the predictions for the incoming batch of data.

The resulting predictions are persisted in the database. Therefore, for any input request, we query the database to get the prediction result.




Deploying ML Models as Docker Containers

As of now, there is no standard, open solution to ML model deployment. As ML model inference being considered stateless, lightweight, and idempotent, containerization becomes the de-facto standard for delivery.

This means we deploy a container that wraps an ML model inference code. For on-premise, cloud, or hybrid deployments, Docker is considered to be de-facto standard containerization technology.

One ubiquitous way is to package the whole ML tech stack (dependencies) and the code for ML model prediction into a Docker container. Then Kubernetes or an alternative (e.g. AWS Fargate) does the orchestration.

The ML model functionality, such as prediction, is then available through a REST API (e.g. implemented as Flask application)




Deploying ML Models as Serverless Functions

Various cloud vendors already provide machine-learning platforms, and you can deploy your model with their services. Examples are Amazon AWS Sagemaker, Google Cloud AI Platform, Azure Machine Learning Studio, and IBM Watson Machine Learning, to name a few.

Commercial cloud services also provide containerization of ML models such as AWS Lambda and Google App Engine servlet host.

In order to deploy an ML model as a serverless function, the application code and dependencies are packaged into .zip files, with a single entry point function.

This function then could be managed by major cloud providers such as Azure Functions, AWS Lambda, or Google Cloud Functions.



MODEL MONITORING

ML Monitoring



Operational - Is it working?

- Latencies
- Memory size
- CPU usage



Are the predictions accurate?


- Model Outputs



Is the data what is expected?

- Model Inputs

Data Drift




Data drift refers to the situation where the statistical properties of the incoming data used for model prediction change over time.

This change can be due to various factors such as shifts in the data distribution, changes in user behavior, or external events.

When data drift occurs, the data that the model encounters in production may differ significantly from the data it was trained on.

Concept Drift




**Training data with
decision boundary**

$P(Y|X)$
Probability of
 y output
given x input

Concept Drift

$P(Y|X)$ Changes




- Reality/behavioral change
- Relationships change, not the input

Concept drift is closely related to data drift but focuses on the underlying relationships between features and labels rather than just statistical properties. It occurs when the relationships between input features and the target variable change over time.


This means that the assumptions the model was built upon are no longer valid. Concept drift can be more subtle and challenging to detect than data drift. Continuous monitoring is necessary to identify concept drift and to retrain or update the model as needed to maintain its

MLOPS PIPELINE


MLOps level 0: Manual process



MLOps level 1: ML pipeline automation



MLOps level 2: CI/CD pipeline automation




Google Cloud MLops

<https://cloud.google.com/architecture/mlops-continuous-delivery-and-automation-pipelines-in-machine-learning>

Machine Learning Operations (MLOps)

MLOps = ML + Dev + Ops



Line of Business

Business requirement

Machine Learning Lifecycle

Data Collection

- Collecting data from various data sources



SMEs

Data Scientists

Data Pipeline

- Data Pipeline Prep
- Data Clean up
- Data Transformation
- Data management Data drift monitoring
- Data support automation scripts/Tools



Data Engineer

Model Building

- Model selection
- Model training
- Evaluation of Scoring
- Experimentation on accuracy
- Model validation



ML Engineer

Model Deployment

- Scaling deployment model
- Model monitoring
- Model drift monitoring
- Model validation
- Assess the streaming and batch process



ML Engineer

DevOps

- CI/CD pipeline
- Testing model
- Monitoring
 - Logging
 - Notification
 - Scaling deployment model
- Versioning
 - Model
 - Code
 - Data
- Model drift monitoring



MLOps Engineers

Catalogs

- Dataset
- Feature
- Model



ML Archives

Governance


- Access control
- Security
- GDPR/CCPA




ML Governance



ML Architect





Azure Storage

- Triggers
- Data-driven
 - Schedule-driven
 - Metrics-driven

(New data location)

Azure Machine Learning pipeline endpoint

Azure Machine Learning retraining pipeline

Publish machine learning pipeline

AML Model Management

Train model

Evaluate model

Register model

Azure Machine Learning Compute

Azure DevOps build pipeline

Data sanity test

Unit test

Runs for new code

Azure Machine Learning

Create machine learning workspace

Create machine learning compute

Publish machine learning pipeline

One-time run

Operationalize model
Model Artifact Trigger

Azure DevOps release pipeline

Package model into image

Deploy model as web service on ACI

Test web service

Staging, QA

Manual release gate

Deploy model as web service on AKS

Test web service

Production

Scoring services


Container Instances

Kubernetes Service

Monitoring

Application Insights

Model performance data






Version Control



CI/CD



Containerization and Orchestration



Model Deployment



Monitoring and Observability

Thank You



ASHISH PAL

PATH TOAI

SUBSCRIBE



www.pathtoai.com