

Experiment 8

Develop a program using malloc(), calloc(), realloc(), and free(). Monitor memory allocation behavior and identify memory leaks using Valgrind. **Code:**

```
#include <stdio.h>

#include <stdlib.h>

int main() {

    int i;

    // 1. malloc()

    int *a = (int *)malloc(3 * sizeof(int));

    if (a == NULL) {

        printf("malloc failed\n");

        return 1;

    }

    printf("Memory allocated using malloc()\n");

    for (i = 0; i < 3; i++) {

        a[i] = (i + 1) * 10;

        printf("a[%d] = %d\n", i, a[i]);

    }

    // 2. calloc()

    int *b = (int *)calloc(3, sizeof(int));
```

```
if (b == NULL) {  
    printf("calloc failed\n");  
    free(a);  
    return 1;  
}
```

```
printf("\nMemory allocated using calloc()\n");
```

```
for (i = 0; i < 3; i++) {  
    printf("b[%d] = %d\n", i, b[i]);  
}
```

```
// 3. realloc()
```

```
a = (int *)realloc(a, 5 * sizeof(int));
```

```
if (a == NULL) {  
    printf("realloc failed\n");  
    free(b);  
    return 1;  
}
```

```
printf("\nMemory resized using realloc()\n");
```

```
a[3] = 40;
```

```
a[4] = 50;
```

```
for (i = 0; i < 5; i++) {  
    printf("a[%d] = %d\n", i, a[i]);  
}  
  
// 4. free()  
free(a);  
printf("\nMemory allocated by malloc/realloc has been freed.\n");  
  
free(b);  
printf("Memory allocated by calloc has been freed.\n");  
  
return 0;  
}
```

```

Experiment07:47:11: Note: include <stdlib.h> or provide a decl...
skjuneeth@LAPTOP-D8SJ2A02:~$ nano Experiment8.c
skjuneeth@LAPTOP-D8SJ2A02:~$ gcc Experiment8.c -o Experiment8
skjuneeth@LAPTOP-D8SJ2A02:~$ ./Experiment8
Memory allocated using malloc()
a[0] = 10
a[1] = 20
a[2] = 30

Memory allocated using calloc()
b[0] = 0
b[1] = 0
b[2] = 0

Memory resized using realloc()
a[0] = 10
a[1] = 20
a[2] = 30
a[3] = 40
a[4] = 50

Memory allocated by malloc/realloc has been freed.
Memory allocated by calloc has been freed.

```

Develop a program that demonstrates Copy-on-Write behavior after a fork(). Analyze memory usage before and after modifying data in the child process.

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <unistd.h>
```

```
#include <sys/wait.h>
```

```
#define SIZE (10 * 1024 * 1024) // 10 MB
```

```
int main() {
```

```
char *data = malloc(SIZE);
```

```
if (data == NULL) {  
    printf("Memory allocation failed\n");  
    return 1;  
}
```

```
// Fill memory so that it is actually allocated
```

```
for (int i = 0; i < SIZE; i++) {  
    data[i] = 'A';  
}
```

```
printf("Parent: 10 MB memory allocated.\n");
```

```
printf("Parent PID: %d\n", getpid());
```

```
pid_t pid = fork();
```

```
if (pid < 0) {  
    printf("fork() failed\n");  
    free(data);  
    return 1;  
}
```

```
if (pid == 0) {  
    // Child process  
  
    printf("\nChild PID: %d\n", getpid());  
  
    printf("Child: Memory is initially shared using Copy-on-Write.\n");  
  
  
    sleep(2);  
  
  
    // Modify the memory  
  
    printf("Child: Modifying 10 MB of memory...\n");  
  
  
    for (int i = 0; i < SIZE; i++) {  
        data[i] = 'B';  
    }  
  
  
    printf("Child: Memory modification completed.\n");  
  
  
    sleep(5);  
  
  
    free(data);  
  
    exit(0);  
}  
  
else {  
    // Parent process
```

```
printf("\nParent: Child created using fork().\n");

printf("Parent: Both processes initially share the same memory pages.\n");


sleep(8);


wait(NULL);


printf("\nParent: Child process completed.\n");


free(data);
}


return 0;
}
```

```
skjuneeth@LAPTOP-D8SJ2A02:~$ nano Experiment8.1.c
skjuneeth@LAPTOP-D8SJ2A02:~$ gcc Experiment8.1.c -o Experiment8.1
skjuneeth@LAPTOP-D8SJ2A02:~$ ./Experiment8.1
Parent: 10 MB memory allocated.
Parent PID: 1890

Parent: Child created using fork().
Parent: Both processes initially share the same memory pages.

Child PID: 1891
Child: Memory is initially shared using Copy-on-Write.
Child: Modifying 10 MB of memory...
Child: Memory modification completed.
```