

1. Finding Mean Using Python

python

```
data = [10, 20, 30, 40, 50]
mean_val = sum(data) / len(data)
print("Mean:", mean_val)
```

2. Finding Median Using Python

python

```
data = [40, 10, 30, 50, 20]
data.sort()
n = len(data)
if n % 2 == 0:
    median_val = (data[n // 2 - 1] + data[n // 2]) / 2
else:
    median_val = data[n // 2]
print("Median:", median_val)
```

3. Finding Mode Using Python

```
from collections import Counter

data = [1, 2, 2, 3, 4, 2, 5]
count = Counter(data)
mode_val = count.most_common(1)[0][0]
print("Mode:", mode_val)
```

4. Finding Range Using Python

```
data = [15, 8, 22, 42, 10]
range_val = max(data) - min(data)
print("Range:", range_val)
```

5. Finding Variance Using Python (Population)

python

```
data = [2, 4, 4, 4, 5, 5, 7, 9]
mean_val = sum(data) / len(data)
variance_val = sum((x - mean_val) ** 2 for x in data) / len(data)
print("Variance:", variance_val)
```

6. Finding Standard Deviation Pure Python

python

```
data = [2, 4, 4, 4, 5, 5, 7, 9]
mean_val = sum(data) / len(data)
variance_val = sum((x - mean_val) ** 2 for x in data) / len(data)
std_dev = variance_val ** 0.5
print("Standard Deviation:", std_dev)
```

7. Using Built-in Module

python

```
import statistics

data = [12, 15, 15, 18, 22, 25]
print("Mean:", statistics.mean(data))
print("Median:", statistics.median(data))
print("Mode:", statistics.mode(data))
print("Variance:", statistics.variance(data))
print("Standard Deviation:", statistics.stdev(data))
```

8. Using NumPy Library

```
import numpy as np

data = np.array([10, 20, 20, 30, 40])
print("Mean:", np.mean(data))
print("Median:", np.median(data))
print("Variance (Sample):", np.var(data, ddof=1))
print("Standard Deviation:", np.std(data, ddof=1))
print("Range:", np.ptp(data)) # Peak-to-peak (max - min)
```

9. Using SciPy for Mode

```
from scipy import stats

data = [5, 2, 5, 3, 5, 4]
mode_result = stats.mode(data, keepdims=True)
print("Mode:", mode_result.mode[0])
print("Count:", mode_result.count[0])
```

10. Using Pandas for Complete Summary

```
import pandas as pd

df = pd.DataFrame({'values': [10, 20, 30, 40, 50, 50]})
print("Mean:", df['values'].mean())
print("Median:", df['values'].median())
print("Mode:", df['values'].mode().tolist())
print("Variance:", df['values'].var())
print("Std Dev:", df['values'].std())

print("Range:", df['values'].max() - df['values'].min())
```