



## M.P. POORV KSHETRA VIDYUT VITRAN COMPANY LIMITED

(Government of M. P. Undertaking)

Regd. Office: Shakti Bhawan, PO: Vidyut Nagar, Rampur, Jabalpur 482008

0761 - 2661795, 2702800 Website <http://www.mpez.co.in/>

CIN NUMBER: U40109MP2002SGC015120

### VENDOR REGISTRATION CERTIFICATE

Company Name & Address	<b>M/s Samriddhi Industries</b> Registered Office Address:D-149, Firdos Nagar Berasia Road,Bhopal, Madhya Pradesh, Bhopal, Madhya Pradesh, 462018																												
Registration No.	<b>EZV0003235214</b>																												
Date of Issue	28-03-2023																												
Valid up To	27-03-2026																												
Area of supply	MP Discom(CZ/EZ/WZ)																												
<b>Equipments/Items</b>	<table border="1"><tr><td>1</td><td>LT XLPE Arial Bunch XLPE Cable 3X70 + 1X16 + 1X50 Sq mm with aluminiumalloy Bare messenger wire .</td></tr><tr><td>2</td><td>LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm.(insulated nuetral massenger) .</td></tr><tr><td>3</td><td>ACSR Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.), (6/4.09 + 1/4.09 mm) .</td></tr><tr><td>4</td><td>ACSR Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.), (6/4.72 + 7/1.57 mm) .</td></tr><tr><td>5</td><td>ACSR Rabbit conductor 0.05 sq. inch (55 sq.mm. Al.Eq.), (6/.3.35 + 1/3.35 mm) .</td></tr><tr><td>6</td><td>LT XLPE Air Bunch cable 1x35 sq. mm+1x25 sq.mm.insulated neutral cummessenger +1x16 sq.mm street light phase, 1100 Volts .</td></tr><tr><td>7</td><td>AAAC Rabbit conductor 0.05 sq. inch. (55 sq.mm. Al.Eq.) .</td></tr><tr><td>8</td><td>AAAC Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.) .</td></tr><tr><td>9</td><td>LT XLPE Aerial bunched Cable 3 X 95+ 1 X 16+ 1 X 70 sqmm with aluminiumalloy insulated messenger wire .</td></tr><tr><td>10</td><td>LT XLPE Arial Bunch XLPE Cable 3X25 + 1X16 + 1X25 Sq mm. with aluminiumalloy Bare messenger wire .</td></tr><tr><td>11</td><td>LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm. (Bareneutral massenger) .</td></tr><tr><td>12</td><td>AAAC Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.) .</td></tr><tr><td>13</td><td>ACSR Panther conductor 0.20 sq. inch (200 sq.mm Al.Eq.) .</td></tr><tr><td>14</td><td>LT XLPE Cable Arial Bunch 3X120 + 1X16 + 1X70 Sq mm. with aluminium alloyinsulated messenger wire 1100 Volts .</td></tr></table>	1	LT XLPE Arial Bunch XLPE Cable 3X70 + 1X16 + 1X50 Sq mm with aluminiumalloy Bare messenger wire .	2	LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm.(insulated nuetral massenger) .	3	ACSR Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.), (6/4.09 + 1/4.09 mm) .	4	ACSR Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.), (6/4.72 + 7/1.57 mm) .	5	ACSR Rabbit conductor 0.05 sq. inch (55 sq.mm. Al.Eq.), (6/.3.35 + 1/3.35 mm) .	6	LT XLPE Air Bunch cable 1x35 sq. mm+1x25 sq.mm.insulated neutral cummessenger +1x16 sq.mm street light phase, 1100 Volts .	7	AAAC Rabbit conductor 0.05 sq. inch. (55 sq.mm. Al.Eq.) .	8	AAAC Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.) .	9	LT XLPE Aerial bunched Cable 3 X 95+ 1 X 16+ 1 X 70 sqmm with aluminiumalloy insulated messenger wire .	10	LT XLPE Arial Bunch XLPE Cable 3X25 + 1X16 + 1X25 Sq mm. with aluminiumalloy Bare messenger wire .	11	LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm. (Bareneutral massenger) .	12	AAAC Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.) .	13	ACSR Panther conductor 0.20 sq. inch (200 sq.mm Al.Eq.) .	14	LT XLPE Cable Arial Bunch 3X120 + 1X16 + 1X70 Sq mm. with aluminium alloyinsulated messenger wire 1100 Volts .
1	LT XLPE Arial Bunch XLPE Cable 3X70 + 1X16 + 1X50 Sq mm with aluminiumalloy Bare messenger wire .																												
2	LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm.(insulated nuetral massenger) .																												
3	ACSR Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.), (6/4.09 + 1/4.09 mm) .																												
4	ACSR Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.), (6/4.72 + 7/1.57 mm) .																												
5	ACSR Rabbit conductor 0.05 sq. inch (55 sq.mm. Al.Eq.), (6/.3.35 + 1/3.35 mm) .																												
6	LT XLPE Air Bunch cable 1x35 sq. mm+1x25 sq.mm.insulated neutral cummessenger +1x16 sq.mm street light phase, 1100 Volts .																												
7	AAAC Rabbit conductor 0.05 sq. inch. (55 sq.mm. Al.Eq.) .																												
8	AAAC Raccoon conductor 0.075 sq. inch (80 sq.mm. Al.Eq.) .																												
9	LT XLPE Aerial bunched Cable 3 X 95+ 1 X 16+ 1 X 70 sqmm with aluminiumalloy insulated messenger wire .																												
10	LT XLPE Arial Bunch XLPE Cable 3X25 + 1X16 + 1X25 Sq mm. with aluminiumalloy Bare messenger wire .																												
11	LT XLPE Aerial bunched XLPE Cable 3 X 50 + 1 X 16 + 1 X 35 sq.mm. (Bareneutral massenger) .																												
12	AAAC Dog conductor 0.10 sq. inch (100 sq.mm. Al.Eq.) .																												
13	ACSR Panther conductor 0.20 sq. inch (200 sq.mm Al.Eq.) .																												
14	LT XLPE Cable Arial Bunch 3X120 + 1X16 + 1X70 Sq mm. with aluminium alloyinsulated messenger wire 1100 Volts .																												

Signed by:**CGM Works**

upload your digital  
signature