

```

Last login: Wed May 27 14:48:00 on ttys002
hs23@Skills-Academy-30 bin % mysql -u root -p
zsh: command not found: mysql
hs23@Skills-Academy-30 bin % /Applications/MAMP/Library/bin/mysql80/bin/mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 25
Server version: 8.0.44 Source distribution
Copyright (c) 2000, 2025, Oracle and/or its affiliates.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.
Type 'help;' or 'h' for help. Type 'c' to clear the current input statement.
mysql> show databases;
+-----+
| Database          |
+-----+
| information_schema |
| mysql              |
| performance_schema |
| sys                |
+-----+
4 rows in set (0.02 sec)
mysql> create database dae;
Query OK, 1 row affected (0.01 sec)
mysql> show databases;
+-----+
| Database          |
+-----+
| dae                |
| information_schema |
| mysql              |
| performance_schema |
| sys                |
+-----+
5 rows in set (0.01 sec)
mysql> use dae;
Database changed
mysql> create table student(id int, fname varchar(20) , lname varchar(30));
Query OK, 0 rows affected (0.02 sec)
mysql> insert into student(id, fname, lname) values (1, "Sunny", "Rose");
Query OK, 1 row affected (0.01 sec)
mysql> insert into student(id, fname, lname) values (2, "Ash", "ley");
Query OK, 1 row affected (0.00 sec)
mysql> insert into student(id, fname, lname) values (3, "Moon", "Flower");
Query OK, 1 row affected (0.00 sec)
mysql> Select * from student;
+----+-----+-----+
| id  | fname | lname |
+----+-----+-----+
| 1   | Sunny | Rose  |
| 2   | Ash   | ley   |
| 3   | Moon  | Flower|
+----+-----+-----+

```

3 rows in set (0.01 sec)

mysql> desc student;

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
fname	varchar(20)	YES		NULL	
lname	varchar(30)	YES		NULL	

3 rows in set (0.01 sec)

mysql> create table hospital(id int primary key, fname varchar(20) , lname varchar(30),bill int);

Query OK, 0 rows affected (0.01 sec)

mysql> insert into hospital(id, fname, lname, bill) values (1, "Jennifer", "Lauren", 100);

Query OK, 1 row affected (0.00 sec)

mysql> insert into hospital(id, fname, lname, bill) values (2, "Umair", "Mohammed", 200);

Query OK, 1 row affected (0.00 sec)

mysql> insert into hospital(id, fname, lname, bill) values (3, "Sean", "Dau", 300);

Query OK, 1 row affected (0.01 sec)

mysql> Select * from hospital;

id	fname	lname	bill
1	Jennifer	Lauren	100
2	Umair	Mohammed	200
3	Sean	Dau	300

3 rows in set (0.00 sec)

mysql> create table bakery(id int primary key, itemName varchar(20) , cost int);

Query OK, 0 rows affected (0.02 sec)

mysql> insert into hospital(id, fname, lname, bill) values (1, "Cake", 200);

ERROR 1136 (21S01): Column count doesn't match value count at row 1

mysql> insert into hospital(id, itemname, cost) values (1, "Cake", 200);

ERROR 1054 (42S22): Unknown column 'itemname' in 'field list'

mysql> insert into hospital(id, itemName, cost) values (1, "Cake", 200);

ERROR 1054 (42S22): Unknown column 'itemName' in 'field list'

mysql> insert into bakery(id, itemName, cost) values (1, "Cake", 200);

Query OK, 1 row affected (0.00 sec)

mysql> insert into bakery(id, itemName, cost) values (2, "Egg puff", 500);

Query OK, 1 row affected (0.00 sec)

mysql> insert into bakery(id, itemName, cost) values (3, "pastery", 700);

Query OK, 1 row affected (0.00 sec)

mysql> Select * from bakery;

id	itemName	cost
1	Cake	200
2	Egg puff	500
3	pastery	700

3 rows in set (0.00 sec)

mysql> desc bakery;

Field	Type	Null	Key	Default	Extra
id	int	NO	PRIMARY		
itemName	varchar(20)	YES			
cost	int	YES			

id	int	NO	PRI	NULL		
itemName	varchar(20)	YES		NULL		
cost	int	YES		NULL		

+-----+-----+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> create table flowershop(id int primary key, flowerName varchar(20) , cost int);

Query OK, 0 rows affected (0.02 sec)

mysql> insert into flowershop(id, flowerName, cost) values (1, "rose", 100);

Query OK, 1 row affected (0.01 sec)

mysql> insert into flowershop(id, flowerName, cost) values (2, "sun flower", 100);

Query OK, 1 row affected (0.01 sec)

mysql> insert into flowershop(id, flowerName, cost) values (3, "jasmine", 40);

Query OK, 1 row affected (0.01 sec)

mysql> desc flowershop;

Field	Type	Null	Key	Default	Extra
id	int	NO	PRI	NULL	
flowerName	varchar(20)	YES		NULL	
cost	int	YES		NULL	

+-----+-----+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> Select * from flowershop;

id	flowerName	cost
1	rose	100
2	sun flower	100
3	jasmine	40

+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> show tables;

Tables_in_dae
bakery
flowershop
hospital
student

4 rows in set (0.01 sec)

mysql> desc bakery;

Field	Type	Null	Key	Default	Extra
id	int	NO	PRI	NULL	
itemName	varchar(20)	YES		NULL	
cost	int	YES		NULL	

+-----+-----+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> desc flowershop;

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

+-----+-----+-----+-----+-----+-----+

id	int	NO	PRI	NULL		
flowerName	varchar(20)	YES		NULL		
cost	int	YES		NULL		

+-----+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> desc hospital;

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

+-----+-----+-----+-----+-----+

id	int	NO	PRI	NULL	
fname	varchar(20)	YES		NULL	
lname	varchar(30)	YES		NULL	
bill	int	YES		NULL	

+-----+-----+-----+-----+-----+

4 rows in set (0.00 sec)

mysql> desc student;

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

+-----+-----+-----+-----+-----+

id	int	YES		NULL	
fname	varchar(20)	YES		NULL	
lname	varchar(30)	YES		NULL	

+-----+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> select * from student;

id	fname	lname
----	-------	-------

+-----+-----+-----+

1	Sunny	Rose
2	Ash	Iey
3	Moon	Flower

+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> select * from bakery;

id	itemName	cost
----	----------	------

+-----+-----+-----+

1	Cake	200
2	Egg puff	500
3	pastery	700

+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> select * from flowershop;

id	flowerName	cost
----	------------	------

+-----+-----+-----+

1	rose	100
2	sun flower	100
3	jasmine	40

+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> select * from hospitsl;

ERROR 1146 (42S02): Table 'dae.hospitsl' doesn't exist

mysql> select * from hospital;

```
+----+-----+-----+----+
| id | fname | lname | bill |
+----+-----+-----+----+
| 1 | Jennifer | Lauren | 100 |
| 2 | Umair | Mohammed | 200 |
| 3 | Sean | Dau | 300 |
+----+-----+-----+----+
3 rows in set (0.00 sec)
mysql>
```