

Vanderbilt University
Leadership, Policy and Organizations
Class Number 9952
Spring 2017

Binary and Cateogrical Variables

Binary and categorical variables can be a headache to work with. It's worth taking some time to think about each step with these kinds of variables in order to make sure that they are being reported effectively.

Coding

First, it's worth thinking pretty carefully about how these variables will be coded. Are you sure that they are mutually exclusive and exhaustive? How about the numbers of categories? Are these appropriate for the task at hand? Are they really categorical or can they be thought of as ordered? How would you figure this out?

In general, it's better to favor fewer categories, but you need to make sure that your decisions reflect the important questions in your theoretical framework.

Below, I recode the race variables as they're constructed by NCES to be more useful in our analysis.

```
. recode byrace (4/5=4) (6=5) (7=6) (.=.), gen(byrace2)
(10633 differences between byrace and byrace2)
.
. label define byrace2 1 "Am.Ind." 2 "Asian/PI" 3 "Black" 4 "Hispanic" 5 "Multiraci
> al" 6 "White"
.
. label values byrace2 byrace
```

Binary Variables

Binary variables must always be constructed to be directional. Never have a binary variable for “sex,” always construct this kind of binary variable as either “male” or “female.” Binary variables in a regression represent an intercept shift– for the group in question, they increase or decrease the intercept by that amount.

```
. gen female=bysex==2
. replace female=. if bysex==.
(819 real changes made, 819 to missing)
.
. lab var female "Female"
```

Categorical Variables

When running a model with categorical variables, Stata won't always know what you're talking about. If the underlying variable is numeric, it will simply include that variable as numeric. This is not good. Instead, we need to use the `i.` formulation, which specifies not only that a given variable is to be understood as a factor variable, but also allows the user some fine-grained control over how this will be constructed.

Remember that categorical variables must always be interpreted relative to their reference category. We cover how to think about that next.

```
. // NOPE!
. eststo order1: svy: reg `y' order_plan
(running regress on estimation sample)
```

Survey: Linear regression

Number of strata	=	361	Number of obs	=	15129
Number of PSUs	=	751	Population size	=	3055917.9
			Design df	=	390
			F(1, 390)	=	1025.42
			Prob > F	=	0.0000
			R-squared	=	0.1261

bynels2m	Coef.	Linearized Std. Err.	t	P> t	[95% Conf. Interval]	
order_plan	.07355	.0022968	32.02	0.000	.0690342	.0780657
_cons	.2704247	.0059146	45.72	0.000	.2587962	.2820531

```
.
.
. //Proper factor notation
. eststo order1: svy: reg `y' i.order_plan byses1 female
(running regress on estimation sample)
```

Survey: Linear regression

Number of strata	=	361	Number of obs	=	14561
Number of PSUs	=	751	Population size	=	2908622
			Design df	=	390
			F(4, 387)	=	647.17
			Prob > F	=	0.0000
			R-squared	=	0.2507

bynels2m	Coef.	Linearized Std. Err.	t	P> t	[95% Conf. Interval]	
order_plan						
Votech/CC	.0174877	.0053254	3.28	0.001	.0070176	.0279577
Four Year	.0899849	.0054533	16.50	0.000	.0792633	.1007065
byses1	.0629814	.0020981	30.02	0.000	.0588565	.0671064
female	-.0208619	.0026488	-7.88	0.000	-.0260696	-.0156542
_cons	.4048229	.0051525	78.57	0.000	.3946927	.414953

```
.
. esttab order1 using order1.rtf, varwidth(50) label ///
> nodepvars ///
> b(3) ///
> se(3) ///
> r2 (2) ///
```

```

>          ar2 (2)          ///
>          scalar(F "df_m DF model" "df_r DF residual" N)  ///
>          sfmt (2 0 0 0)    ///
>          replace
(output written to order1.rtf)

.
.
. esttab order1 using order1.rtf, varwidth(50) label ///
>   refcat(2.order_plan "Plans, Reference= No Plans/ Don't Know",nolabel) ///
>   nobaselevels ///
>   nomtitles ///
>   nodepvars          ///
>   b(3)                ///
>   se(3)                ///
>   r2 (2)              ///
>   ar2 (2)             ///
>   scalar(F "df_m DF model" "df_r DF residual" N)  ///
>   sfmt (2 0 0 0)      ///
>   replace
(output written to order1.rtf)

.

```

Reference Categories for Categorical Variables

It's important to put some thought into reference categories for category variables. If you have no other preference, then use the largest group. You can accomplish this via the `ib(freq)` command. You should put some careful thought into the contrasts you'd like to draw—which groups do you want to compare and why?

```

. //Proper factor notation: setting base levels
. eststo order2: svy: reg `y' ib(freq).order_plan byses1 female
(running regress on estimation sample)

Survey: Linear regression

Number of strata   =      361          Number of obs       =    14561
Number of PSUs     =      751          Population size      =   2908622
                                                Design df           =      390
                                                F(   4,   387)      =    647.17
                                                Prob > F             =    0.0000
                                                R-squared            =    0.2507

-----+-----
      bynels2m |               Linearized
               |      Coef.   Std. Err.      t    P>|t|     [95% Conf. Interval]
-----+-----
order_plan |
No Plans/DK | -.0899849   .0054533   -16.50  0.000   -.1007065   -.0792633
Votech/CC   | -.0724972   .0028019   -25.87  0.000   -.0780059   -.0669885
byses1      | .0629814    .0020981    30.02  0.000   .0588565   .0671064
female      | -.0208619   .0026488    -7.88  0.000   -.0260696   -.0156542
_cons       | .4948077    .0028725   172.25  0.000   .4891601   .5004553
-----+-----

.
. esttab order2 using order2.rtf, varwidth(50) label ///
>   nodepvars          ///
>   b(3)                ///

```

```

>          se(3)                ///
>          r2 (2)                ///
>          ar2 (2)               ///
>          scalar(F "df_m DF model" "df_r DF residual" N)  ///
>          sfmt (2 0 0 0)        ///
>          replace
(output written to order2.rtf)

.
.
. esttab order2 using order2.rtf, varwidth(50)  ///
>   refcat(1.order_plan "College Plans, Reference=Plans to go to College",nolabel
> ) ///
>   label ///
>       nomtitles ///
>       nobaselevels ///
>       nodepvars      ///
>       b(3)           ///
>       se(3)          ///
>       r2 (2)         ///
>       ar2 (2)        ///
>       scalar(F "df_m DF model" "df_r DF residual" N)  ///
>       sfmt (2 0 0 0)  ///
>       replace
(output written to order2.rtf)

.

```

Interactions

When interacting a binary variable with a categorical variable, you must do the FULL interaction—you can't just interact with one level. Same thing applies to continuous variables.

Using Margins

Once you're undertaking interactions with categorical variables, it's generally a good idea to interpret them using the margins command. In the below code I use margins to interpret the interaction between a categorical and a binary variable and to make a table with confidence intervals from the output.

```

. // Factor notation, interaction
.
. //Proper factor notation: setting base levels
. eststo order3: svy: reg `y' b3.order_plan##i.female byses1
(running regress on estimation sample)

```

Survey: Linear regression

Number of strata	=	361	Number of obs	=	14561
Number of PSUs	=	751	Population size	=	2908622
			Design df	=	390
			F(6, 385)	=	436.30
			Prob > F	=	0.0000
			R-squared	=	0.2508

		Linearized				
bylnels2m	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
-----+-----						

order_plan						
No Plans/DK	-.0852546	.0068928	-12.37	0.000	-.0988062	-.0717029
Votech/CC	-.0712396	.0038389	-18.56	0.000	-.0787872	-.0636921
1.female	-.0190811	.0031363	-6.08	0.000	-.0252473	-.0129149
order_plan#						
female						
No Plans/DK#1	-.0140878	.0101094	-1.39	0.164	-.0339636	.005788
Votech/CC#1	-.002454	.0051646	-0.48	0.635	-.0126079	.0076999
byses1	.0629263	.0020983	29.99	0.000	.058801	.0670516
_cons	.4938647	.0029628	166.69	0.000	.4880397	.4996898

```

.
. esttab order3 using order3.rtf, varwidth(50) ///
> refcat(1.order_plan "College Plans, Reference=Plans to go to College:" 1.orde
> r_plan#1.female "Interaction of Plans with Female:", nolabel) ///
> interaction(" X ") ///
> label ///
>
> nomtitles ///
> nobaselevels ///
> nodepvars ///
> b(3) ///
> se(3) ///
> r2 (2) ///
> ar2 (2) ///
> scalar(F "df_m DF model" "df_r DF residual" N) ///
> sfmt (2 0 0 0) ///
> replace
(output written to order3.rtf)

```

```

.
. // Margins to figure out what's going on
. margins, predict(xb) at((mean) byses1 order_plan=(1 2 3) female=(0 1)) post

```

```

Adjusted predictions      Number of obs      =      13055
Model VCE      : Linearized

```

```

Expression      : Linear prediction, predict(xb)

1._at      : order_plan      =      1
             female          =      0
             byses1          =      .0400221 (mean)

2._at      : order_plan      =      1
             female          =      1
             byses1          =      .0400221 (mean)

3._at      : order_plan      =      2
             female          =      0
             byses1          =      .0400221 (mean)

4._at      : order_plan      =      2
             female          =      1
             byses1          =      .0400221 (mean)

5._at      : order_plan      =      3
             female          =      0
             byses1          =      .0400221 (mean)

6._at      : order_plan      =      3
             female          =      1
             byses1          =      .0400221 (mean)

```

		Delta-method			
	Margin	Std. Err.	t	P> t	[95% Conf. Interval]

_at						
1	.4111286	.0063766	64.47	0.000	.3985917	.4236655
2	.3779598	.007331	51.56	0.000	.3635465	.392373
3	.4251435	.0034677	122.60	0.000	.4183258	.4319613
4	.4036084	.0034357	117.47	0.000	.3968536	.4103633
5	.4963832	.0029395	168.86	0.000	.4906039	.5021625
6	.4773021	.0025748	185.38	0.000	.4722399	.4823643

```

.
. esttab . using margins.rtf , margin label nostar ci ///
>   varlabels(1._at "No College Plans, Male" ///
>             2._at "No College Plans, Female" ///
>             3._at "Vo-Tech/Community College, Male" ///
>             4._at "Vo-Tech/Community College, Female" ///
>             5._at "Four-Year College Plans, Male" ///
>             6._at "Four-Year College Plans, Female" ) ///
>   replace
(output written to margins.rtf)

```