

# Tumour Detection By Volumetric Image Analysis

**Author:** Mr Ashley J. Robinson


**Email:** [ajr2g10@ecs.soton.ac.uk](mailto:ajr2g10@ecs.soton.ac.uk)

**Supervisor:** Professor Mark S. Nixon

**Full Report:** [www.ajrobinson.org/tumour.pdf](http://www.ajrobinson.org/tumour.pdf)

This research review covers the use of volumetric image analysis in medicine to accurately detect the presence of tumours in the human body. The problem is to be approached by considering the general cases therefore concentration is not set on a specific area of the body. Rather than trying to classify lung or brain tumours individually the goal is to consider what features tumours have in common. Given an entire image of a human body is it possible to classify the presence of a tumour in any given section whilst using the same approach?

The motivation behind this is to make the most of medical scanning. Dosages of radiation, cost and capture time are all reasons to reduce the number of required patient scans. Thoroughly inspecting any data gathered is a constructive method of scan reduction. A practical end objective is used to provide direction to research and maximise the resultant impact. This is to provide an implementation recommendation for a tool that can assist with medical practitioner diagnosis.




## Pre-Processing

**Original**



**Anisotropic Diffusion**




**Fig. 2 Example smoothing [1].**

Anisotropic diffusion is a powerful technique used to enhance images where it is possible to remove noise yet retain clear edges. The technique has been expanded from common 2D applications to 3D medical usage on MRI data [19]. The diffusion effect has the same outcome as a low pass filter with reasonably adjusted values for resolution,  $\Delta t$ , and the decay constant,  $k$ . The spatial scalar decay constant is a function of the image and time which must preserve edges by setting iterative approach is provided in Eq. (6) where the original image is the value of  $I$  at time zero. Iteration monitoring and reasonable scalar values in the




## Feature Extraction

The active contour model is a method for flexible shape extraction and has been thoroughly trialled in 2D [18]. Volumetric implementations are state of the art and have been successfully applied to prostate, nerve fibre and artery segmentation [22]–[24]. These are not pure active contours and emulate behave by segmenting 2D regions then using volumetric growth algorithms to actively converge upon a 3D shape. This works for certain parts of human anatomy but typically known geometry is required to influence the growing algorithm. Pure active contours could improve performance and using current research it is possible to expand dimensionality. The




**A segmented volumetric brain tumour viewed in 3DSlicer [3][4].**



## Feature Selection

Commonly large datasets contain some features in the input space will be have no effect upon or even reduce the performance of a classifier. It is naive to use just the raw image data. Tumour features for extraction have been considered in section III which already removes some redundant information. Mapping input data into a lower dimensional space is possible and can improve performance but if ill-applied can remove key features. A brute-force approach would find the optimal combination of features but the input space is expected to be too large,  $2^n$  is a challenge even moderate value of  $n$ , to be completely shattered within reasonable execution time. A. Sequential Floating Search (SFS) This heuristic algorithm uses feature subsets and has been applied to tumour classification [3]. It is possible to start from either the full or empty set of features then iteratively add and remove features to improve the performance of the classifier. A performance function is required for feature set comparison. Listing 1 contains the algorithm starting from an initial subset of no features and repeated until convergence.



## Classification

Classification must differentiate between extracted geometric shapes that are expected and those which may potentially be tumours. Tumours will also be attached to normal internal body parts so the classifier must be able to handle any abnormalities in organs. Supervised techniques for classification are considered even though datasets have not yet been sourced. A. Artificial Neural Networks (ANNs) ANNs contain summation nodes where data is propagated through weighted connections towards an output. As a supervised technique weights are trained by propagating the error backwards through the network. Multilayer nets can provided non-linear separation functions and increasing the number of layers only increases possible function complexity. Neural networks have been applied successfully to classification of brain tumours [27]. Eq. (12) is an example of a two layer network with an  $n$  dimensional input space and  $m$  hidden nodes. A tanh activation function is used on the output of the hidden nodes but only the sign is used for the binary classification task. There is also a scalar offset,  $b$ , on the output and an offset vector,  $c$ , on the hidden layer.



Anisotropic diffusion is recommended to reduce noise because edge detection is important in later stages. This method can also be easily tuned by limiting iterations of the algorithm to match the image source. Edge detection is required for both pre-processing and feature extraction. Canny edge detection produces significantly better results than simple filter kernels but at the expense of computation. Edge, curvature and active contour feature extraction techniques are recommended for implementation. To deal with amount of features PCA can be used to remove redundant components but also AdaBoost in conjunction with the classifier algorithm. SVMs are robust machine learning architectures and should definitely provide at least weak hypotheses which should prove useful in the boosting algorithm.

## Confidence Analysis

The confidence analysis unit will take noise information from the initial image by differencing the input and output of the pre-processing stage. In feature extraction it can report on the quantity of shape extraction from an image. Dimensionality reduction will have no output as the reduction value is tuned prior to deployment. The binary classifier also has a nondiscrete output before hard thresholding which can be used as a measure of confidence. This can also be used to adaptively control the number of boosting rounds.

## References

- [1] B. Nakhjavanlo, T. Ellis, P. H. Soan, and J. Dehmeshki, *3d medical image segmentation using level set models and anisotropic diffusion*, SITIS, 2011 7<sup>th</sup> Int. Con. on, Nov 2011, pp. 403–408.
- [2] G. Cooper, *Elements of Human Cancer*, ser. Biology Series. Jones and Bartlett Publishers, 1992
- [3] Eggar et al., *GBM Volumetry using the 3D Slicer Medical Image Computing Platform*, CoRR, 2013.
- [4] 3DSlicer. [Visited] 06/05/14. [Online]. Available: <http://www.slicer.org/>



UNIVERSITY OF  
**Southampton**  
School of Electronics  
and Computer Science