

Manage2 API Function - Add Licenses

Last modified: *March 12, 2021*

Description

This function adds a new license to a Manage2 account.

Examples

Browser-based calls

cPanelLicensing PHP Class

cPanelLicensing Perl Module

Output (XML)

Output (JSON)

Output (YAML)

1

2

3

4

5

6

7

8

monthly_price: '21.34'

status: 1

yearly: 0

reason: Activated EXAMPLECOMPANY license on 192.0.2.0 in the 'example'

price: '100.00'

promoinfo: ''

licenseid: '6793969'

Table of Contents

Description

Examples

Parameters

Returns

Did you find this document helpful?



Parameters

This function accepts the following parameters:

Parameter	Type	Description	Example
ip	string	Required The IP address for which to add a license.	192.0.2.0
packageid	string	Required The package's ID number. The Manage2 List Package Information function returns a list of possible values.	008
groupid	string	Required The ID of the group to which to add the license. The Manage2 Display Groups function returns a list of possible values.	013

Parameter	Type	Description	Example
<code>force</code> or <code>reactivateok</code>	<i>Boolean</i>	Whether to forcibly add the license to the specified IP address: <ul style="list-style-type: none"><code>1</code> — Forcibly add the license.<code>0</code> — Do not forcibly add the license. This parameter defaults to <code>1</code> .	<code>0</code>
<code>dryrun</code>	<i>Boolean</i>	Whether to display error messages and price information, but not activate the license: <ul style="list-style-type: none"><code>1</code> — Display fee information but do not activate the license.<code>0</code> — Do not display fee information but activate the license. This parameter defaults to <code>0</code> .	<code>1</code>
<code>maxusers</code>	<i>integer</i>	The maximum number of users allowed on the license.	<code>120</code>
<code>external_notes</code>	<i>string</i>	A space for additional information associated with the license, up to 64 characters long.	<code>testlicense</code>

Returns

This function returns the following values:

Return	Type	Description	Example
<code>licenseid</code>	<i>integer</i>	The new license ID.	<code>6793969</code>
<code>monthly_price</code>	<i>numeric</i>	The monthly base price of a license, in US dollars.	<code>21.34</code>
<code>price</code>	<i>numeric</i>	The price for a license, in US dollars.	<code>100.00</code>
<code>promoinfo</code>	<i>string</i>	Information about any applied promotional rates. One of: <ul style="list-style-type: none">A string value.<code>""</code> — No promotion applied.	<code>""</code>
<code>reason</code>	<i>string</i>	Information about the license activation.	<code>Activated EXAMPLECOMPANY license on 192.0.2.0 in the 'example' group.</code>
<code>status</code>	<i>Boolean</i>	Whether the function succeeded: <ul style="list-style-type: none"><code>1</code> — Success.<code>0</code> — Failure.	<code>1</code>
<code>yearly</code>	<i>Boolean</i>	Whether the license is a yearly license: <ul style="list-style-type: none"><code>1</code> — A yearly license.<code>0</code> — Not a yearly license.	<code>0</code>



cPanel, WebHost Manager and WHM are registered trademarks of cPanel, L.L.C. for providing its computer software that facilitates the management and configuration of internet web servers.