



Newman command reference

✳️ Ask a question | 📄 Copy page | 📄 View as Markdown | More actions ▾

Use Newman's command line options to customize your collection runs. You can use options to set up a collection run, configure request delays and timeouts, specify SSL details, and more. When you run a collection iteratively, you can [specify different data sets and variables](#) for each iteration. After a run finishes, Newman exits with a [status code](#) that you can pass to your continuous integration (CI) tool.

To use options, add them to the `newman run` command after you [specify the collection file or URL](#):

```
$ newman run my-collection.json [options]
```

To view a list of available options for Newman, run the following command:

```
$ newman run -h
```

Basic options

-h, --help

Output usage information.

-v, --version

Output the version number.

Setup options

[Pricing](#)[Enterprise](#)[Contact Sales](#)

Specify the file path or URL of environment variables.

-g, --globals [file\|URL]

Specify the file path or URL of global variables.

-d, --iteration-data [file]

Specify the local file path to a data file (JSON or CSV) to use for each iteration. To learn more, see [Data file example](#).

-n, --iteration-count [number]

Specify the number of times for the collection to run. Use with the iteration data file.

--folder [folderName]

Specify a folder to run requests from. You can specify more than one folder by using this option multiple times, specifying one folder for each time the option is used.

--working-dir [path]

Set the path of the working directory to use while reading files with relative paths. Defaults to the current directory.

--no-insecure-file-read

Prevents reading of files located outside of the working directory.

--export-environment [path]

The path to the file where Newman will output the final environment variables file before completing a run.

--export-globals [path]

The path to the file where Newman will output the final global variables file before completing a run.

--export-collection [path]

The path to the file where Newman will output the final collection file before completing a run.

[Pricing](#)[Enterprise](#)[Contact Sales](#)

The [Postman API key](#) used to load resources using the Postman API.

Request options

--delay-request [number]

Specify a delay (in milliseconds) between requests.

--timeout [number]

Specify the time (in milliseconds) to wait for the entire collection run to complete.

--timeout-request [number]

Specify the time (in milliseconds) to wait for requests to return a response.

--timeout-script [number]

Specify the time (in milliseconds) to wait for scripts to complete.

SSL options

--ssl-client-cert [path]

The path to the public client certificate file. Use this option to make authenticated requests.

--ssl-client-key [path]

Optionally, you can add the path to the private client key that verifies certificate ownership.

--ssl-client-passphrase [passphrase]

Optionally, you can add a secret passphrase to protect the private client key.

--ssl-client-cert-list [path]

The path to the configuration JSON file containing the SSL client certificate list. Use this option to set several SSL client certificates according to a URL or hostname. To learn more, see [an example client certificate list](#) [↗](#).

[Pricing](#)[Enterprise](#)[Contact Sales](#)

options are used instead.

`--ssl-extra-ca-certs [path]`

The path to the file that has one or more trusted CA certificates in PEM format. You can use this option when you don't want to use the `--insecure` option.

Output options

`--color [value]`

Specify the color of the CLI output: `on`, `off`, or `auto` (default).

`--verbose`

Show detailed information of the collection run and each request sent.

`--silent`

Prevent Newman from showing CLI output.

`-x, --suppress-exit-code`

Specify whether to override the default exit code for the current run. Continue running tests even after a failure, but exit with `code=0`. To learn more, see [Exit status](#).

`--disable-unicode`

Turn off Unicode text encoding. When supplied, all symbols in the output will be replaced by their plain text equivalents.

`-r [reporter-name], --reporters [reporter-name]`

Generate a report about the current collection run. Specify one or more reporter names: `cli` (default when using Newman as a CLI), `json`, `junit`, `progress`, and `emojitrain`. Specify more than one reporter name as a comma-separated list, for example, `-r cli,json`. Learn more about [using reporters with Newman](#).

More configuration options

`--bail [optionalModifiers]`

[Pricing](#)[Enterprise](#)[Contact Sales](#)

optionally, you can add `--fail-fast` to the option `--fail`. You can add `--fail-fast` to skip the entire collection run if an invalid folder was specified using the `--folder` option, or an error was encountered in general. You can add `--failure` to stop an entire collection run (after completing the current test script) when a test fails.

-k, --insecure

Turn off SSL verification checks, and allow self-signed SSL certificates.

--ignore-redirects

Turn off automatic following of `3XX` redirect responses.

--cookie-jar [path]

Specify the file path for a JSON Cookie Jar. Uses `tough-cookie` to deserialize the file.

--export-cookie-jar [path]

The path to the file where Newman will output the final cookie jar file before completing a run. Uses `tough-cookie` to serialize the file.

--global-var "[global-variable-name]=[global-variable-value]"

Specifies global variables on the command line, in a key=value format. Multiple global variables can be added by using `--global-var` multiple times, for example, `--global-var "color=blue" --global-var "pet=cat"`.

--env-var "[environment-variable-name]=[environment-variable-value]"

Specifies environment variables in a key=value format on the command line. You can add multiple environment variables using `--env-var` multiple times, for example: `--env-var "color=blue" --env-var "pet=cat"`.

Exit status

By default, Newman exits with a status code of `0` if everything runs as expected without any exceptions. You can configure your continuous integration (CI) tool to pass or fail a build based on Newman's exit codes. To override the default exit code for the current run, use `-x` or `--suppress-exit-code` option.

[Pricing](#)[Enterprise](#)[Contact Sales](#)

example:

```
$ newman run my-collection.json -e dev-environment.json --bail
```

Data file example

To use a different set of data or variables for each iteration in a collection run, use the `-d` option to specify a JSON or CSV file.

The following example shows a JSON data file for a run with two iterations, with each iteration using different values for a set of variables.

```
1  [  
2    {  
3      "url": "http://127.0.0.1:5000",  
4      "user_id": "1",  
5      "id": "1",  
6      "token_id": "123123"  
7    },  
8    {  
9      "url": "http://postman-echo.com",  
10     "user_id": "2",  
11     "id": "2",  
12     "token_id": "899899"  
13   }  
14 ]
```

To run the collection, use the `-d` option and specify the data file. For example:

```
$ newman run my-collection.json -d data-file.json
```

The following example shows the same data formatted in a CSV file.

```
$ url, user_id, id, token_id  
$ http://127.0.0.1:5000, 1, 1, 123123123
```

[Pricing](#)[Enterprise](#)[Contact Sales](#)

To learn more about formatting data files for collection runs, see [Run collections using imported data](#).

Was this page helpful?

Yes

No

[< Previous](#)

[Next >](#)

[Install and run Newman](#)

[Upload test data files with Newman](#)

Built with fern

Product

[Postman Overview](#)

[Enterprise](#)

[Spec Hub](#)

[Flows](#)

[Agent Mode](#)

[API Catalog](#)

[Fern](#)

[Postman CLI](#)

[Integrations](#)

[Workspaces](#)

API Network

[App Security](#)

[Artificial Intelligence](#)

[Communication](#)

[Data Analytics](#)

[Database](#)

[Developer Productivity](#)

[DevOps](#)

[Ecommerce](#)

[eSignature](#)

[Financial Services](#)



Pricing

Enterprise



Contact Sales

Resources

[Postman Docs](#)

[Academy](#)

[Community](#)

[Templates](#)

[Intergalactic](#)

[Videos](#)

[MCP Servers](#)

Legal and Security

[Legal Terms Hub](#)

[Terms of Service](#)

[Postman Product Terms](#)

[Security](#)

[Website Terms of Use](#)

Company

[About](#)

[Careers and culture](#)

[Contact us](#)

[Partner program](#)

[Customer stories](#)

[Student programs](#)

[Press and media](#)



POSTMAN



[Download Postman](#)

[Privacy Policy](#)

[Do Not Sell or Share My Personal Information](#)

[Cookie Preferences](#)

© 2026 Postman, Inc.



Pricing

Enterprise



Contact Sales