

*Bliss**

A laissez-faire SAGA Implementation

Bliss Intro | 11/02/11 | Ole Weidner

Preamble

- Bliss is not a replacement for SAGA C++ and the Python Bindings and is not striving to be
- I wrote it to get *my own* research in dynamic and autonomic distributed computing and applications off the ground

Design Goals

- Pure Python Implementation (2.4 +)
- *Pythonic* API Feeling
- Simple Installation and Deployment
- Simple Adaptor Development
- Demand-Driven v.s. Standard-Driven
- A Playground for New Ideas!

Metrics

	SAGA C++	Python Bindings	A Few Adaptors*
<i>Total Physical Source Lines of Code (SLOC)</i>	153,693	6,203	13,551
<i>Estimated Development Effort (in Person-Years)</i>	39.54	1.36	2.94
<i>Estimated Development Cost (in US-\$)</i>	\$5,341,072	\$183,600	\$397,261

Generated with SLOCCount: <http://www.dwheeler.com/sloccount/>

* Condor, Globus & SSH

Linux 1.0.0 (March 1994) had a SLOC count of 176,250

http://en.wikipedia.org/wiki/Linux_kernel

Industry average: about 15-50 errors per 1000 lines of delivered code

Code Complete, Microsoft Press Redmond, WA, USA, 2004

Status Quo

- GFD.90 Base Classes a.k.a. *Look & Feel*
 - Object, Url, Session, Context, Exceptions
- Lightweight Runtime & Plug-In Mechanism
- Logging Facilities (yes: *SAGA_VERBOSE*)
- SAGA Job Package (Synchronous)
- Proof-of-Concept Local *fork://* Job Adaptor

Compatibility

- Focus on *Pythonic* API (Naming, Properties, ...) but trying to maintain compatibility with the SAGA Python Bindings, e.g.

```
# separate namespace – can be renamed
import bliss.saga as saga

saga.url = saga.Url # classes can be renamed, too
saga.job.description = saga.job.Description

jd = saga.job.description()
jd.set_attribute("Executable", "/usr/bin/bfast") # old-style
jd.arguments = ['xx', 'yy'] # new-style (preferred!)

js = saga.job.Service("fork://localhost")
job = js.create_job(jd)
```


Installation

- Bliss is in the Python Package Index (*PyPI*):
<http://pypi.python.org/pypi/bliss>

- Installation via *easy_install* or *pip*:

```
$> easy_install bliss
```

- Or bootstrap in user-space on a remote machine including *easy_install* & *virtualenv*:

```
$> curl -fsSLk https://raw.githubusercontent.com/1321016 > \
pystrap.sh && /bin/sh pystrap.sh -lbliss
```


Contribute

- Yes, Please! It's a Communal Playground...
- Give Feedback / Make Suggestions:
<https://github.com/oweidner/bliss/issues>
- Start Developing: Fork Bliss on GitHub
<https://github.com/oweidner/bliss>

Roadmap

- A Globus GRAM Adaptor
- A PBS via SSH Adaptor
- Tackling Thread-Safety / Metrics Interface ?
- A Minimal File Package ?

Resources

- Preliminary API Documentation:
<http://oweidner.github.com/bliss/apidoc/>
- Wiki & Documentation:
<https://github.com/oweidner/bliss/wiki>
- The *User-Space Bootstrapping Script*:
<https://gist.github.com/1321016>
- These Slides: https://github.com/oweidner/bliss/blob/docs/bliss_intro.pdf?raw=true