



✓ **Congratulations! You passed!**

[Next Item](#)



1. If you have 10,000,000 examples, how would you split the train/dev/test set?

1 / 1
point

- ☐ 60% train . 20% dev . 20% test
- ☒ 98% train . 1% dev . 1% test
- ☐ 33% train . 33% dev . 33% test

Correct



2. The dev and test set should:

1 / 1
point

- ☒ Come from the same distribution
- ☐ Come from different distributions
- ☐ Be identical to each other (same (x,y) pairs)
- ☐ **Have the same number of examples**

Correct



3. If your Neural Network model seems to have high bias, what of the following would be promising things to try? (Check all that apply.)

0 / 1
point

- ☐ Make the Neural Network deeper
- ☐ Increase the number of units in each hidden layer
- ☐ Get more test data
- ☒ Add regularization
- ☒ Get more training data

This should be selected

This should be selected

Un-selected is correct

This should not be selected

This should not be selected



4. You are working on an automated check-out kiosk for a supermarket, and are building a classifier for apples, bananas and oranges. Suppose your classifier obtains a training set error of 0.5%, and a dev set error of 7%. Which of the following are promising things to try to improve your classifier? (Check all that apply.)

1 / 1
point

- ☒ Increase the regularization parameter lambda

Correct

- ☐ Decrease the regularization parameter lambda

☐ Decrease the regularization parameter lambda

Un-selected is correct

☒ Get more training data

Correct

☐ Use a bigger neural network

Un-selected is correct



5. What is weight decay?

1 / 1
point

- ☐ A technique to avoid vanishing gradient by imposing a ceiling on the values of the weights.
- ☐ The process of gradually decreasing the learning rate during training.
- ☐ Gradual corruption of the weights in the neural network if it is trained on noisy data.
- ☒ A regularization technique (such as L2 regularization) that results in gradient descent shrinking the weights on every iteration.

Correct



6. What happens when you increase the regularization hyperparameter lambda?

1 / 1
point

☒ Weights are pushed toward becoming smaller (closer to 0)

Correct

- ☐ Weights are pushed toward becoming bigger (further from 0)
- ☐ Doubling lambda should roughly result in doubling the weights
- ☐ Gradient descent taking bigger steps with each iteration (proportional to lambda)



7. With the inverted dropout technique, at test time:

1 / 1
point

- ☐ You do not apply dropout (do not randomly eliminate units), but keep the 1/keep_prob factor in the calculations used in training.
- ☐ You apply dropout (randomly eliminating units) but keep the 1/keep_prob factor in the calculations used in training.
- ☒ You do not apply dropout (do not randomly eliminate units) and do not keep the 1/keep_prob factor in the calculations used in training

Correct

☐ You apply dropout (randomly eliminating units) and do not keep the 1/keep_prob factor in the calculations used in training



8. Increasing the parameter keep_prob from (say) 0.5 to 0.6 will likely cause the following: (Check the two that apply)

1 / 1
point

☐ Increasing the regularization effect

Un-selected is correct

☒ Reducing the regularization effect

Correct

☐ Causing the neural network to end up with a higher training set error

Un-selected is correct

☒ Causing the neural network to end up with a lower training set error

Correct



9. Which of these techniques are useful for reducing variance (reducing overfitting)? (Check all that apply.)

1 / 1
point

☒ L2 regularization

Correct

☐ Gradient Checking

Un-selected is correct

☐ Xavier initialization

Un-selected is correct

☒ Dropout

Correct

☒ Data augmentation

Correct

☐ Exploding gradient

Un-selected is correct

☐ Vanishing gradient

Un-selected is correct



10. Why do we normalize the inputs x ?

1 / 1
point

☐ It makes the parameter initialization faster

☐ It makes it easier to visualize the data

☐ Normalization is another word for regularization--It helps to reduce variance

☒ It makes the cost function faster to optimize

Correct