

## C# - DELEGATES

[https://www.tutorialspoint.com/csharp/csharp\\_delegates.htm](https://www.tutorialspoint.com/csharp/csharp_delegates.htm)

Copyright © tutorialspoint.com

### Advertisements

C# delegates are similar to pointers to functions, in C or C++. A **delegate** is a reference type variable that holds the reference to a method. The reference can be changed at runtime.

Delegates are especially used for implementing events and the call-back methods. All delegates are implicitly derived from the **System.Delegate** class.

### Declaring Delegates

Delegate declaration determines the methods that can be referenced by the delegate. A delegate can refer to a method, which has the same signature as that of the delegate.

For example, consider a delegate –

```
public delegate int MyDelegate (string s);
```

The preceding delegate can be used to reference any method that has a single *string* parameter and returns an *int* type variable.

Syntax for delegate declaration is –

```
delegate <return type> <delegate-name> <parameter list>
```

### Instantiating Delegates

Once a delegate type is declared, a delegate object must be created with the **new** keyword and be associated with a particular method. When creating a delegate, the argument passed to the **new** expression is written similar to a method call, but without the arguments to the method. For example –

```
public delegate void printString(string s);  
...  
printString ps1 = new printString(WriteToScreen);  
printString ps2 = new printString(WriteToFile);
```

Following example demonstrates declaration, instantiation, and use of a delegate that can be used to reference methods that take an integer parameter and returns an integer value.

#### [Live Demo](#)

```
using System;  
  
delegate int NumberChanger(int n);  
namespace DelegateAppl {  
  
    class TestDelegate {  
        static int num = 10;  
  
        public static int AddNum(int p) {
```

```

        num += p;
        return num;
    }
    public static int MultNum(int q) {
        num *= q;
        return num;
    }
    public static int getNum() {
        return num;
    }
    static void Main(string[] args) {
        //create delegate instances
        NumberChanger nc1 = new NumberChanger(AddNum);
        NumberChanger nc2 = new NumberChanger(MultNum);

        //calling the methods using the delegate objects
        nc1(25);
        Console.WriteLine("Value of Num: {0}", getNum());
        nc2(5);
        Console.WriteLine("Value of Num: {0}", getNum());
        Console.ReadKey();
    }
}

```

When the above code is compiled and executed, it produces the following result –

```

Value of Num: 35
Value of Num: 175

```

## Multicasting of a Delegate

Delegate objects can be composed using the "+" operator. A composed delegate calls the two delegates it was composed from. Only delegates of the same type can be composed. The "-" operator can be used to remove a component delegate from a composed delegate.

Using this property of delegates you can create an invocation list of methods that will be called when a delegate is invoked. This is called **multicasting** of a delegate. The following program demonstrates multicasting of a delegate –

[Live Demo](#)

```

using System;

delegate int NumberChanger(int n);
namespace DelegateAppl {
    class TestDelegate {
        static int num = 10;

        public static int AddNum(int p) {
            num += p;
            return num;
        }
        public static int MultNum(int q) {
            num *= q;
            return num;
        }
    }
}

```

```
}
public static int getNum() {
    return num;
}
static void Main(string[] args) {
    //create delegate instances
    NumberChanger nc;
    NumberChanger nc1 = new NumberChanger(AddNum);
    NumberChanger nc2 = new NumberChanger(MultNum);

    nc = nc1;
    nc += nc2;

    //calling multicast
    nc(5);
    Console.WriteLine("Value of Num: {0}", getNum());
    Console.ReadKey();
}
}
```

When the above code is compiled and executed, it produces the following result –

```
Value of Num: 75
```

## Using Delegates

The following example demonstrates the use of delegate. The delegate *printString* can be used to reference method that takes a string as input and returns nothing.

We use this delegate to call two methods, the first prints the string to the console, and the second one prints it to a file –

### [Live Demo](#)

```
using System;
using System.IO;

namespace DelegateAppl {

    class PrintString {
        static FileStream fs;
        static StreamWriter sw;

        // delegate declaration
        public delegate void printString(string s);

        // this method prints to the console
        public static void WriteToScreen(string str) {
            Console.WriteLine("The String is: {0}", str);
        }

        //this method prints to a file
        public static void WriteToFile(string s) {
            fs = new FileStream("c:\\message.txt",
                FileMode.Append, FileAccess.Write);
        }
    }
}
```

```
        SW = new StreamWriter(fs);
        SW.WriteLine(s);
        SW.Flush();
        SW.Close();
        fs.Close();
    }

    // this method takes the delegate as parameter and uses it to
    // call the methods as required
    public static void sendString(printString ps) {
        ps("Hello World");
    }

    static void Main(string[] args) {
        printString ps1 = new printString(WriteToScreen);
        printString ps2 = new printString(WriteToFile);
        sendString(ps1);
        sendString(ps2);
        Console.ReadKey();
    }
}
```

When the above code is compiled and executed, it produces the following result –

The String is: Hello World