

# C By Vikash Sarraf


## Introduction (I)

### Computer

Any Calculating device is called Computer.

#### **Definition - What Does Computer mean?**

A computer is a machine or device that performs processes, calculations and operations based on instructions provided by a software or hardware program. It is designed to execute applications and provides a variety of solutions by combining integrated hardware and software components.



#### **Full Form**

**C= Common**

**O= Oriented**

**M= Machine**

**P= Particularly**

**U= United and used under**


**T= Technical and**

**E= Educational**

**R= Research**


# **Brain Vs. Computer**

Speed  
Accuracy  
Processing  
Size and Complexity  
Storage  
Control Mechanism  
Automation  
Versatile  
Diligency  
Reliability



## **Software**

Collection of programs is called Software.



## Program

Collection of instructions is called program.


## Programing

Solving the problem step by step is called is called Programming.

## Algorithm

An algorithm (pronounced AL-go-rith-um) is a procedure or formula for solving a problem, based on conducting a sequence of specified actions. A computer program can be viewed as an elaborate algorithm. In mathematics and computer science, an algorithm usually means a small procedure that solves a recurrent problem.






# Programming Languages

There are two types of programming language.


1. Low level language (L.L.L)
2. High level language (H.L.L)



# Translators

There are three types of translators

1. Assembler
2. Interpreter
3. Compiler



## **Assembler**

It Converts the program written in Assembly language to Low Level Language.

## **Interpreter**

It converts the program written in High Level Language into Low Level Language line by line if any error in any line then Execution process will terminate.

## **Compiler**

It converts the program written in High Level Language into Low Level Language at one go. If there is any syntax error in program, program won't be execute.



## **( II )Introduction of C**

C is the functional programming language developed by Dennis Ritchie in 1970 at AT & T Bell lab USA.

But c was appeared in 1972

In 1982 a committee established by ANST to fix the standard of C Language.

In 1989 ANSI introduce ANSI C

C is derived from B language and B is derived from BCPL (Basic Combine Programming Language)

## **Application Areas of C Language**

We can develop standalone application by using C language.

Desktop App

GUI App

Games

Operating System

Compilers

To develop New Language

# **Structure of C Program**

**Comments**

**Global Variables**

**main()**

**{  
}**

**func1()**

**{  
}**

**funct2()**

**{  
}**

## (III) Reserve words

### Reserve words

Reserve words are also called keywords. It is predefine words which is used for do specific task in program.

C has 32 Reserve words

All keywords in python are in lower case

Keywords in C Programming			
<a href="#"><u>auto</u></a>	<a href="#"><u>break</u></a>	<a href="#"><u>case</u></a>	<a href="#"><u>char</u></a>
<a href="#"><u>const</u></a>	<a href="#"><u>continue</u></a>	<a href="#"><u>default</u></a>	<a href="#"><u>do</u></a>
<a href="#"><u>double</u></a>	<a href="#"><u>else</u></a>	<a href="#"><u>enum</u></a>	<a href="#"><u>extern</u></a>
<a href="#"><u>float</u></a>	<a href="#"><u>for</u></a>	<a href="#"><u>goto</u></a>	<a href="#"><u>if</u></a>
<a href="#"><u>int</u></a>	<a href="#"><u>long</u></a>	<a href="#"><u>register</u></a>	<a href="#"><u>return</u></a>
<a href="#"><u>short</u></a>	<a href="#"><u>signed</u></a>	<a href="#"><u>sizeof</u></a>	<a href="#"><u>static</u></a>
<a href="#"><u>struct</u></a>	<a href="#"><u>switch</u></a>	<a href="#"><u>typedef</u></a>	<a href="#"><u>union</u></a>
<a href="#"><u>unsigned</u></a>	<a href="#"><u>void</u></a>	<a href="#"><u>volatile</u></a>	<a href="#"><u>while</u></a>

## **(IV) Identifier**

A name in program which, can be used for identification purpose is called an Identifier.

It can be function name, variable name.

### **Rules to define identifier in C**

1. Identifiers can be combination of uppercase and lowercase letters, digits or an underscore (\_) sign so We can't use special any symbols like !, #, @, %, \$ etc in our Identifier.

2. An Identifier can not start with digit

3. We can't use reserve words as identifier.

4. Identifier can be only 31 Character

5. C is case sensitive so

var1 & Var both are two different identifier (variable)

i.e. var ----- valid

var123 ----- valid

Var121 ----- valid

var\_123 ----- valid

\_Var245 ----- valid


2121Var245 ----- invalid

if=20 invalid

\_Var&45 ----- invalid

\_Var\$45 ----- invalid

## (V) Data types



### Integer data type

short memory 2 byte range

int memory 2/4 byte range

long memory 4 byte range

format specifier %d and %u

### float data type

float memory 4 byte

double memory 8 byte

format specifier %f

## **char data type**

char memory 1 byte

format specifier %c

## **(VI) Operators**

**Arithmetic**

**Increment/Decrement**

**Relational (<, >, <=, >=, ==, !=)**

**Assignment (=)**

**Logical**

**Bitwise (&, |, ~, <<, >>)**

**Ternary**

## **Arithmetic Operators**

Operators are symbols used to perform certain operations

There are various operators in C

+ -----> for addition

- -----> for subtraction

\* -----> for multiplication

/ -----> for division

% -----> for remainder (modulo)

**Assignment (=)**

**Increment/Decrement**

**Relational (<,>,<=,>=,==,!=)**

**Logical (&&, || and !)**

## **(VII) Input/output statements**

**Reading data from keyboard**

scanf("Control String",address of var)


ie. scanf("%d,%d",&a,&b)

**printing data to consol**

printf("Control String", variables)

ie. printf("%d,%d",a,b)

## **(VIII) Control Statements**



**if**

### **Syntax**

If (condition)

{

statements

}



# If-else

## Syntax

```
    If (condition)
```

```
{
```

```
    statements
```

```
}
```

```
else
```

```
{
```

```
    statements
```

```
}
```

```
/* wap to input a number & check number is 'negative or not */
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n;
```

```
printf("Enter a number:");
```

```
scanf("%d",&n);
```

```
if (n<0)
```

```
printf("%d is negative number",n);
```

```
}
```

**/\* wap to input a number & check number is even or odd**

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n;
```

```
printf("Enter a number:");
```

```
scanf("%d",&n);
```

```
if (n%2==0)
```

```
printf("%d is even number",n);
```

```
else
```

```
printf("%d is odd number",n);
```

```
}
```

**/\* wap to input Year & check year is leap or not**

**s**

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
int year;
printf("Enter a year:");
scanf("%d",&year);
if ((year%4==0 && year%100!=0) || (year%400==0) )
printf("%d is leap",year);
else
printf("%d is not leap",year);
}
```

/\* Wap to input two numbers & print greater number

```
#include<stdio.h>
#include<conio.h>
void main()
{
int n1,n2;
printf("Enter numbers:\n");
scanf("%d%d",&n1,&n2);
if (n1>n2)
printf("%d is greater number",n1);
else
```

```
printf("%d is greater number",n2);  
}
```

```
/* Wap to find the quotient & remainder
```

## **Nesting of if-else**

### **Syntax**

```
    If (condition)  
    {  
        If (condition)  
            statements  
        else  
            statements  
    }  
else  
{  
    If (condition)  
        statements  
    else  
        statements  
  
}
```

```
/* Wap to input three numbers & print greater number
```

```
#include<stdio.h>
#include<conio.h>
void main()
{
int n1,n2,n3;
printf("Enter numbers:\n");
scanf("%d%d%d",&n1,&n2,&n3);
if (n1>n2 && n1>n3)
printf("%d is greater number",n1);
else
{
if (n2>n3)
printf("%d is greater number",n2);
else
printf("%d is greater number",n3);
}
}
```

## **Dangling Else problem**

if

if

Statements

else

statements

## **Iterative/looping**

If we want to execute a group of statements multiple times then we should go for iterative statements.

C has three types of iterative statements

for loop

while loop

do while loop

### **for loop**

#### **Syntax**

for(initialization;condition;updation)

{

Statements

}

/\* Wap to print Hello C world 10 times

```
#include<stdio.h>
#include<conio.h>
void main()
{
    int i;
    for (i=0;i<=10;i++)
    {
        printf("I am Your c instructor\n");
    }
    getch();
}
```

```
#include<stdio.h>
#include<conio.h>
void main()
{
    int i;
    for (i=1;i<=100;i++)
    {
        printf("%d\n",i);
    }
    getch();
}
```

```
}
```

```
/* Wap to print 100 to 1
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
    int i;
```

```
    for (i=100;i>1;i--)
```

```
    {
```

```
        printf("%d\t",i);
```

```
    }
```

```
getch();
```

```
}
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```



```
{  
    int i;  
    for (i=100;i>1;i-=2)  
    {  
        printf("%d\t",i);  
    }  
    getch();  
}
```

**/\* W.A.P to input a number and print their table**

```
#include<stdio.h>  
#include<conio.h>  
void main()  
{  
    int n,i;  
    printf("Enter a numbers:\n");  
    scanf("%d",&n);  
    printf("Table of %d is\n",n);  
    for (i=1;i<=10;i++)  
    {  
        printf("%d\n",n*i);  
    }
```

```
}  
}
```

```
/* W.A.P to input a number a print its factorial
```

```
#include<stdio.h>  
#include<conio.h>  
void main()  
{  
int n,fact=1,i;  
printf("Enter a numbers:\n");  
scanf("%d",&n);  
printf("Fatorial of %d is\n",n);  
for (i=n;i>=1;i--)  
{  
    fact=i*fact;  
  
}  
printf("%d",fact);  
}
```

```
/* Fibonacci Series
```

```
#include <stdio.h>  
int main()  
{  
    int i, n, x = 0, y = 1, z;  
  
    printf("Enter the number of terms: ");  
    scanf("%d", &n);
```

```

printf("Fibonacci Series: ");

for (i = 1; i <= n; ++i)
{
    printf("%d, ", x);
    z = x + y;
    x = y;
    y = z;
}
return 0;
}

```

## **while loop**

if we want to execute a group of statements iteratively until some condition false, then we should use while loop

### **syntax**

```

while (condition)
    statement

```

/\* Wap to print Hello C world 10 times

```

#include<stdio.h>
#include<conio.h>
void main()
{
    int i=0;
    while (i<=10)
    {
        printf("Your name\n");
    }
}

```

```
        i++ ;  
    }  
    getch();  
}
```

# W.A.P. to print 100 to 1 by using while loop.

**/\* W.A.P to input a number and print their table**

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n,i;
```

```
printf("Enter a numbers:\n");
```

```
scanf("%d",&n);
```

```
printf("Table of %d is\n",n);
```

```
i=1;
```

```
while (i<=10)
```

```
{
```

```
    printf("%d\n",n*i);
```

```
    i++;
```

```
}
```

```
}
```

```
/* W.A.P to input a number a print its factorial
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n,fact=1;
```

```
printf("Enter a numbers:\n");
```

```
scanf("%d",&n);
```

```
printf("Fatorial of %d is\n",n);
```

```
while (n>=1)
```

```
{
```

```
    fact=n*fact;
```

```
    n--;
```

```
}
```

```
printf("%d",fact);
```

```
}
```

```
/* Wap to input a number & print their digit sum
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
int n,tot=0,rem;
printf("Enter number:");
scanf("%d",&n);
while (n>0)
{
rem=n%10;
tot=tot+rem;
n=n/10;
}
printf("The sum=%d",tot);
}
```

### **do while loop**

#### **syntax**

```
do
{
    statement
}
while (condition);
```

### **# Nested Loop**

## Pattern printing

```
/*  
#  
# #  
# # #  
# # # #  
# # # # #  
*/  
  
#include<stdio.h>  
#include<conio.h>  
  
void main()  
{  
    int n,i,j;  
    printf("Enter number of rows:");  
    scanf("%d",&n);  
    for(i=1;i<=n;i++)  
    {  
        for (j=1;j<=i;j++)  
        {  
            printf("#");  
        }  
    }
```

```
printf("\n");
```

```
}
```

```
}
```

```
/*
```

```
1
```

```
1 2
```

```
1 2 3
```

```
1 2 3 4
```

```
1 2 3 4 5
```

```
*/
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n,i,j;
```

```
printf("Enter number of rows:");
```

```
scanf("%d",&n);
```

```
for(i=1;i<=n;i++)
```

```
{
```

```
    for (j=1;j<=i;j++)
```

```
    {
```



```
        printf("%d ",j);  
    }  
    printf("\n");  
}  
}
```

```
/*  
1  
2 2  
3 3 3  
4 4 4 4  
5 5 5 5 5  
*/
```

```
#include<stdio.h>  
#include<conio.h>  
void main()  
{  
    int n,i,j;  
    printf("Enter number of rows:");  
    scanf("%d",&n);  
    for(i=1;i<=n;i++)
```

```
{  
    for (j=1;j<=i;j++)  
    {  
        printf("%d ",i);  
    }  
    printf("\n");  
}  
}
```

```
/*
```

```
1
```

```
2 3
```

```
4 5 6
```

```
7 8 9 10
```

```
11 12 13 14 15
```

```
*/
```

```
#include<stdio.h>
```

```
#include<conio.h>
```

```
void main()
```

```
{
```

```
int n,i,j,a=1;
```

```
printf("Enter number of rows:");
```

```
scanf("%d",&n);
for(i=1;i<=n;i++)
{
    for (j=1;j<=i;j++)
    {
        printf("%d ",a);
        a++;
    }
    printf("\n");
}
}
```

## **Transfer Statements**

break

continue

goto

/\* Wap to print number is even or odd

```
#include<stdio.h>
#include<conio.h>
void main()
{
int n;
printf("Enter a number:");
scanf("%d",&n);
if (n%2==0)
goto even;
else
goto odd;
even:
printf("%d is even number",n);
odd:
printf("%d is odd number",n);
}
```

## Switch

Switch is a multi-way conditional control statements which helps us to make choice among a number of alternative.

The syntax of switch statements is

```
switch (expression)
```

```
{  
case constant1:  
    statements  
case constant2:  
    statements  
case constant3:  
    statements  
default:  
    statements  
}
```

```
#include <stdio.h>
```

```
int main() {
```

```
    char operator;
```

```
    float firstNumber,secondNumber;
```

```
    printf("Enter an operator (+, -, *, /): ");
```

```
    scanf("%c", &operator);
```

```
printf("Enter two operands: ");  
scanf("%f %f",&firstNumber, &secondNumber);  
  
switch(operator)  
{  
    case '+':  
        printf("%f ", firstNumber+secondNumber);  
        break;  
  
    case '-':  
        printf("%f", firstNumber-secondNumber);  
        break;  
  
    case '*':  
        printf("%f", firstNumber*secondNumber);  
        break;  
  
    case '/':  
        printf("%f", firstNumber-secondNumber);  
        break;  
    default:  
        printf("Error! operator is not correct");
```

```
}  
}
```

## **Functions**

If a group of statements is repeatedly required then it is not recommended to write these statements everytime seperately. We have to define these statements as a single

unit and we can call that unit any number of times based on our requirement without rewriting.

This unit is nothing but function.

The main advantage of functions is code Reusability.

function is a group of statements.

it's the smallest part of the program.

It is not automatically executed.

There are two types of function in C

1. predefine
2. user defined function

### 1. Predefine:

The functions which are coming along with C software automatically, are called pre-defined functions



Eg:

printf()

scanf()

sizeof()

pow()

etc..

## 2. User Defined Functions:

The functions which are developed by programmer explicitly according to business requirements ,are called user defined functions.

1. Function definition
2. Function declaration
3. Function call

## How to create Function in C

### Syntax

```
Return_type func_name(parameter)
{
    Statements;
    return statements
}
```

### Parameter

Parameters are input to the functions. It is also called arguments.

Explain formal/dummy & Actual Parameter .

### Return Statement

```
#include<stdio.h>
#include<conio.h>
int sum(int a,int b);
void main()
{
int n1,n2,n3;
printf("Enter numbers:");
scanf("%d,%d",&n1,&n2);
n3=sum(n1,n2);
printf("The sum=%d",n3);
}
int sum(int a,int b)
{
    int c;
    c=a+b;
return c;
}
```

```
#include<stdio.h>
#include<conio.h>
void even_odd(int a); /* declaration
void main()
```

```
{  
int n;  
printf("Enter a number:");  
scanf("%d",&n);  
even_odd(n);  
}
```

```
void even_odd(int a)
```

```
{  
if (a%2==0){
```

```
printf("%d even\n",a);
```

```
}
```

```
else{
```

```
printf("%dis odd\n",a);
```

```
}
```

```
}
```

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
int row;
```

```
    printf("Enter number of rows");
    scanf("%d",&row);
    pattern(row);
}
void pattern(int r)
{
    int i,j;
    for (i=1;i<=r;i++)
    {
        for(j=1;j<=i;j++)
        {
            printf("$ ");
        }
        printf("\n");
    }
}
```

Types of function basis on parameter

main()

# Arrays

1 d array declaration & initialization

```
data_type array_name[size];
```

```
ie. int age[100];
```

```
float sal[15];
```

```
char nm[30];
```

```
int lakshya[5]={1,2,3,4,5 }
```

# WAP input values into array & print them

```
#include <stdio.h>
```

```
void main()
```

```
{
```

```
int i =0,arr[5];
```

```
printf("\nEnter elements : \n");
```

```
for(i=0; i<5; i++)
```

```
{  
    printf("Enter arr[%d] : ",i);  
    scanf("%d",&arr[i]);  
}  
printf("\nElements are : ");  
  
for(i=0; i<5; i++)  
{  
    printf("%d ",arr[i]);  
}  
printf("\n");  
}
```

# WAP to find even & odd number from given array

```
void main()  
{  
    int i =0,arr[5],even=0,odd=0;  
  
    printf("\nEnter elements : \n");
```

```

for(i=0; i<5; i++)
{
    printf("Enter arr[%d] : ",i);
    scanf("%d",&arr[i]);
}
for(i=0; i<5; i++)
{
    if (arr[i]%2==0)
        even++;
    else
        odd++;
}

printf("\neven number=%d and odd number=%d:
",even,odd);

printf("\n");
}

```

# Wap to input two 1-d arrays & add them

```
#include <stdio.h>
```



```
void main()
{
    int i =0,a1[5],a2[5],c[5];

    printf("\nEnter first array elements : \n");

    for(i=0; i<5; i++)
    {
        printf("Enter a1[%d] : ",i);
        scanf("%d",&a1[i]);
    }

    printf("\nEnter second array elements : \n");

    for(i=0; i<5; i++)
    {
        printf("Enter a2[%d] : ",i);
        scanf("%d",&a2[i]);
    }

    for(i=0; i<5; i++)
```

```
{
    c[i]=a1[i]+a2[i];
}
printf("\nThe sum of Elements are : ");
for(i=0; i<5; i++)
{
    printf("%d ",c[i]);
}

printf("\n");
}
```

# traverse of array in backward direction

```
void main()
```

```
{
```

```
int i ,j,arr[5],temp;
```

```
printf("\nEnter elements : \n");
```

```
for(i=0; i<5; i++)
```

```
{
```

```
    printf("Enter arr[%d] : ",i);
```

```
    scanf("%d",&arr[i]);
```

```
}
```

```
for(i=0,j=4; i<j; i++,j--)
```

```
{
```

```
    temp=arr[i];
```

```
    arr[i]=arr[j];
```

```
    arr[j]=temp;
```

```
}
```

```
printf("\nAfter Traversing of an array ");
```

```
for(i=0; i<5; i++)
```

```
{
```

```
    printf("%d ",arr[i]);
```

```
}
```

```
printf("\n");  
}
```

Passing 1-d array into a function

# WAP to find even and odd number from array

```
#include <stdio.h>  
  
void readArray(int arr[], int size)  
{  
    int i =0;  
  
    printf("\nEnter elements : \n");  
  
    for(i=0; i<size; i++)  
    {  
        printf("Enter arr[%d] : ",i);
```

```
        scanf("%d",&arr[i]);
    }
}

void printArray(int arr[],int size)
{
    int i =0;

    printf("\nElements are : ");

    for(i=0; i<size; i++)
    {
        printf("\n\tarr[%d] : %d",i,arr[i]);
    }
    printf("\n");
}

int main()
{
    int arr[10];

    readArray(arr,10);
    printArray(arr,10);
}
```

```
    return 0;  
}
```

2 d array declaration & initialization

```
data_type array_name[row_size][col_size];
```

```
ie. int age[3][3]={1,2,3},  
                {4,5,6},  
                {7,8,9}}
```

# Wap to input 2-d array & print all elements

```
#include <stdio.h>
```

```
void main()
{
    int i ,j,arr[3][3];

    printf("\nEnter elements : \n");

    for(i=0; i<3; i++)
    {
        for(j=0; j<3; j++)
        {
            scanf("%d",&arr[i][j]);
        }
    }
    printf("\nElements are : \n");

    for(i=0; i<3; i++)
    {
        for(j=0; j<3; j++)
        {
            printf("%d ",arr[i][j]);
        }
        printf("\n");
    }
}
```

```
}
```

```
}
```

# WAP to input two 2-d array nd Add them

```
#include <stdio.h>
```

```
void main()
```

```
{
```

```
    int i ,j,a[3][3],b[3][3],c[3][3];
```

```
    printf("\nEnter First Array elements : \n");
```

```
    for(i=0; i<3; i++)
```

```
    {
```

```
        for(j=0; j<3; j++)
```

```
        {
```

```
            scanf("%d",&a[i][j]);
```

```
        }
```

```
    }
```

```
    printf("\nEnter Second Array elements : \n");
```



```
for(i=0; i<3; i++)
{
    for(j=0; j<3; j++)
    {
        scanf("%d",&b[i][j]);
    }
}
for(i=0; i<3; i++)
{
    for(j=0; j<3; j++)
    {
        c[i][j]=a[i][j]+b[i][j];
    }
}
printf("\nArray Elements sum : \n");
```

```
for(i=0; i<3; i++)
{
    for(j=0; j<3; j++)
    {
        printf("%d ",c[i][j]);
    }
}
```

```
        printf("\n");
    }

}
```

## Pointer

**Pointers in C** language is a variable that stores/points the address of another variable. A **Pointer in C** is used to allocate memory dynamically i.e. at run time

Find the address of variable

```
#include<stdio.h>
#include<conio.h>
void main()
{
    int n1=10;
    float n2=10.5;
    printf("Address of n1=%p\n",&n1);
    printf("Address of n2=%p",&n2);
}
```

## Declaration of pointer

```
data_type *pname;
```

## Dereference of a pointer variable

```
#include<stdio.h>
#include<conio.h>
void main()
{
    int n1=10;
    float n2=10.5;
    int *p1=&n1;
    float *p2=&n2;
    printf("Value of p1= address of n1=%p\n",p1);
    printf("Value of p2= address of n2=%p\n",p2);
    printf("address of p1=%p\n",p1);
    printf("address of p2=%p\n",p2);
    printf("Value of n1=%d\n",*(&n1));
    printf("Value of n2=%f\n",*(&n2));
}
```

```
#include <stdio.h>
```

```
void swap(int *x, int *y);
```

```
int main () {
```

```
    int a = 100;
```

```
    int b = 200;
```

```
    printf("Before swap, value of a : %d\n", a );
```

```
    printf("Before swap, value of b : %d\n", b );
```

```
    swap(&a, &b);
```

```
    printf("After swap, value of a : %d\n", a );
```

```
    printf("After swap, value of b : %d\n", b );
```

```
    return 0;
```

```
}
```

```
void swap(int *x, int *y) {
```

```
    int temp;
```

```
    temp = *x;
```

```
    *x = *y;
```

```
*y = temp;  
  
}
```

## Strings

```
#include <stdio.h>  
  
int main()  
{  
    char array[100];  
  
    printf("Enter a string\n");  
    scanf("%s", array);  
  
    printf("Your string: %s\n", array);  
    return 0;  
}  
  
#include <stdio.h>
```

```

int main()
{
    char z[100];

    printf("Enter a string\n");
    gets(z);

    printf("The string: %s\n", z);
    return 0;
}

```

Function	Work of Function
<a href="#">strlen()</a>	Calculates the length of string
<a href="#">strcpy()</a>	Copies a string to another string
<a href="#">strcat()</a>	Concatenates(joins) two strings
<a href="#">strcmp()</a>	Compares two string
<a href="#">strlwr()</a>	Converts string to lowercase
<a href="#">strupr()</a>	Converts string to uppercase

WAP to find the length of a string

```
#include <stdio.h>
```

```
#include <string.h>
```

```
int main()
```

```
{
```

```
    char a[100];
```

```
    int length;
```

```
    printf("Enter a string to calculate it's length\n");
```

```
    gets(a);
```

```
    length = strlen(a);
```

```
    printf("Length of the string = %d\n", length);
```

```
    return 0;
```

```
}
```

```
strcmp() return 0
```

```
#include <stdio.h>
```

```
#include <string.h>
```

```
int main()
```

```
{
```

```
    char a[100], b[100];
```

```
    printf("Enter a string\n");
```

```
    gets(a);
```

```
    printf("Enter a string\n");
```

```
    gets(b);
```

```
    if (strcmp(a,b) == 0)
```

```
        printf("The strings are equal.\n");
```

```
    else
```

```
        printf("The strings are not equal.\n");
```

```
    return 0;
```

```
}
```

**strcpy()**



```
#include <stdio.h>
#include <string.h>
```

```
int main()
{
    char str1[10]= "awesome";
    char str2[10];
    char str3[10];

    strcpy(str2, str1);
    strcpy(str3, "well");
    puts(str2);
    puts(str3);

    return 0;
}
```

## **strcat() function**

```
#include <stdio.h>
#include <string.h>
int main()
```

```
{  
    char str1[100] = "This is ", str2[100] = "C Programming";  
  
    strcat(str1,str2);  
  
    puts(str1);  
    puts(str2);  
  
    return 0;  
}
```