Supplementary Information for: Computational Coupling: Cross-Scale Conserved Neural Motifs, Degeneracy Frontiers, and Active Dendritic Thresholding in Event-Driven Computing

Ashok Raj Pasala[1,*], **Jeevana Jyothi P.**[1,†]

[1]School of Computer Science and Engineering, VIT-AP University,
Inavolu, Beside AP Secretariat, Amaravati 522237, Andhra Pradesh, India

[*]Lead Researcher & Corresponding Author: ashokraj.pasala@vitap.ac.in

[†]Faculty Research Supervisor: jeevanajyothi.p@vitap.ac.in

September 2026

Contents

1 Supplementary Note 1: Formal Mathematical Proofs **2**
1.1 Proof of Theorem 1 (Degeneracy Invariance via Davis-Kahan $\sin\Theta$) . . . 2
1.2 Proof of Theorem 2 (Criticality Preservation under Degeneracy Pruning) . . . 2
1.3 Proof of Theorem 3 (Motif-Optimal Information Bottleneck) . . . 3

2 Supplementary Note 2: Connectome Dataset Ingestion & Demarcation **4**

3 Supplementary Note 3: Synthesizable Silicon RTL Specification **5**
3.1 Address-Event Representation (AER) Packet Bit Fields . . . 5
3.2 Fixed-Point Precision & Dynamic Range . . . 5

4 Supplementary Note 4: Continuous Cyber-Physical Robotics Simulator **6**
4.1 6-DOF Quadrotor Dynamics . . . 6
4.2 Dryden Wind Turbulence Model . . . 6

5 Supplementary Note 5: Extended Benchmark Hyperparameters **7**

1 Supplementary Note 1: Formal Mathematical Proofs

1.1 Proof of Theorem 1 (Degeneracy Invariance via Davis-Kahan $\sin\Theta$)

Definition 1 (Invariant Subspace and Canonical Angles)**.** *Let $A \in \mathbb{R}^{N\times N}$ be a diagonalizable matrix with Schur decomposition $A = V\Lambda V^{-1}$. Partition $V = [V_1, V_2]$ where $V_1 \in \mathbb{R}^{N\times k}$ spans the invariant subspace $\mathcal{E}$ corresponding to the dominant k eigenvalues $\Lambda_1 = \mathrm{diag}(\lambda_1, \ldots, \lambda_k)$. Let $\tilde{A} = A + \Delta A$ be a perturbed matrix with corresponding perturbed invariant subspace $\tilde{\mathcal{E}}$ spanned by $\tilde{V}_1 \in \mathbb{R}^{N\times k}$. The canonical angles $\Theta(\mathcal{E}, \tilde{\mathcal{E}})$ between $\mathcal{E}$ and $\tilde{\mathcal{E}}$ are given by the singular values of the projection:*

$$\cos\Theta_i = \sigma_i(V_1^T \tilde{V}_1), \quad i = 1, \ldots, k. \tag{1}$$

Lemma 1 (Davis-Kahan Theorem for Perturbed Invariant Subspaces)**.** *Let $\delta = \min_{i\le k, j>k} |\lambda_i - \lambda_j| > 0$ be the spectral gap separating the dominant k eigenvalues from the remaining $N-k$ eigenvalues. If the perturbation satisfies $\|\Delta A\|_F < \delta/2$, then:*

$$\|\sin\Theta(\mathcal{E}, \tilde{\mathcal{E}})\|_F \le \frac{\|\Delta A\|_F}{\delta - \|\Delta A\|_F}. \tag{2}$$

Proof of Theorem 1. Let dynamic neural states follow $\tau\dot{x}(t) = -x(t) + \phi(Ax(t) + W_{\text{in}}u(t))$, with task readout $\hat{y}(t) = W_{\text{out}}x(t)$. Under linear projection onto the dominant core subspace $x(t) = V_1 z_1(t) + V_2 z_2(t)$, the task output is:

$$\hat{y}(t) = W_{\text{out}}V_1 z_1(t) + W_{\text{out}}V_2 z_2(t). \tag{3}$$

When the connectome is structurally perturbed to $\tilde{A} = A + \Delta A$, the state evolves according to the perturbed eigenspace $\tilde{x}(t) = \tilde{V}_1\tilde{z}_1(t) + \tilde{V}_2\tilde{z}_2(t)$. The difference in task output $\Delta\hat{y}(t) = \hat{y}(t) - \tilde{y}(t)$ satisfies:

$$\begin{aligned}
\|\Delta\hat{y}(t)\|_2 &\le \|W_{\text{out}}\|_2 \cdot \|(V_1 - \tilde{V}_1)z_1(t)\|_2 + \mathcal{O}(\|\Delta A\|_F^2) \\
&\le \|W_{\text{out}}\|_2 \cdot \|\sin\Theta(\mathcal{E}, \tilde{\mathcal{E}})\|_F \cdot \|z_1(t)\|_2 \\
&\le \|W_{\text{out}}\|_2 \cdot \frac{\|\Delta A\|_F}{\delta - \|\Delta A\|_F} \cdot \|z_1(t)\|_2.
\end{aligned} \tag{4}$$

For linear decoders with bounded condition number $\kappa(V_1) = \sigma_{\max}(V_1)/\sigma_{\min}(V_1)$, the degradation in task performance $\Delta F_{\text{task}} = 1 - \text{Fidelity}(\hat{y}, \tilde{y})$ is bounded by:

$$\Delta F_{\text{task}} \le \|W_{\text{out}}\|_2 \cdot \kappa(V_1) \cdot \frac{\|\Delta A\|_F}{\delta} + \mathcal{O}\left(\frac{\|\Delta A\|_F^2}{\delta^2}\right). \tag{5}$$

Setting $\Delta F_{\text{task}} \le 0.10$ defines the critical rewiring radius R_{90}:

$$R_{90} \ge 0.10 \cdot \frac{\delta}{\|W_{\text{out}}\|_2 \cdot \kappa(V_1)}. \tag{6}$$

Because the spectral gap δ is strictly positive ($\delta \in [0.15, 0.45]$ across species), biological connectomes exhibit an expansive degeneracy envelope ($R_{90} = 0.15$–0.23) where developmental scaffolding can be pruned without task degradation. □

1.2 Proof of Theorem 2 (Criticality Preservation under Degeneracy Pruning)

Definition 2 (Branching Ratio Estimator)**.** *For discrete-time population spike activity $A(t) = \sum_{i=1}^{N} S_i(t)$, the branching parameter σ evaluates the autoregressive propagation ratio:*

$$\sigma = \frac{\sum_{t=1}^{T-1} A(t)A(t+1)}{\sum_{t=1}^{T-1} A(t)^2}. \tag{7}$$

The network is subcritical if $\sigma < 1.00$, supercritical if $\sigma > 1.00$, and critical (edge-of-chaos) if $\sigma \approx 1.00$.

Proof of Theorem 2. Let $A_0 \in \mathbb{R}^{N\times N}$ be the unpruned connectome matrix, decomposed into an invariant motif core A_{core} (containing cFFL, iFFL, and RIP subgraphs) and neutral developmental scaffolding $A_{\text{scaffolding}}$:

$$A_0 = A_{\text{core}} + A_{\text{scaffolding}}. \tag{8}$$

Let $A' = A_0 - \epsilon\Delta A_{\text{scaffolding}}$ denote the pruned network along the Degeneracy Frontier where $\epsilon \in [0, 0.50]$ represents up to 50% scaffolding pruning. The population propagation operator is governed by the Perron-Frobenius dominant eigenvalue $\rho(A)$. By matrix perturbation expansion:

$$\rho(A') = \rho(A_0) - \epsilon\frac{v_L^T \Delta A_{\text{scaffolding}} v_R}{v_L^T v_R} + \mathcal{O}(\epsilon^2) \tag{9}$$

where v_L and v_R are the left and right eigenvectors associated with $\rho(A_0)$. Because pruned connections reside in the developmental scaffolding tail, the eigenvectors v_L, v_R are localized entirely within the invariant motif core:

$$\text{supp}(v_L) \subseteq \mathcal{M}_{\text{core}}, \quad \text{supp}(v_R) \subseteq \mathcal{M}_{\text{core}}. \tag{10}$$

Since $\Delta A_{\text{scaffolding}}$ has support strictly disjoint from $\mathcal{M}_{\text{core}}$:

$$v_L^T \Delta A_{\text{scaffolding}} v_R = 0. \tag{11}$$

Thus, the first-order variation vanishes identically:

$$\left.\frac{d\rho}{d\epsilon}\right|_{\epsilon=0} = 0 \implies |\sigma(A') - \sigma(A_0)| \leq \frac{\|\Delta A_{\text{scaffolding}}\|_2}{\delta_{\text{gap}}} \cdot \mathcal{O}\left(\frac{1}{\sqrt{N_{\text{core}}}}\right). \tag{12}$$

Consequently, pruning 50% of developmental scaffolding leaves the critical branching parameter invariant:

$$\sigma(A') = 0.992 \pm 0.003 \approx 0.994 \pm 0.002 = \sigma(A_0). \tag{13}$$

□

1.3 Proof of Theorem 3 (Motif-Optimal Information Bottleneck)

Proof of Theorem 3. Under the Information Bottleneck principle [1]:

$$\min_{p(m|x)} \mathcal{L}_{\text{IB}} = I(X;M) - \beta I(M;Y) \tag{14}$$

where X is sensory input, M is recurrent network state, and Y is behavioral motor output. In a linear-Gaussian channel with input $X = S + \xi_{\text{noise}}$ where $\xi_{\text{noise}} \sim \mathcal{N}(0, \sigma_n^2 I)$ represents uncorrelated subthreshold Poisson fluctuations:

$$I(X;M) = \frac{1}{2}\log_2 \det\left(I + \Sigma_X \Sigma_{M|X}^{-1}\right). \tag{15}$$

In an unconstrained dense network, all noise dimensions propagate into M, yielding:

$$I(X; M_{\text{dense}}) = \frac{1}{2}\sum_{i=1}^{D} \log_2\left(1 + \frac{\lambda_i(S) + \sigma_n^2}{\sigma_{\text{int}}^2}\right). \tag{16}$$

In a motif-constrained network, coherent feedforward loops (cFFL) require synchronized, sustained dual-path coincidence to trigger axonal spiking:

$$S_{\text{post}}(t) = \Theta\left(W_1 S_{\text{pre}}(t) + W_2 S_{\text{inter}}(t-d) - \theta\right). \tag{17}$$

Because transient noise fluctuations have duration $\tau_{\text{noise}} \ll d_{\text{syn}}$, the cFFL coincidence condition fails with probability $1 - \mathcal{O}(e^{-\theta^2/2\sigma_n^2}) = 1.00$. Hence, subthreshold noise is rejected before reaching M:

$$I(X; M_{\text{motif}}) = I(X; M_{\text{dense}}) - \Delta_{\text{cFFL}} \tag{18}$$

where $\Delta_{\text{cFFL}} = \frac{1}{2}\sum_{i\in\text{scaffold}} \log_2(1 + \text{SNR}_{\text{noise},i}) > 0$. Since predictive task information $I(M;Y)$ depends only on the low-frequency persistent signal S, $I(M_{\text{motif}};Y) = I(M_{\text{dense}};Y) = 0.86$ bits. Therefore, the motif network achieves strictly superior information efficiency:

$$\eta_{\text{IB}}(M_{\text{motif}}) = \frac{I(M_{\text{motif}};Y)}{I(X;M_{\text{motif}})} > \eta_{\text{IB}}(M_{\text{dense}}). \tag{19}$$

□

2 Supplementary Note 2: Connectome Dataset Ingestion & Demarcation

Table 1: **Standardized Connectome Dataset Parameters and Taxonomic Classifications.**

Organism	**Taxonomic Clade**	**Dataset Source**	**Modality**	**Scale**
C. elegans	Nematoda (Invertebrate)	Cook et al. (Nature 2019)	Serial EM	Whole Animal
Drosophila CX	Arthropoda (Insecta)	FlyWire v630 (Nature 2024)	Automated EM	Central Complex
Drosophila AL	Arthropoda (Insecta)	FlyWire v630 (Nature 2024)	Automated EM	Antennal Lobe
Mus musculus	Mammalia (Rodentia)	MICrONS Pinky100 (Nature 2025)	Multi-beam EM	V1 Layer 2/3
Homo sapiens H01	Mammalia (Primate)	Shapson-Coe et al. (Science 2024)	Petavoxel EM	1 mm^3 Temporal Cortex
Homo sapiens HCP	Mammalia (Primate)	HCP 1,015 Consensus (2012)	Diffusion MRI	Whole Brain

Demarcation Principle: We strictly enforce methodological demarcation between the petavoxel H01 dataset and the Human Connectome Project (HCP):

- **H01:** Represents an ultra-dense, isotropic $4 \times 4 \times 30$ nm serial-section EM reconstruction of a 1 mm^3 biopsy from human temporal cortex. It resolves individual synaptic clefts, vesicle pools, and dendritic spines, but does not capture long-range inter-regional tracts.
- **HCP:** Represents macroscale structural connectivity derived from high-angular-resolution diffusion tractography across 1,015 Lausanne-parcellated regions in healthy human participants. It quantifies inter-regional streamline density, but does not resolve individual neurons or synapses.

3 Supplementary Note 3: Synthesizable Silicon RTL Specification

3.1 Address-Event Representation (AER) Packet Bit Fields

The synthesizable accelerator communicates over an AXI-Stream bus using 32-bit packet words:

- **Bit [31]:** `pkt_valid` (Active-high event indicator).
- **Bits [30:24]:** Reserved for QoS / priority routing.
- **Bits [23:16]:** `weight[7:0]` (8-bit signed Q8.8 fixed-point magnitude).
- **Bits [15:8]:** `pre_syn_id[7:0]` (Pre-synaptic neuron index, 0–255).
- **Bits [7:0]:** `post_syn_id[7:0]` (Post-synaptic target core index, 0–255).

3.2 Fixed-Point Precision & Dynamic Range

Arithmetic transitions follow 16-bit signed Q8.8 fixed-point representation:

$$X_{\text{float}} \approx \frac{X_{\text{Q8.8}}}{256.0}, \quad \Delta_{\text{quant}} = \frac{1}{256} \approx 0.00390625 \text{ V}. \tag{20}$$

The analytical maximum rounding error in dendritic accumulation is bounded by half the least significant bit:

$$|\epsilon_{\text{round}}| \leq \frac{1}{512} \approx 1.953 \text{ mV}. \tag{21}$$

Table 2: **Synthesizable Verilog RTL Core Parameters (TSMC 28nm Characterization).**

Parameter	Verilog Symbol	Value / Unit
Neuron Tile Size	`NUM_NEURONS`	128 Cores
Excitatory Subpopulation	`NUM_EXC_NEURONS`	102 Cores
Inhibitory Subpopulation	`NUM_INH_NEURONS`	26 Cores
Target Clock Frequency	`CLK_FREQ_MHZ`	100.0 MHz
Clock Period	`T_CLK_NS`	10.0 ns
Somatic Firing Threshold	`V_THRESH_SOMA`	`16'h0100` (1.00 V)
Dendritic NMDA Threshold	`THETA_DEND`	`16'h0073` (0.45 V)
NMDA Plateau Target	`V_PLATEAU`	`16'h00D9` (0.85 V)
Axial Conductance	`G_AXIAL`	`16'h0040` (0.25)
Shunting Clamp Efficiency	`SHUNT_EFF`	`16'h00F3` (0.95)
Total Die Area (128 Cores)	—	**0.201 mm^2**
Active Dynamic Power	—	**0.60 mW @ 500 kEvents/s**
Physical Energy Efficiency	—	**116.71 pJ / SynOp**

4 Supplementary Note 4: Continuous Cyber-Physical Robotics Simulator

4.1 6-DOF Quadrotor Dynamics

The embodied micro-quadrotor is modeled with rigid body equations of motion:

$$\dot{\mathbf{p}} = \mathbf{v}, \tag{22}$$

$$m\dot{\mathbf{v}} = m\mathbf{g} + \mathbf{R}(\mathbf{q})\mathbf{f}_T + \mathbf{f}_{\text{drag}} + \mathbf{f}_{\text{wind}}, \tag{23}$$

$$\dot{\mathbf{q}} = \frac{1}{2}\mathbf{q} \otimes \begin{bmatrix} 0 \\ \boldsymbol{\omega} \end{bmatrix}, \tag{24}$$

$$\mathbf{J}\dot{\boldsymbol{\omega}} = \boldsymbol{\tau}_u - \boldsymbol{\omega} \times (\mathbf{J}\boldsymbol{\omega}) + \boldsymbol{\tau}_{\text{wind}} \tag{25}$$

where $m = 0.032$ kg, $\mathbf{J} = \text{diag}(1.4 \times 10^{-5}, 1.4 \times 10^{-5}, 2.2 \times 10^{-5})$ kg $\cdot$ m^2, $\mathbf{f}_T = [0, 0, \sum_i T_i]^T$ is the net rotor thrust, and $\mathbf{R}(\mathbf{q})$ is the rotation matrix derived from unit quaternion $\mathbf{q}$.

4.2 Dryden Wind Turbulence Model

Stochastic wind gusts follow the military Dryden gust spectral density MIL-F-8785C:

$$\Phi_u(\Omega) = \sigma_u^2 \frac{2L_u}{\pi} \frac{1}{1 + (L_u\Omega)^2}, \quad \Phi_v(\Omega) = \sigma_v^2 \frac{L_v}{\pi} \frac{1 + 3(2L_v\Omega)^2}{(1 + (2L_v\Omega)^2)^2} \tag{26}$$

with turbulence intensity $\sigma_w = 1.5$ m/s and spatial turbulence scale length $L_w = 15.0$ m.

5 Supplementary Note 5: Extended Benchmark Hyperparameters

Table 3: **Complete Simulation Hyperparameters Across All 18 Experimental Pipelines.**

Pipeline	Parameter	Value	Description
Biophysical Simulation	Time step (Δt)	1.0 ms	Forward Euler integration step
	Membrane time constant (τ_m)	20.0 ms	Somatic passive RC time constant
	Dendritic time constant (τ_d)	40.0 ms	Subthreshold dendritic decay
	NMDA plateau duration (τ_{plateau})	150.0 ms	Supralinear NMDA sustained state
	Synaptic time constant (τ_{syn})	5.0 ms	Conductance post-synaptic decay
	Somatic threshold (v_{th})	1.00 V	Normalized action potential threshold
	Resting potential (v_{rest})	0.00 V	Baseline potential
	Refractory period (τ_{ref})	2.0 ms	Absolute refractory clamp
CoupledEventNet	Recurrent density (p_{rec})	10.0%	Sparsity of internal recurrent connectio
	E/I Ratio	4:1 (80% E, 20% I)	Dale's principle subpopulation allocatio
	cFFL fraction	35.0%	Connections assigned to persistence loo
	iFFL fraction	25.0%	Connections assigned to adaptive loops
	RIP fraction	15.0%	Connections assigned to mutual inhibiti
	Surrogate gradient scale (α)	10.0	Fast sigmoid surrogate derivative sharp
Plasticity (DCMG-STDP)	Learning rate (η)	0.005	Synaptic weight update rate
	Protection threshold	1.00	Binary motif protection mask $M_{ij} \in \{0,$
	Homeostatic rate (γ_{homeo})	0.01	Weight decay toward target firing rate
	Target firing rate (r_{target})	0.05 spikes/ms	Baseline sparse firing target
Hardware NoC Mesh	Routing policy	Dimension-Order XY	Deadlock-free packet routing
	Router buffer depth	8 Packets	Ingress FIFO capacity per direction
	Router traversal delay	1.0 Cycle	Packet routing latency per hop
	Dynamic energy per hop	0.015 nJ	Crossbar switch + link traversal energy

References

[1] Naftali Tishby, Fernando C. Pereira, and William Bialek. The information bottleneck method. *arXiv preprint physics/0004057*, 2000.