MARK SCHEME · TEACHER COPY

11BR · Topic 5: System Software

Cambridge AS Level Computer Science 9618

Paper 1 Theory Fundamentals

Total marks: 74

Official Cambridge mark scheme extracts for each question in the matching exam paper, with question numbers changed to match the exam. Source of each question is shown above its rows.

For teacher / admin use only. Do not give to students before they have attempted the paper.

Mark scheme extracts © Cambridge University Press & Assessment.

Question 1 · May/June 2023 Paper 12, original Q5 (d) [7 marks]

Question	Answer	Marks
1(a)(i)	**1 mark** each to **max 5** • Manages the scheduling of processes // decides which order to run processes • Manages which resources the processes require • … such as allocating memory • Enables processes to share data • Prevents interference between processes // resolution of conflicts • Handles the process queue • It allows multi-tasking / multi-processing • ... by ensuring fair access, handling priorities **and** handling interrupts	**5**
1(a)(ii)	**1 mark** each to **max 2** • To help users to set-up / configure / analyse / optimise / maintain the computer ... • ... by for example, making memory allocation more efficient • ... by for example, checking the system for faults	**2**

Question 2 · May/June 2023 Paper 12, original Q7 (a),(b),(c) [13 marks]

Question	Answer	Marks
2(a)(i)	**1 mark** each to max 2 • Set of pre-written / pre-compiled / pre-tested subroutines • ... which can be **called** in other programs • ... by **installing/importing** the library	**2**

2(a)(ii)	**1 mark** for each bullet point. Mark in pairs; **1 mark** for a benefit and **1 mark** for an appropriate expansion • (main) memory requirements for program is reduced • ... as dynamic link library is loaded only once / when required • the executable file size of the program using the DLL will be smaller • ... because the executable does not contain (all) the library routines • maintenance not needed to be done by the programmer • ... because the DLL is separate from program • no need to **recompile** the main program when changes are made to DLL • ... because changes / improvements/ error correction to the DLL file code are done independently of the main program • A single DLL file can be made available to several application programs • ... Saving space in memory / easing the pressure on memory	**4**

2(b)	No mark for choice. **1 mark** each to **max 3** for justification Interpreter • Allows the developer to make real-time changes • … so the program can be debugged **at each stage** • ... the effect of any changes made by the developer can be seen immediately • The developer can test when incomplete • … so small parts can be tested without having to test the rest of the program • … if one section does not work others can still be tested • To avoid dependent errors Compiler • The developer can debug multiple errors simultaneously • Produces an executable file • … so that the developer can test the program multiple times without recompiling	**3**

2(c)	**1 mark** each Breakpoints: • **Stop the code** at a specific line to check the current progress / values Dynamic syntax checks: • Highlight / underline / colour syntax errors **as the code is entered** Context-sensitive prompts: • Suggest the code to add // automatically complete statements Single stepping: • Run the code **one line at a time** so the values can be checked	**4**

Question 3 · May/June 2024 Paper 12, original Q6 [4 marks]

Question	Answer	Marks

3	**1 mark** each to **max 4** **Max 3** marks for each management task: *Memory management:* **Max 3 marks** • Stores data from all currently running programs concurrently in RAM • Stops the data from overwriting each other in RAM/primary storage • Decides which processes should be in main memory • Makes efficient use of memory *Process management:* **Max 3 marks** • Allows one process to be paused whilst another process can be actioned • Decides which process is to be run next • Switches between processes to allow them to share the use of the processor • Identification/description of scheduling	**4**

Question 4 · May/June 2024 Paper 12, original Q8 (a),(b),(c) [10 marks]

Question	Answer	Marks
4(a)	**1 mark** each to **max 2**: • Creates an executable file • … so the code can be tested multiple times without having to recompile • … so **repeated testing** takes less time	**2**
4(b)	**1 mark** for identification of each feature and **1 mark** for matching description: e.g. *For coding:*	**6**

IDE feature	Description
Context-sensitive prompts	**Gives suggestions** for code as the user types instead of having to write/remember the code
Auto-correct	Corrects spelling mistakes so that user has fewer errors to correct

For presentation:

IDE feature	Description
Pretty-printing	Colour code keywords so the user can identify any errors
Expand/collapse (code) blocks	The user can hide code that they are not currently working on

For debugging:

IDE feature	Description
Single stepping	Run the code **one line at a time** // shows the effect of each line of code
Breakpoints	Stop the code running at a set point to check the flow/variable contents

4(c)	**1 mark** each to **max 2**: • Saves programming/testing time as code does not have to be written/re-written from scratch // code does not have to be tested • Code is already tested so it is more robust/likely to work • The programmer does not need to maintain the library // library routines are updated automatically • Can perform complex calculations that the programmer may be unable to do • Makes code more easily readable	**2**

Question 5 · May/June 2026 Paper 12, original Q7 (a),(b) [13 marks]

Question	Answer	Marks	Guidance
5(a)(i)	**1 mark** for each correct point to **max 2** • Efficient allocation of resources to processes • Moving processes between states • Allocating time slices to processes • Scheduling processes // An example of a scheduling algorithm • Resolution of conflicts when two processes require the same resource • Allows communication between processes	**2**	Do not accept allows multi-programming – that is a benefit not a task resource management is NE Accept checking priorities as scheduling Take care that answers do not refer to tasks done by the kernel or by memory management.
5(a)(ii)	**1 mark** for each correct point to **max 2** • Dynamically allocates RAM to processes • Frees up memory when the process closes • Makes sure two processes do not access the same memory • Accesses data from RAM when needed	**2**	Accept software or applications for processes in first mark point Take care that answers do not refer to tasks done by process management or by file management

5(a)(iii)	**1 mark** for each correct point to **max 3** • With continued use **files** can be split and stored in different locations on the disk so time is spent by the disk head moving between locations to access all parts of file • Defragmentation software moves split **files** into contiguous blocks // defragmentation software collects all the free space into a • contiguous block • … which means that the disk head does not need to move as much to access the next part of the file // … which means that the disk head does not need to move as much when writing a file • After defragmentation data **access/read/write** takes less time, so performance is improved	**3**	Note: The question asks how defragmentation improves computer performance. So just a description of the process is NE
5(b)(i)	**1 mark** for each correct point to **max 4,** mark in pairs • (Single) Stepping • …the student runs one line of code at a time **and** looks at the output/results/flow before moving to run the next line • Breakpoints • …These are inserted in the code to stop the code at a specific point **so that** the student can check the flow/values / test sub-sections of the code • (Variable) Watch window • …the student can view how/when the variables change during execution	**4**	Take care that the answer says how the student **uses** the tools and doesn't just describe each tool Award a maximum of two marks for names of debugging tools with no further suitable explanation Just check for errors is not enough for an explanation, that is what debugging means
5(b)(ii)	**1 mark** for each correct point to **max 2** • Partially compiled programs can be used on different platforms as they are interpreted when run • The code is optimised for the CPU as machine code is generated at run time • It is more efficient to run as the source code does not need recompiling	**2**	Note: Candidate responses need to answer the question why?

Question 6 · May/June 2026 Paper 13, original Q5 (a),(b),(c) [10 marks]

Question	Answer	Marks	Guidance
6	Examiners must use the **full range of marks** defined in the mark scheme, unless limited by the quality of the candidate responses seen.		

6(a)(i)	**1 mark** each to max 2 e.g. • Transfer data between peripheral devices • Translate data from I/O/peripheral devices • Loading and installation of device drivers • Hardware abstraction — hiding hardware differences from applications • Power management — sleep states, CPU throttling, battery control	**2**	
6(a)(ii)	**1 mark** each to max 2 e.g. • Memory management • Process management • File management • Security management // managing user accounts • Provide platform for running applications	**2**	
6(b)(i)	**1 mark** for: • Perform housekeeping/maintenance tasks // improving/optimising overall performance	**1**	
6(b)(ii)	**1 mark** each to **max 2** e.g. • Prepared a disk for future use by // initialising • …changing/setting file system // by example // directory structure // allocation tables • … naming the disk (volume label) • … creating a boot sector • …erasing all data • …creating partitions	**2**	
6(c)(i)	**1 mark** for: • Set of pre-written / pre-compiled / pre-tested routines	**1**	

6(c)(ii)	**1 mark** for benefit **1 for expansion** e.g. • Maintenance not needed to be done by the programmer • ... because the DLL is separate from program // maintained by library creator • The calling program does not need recompilation by the programmer when a DLL file changes • ... because the DLL file can be updated independently of the calling program • … updates will apply to all programs that use the DLL file • (Executable) file is smaller • ... because it does not contain (all) the library routines // code only linked at execution • (Main) memory requirements for program is reduced • … because the DLL files are only loaded into memory when required • ... one DLL file can be used by several running programs	**2**	

Question 7 · Oct/Nov 2023 Paper 13, original Q5 (a),(b) [9 marks]

Question	Answer	Marks
7(a)	**1 mark** for each bullet point (**max 2** for each feature). Context-sensitive prompts: • As the code is being written • …the options to complete the statement are shown Single stepping: • allows the programmer to execute the program one line at a time • …so that the effects of each statement can be seen	**4**

7(b)(i)	**1 mark** for each bullet point (**max 2**). • To reduce the time it takes to download the program files from the web server // to upload them to the server in the first place • To reduce the amount of storage space used on the web server // user's device	**2**
7(b)(ii)	**1 mark** for each bullet point (**max 3**). • Disk needs to be prepared for initial use • Disk needs to be checked for errors • A new file system needs to be generated on the disk • The file allocation table needs to be set up	**3**

Question 8 · Oct/Nov 2025 Paper 13, original Q8 (a),(b),(d) [8 marks]

Question	Answer	Marks
8(a)	**1 mark** per bullet point, **max 2** • Large amounts of source code take time to compile • It can be slower to produce the object code than an interpreter • The code must be recompiled when it is changed • The program cannot run if there are errors • It is not possible to correct errors in real-time • One error can cause false reporting of multiple further errors • Sections of code / unfinished code cannot easily be tested	**2**

8(b)	**1 mark** per bullet point, **max 3** marks • Programming time is saved as code does not have to written from scratch • Testing time is saved as code is already tested / documented • A library routine is more likely to work, as code is already tested • Library routines automatically update if they are changed / improved • The programmer can use library routines to perform complex functions / procedures that they may not be able to write themselves	**3**
8(c)	**1 mark** for each bullet point, **max 3** marks • File management • Security management • Hardware / peripheral management // input / output management • Process management	**3**