

PIZZA SALES SQL QUERIES

A. KPI's

1. Total Revenue:

```
SELECT SUM(total_price) AS Total_Revenue FROM pizza_sales;
```

Results		Messages
	Total_Revenue	
1	817860.05083847	

2. Average Order Value

```
SELECT (SUM(total_price) / COUNT(DISTINCT order_id)) AS Avg_order_Value  
FROM pizza_sales
```

Results		Messages
	Avg_order_Value	
1	38.3072623343546	

3. Total Pizzas Sold

```
SELECT SUM(quantity) AS Total_pizza_sold FROM pizza_sales
```

Results		Messages
	Total_pizza_sold	
1	49574	

4. Total Orders

```
SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales
```

Results		Messages
	Total_Orders	
1	21350	

5. Average Pizzas Per Order

```
SELECT CAST(CAST(SUM(quantity) AS DECIMAL(10,2)) /  
CAST(COUNT(DISTINCT order_id) AS DECIMAL(10,2)) AS DECIMAL(10,2))  
AS Avg_Pizzas_per_order  
FROM pizza_sales
```

Pizza sales Project

By Ashraf Ahmad Khan

Results		Messages	
	Avg_Pizzas_per_order		
1	2.32		

B. Hourly Trend for Total Pizzas Sold

```
SELECT DATEPART(HOUR, order_time) as order_hours, SUM(quantity) as  
total_pizzas_sold  
from pizza_sales  
group by DATEPART(HOUR, order_time)  
order by DATEPART(HOUR, order_time)
```

Output

	order_hours	total_pizzas_sold
1	9	4
2	10	18
3	11	2728
4	12	6776
5	13	6413
6	14	3613
7	15	3216
8	16	4239
9	17	5211
10	18	5417
11	19	4406
12	20	3534
13	21	2545
14	22	1386
15	23	68

Pizza sales Project

By Ashraf Ahmad Khan

C. Weekly Trend for Orders

```
SELECT
    DATEPART(ISO_WEEK, order_date) AS WeekNumber,
    YEAR(order_date) AS Year,
    COUNT(DISTINCT order_id) AS Total_orders
FROM
    pizza_sales
GROUP BY
    DATEPART(ISO_WEEK, order_date),
    YEAR(order_date)
ORDER BY
    Year, WeekNumber;
```

Pizza sales Project

By Ashraf Ahmad Khan

	WeekNumber	Year	Total_orders
1	1	2015	254
2	2	2015	427
3	3	2015	400
4	4	2015	415
5	5	2015	436
6	6	2015	422
7	7	2015	423
8	8	2015	393
9	9	2015	409
10	10	2015	420
11	11	2015	404
12	12	2015	416
13	13	2015	427
14	14	2015	433
15	15	2015	408
16	16	2015	414
17	17	2015	437
18	18	2015	423
19	19	2015	399
20	20	2015	458
21	21	2015	414
22	22	2015	390
23	23	2015	423
24	24	2015	418
25	25	2015	410
26	26	2015	416
27	27	2015	474

28	28	2015	417
29	29	2015	420
30	30	2015	433
31	31	2015	419
32	32	2015	426
33	33	2015	435
34	34	2015	407
35	35	2015	394
36	36	2015	397
37	37	2015	435
38	38	2015	423
39	39	2015	288
40	40	2015	433
41	41	2015	334
42	42	2015	386
43	43	2015	352
44	44	2015	371
45	45	2015	394
46	46	2015	400
47	47	2015	392
48	48	2015	491
49	49	2015	424
50	50	2015	417
51	51	2015	430
52	52	2015	298
53	53	2015	171

D. % of Sales by Pizza Category

```
SELECT pizza_category, CAST(SUM(total_price) AS DECIMAL(10,2)) as  
total_revenue,  
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales)  
AS DECIMAL(10,2)) AS PCT  
FROM pizza_sales  
GROUP BY pizza_category
```

Output

Pizza sales Project

By Ashraf Ahmad Khan

Results		Messages	
	pizza_category	total_revenue	PCT
1	Classic	220053.10	26.91
2	Chicken	195919.50	23.96
3	Veggie	193690.45	23.68
4	Supreme	208197.00	25.46

E. % of Sales by Pizza Size

```
SELECT pizza_size, CAST(SUM(total_price) AS DECIMAL(10,2)) as  
total_revenue,  
CAST(SUM(total_price) * 100 / (SELECT SUM(total_price) from pizza_sales)  
AS DECIMAL(10,2)) AS PCT  
FROM pizza_sales  
GROUP BY pizza_size  
ORDER BY pizza_size
```

Output

Results		Messages	
	pizza_size	total_revenue	PCT
1	L	375318.70	45.89
2	M	249382.25	30.49
3	S	178076.50	21.77
4	XL	14076.00	1.72
5	XXL	1006.60	0.12

F. Total Pizzas Sold by Pizza Category

```
SELECT pizza_category, SUM(quantity) as Total_Quantity_Sold  
FROM pizza_sales  
WHERE MONTH(order_date) = 2  
GROUP BY pizza_category  
ORDER BY Total_Quantity_Sold DESC
```

Output

Pizza sales Project

By Ashraf Ahmad Khan

Results Messages		
	pizza_category	Total_Quantity_Sold
1	Classic	14888
2	Supreme	11987
3	Veggie	11649
4	Chicken	11050

G. Top 5 Pizzas by Revenue

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue DESC
```

Results Messages		
	pizza_name	Total_Revenue
1	The Thai Chicken Pizza	43434.25
2	The Barbecue Chicken Pizza	42768
3	The California Chicken Pizza	41409.5
4	The Classic Deluxe Pizza	38180.5
5	The Spicy Italian Pizza	34831.25

H. Bottom 5 Pizzas by Revenue

```
SELECT Top 5 pizza_name, SUM(total_price) AS Total_Revenue
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Revenue ASC
```

	pizza_name	Total_Revenue
1	The Brie Carre Pizza	11588.4998130798
2	The Green Garden Pizza	13955.75
3	The Spinach Supreme Pizza	15277.75
4	The Mediterranean Pizza	15360.5
5	The Spinach Pesto Pizza	15596

I. Top 5 Pizzas by Quantity

```
SELECT Top 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold DESC
```

Pizza sales Project

By Ashraf Ahmad Khan

Output

	pizza_name	Total_Pizza_Sold
1	The Classic Deluxe Pizza	2453
2	The Barbecue Chicken Pizza	2432
3	The Hawaiian Pizza	2422
4	The Pepperoni Pizza	2418
5	The Thai Chicken Pizza	2371

J. Bottom 5 Pizzas by Quantity

```
SELECT TOP 5 pizza_name, SUM(quantity) AS Total_Pizza_Sold
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Pizza_Sold ASC
```

Output

	pizza_name	Total_Pizza_Sold
1	The Brie Carre Pizza	490
2	The Mediterranean Pizza	934
3	The Calabrese Pizza	937
4	The Spinach Supreme Pizza	950
5	The Soppressata Pizza	961

K. Top 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
```

Pizza sales Project

By Ashraf Ahmad Khan

```
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders DESC
```

Results Messages		
	pizza_name	Total_Orders
1	The Classic Deluxe Pizza	2329
2	The Hawaiian Pizza	2280
3	The Pepperoni Pizza	2278
4	The Barbecue Chicken Pizza	2273
5	The Thai Chicken Pizza	2225

L. Borrom 5 Pizzas by Total Orders

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```

	pizza_name	Total_Orders
1	The Brie Carre Pizza	480
2	The Mediterranean Pizza	912
3	The Spinach Supreme Pizza	918
4	The Calabrese Pizza	918
5	The Chicken Pesto Pizza	938

NOTE

If you want to apply the pizza_category or pizza_size filters to the above queries you can use WHERE clause. Follow some of below examples

```
SELECT Top 5 pizza_name, COUNT(DISTINCT order_id) AS Total_Orders
FROM pizza_sales
WHERE pizza_category = 'Classic'
GROUP BY pizza_name
ORDER BY Total_Orders ASC
```