

Jeeran Network — Use Cases & Test Plan

Full application test scenarios: preconditions, inputs, and expected outputs

Generated: 2026-07-20, from a complete read of the codebase (routes, business logic, database schema).

Environment: Pre-launch — the Supabase project in use will be wiped before go-live.

Not yet configured in this environment: Stripe billing (no secret key), SMTP email, Apple Wallet certificates. Those use cases document the intended happy path for later, and confirm the app fails *cleanly* (a clear error, not a crash) in their absence today.

EXECUTABLE can be
tested right now

BLOCKED needs a credential
not yet configured

DOCUMENTED scenario specified, needs real
3rd-party integration to run

A. Authentication & Onboarding

A1 — Sign up new business owner **EXECUTABLE**

PRECONDITIONS

Fresh email not already registered.

INPUT

Signup form: `email`, `password` (≥ 6 chars).

EXPECTED OUTPUT

Account created. If email confirmation is required, shows confirmation notice; otherwise redirects to `/dashboard` → `/dashboard/onboarding` (no business yet).

A2 — Sign up with an already-registered email **EXECUTABLE**

INPUT

Same email as an existing account.

EXPECTED OUTPUT

Inline error, no new account created.

A3 — Sign up with a short password **EXECUTABLE**

INPUT

Password under 6 characters.

EXPECTED OUTPUT

Client-side validation blocks submission.

A4 — Login with correct credentials EXECUTABLE

INPUT

Registered email + correct password.

EXPECTED OUTPUT

Redirects to `?redirect=` target or `/dashboard` .

A5 — Login with wrong password EXECUTABLE

EXPECTED OUTPUT

Inline error, no session created.

A6 — Login with unregistered email EXECUTABLE

EXPECTED OUTPUT

Generic invalid-credentials message (doesn't reveal whether the email exists).

A7 — Access /dashboard while unauthenticated EXECUTABLE

EXPECTED OUTPUT

Redirect to `/login` .

A8 — Sign out EXECUTABLE

EXPECTED OUTPUT

Session cleared; subsequent `/dashboard` visit redirects to login.

A9 — Complete onboarding (happy path) EXECUTABLE

INPUT

`POST /api/onboarding` — `{ fullName, businessName, category, latitude, longitude }` , all valid.

EXPECTED OUTPUT

`200 { success: true }` . Business created with a 3-month trial (`is_subscription_active=true` , `trial_ends_at = now()+3mo`). Redirects to `/dashboard/owner` .

A10 — Onboarding with missing required fields EXECUTABLE

EXPECTED OUTPUT

`400` with a field-specific error message; no rows written.

A11 — Onboarding when a business already exists for this owner EXECUTABLE

EXPECTED OUTPUT

`500` — unique constraint violation (one business per owner, DB-enforced). Not pre-checked client-side.

A12 — /dashboard routing logic

EXECUTABLE

EXPECTED OUTPUT

No business → onboarding. Business exists → owner dashboard.

B. Owner Dashboard

B1 — Owner dashboard metrics render

EXECUTABLE

EXPECTED OUTPUT

Business name/category, subscription banner (conditional), 3 metric tiles (credits, scans hosted, customers acquired).

B2 — QR PNG generation

EXECUTABLE

INPUT

GET /api/qr/{business_id}

EXPECTED OUTPUT

200 , PNG encoding the scan URL.

B3 — QR PDF generation

EXECUTABLE

INPUT

GET /api/qr/{business_id}/pdf

EXPECTED OUTPUT

200 , print-ready card with logo, shop name (Arabic-shaped if applicable), QR code. Nonexistent business → 404 .

B4 — Subscription banner visibility

EXECUTABLE

EXPECTED OUTPUT

Inactive subscription or zero credits → banner shows. Active + credits > 0 → hidden.

C. Campaign Management

C1 — Create campaign (happy path)

EXECUTABLE

INPUT

POST /api/campaigns — { title, description?, bid_per_view: 2..10 } .

EXPECTED OUTPUT

200 , campaign created active. Triggers geo-push notification (best-effort).

C2 — Create campaign with out-of-range bid

EXECUTABLE

INPUT

`bid_per_view` = 1 or 11.

EXPECTED OUTPUT

`400` .**C3 — Second campaign while one is active**

EXECUTABLE

EXPECTED OUTPUT

`409` — one active campaign per creator, DB-enforced.**C4 — Reactivate a campaign while another is active**

EXECUTABLE

EXPECTED OUTPUT

`409` .**C5 — Deactivate a campaign**

EXECUTABLE

EXPECTED OUTPUT

`200` . No geo-push triggered on deactivation.**C6 — Missing title on create**

EXECUTABLE

EXPECTED OUTPUT

`400` .**C7 — Unauthenticated campaign requests**

EXECUTABLE

EXPECTED OUTPUT

`401` .**C8 — PATCH a campaign not owned by the caller**

EXECUTABLE

EXPECTED OUTPUT

`404` (RLS-filtered, treated as not-found).

D. Matchmaking / Scan Page (customer-facing, anonymous)

D1 — Scan a business with eligible ads

EXECUTABLE

EXPECTED OUTPUT

Up to 3 ad cards, ranked by bid descending, then randomized tiebreak.

D2 — Scan a business with no eligible ads EXECUTABLE

EXPECTED OUTPUT

"No offers nearby right now — check back later."

D3 — Scan a non-existent business_id EXECUTABLE

EXPECTED OUTPUT

404 .

D4 — Host's own campaign excluded from its own scan page EXECUTABLE

EXPECTED OUTPUT

Never shown on the creating business's own scan page.

D5 — Same-category business excluded EXECUTABLE

EXPECTED OUTPUT

Excluded from same-category businesses' pages; still shown to different categories.

D6 — Technician campaign excluded from linked business EXECUTABLE

EXPECTED OUTPUT

Excluded only from the specifically linked business's page.

D7 — Insufficient-credit creator excluded EXECUTABLE

EXPECTED OUTPUT

Excluded when `credits <= bid_per_view` (strict boundary).

D8 — Inactive-subscription creator excluded EXECUTABLE

EXPECTED OUTPUT

Excluded regardless of credit balance.

D9 — Inactive campaign excluded EXECUTABLE

EXPECTED OUTPUT

Never appears.

E. Wallet — Legacy One-off Passes

E1 — Apple Wallet one-off generate BLOCKED

EXPECTED OUTPUT TODAY

501 — no signer certificate configured.

E2 — Google Wallet one-off generate EXECUTABLE

EXPECTED OUTPUT

200 { saveUrl, claimToken } .

E3 — Wallet callback records the ad-credit claim EXECUTABLE

EXPECTED OUTPUT

200 , credits move from creator to host by bid_per_view .

F. Wallet — Membership Pass (geo-push, new)

F1 — First-time device creates a membership pass EXECUTABLE

EXPECTED OUTPUT

200 { alreadyMember: false, saveUrl } . New member row, Google Wallet object created, device cookie set.

F2 — Returning device reuses the existing pass EXECUTABLE

EXPECTED OUTPUT

200 { alreadyMember: true, saveUrl } , no duplicate row.

F3 — No geolocation, business has coordinates EXECUTABLE

EXPECTED OUTPUT

Falls back to the business's own coordinates.

F4 — No geolocation, business has no coordinates EXECUTABLE

EXPECTED OUTPUT

400 .

F5 — Missing/invalid businessId EXECUTABLE

EXPECTED OUTPUT

400 (missing) / 404 (nonexistent).

F6/F7 — Google Wallet save/delete callback

DOCUMENTED

NOTE

Requires a genuinely Google-signed JWT — verifiable only against real Google Wallet app events.

F8 — Geo-push on campaign activation

EXECUTABLE

EXPECTED OUTPUT

Nearby members within push radius get their pass PATCHed; `offer_notifications` logged.

F9 — nearby_active_offers is platform-wide, not origin-scoped

EXECUTABLE

EXPECTED OUTPUT

Offers from businesses other than the member's recruiting shop still appear.

G. Redemption

G1 — Legacy /validate: successful redemption

EXECUTABLE

EXPECTED OUTPUT

`200`, marks redeemed.

G2 — Legacy /validate: already redeemed

EXECUTABLE

EXPECTED OUTPUT

`409`.

G3 — Legacy /validate: tampered hash

EXECUTABLE

EXPECTED OUTPUT

`400` signature failure.

G4 — Legacy /validate: wrong business redeeming

EXECUTABLE

EXPECTED OUTPUT

`403`.

G5 — New /api/redeem: successful redemption

EXECUTABLE

EXPECTED OUTPUT

`200`, credits move from redeeming business to member's origin business.

G6 — New /api/redeem: invalid barcode

EXECUTABLE

EXPECTED OUTPUT

`400 .`**G7 — New /api/redeem: no active offer for scanning business**

EXECUTABLE

EXPECTED OUTPUT

`404 .`**G8 — New /api/redeem: already redeemed**

EXECUTABLE

EXPECTED OUTPUT

`409 .`**G9 — New /api/redeem: self-recruited redemption**

EXECUTABLE

EXPECTED OUTPUT

Redemption succeeds; credit transfer is a no-op.

G10 — New /api/redeem: unauthenticated

EXECUTABLE

EXPECTED OUTPUT

`401 .`

H. Dashboard / Admin Analytics

H1 — /api/dashboard/redemptions happy path

EXECUTABLE

EXPECTED OUTPUT

`200 { summary, series, conversion } .`**H2 — /api/dashboard/redemptions unauthenticated**

EXECUTABLE

EXPECTED OUTPUT

`401 .`**H3 — /api/admin/redemptions — always unauthorized**

EXECUTABLE

EXPECTED OUTPUT

`401` regardless of caller — no admin auth exists yet (documented gap).

H4 — /admin page renders with no authentication EXECUTABLE

EXPECTED OUTPUT

Full shop list visible to anyone with the URL (documented gap).

I. Billing (Stripe)

I1 — Checkout unauthenticated EXECUTABLE

EXPECTED OUTPUT

401 .

I2 — Checkout with unknown price_id EXECUTABLE

EXPECTED OUTPUT

400 .

I3 — Checkout with no business account EXECUTABLE

EXPECTED OUTPUT

404 .

I4 — Checkout, valid request, Stripe not configured BLOCKED

EXPECTED OUTPUT TODAY

501 .

I5 — Checkout happy path DOCUMENTED

INPUT (ONCE CONFIGURED)

POST /api/billing/checkout with a real catalog price_id .

EXPECTED OUTPUT

200 { url } — real Stripe Checkout session. Test card 4242 4242 4242 4242 completes and grants credits via webhook.

I6 — Webhook missing signature DOCUMENTED

NOTE

Currently collapses into I7 (not-configured check runs first).

I7 — Webhook, Stripe not configured BLOCKED

EXPECTED OUTPUT TODAY

501 .

I8 — Webhook happy path

DOCUMENTED

INPUT

Real `checkout.session.completed` event (Stripe CLI or test-mode purchase).

EXPECTED OUTPUT

Credits granted once; a replayed webhook event does not double-grant (deduped on `stripe_event_id`).

I9 — Billing page ledger rendering

EXECUTABLE

EXPECTED OUTPUT

Credits (green) and usage debits (grey) merged, sorted newest-first.

J. Trial Lifecycle

J1 — New business gets a 3-month trial

EXECUTABLE

EXPECTED OUTPUT

Confirmed via A9.

J2 — Cron endpoint auth check

EXECUTABLE

EXPECTED OUTPUT

`401` on wrong/missing Bearer token.

J3 — Cron endpoint, correct token, nothing due

EXECUTABLE

EXPECTED OUTPUT

`200 { warned: 0, expired: N } .`

J4 — Cron endpoint, a shop is due, email not configured

BLOCKED

EXPECTED OUTPUT TODAY

`501` .

J5 — Cron happy path

DOCUMENTED

INPUT (ONCE SMTP CONFIGURED)

A business due within 7 days, not yet notified.

EXPECTED OUTPUT

Owner receives the trial-ending email; won't re-send on next run.

J6 — Expired trial auto-deactivates EXECUTABLE

EXPECTED OUTPUT

`is_subscription_active` flips to `false` once `trial_ends_at` has passed with no paid subscription.

Summary counts

Area	Executable	Blocked	Documented-only
Auth / Onboarding	12	0	0
Owner Dashboard	4	0	0
Campaigns	8	0	0
Matchmaking / Scan	9	0	0
Wallet (legacy)	2	1 (Apple)	0
Wallet (membership)	7	0	2 (Google-signed callback)
Redemption	10	0	0
Dashboard / Admin	4	0	0
Billing	6	2	2
Trial lifecycle	4	1	1