James Alexander

in close collaboration with
Isaac Starkman, Juan Estadella, and Fadi Mazboudi

Astrologers' Workbench

User Manual

In honor of Alexander Marr,
and deeply indebted to Isaac Starkman…

Birthtime rectification, predictive techniques
and chart comparison.

james-alexander.de

36 different modules with practical instructions and reference pages.

Portable reference edition | 26 October 2026
Version 2.0.1 | User Manual and Quick Reference

About this edition

The Launcher, User Manual and Quick Reference cover the same 36 modules in portable version 2.0.1.

CATEGORY ACTIVATION TIMELINE

The new module shows event-category scores through time as a heatmap and a focused graph. Its inspector lists the contacts behind a sample. It sits beside House Activation Timeline in the Launcher, with its own alphabetical entry in both guides.

MODULE VERSIONS

CategoryActivationTimeline.html is the attached CategoryActivationTimeline(1).html without changes. The other 35 HTML modules are unchanged from version 2.0.0, including the separately supplied DualTest update.

TWO GUIDES IN THE LAUNCHER

User Manual provides workflows and method notes. Quick Reference provides an alphabetical illustrated overview. Both PDF guides are bundled locally and open from dedicated buttons in the left panel.

READING THE RESULTS

Settings, scoring and time keys can differ among modules. Use each tool’s controls and method notes. Category Activation Timeline uses category-specific point scores or systems agreeing; House Activation Timeline uses house-based measures.

PORTABLE USE

Extract the complete ZIP into a new folder. Calculations and guides are local; optional city lookups and external links require internet access. Save work inside each module before closing.

Alphabetical module index

Select a module name to open its reference page.

01	Age Harmonics AgeHarmonics.html	7
02	Age Harmonics Hitlist AgeHarmonicsHitlist.html	8
03	Age Harmonics Live AgeHarmonicsLive.html	9
04	Age Harmonics Research AgeHarmonics_Research.html	10
05	Ascensional Transit Hit List AscensionalTransitsHitlist.html	11
06	Ascensional Transits AscensionalTransits.html	12
07	Ascensional Transits LIVE AscensionalTransits_LIVE.html	13
08	Aspect Overlap Finder OverlapFinder.html	14
09	Astrological Event Convergence Scanner AstroConvergenceScanner.html	15
10	Category Activation Timeline CategoryActivationTimeline.html	16
11	Central Scrutinizer CentralScrutinizer.html	17
12	Cusp Category Graph CuspCategoryGraph.html	18
13	Epoch Chart Finder EpochFinder.html	19
14	Fixed Star Parans FixedStarParans.html	20
15	House Activation Timeline HouseActivationTimeline.html	21
16	Lunar Angles LunarAngles.html	22
17	Midpoint Lab MidpointLab.html	23
18	Polaris2 Polaris2.html	24

Alphabetical module index

Select a module name to open its reference page.

19	PSSR Aspects PSSR_Aspects.html	25
20	PSSR Sieve PSSR_Sieve.html	26
21	Radix and Epoch Aspect Studio DualTest.html	27
22	Solar Contacts SRA.html	28
23	Studio Hitlists StudioHitlist.html	29
24	The New Partner Horoscope NewPartnerHoroscope.html	30
25	The Sieve TheSieve.html	31
26	Timeline Timeline.html	32
27	Topocentric Birthtime Convergence Matrix TBCM.html	33
28	Topocentric Exact Contact Navigator TPD_ContactNavigator.html	34
29	Topocentric Primary Directions TopocentricPrimaryDirections.html	35
30	Topocentric Primary Directions: Radix and Epoch TopocentricPrimaryDirections2.html	36
31	TPD Anchor Mapper TPD_AnchorMapper.html	37
32	TPD Bi-Wheel TPD_BiWheel.html	38
33	TPD Event Meters TPD_Event_Meters.html	39
34	TPD Event Timeline TPD_Event_Timeline.html	40
35	TPD Pair Timeline TPD_Pair_Timeline.html	41
36	TPD Three Birth Times TPD_3xCompare.html	42

Before using the modules

TIME AND PLACE

Check each module’s longitude convention. Explicit N/S and E/W letters are preferable where accepted. A city lookup supplies coordinates; check the historical UTC offset separately. Use local mean time only when the record uses it.

EVENT TIMES

A database event may supply only a date. Central Scrutinizer uses noon UTC for date-only events where a timed instant is needed. Primary directions retain their calendar-date key. Other systems use their documented time keys and ephemeris limits.

DIFFERENT VIEWS

A single-date list shows contacts within orb. A hitlist searches exact contacts over a range. A rectifier compares birthtimes. House Activation Timeline samples activity through time; Overlap Finder intersects chosen in-orb intervals. These outputs serve different purposes.

PRE-BIRTH EVENTS

Central Scrutinizer can show pre-birth TPD, progressions, arcs and transits using signed elapsed time. Its AH and PSSR panels are not applied before birth. Other tools have their own date rules and coverage.

SAVING YOUR WORK

Save or export before closing. Central Scrutinizer’s Save to database stores personal cases in this browser; Backup creates a transferable .awbdb copy. Save .awb stores an individual case. Tools otherwise keep their own data and settings.

GUIDES AND OFFLINE USE

User Manual and Quick Reference are available from the Launcher’s left panel. Calculations and PDF guides are local. Optional online city searches and external links need internet. Each module can also be opened directly from _internal/modules.

Using the Launcher

START THE PORTABLE PACKAGE

Quit the previous Launcher using ? > Quit launcher. Extract AstrologersWorkbench2.0.1.zip into a new folder and run AstrologersWorkbench.exe inside AstrologersWorkbench2.0.1. Keep the complete folder together, including _internal.

FIND AND COMPARE

The sidebar and tiles list all 36 modules. Ctrl K searches tools. Category Activation Timeline is beside House Activation Timeline under Inspect an event. Compare places two running modules beside one another.

USER MANUAL AND QUICK REFERENCE

The two PDF buttons in the left panel open their bundled guides in a new browser tab. Both guides cover the complete 36-module inventory. Their alphabetical entries and bookmarks include Category Activation Timeline.

FAVORITES

The default order is Polaris2, Central Scrutinizer, PSSR Aspects and Timeline. Older Studio Favorites migrate to Central Scrutinizer in their original place. Other saved Favorites are retained where their tools remain included.

WORKSPACE AND SAVES

Focus hides the left panel. The divider and tool zoom help fit wide results; F11 toggles full screen. New copy opens an independent instance. Switching tabs keeps running state; closing can lose unsaved work. Save inside each module first.

SHARING

Distribute the complete portable ZIP. Each colleague should extract a full copy. Click the logo for the project story, and use ? > Quit launcher before starting another package version.

01 Age Harmonics

AgeHarmonics.html

Age Harmonics calculates the internal aspects of an age-harmonic chart for one event. Each natal tropical longitude is multiplied by the exact fractional age and reduced modulo 360°. The resulting planets, Nodes, angles and all twelve Topocentric cusps are compared with one another. This is an internal harmonic comparison, rather than harmonic positions compared with natal targets.

USE THE MODULE

01 Enter the birth date, local time to seconds, historical UTC offset and birthplace coordinates. Select local mean time only for a record that actually uses that convention. The optional city search fills coordinates; saved cities can be reused offline. Longitude is west positive.

02 Choose Mean or True Node. Use Check natal positions to confirm the natal chart before examining harmonic results. The small time-adjustment buttons let you test changes of one or ten seconds.

03 Enter the event date, local event time and its own UTC offset. Noon is the initial event-time default. Keep Days per age year at 365.2422 unless deliberately comparing another year convention.

04 Set the maximum orb in degrees and arcminutes. The initial setting is 20′ for all nine supported aspects. Choose an event category, then click Calculate age harmonic aspects.

05 Read the contact list in order of absolute orb. Both endpoints of every aspect are harmonic positions. Consult the harmonic-position table to see each transformed longitude beside its natal value.

06 Category highlighting marks contacts receiving at least 4 points from the adapted table. Show only highlighted aspects reduces the display to those contacts. The displayed total sums highlighted contacts once each. Export CSV or print when you need a record.

RESULT VIEW

Calculated harmonic aspects with an event category selected, plus the harmonic-position table. Both ends of every contact belong to the harmonic chart.

READING THE RESULTS

In this version, cusp weights follow the individual house meaning. The 3rd can receive sibling-event weight without passing that weight to the harmonic 9th; the same distinction applies to the 8th/2nd and 5th/11th. ASC and MC retain their general event weights, while DSC and IC do not automatically inherit them. Every cusp is multiplied independently, so natal opposition between cusps does not guarantee harmonic opposition at a fractional age. The imported primary-direction weights are being used as an event-relevance reference for harmonics.

02 Age Harmonics Hitlist

AgeHarmonicsHitlist.html

Age Harmonics Hitlist searches a date range for exact internal age-harmonic contacts and lists them chronologically. Each natal planet, Node and cusp is multiplied by the exact fractional age. Category highlighting applies the adapted Isaac weighting table.

USE THE MODULE

01 Open Age Harmonics Hitlist in the Launcher's Age Harmonics group. Enter birth date and time to seconds, coordinates and the historical UTC offset. City lookup supplies coordinates; select local mean time only for a record using that time basis.

02 Use Check natal positions to confirm the chart. Choose Mean or True Node under the additional settings. Load James's example supplies a worked example.

03 Set the date range and the fixed UTC offset used for list dates. Keep Days per age year at 365.2422 unless deliberately comparing another convention.

04 The supplied defaults are conjunctions/oppositions only, 1°22′ orb and a 16-point highlight threshold. Select an event category, then click Generate chronological hit-list. Broader aspect sets and factor-pair filters are available.

05 Highlighted contacts appear by default. Use Show all aspects to reveal the rest. Each entry gives the exact contact time, fractional age, harmonic positions and In orb entry-to-exit dates. Orb-window times show hours and minutes.

06 Use Export all as text, Export highlighted as text or Print to keep the results. The highlighted export follows the category and point threshold.

RESULT VIEW

A populated chronological hitlist showing exact dates, Isaac points, and the entry-to-exit orb window for at least one contact.

READING THE RESULTS

Each harmonic cusp and each Node is independent. A sextile to the harmonic 3rd is not substituted for a trine to the harmonic 9th. The Ascendant/Descendant and North/South Nodes are not assumed to remain opposite in Age Harmonics. Imported category weights are used here as an event-relevance reference.

03 Age Harmonics Live

AgeHarmonicsLive.html

Display an age-harmonic chart that follows the computer clock, or inspect a fixed date and time.

USE THE MODULE

01 Click Birth data and enter the local birth date and time, historical UTC offset or local mean time, latitude and west-positive longitude.

02 Choose Mean or True Node and the days-per-age-year convention, then click Show live chart. James's example provides a starting chart.

03 Use Choose date to enter a fixed date, time and UTC offset. Show chart freezes that moment; Live now returns to the computer clock.

04 Hover for positions and contacts. Full screen enlarges the display. The legend identifies planets, nodes, angles and independent cusps, with all nine aspects within the displayed 1 degree 22 minute orb.

RESULT VIEW

The generated harmonic wheel at a fixed chosen moment, with its factor legend and visible aspect connections.

READING THE RESULTS

The display is one generated harmonic chart. Every natal cusp and both Nodes are multiplied independently by exact fractional age. Opposite natal endpoints need not remain opposite in the resulting chart. The embedded Swiss Ephemeris supports offline calculation.

04 Age Harmonics Research

AgeHarmonics_Research.html

Research internal age-harmonic aspects using the built-in rectification database. Select a person and a dated event to load the calculation, or produce a Power write-up across that person’s event list. Manual birth and event entry remain available.

USE THE MODULE

01 Search the rectification database by person or chart number, then choose a person. Their rectified GMT birth data loads into the birth controls. Reload person’s birth data restores the database values.

02 Choose a dated event or move through events with Previous event and Next event. Database events supply a date and category; the initial event time is 12:00 UTC and can be edited.

03 Review the birth and event time bases, days per age year, node choice and maximum orb in degrees and minutes. Use Check natal positions to inspect the natal chart. Online city search and saved offline cities support manual cases.

04 Click Calculate age harmonic aspects. Show only highlighted aspects limits the list to contacts meeting the event-weight threshold. Inspect the harmonic-position table and adjust birthtime in one- or ten-second steps as needed.

05 Power write-up - all events steps through the loaded event list and reports theme-relevant AH contacts by event. Copy write-up or Download TXT saves the report. The single-event list also offers Export CSV and Print.

RESULT VIEW

A database person and selected event with sorted harmonic contacts, followed by a Power write-up over the event list.

READING THE RESULTS

Each contact joins two age-harmonic positions. Natal longitudes are multiplied by fractional age and reduced modulo 360 degrees. All cusps and both nodes are multiplied independently; this is not a comparison of harmonic positions with natal targets.

The selected event determines which cusp receives its house weight. Siblings use the 3rd, death the 8th, and children or romance the 5th; their opposite cusps do not inherit those weights. The highlighting threshold is 4 points.

The supplied engine covers 1200-2399. Online city lookup supplies coordinates only; the historical UTC offset remains a separate entry. Power write-up is a research report, rather than an automatic birthtime scan.

05 Ascensional Transit Hit List

AscensionalTransitsHitlist.html

This tool produces a chronological list of exact ascensional contacts over a chosen interval. It includes direct and converse searches, with optional antiscia, Nodes and Pars Fortuna. It is useful for examining the sequence around a timed event or preparing a short forecast list.

USE THE MODULE

01 Enter the natal date, UT/UTC birthtime and birthplace coordinates. Enter the transit-location coordinates separately. Longitude is east positive, west negative.

02 Enter the start and end dates and their UT/UTC times. Begin with ten to sixty minutes: the diurnal motion can generate thousands of contacts in a day. The search range refers to actual event time even when converse motion is included.

03 Choose direct/converse scope. Select ten planets only or the expanded set with both mean Nodes and Pars Fortuna. Decide whether to include antiscia and the optional precession/ΔT correction.

04 Click Build hit list. Stop search ends a search that is too large. Use Previous and Next to move through the result pages.

05 Read Exact actual time as the event-timeline instant. Chart instant identifies the ephemeris instant used for the direct or prenatal chart. The direction column keeps the two methods separate.

06 Export CSV to retain or analyse the list. The Elizabeth II example restores the supplied comparison data.

RESULT VIEW

A populated hitlist with direct/converse labels, exact UTC times and natal targets. Include the search period in the frame.

READING THE RESULTS

The hitlist has no orb cutoff: it lists exact crossings inside the range, including a contact already forming at the start if it becomes exact within the interval. A nearby contact whose exact instant lies outside the interval is omitted. Equivalent conjunction/opposition expressions to opposite cusps are shown once, preferring conjunction; equivalent Node contacts are consolidated. Independent factors and direct/converse contacts remain separate. Converse time is 2 × birth - actual event time, and both motions use the transit location. Fortune uses Ascendant + Moon - Sun for day and night. Numerical refinement gives a 0.1-second bracket, although the engine’s astronomical accuracy is more limited and grazing contacts may be missed.

06 Ascensional Transits

AscensionalTransits.html

Ascensional Transits compares an event sky with the fixed natal MDO positions using the Marr/Estadella method. It displays direct ascensional conjunctions, oppositions and antiscia within selected orbs, together with natal and event specula. This first calculator is a snapshot for one event instant.

USE THE MODULE

01 Enter the birth date and birth time in UT/UTC, followed by the birthplace latitude and longitude. Enter east longitude as positive and west as negative. There is no civil-time or daylight-saving conversion.

02 Enter the event date and time in UT/UTC and the event-location coordinates. These coordinates affect the event's local ascensional geometry. Convert a recorded local time to UTC before entering it.

03 Open Calculation settings and optional correction values. The initial conjunction/opposition orb is 25′; the antiscia orb is 10′. Adjust them for your comparison.

04 Leave Apply the special precession and ΔT correction unchecked for an uncorrected calculation. When enabled, it adjusts event RAMC while natal MDO remains fixed. Blank correction fields use estimates. Enter precession, event RAMC and birth/event ΔT overrides only when reproducing a particular reference calculation.

05 Click Calculate transits. Read the event planet, contact, natal factor, orb and MDO/quadrant columns. Use the specula to inspect the underlying geometry. Load Elizabeth II example provides a supplied comparison case.

06 Use Export aspect table for the results or Print / save PDF for a report. City lookup, when used, supplies location coordinates without converting times.

RESULT VIEW

The calculated aspect table and the natal/event specula, preferably from the supplied Elizabeth II example.

READING THE RESULTS

MDO is 90 times meridian distance divided by semi-arc. Equal MDO in the same quadrant gives conjunction; opposite quadrants give opposition; adjacent quadrants give antiscia. Natal cusps use the method's fixed MDO values. This file includes ten transiting planets and natal planets/cusps; it does not include prenatal transits, Nodes, parts or ecliptic aspects. Those additional scopes appear in the hitlist and live tools. Circumpolar bodies without ordinary semi-arcs are excluded and noted. This calculator uses Astronomy Engine, with about one-arcminute planetary accuracy, so displayed arcseconds should not be treated as a matching accuracy guarantee.

07 Ascensional Transits LIVE

AscensionalTransits_LIVE.html

Ascensional Transits LIVE is a moving display of exact ascensional contacts for the current instant. It shows two past entries and three upcoming entries, with a countdown to the next exact contact. Direct and converse contacts can be followed together.

USE THE MODULE

01 Open Edit data and replace the prefilled natal information with the chart you want. Birth time is UT/UTC. Latitude is north positive; longitude is east positive.

02 Enter the current-location coordinates. Use a city lookup or Use my location if appropriate, then verify the chosen location. Both direct and converse charts use this location.

03 Choose Direct + converse, Direct only or Converse only. Decide whether to include antiscia and Nodes & Pars Fortuna, both initially enabled. The special precession/ΔT correction is optional and initially off.

04 Click Apply & run or Run live. The calculator follows the computer clock. Confirm that the computer’s time and local time-zone setting are correct before using the countdown.

05 Read PAST 1 as the latest completed contact and PAST 2 as the preceding entry. NEXT, UPCOMING 2 and UPCOMING 3 are the next three entries. When the next exact instant arrives, the display advances automatically.

06 Several contacts can share one entry if they occur at the same instant. Tap that entry to see the full set. The motion badge distinguishes direct from converse. Use Pause to hold the display and Edit data to change the chart or location.

RESULT VIEW

The populated contact roller with two past and three upcoming entries, motion badges, and the next-contact countdown.

READING THE RESULTS

Wheel times follow the computer’s local time zone; the clock also shows UTC. Converse chart time is 2 × birth instant - now, so its ephemeris moves backward while the countdown follows actual forward time. Equivalent opposite-cusp contacts are consolidated. Settings are remembered in the browser when storage is available. Crossings are sampled at ten-second intervals and refined numerically; rare grazing contacts, particularly Fortune contacts, can be missed. Use the snapshot calculator when you want to inspect the complete MDO geometry at a chosen historical instant.

08 Aspect Overlap Finder

OverlapFinder.html

Find the calendar dates shared by selected event-related aspects. The module searches primary directions, progressions, arcs and transits, then intersects the chosen in-orb intervals. Select supporting contacts across systems to narrow the remaining period.

USE THE MODULE

01 Enter birth data, historical UTC offset and coordinates, or import a Janus speculum. Online city lookup fills coordinates. Check the time keys, node choices and Fortune settings.

02 Set Period begins, Period ends, the fixed Noon UTC offset and Event type. Click Find event-related aspects. Moving-system panels start collapsed; expand them to inspect their lists.

03 Review the contacts, ordered by highest Isaac points within each system. Check the contacts you want to require. Each additional selection intersects its interval with the current remaining dates.

04 Read Remaining overlapping period and the selected interval bars. Separate surviving runs can remain. The final display includes the middle day between each resulting start and end.

05 Use Clear selection to restart the intersection. Export selected intervals keeps the chosen date windows. Export aspect list and Export CSV provide the aspect listings.

RESULT VIEW

Selected aspect intervals on a shared date scale, with the remaining overlapping dates and their middle day.

READING THE RESULTS

Intervals use daily noon samples, plus one extra day at each end, clipped to the requested range. This allowance is always included in the overlap; bars distinguish it from the sampled in-orb interval.

The supplied limits are TPD 12′ for conjunction/opposition and 6′ otherwise; progressions 12′ / 9′; solar and lunar arcs 22′ for hard aspects; outer-planet transits 1°22′. PSSR is not included.

Moving Moon is excluded from secondary, tertiary and minor progressions, while contacts to the natal Moon remain included. Direct and converse are available where supported; arcs are direct only.

The result is the intersection of selected contacts within the module’s sampling and allowance rules. Check the visible settings and Calculation notes when comparing with other tools.

09 Astrological Event Convergence Scanner

AstroConvergenceScanner.html

The Event Convergence Scanner calculates several predictive systems for one event, then groups their contacts into repeated factor-pair themes. It shows where the same relationship recurs across primary directions, secondary/tertiary/minor progressions, direct solar/lunar arcs and direct/converse transits.

USE THE MODULE

01 Enter the natal chart, historical offset and coordinates, or import a complete Janus speculum. Longitude is west positive. An imported speculum supplies natal geometry while Swiss Ephemeris supplies moving positions.

02 Enter the event date, clock time and offset. The event instant affects systems other than primary directions, which retain the calendar-day Naibod key. Select one Node convention for all systems.

03 Set whether progressed-to-progressed contacts, Eris and Fortune are included. Choose the progression/arc year length and Fortune rule where relevant. Transits have a fixed moving-factor scope and do not use moving angles or cusps.

04 Click Calculate convergence. The summary reports qualifying hits, unique factor pairs, repeated pairs and the leading theme's hit count.

05 Choose grouping by Factor pair to combine its aspect types, or Factor pair + exact aspect to keep conjunction, square and other aspects separate. The initial minimum is two hits. Show single-hit themes broadens the view.

06 Search for a factor or pair and use direct/converse and technique/factor filters to compare the retained evidence. Expand a theme to read each original source, target, direction and reference frame. Reciprocal pairs share a theme without losing their original orientation.

07 Review the individual technique lists and calculation epochs beneath the convergence view. Export the filtered hits for a record. Minimum theme count and text search affect the convergence display, rather than the individual technique lists.

RESULT VIEW

The convergence summary and one expanded repeated factor-pair theme, showing its separate technique and motion labels.

READING THE RESULTS

The scanner uses 11′/6′ primary-direction limits, 11′/9′ progression limits, 22′ hard-aspect arc limits and 1°22′ transits. These are intentionally not identical to every source calculator's limits. Ranking uses raw hit count, then mean normalized orb, closest orb and names. Several hits from one system remain several hits; a theme count is therefore not a count of independent techniques. Expanding factor scope can increase counts. Use the source labels to distinguish repeated mathematical expressions from support across separate methods.

10 Category Activation Timeline

CategoryActivationTimeline.html

Follow event-category activation through time with a forty-row heatmap, a focused activity graph and a contact inspector. Nine calculation systems can supply the underlying contacts. Category scores use the supplied Isaac weighting matrix.

USE THE MODULE

01 Enter birth data, or load James’s example. Find city fills coordinates. Set the historical UTC offset or LMT basis; longitude is west positive.

02 Set Start date, End date and Sample interval. AH orb is adjustable in arcminutes. Pars Fortuna and progressed-to-progressed contacts are always included.

03 TPD, Secondary, Tertiary and PSSR start enabled at 100% each. Systems starts closed; open it to change enabled systems and weights. Click Scan timeline, or Stop to keep an inspectable partial scan.

04 Choose Isaac score or Systems agreeing, then select an event category in standard numbered order. Its row scrolls into view. Click the heatmap, graph or a sampled peak to inspect the contributing contacts.

05 Examine date uses the current Start date as its center, sets the range from 30 days before to 30 days after, starts the scan and scrolls to Category activity. Export CSV saves all forty category series.

RESULT VIEW

The category heatmap, the selected category’s profile and contact inspector, with the chosen measure and system weights.

READING THE RESULTS

Isaac score sums qualifying positive matrix weights multiplied by system percentages. Orb is a qualifying limit; points are not reduced by distance from exactness. Systems agreeing counts enabled systems with at least one scoring contact.

Each category has its own observed minimum and maximum. Its minimum is dark blue and maximum bright red; constant rows stay dark blue. Colors compare dates within one category, not scores between different categories.

The graph’s centered reference is (minimum + maximum) / 2. Red and blue shade above and below it. Guide lines mark whole values. The inspector uses event-relevant house references; AH cusps remain independent.

This is a sampled timeline, with a 10,000-sample limit. Brief contacts can fall between samples. Scores describe selected contact rules and system weights; they are not probabilities or forecasts of an event occurring.

11 Central Scrutinizer

CentralScrutinizer.html

One person, one event, nine connected systems. Central Scrutinizer combines a searchable case library and life events with TPD, Age Harmonics, PSSR, three progression systems, solar/lunar arcs and transits. Its updated dark display keeps relevant contacts easy to distinguish.

USE THE MODULE

01 Choose a database person, open a .awb case, or edit birth data. Find city fills coordinates; enter the historical offset separately. Select a life event to calculate all nine systems.

02 Import CSV events or edit them directly. Save to database stores the person, birth data, events and settings in this browser. Update the selected entry or add a new person. Saved people lists your personal records.

03 Use Backup to download an .awbdb file, and Restore to recover or transfer saved database entries. Save .awb and Open case remain available for individual cases.

04 Choose a system tab or All systems. Highlighted only filters the aspect lists; Relevance shows their applicable weights. The small AH orb control affects Age Harmonics only. Other system orbs are fixed.

05 Adjust working birthtime by one second with minus/plus. Copy and Export save the current event. Master export calculates all nine systems for every event, using the current birthtime, settings and Highlighted only filter.

RESULT VIEW

A case with populated dark aspect panels, selected event, relevance values and shared birthtime controls.

READING THE RESULTS

Date-only events use noon UTC where a timed instant is needed. TPD keeps its calendar-date key. Pre-birth TPD, progressions, arcs and transits use signed elapsed time; AH and PSSR show not applied before birth.

Transits include Jupiter through Pluto and the Mean Node axis. Tertiary/minor moving Moon contacts are omitted; natal Moon targets remain. Each system keeps its own scoring rules, with no combined score.

Orbs are calculated at full precision and truncated to whole arcminutes in display and export. House-axis references follow the event theme. AH cusps and nodes remain independent. Keep database backups when moving between browsers or program copies.

12 Cusp Category Graph

CuspCategoryGraph.html

Cusp Category Graph plots the activity of six cusp axes across a date range. Select Topocentric Primary Directions, arcs, progressions or transits, alone or together. A second graph follows the selected Isaac event category using normalized scores.

USE THE MODULE

01 Enter birth data, the historical UTC offset and west-positive longitude.

02 Choose start and end dates and the timeline's display offset. The initial range is one year from today, with Primary Directions only selected.

03 Click Build timeline. Choose the systems to display with the checkboxes above the graph. Sampling and scale controls set the resolution and normalization.

04 Read the six lanes: Asc/Dsc, 2nd/8th, 3rd/9th, MC/IC, 5th/11th and 6th/12th. Hover for the date and contributing contacts; click to freeze the inspection.

05 Select one of Isaac's event categories for the lower graph. It uses the same selected systems. Change categories without rebuilding the timeline.

06 Use Export CSV and Save graph PNG for the cusp graph. The category graph has its own CSV and PNG controls.

RESULT VIEW

The calculated six-axis activation graph and category graph for the same period, with the selected systems and category visible.

READING THE RESULTS

The cusp graph measures orb-sensitive activation. The category graph uses Isaac points for the three strongest distinct contact pairs per system, scaled against its rule ceiling. Peaks show concentrated activity within the chosen settings; inspect the contributing contacts when comparing periods.

13 Epoch Chart Finder

EpochFinder.html

Epoch Chart Finder derives five prenatal lunar crossings from the natal Ascendant and Descendant. It finds the Moon’s Ascendant crossing nearest 250 elapsed days before birth, adds the four immediately preceding crossings of either natal angle and highlights the listed crossing nearest 273 days before birth.

USE THE MODULE

01 Enter the birth date and recorded local birthtime to seconds. Search the embedded city directory and select the correct birthplace. A name is optional.

02 Check the latitude, longitude and named birth time zone under Coordinates & time-zone options. Longitude is east positive. Manual coordinates allow locations outside the directory.

03 Keep Historical city time zone selected when the named zone correctly represents the record. Historical daylight saving is applied automatically. If the record gives a specific UTC offset, select Recorded UTC offset and enter it instead.

04 If the clock time occurred twice during a time-zone change, choose the recorded occurrence. A fixed-offset calculation applies that same offset to the displayed events, rather than determining a separate historical zone offset for each crossing.

05 Run the calculation after the engine is ready. Read the natal ASC/DSC and the five crossings in chronological order, oldest first. Each row identifies whether the Moon meets ASC or DSC and how long before birth it occurs.

06 Compare the highlighted crossing with the other four. The highlight identifies the smallest distance from the 273-day reference within this selected set. Save results as CSV when you need to transfer dates to another chart tool.

RESULT VIEW

All five calculated prenatal lunar crossings, including the highlighted crossing nearest the 273-day reference and the natal angles.

READING THE RESULTS

The five results are not a general search of every prenatal Moon-angle crossing. Their selection follows the stated 250-day reference and preceding-crossing rule. The natal angles are fixed targets; they are not recast at each prenatal date. Apparent geocentric tropical Moon longitude is used. Local and UTC times are both shown, with local offsets determined at each event when named-zone mode is used. Birth input covers 1801-2399, allowing room for the prenatal search. The city directory and Swiss Ephemeris are embedded for offline use.

14 Fixed Star Parans

FixedStarParans.html

Angular Sky lists fixed stars on the angles at an entered moment and daily parans based on the time difference between angular crossings.

USE THE MODULE

01 Select a place with offline lookup, enter local date and time, historical UTC offset and west-positive longitude, then click Calculate.

02 In Settings, choose the star selection, magnitude limit, daily interval and horizon model. Observer elevation, horizon altitude and planet/Mean Node inclusion are also available. Apply the settings.

03 Set the angular and paran orbs in minutes. Inspect Angles at entered time and Daily parans. Filter star/planet combinations without recalculating.

04 Click a row for sky position and Jump to exact. The time-step controls move through the sky. Now and Live follow the current clock; Natal restores the separately saved birth data.

05 Use Settings to save entered birth data as natal or load James's example. Export retains the available results.

RESULT VIEW

Daily parans with populated crossing pairs. A second detail view can show the sky position and Jump to exact control.

READING THE RESULTS

Paran orb is the difference between two crossing times. Upper and lower culmination mean meridian transit; circumpolar bodies may cross both meridians without rising or setting. Stars near sunrise lists horizon crossings relative to sunrise, rather than a first/last-visibility calculation.

15 House Activation Timeline

HouseActivationTimeline.html

Explore the activity of all twelve houses through time using nine systems. A heatmap compares dates within each house; the focused house’s graph, sampled peaks and contact inspector provide a closer view.

USE THE MODULE

01 Enter birth data, or load James’s example. Find city fills coordinates. Check the historical UTC offset or LMT basis; longitude is west positive.

02 Set the start and end dates and sample interval. Daily samples use noon UTC. Choose the systems and their percentage weights, the AH orb, progressed-to-progressed scope and Pars Fortuna option.

03 Click Scan timeline. Use Stop to keep an inspectable partial scan. A completed scan can be reweighted instantly; enabling a system that was not scanned requires another scan.

04 Switch Show between Systems agreeing and Contact intensity. Click a heatmap cell or use the house buttons to focus a house. Read its activity profile and strongest sampled peaks; click a peak or profile sample to inspect contacts.

05 Export CSV saves the sampled results. Use a finer interval around activity of interest, particularly when tight AH orbs make short contacts easy to miss.

RESULT VIEW

The twelve-row heatmap, the selected house’s activity profile, and a populated contact inspector.

READING THE RESULTS

Systems agreeing counts enabled systems with at least one qualifying cusp contact. Contact intensity sums weight/100 × max(0, 1 - orb/allowed orb) across distinct contacts. These are two different measures.

Each heatmap row uses that house’s own sampled peak as its color maximum. Compare dates within a row; use numerical values to compare houses. Ordinary house axes activate both ends, while AH cusps remain independent.

The graph’s centered reference is (lowest + highest sampled value) / 2. Red and blue shade values above and below it. Light guide lines mark whole numbers. This is a sampled timeline, not an exact-contact search; there is a 10,000-sample limit.

16 Lunar Angles

LunarAngles.html

Lunar Angles examines planets near the angles in eight precessed lunar-return streams: Moon returns to natal Moon, Sun, Ascendant and Midheaven, in direct and converse motion. Each stream selects its applicable lunar or demi-lunar phase and erects the chart at the event location.

USE THE MODULE

01 Enter the natal date, local time, historical offset and birthplace coordinates. Longitude is east positive. A supplied IANA time zone overrides the numeric offset; clear the zone to use a verified manual offset.

02 Enter the event date and location. Leave Unknown checked if the event time is unavailable, or uncheck it and enter a time. Unknown-time mode considers the whole local day instead of assuming a single noon instant.

03 Set Angular distance, initially 3°. Choose the measurement you want: ecliptic longitude, actual horizon/meridian or exact angle-point sky separation.

04 Set Include upcoming, initially 24 hours, to show nearby following crossings as comparisons. Zero disables that allowance. Click Calculate eight returns.

05 Read the stream and phase labels, return times, angular planets and exact distances. Open chart details to inspect positions and prime-vertical longitude. A preceding chart can remain visible alongside a following crossing within the allowance.

06 Save/load the inputs as JSON. Use Print / PDF for the displayed results. Online place searches are optional; coordinates and offsets can be entered offline.

RESULT VIEW

Populated return cards showing stream, phase, return time and angular planets. Expand one card to show angular distances.

READING THE RESULTS

The three angularity modes are different tests. Ecliptic longitude ignores planetary latitude. Actual horizon/meridian measures distance to a physical plane, including latitude, and labels the appropriate ASC/DSC or MC/IC branch. Exact angle-point mode measures great-circle separation from the actual ecliptic angle point. Prime-vertical longitude appears in details but does not independently qualify a planet.

Precession advances the natal target in longitude using the birth-epoch model. Converse crossings are solved in the prenatal sky and mapped back to the event timeline. All charts use event coordinates, while natal targets use the birthplace. Return details use UTC/UT to avoid assuming prenatal local clock conventions. The embedded data cover 1200-2399; converse dates and search margins must also fit. Mean Nodes are included, without Chiron. An upcoming comparison does not replace the preceding phase automatically or establish a sudden change of influence.

17 Midpoint Lab

MidpointLab.html

Explore midpoint structures using 45-degree and 22.5-degree displays, with Witte reference definitions for the selected planetary picture.

USE THE MODULE

01 Choose a birthplace through the offline lookup, then enter birth date, time, historical UTC offset, latitude and west-positive longitude. Click Calculate natal.

02 Set the midpoint orb in arcminutes. Enable the eight hypothetical planets if required, and choose the available dial or tree display.

03 Keep the overlay at natal only, or select Transiting planets and enter the requested UTC moment. Inspect the structures shown for the current settings.

04 Click a planetary picture to read its matching Witte meaning context. Previous, Next and Witte reference let you browse the embedded definitions; Open source page follows the source reference.

05 Use Export to retain the available output. The Light control changes the display theme.

RESULT VIEW

The calculated dial or tree with one planetary picture selected and its matching Witte meaning context visible.

READING THE RESULTS

The embedded lookup contains 231 midpoint definitions, 4,620 planetary pictures and 22 factor definitions from the supplied Witte/Rudolph/Lefeldt reference. Natal positions use the tropical zodiac, Mean Node and Topocentric angles. Definitions describe symbolic possibilities for the selected structure.

18 Polaris2

Polaris2.html

Polaris2 searches candidate birthtimes with Topocentric Primary Directions and dated events, then compares a shortlist with secondary progressions and PSSR. Its Combined graph sums the selected systems using editable weights. The full TPD scan and the refinement shortlist have different scopes.

USE THE MODULE

01 Enter the birth date, latitude, west-positive longitude and historical UTC offset or LMT basis. The offline city search fills coordinates. Candidate birthtimes come from the scan range.

02 Use View Database to load a rectified case and its events, open a saved project, load the sample, or import Date, Category and Description columns. Set each event to score or validation. Month-only dates use the 15th and receive an extra 2.5′ TPD allowance.

03 Set the earliest and latest candidate times and interval. The database transfer supplies a range around the stored rectification. Review the day selectors as well as the clock times. Both range endpoints are included.

04 Review TPD orbs: the supplied fields show 10.8′ for conjunction/opposition and 5.6′ otherwise. Major Aspects Only restricts TPD scoring to 0°, 60°, 90°, 120° and 180°. Polaris table uses stored weights; Equal hits uses the editable category factor lists.

05 Set Secondary % and PSSR %, both initially 50, relative to TPD = 100. PSSR Moon house bonus initially shows 25. TPDs ONLY skips the later calculation stages; No partility averages suppresses that calculation. Choose these options before Start scan.

06 Compare Rank with Coverage. Review the two proximity fields: their supplied values are 48 seconds for long ranges and 5 seconds for ranges of two minutes or less. Entering a range can reset the long value to 48 or 120 seconds according to its duration. Use the visible fields as the active settings.

07 Read Combined first, followed by TPD, Secondary and PSSR. Sum these systems controls the Combined view. Secondary/PSSR points are evaluated at shortlisted times. The colored triangles identify the leading TPD positions in the selected Rank/Coverage mode.

08 Click a candidate or graph point to inspect event evidence. Use Epoch finder for the three nearby prenatal crossings around the 273-day reference. Save the project or export the ranked/evidence lists after the calculation.

RESULT VIEW

The completed Combined, TPD, Secondary and PSSR graphs, with the system weights visible and a selected candidate's event evidence below.

READING THE RESULTS

Combined = TPD + (Secondary % ÷ 100) × Secondary + (PSSR % ÷ 100) × PSSR for the checked systems. Combined coverage counts distinct scoring events. Validation events remain separate and never determine rank.

Secondary refinement scores progressed cusps to natal planets and progressed Moon to natal cusps. Age Harmonics remains available in event panels but is absent from the Combined graph. Refinement uses fixed noon UT; PSSR uses Mean Node and keeps the strongest contact across its four variants. A missing required epoch is unavailable, rather than a zero score.

19 PSSR Aspects

PSSR_Aspects.html

PSSR Aspects lists contacts from four variants of progressed/regressed precessed solar returns to the natal chart. It combines the results into one orb-sorted list, retains variant labels and shows forming/separating status. Event categories highlight relevant contacts, with special Moon-actuation rules.

USE THE MODULE

01 Enter the birth date, local birthtime, UTC offset in hours and coordinates. DMS with hemisphere letters is accepted; unsigned coordinates use north/west positive. Natal houses are Topocentric and the Node is Mean North Node.

02 Enter the event date, time and UTC offset. Noon is the default when event time is empty. Select an event category if you want expected contacts highlighted. No event-location entry is needed.

03 Click Calculate aspects. The list merges contacts across progressed direct, regressed direct, progressed converse and regressed converse variants, retaining the smallest orb for repeated contacts.

04 Read the variant, moving planet, natal target, orb and phase. Forming means the orb decreases as the event date advances within the return year. Open Planetary positions and return dates to inspect the direct/prenatal returns and their derived positions.

05 Turn on Event matches only to limit the displayed list. Gold rows identify category matches. Moving Moon contacts to event-relevant natal cusps qualify as actuation even when Moon is absent from the category's planet list; Moon contacts to listed natal planets/Node also qualify.

06 Select rows with their copy checkboxes and click Copy selected. The event-match filter also limits copied rows. Save/open the chart as JSON or use Print / PDF. The example selector provides supplied benchmark cases.

RESULT VIEW

Calculated natal contacts across the four return variants, an event category, and the return-date/position details.

READING THE RESULTS

The moving Sun is excluded; the natal Sun remains a target. Non-Moon moving factors use a 12′ maximum. Moving Moon conjunction/opposition uses 31′ and other aspects 20′. Opposite-cusp equivalents are combined, with the event category choosing the relevant axis end where appropriate. This is category highlighting rather than the Rectifier's numeric PSSR scoring model.

Returns are solved against the natal sidereal Sun, but displayed positions and natal comparisons remain tropical. The program does not calculate return houses or angles. Its birth-location data establish natal cusps; an event location cannot relocate return angles here. Direct/prenatal returns and progressed dates must all fit the embedded 1800-2399 span.

20 PSSR Sieve

PSSR_Sieve.html

PSSR Sieve searches a birthtime interval and shows where selected PSSR contacts remain within orb. You inspect and select contacts as constraints; their intersection becomes a narrower range for further rectification. It supports broad planetary searches and a directed-Moon refinement of narrower ranges.

USE THE MODULE

01 Enter the birth data, historical offset and original range on one birth date. Longitude is west positive. Set the common event-time convention in UTC, initially noon. Coordinates are needed for optional natal-cusp contacts; the planetary search is geocentric.

02 Add dated events, choose categories and provide descriptions. Import CSV/TSV or paste Date, Category, Description columns. Optional Use values can disable rows.

03 Choose Automatic, Planetary contacts only or Moon + planetary contacts. Automatic mode adds directed Moon contacts when the searched range is three hours or less. Select standard or restricted planetary-pair coverage and whether natal cusps are included.

04 Review the orbs and Minimum fast-planet motion, initially 35′ per ephemeris day. Defaults are 12′ for ordinary planetary contacts, 30′ when natal Moon is the target, and 31′/20′ for directed Moon. Directed-Moon limits take precedence when Moon is on the moving side.

05 Click Calculate intervals. Inspect each bar against the common original range. Gold marks exactness/closest approach or category relevance. Contacts start unselected; checking a contact makes it a constraint.

06 Select only the contacts you want to require simultaneously. Read the surviving width, reduction, active constraints and contributing events. Disjoint surviving intervals remain separate. Display filters, including the initially checked conjunction/opposition filter, hide rows without removing selected constraints.

07 Choose a surviving interval and use Refine surviving range with Moon. Review the added constraints rather than assuming they were selected for you. Copy the result, download the summary, print a report or download the full project. Browser saves offer a convenient local checkpoint.

RESULT VIEW

Calculated contact bars with several constraints checked, and the resulting surviving birthtime interval and width.

READING THE RESULTS

Standard coverage includes Mercury/Venus/Mars with slow planets/Node in either orientation and moving fast planets to natal Sun, Moon and other fast planets. All four PSSR variants are separate constraints. Category assignments are editable symbolic filters; they do not replace the motion test. The Mike Tyson example includes quoted reference windows, not forced calculated answers. Its slow Venus-Moon case is excluded at the default motion cutoff, so lower that cutoff explicitly to inspect it. Event times, year convention, variant and motion settings all affect the surviving interval.

21 Radix and Epoch Aspect Studio

DualTest.html

Compare radix and epoch charts through primary directions, secondary progressions and PSSR. Nine panels combine three methods with Radix, Epoch and their interactions. The supplied update refines the aspect tiles while retaining event-category highlighting and chart-route labels.

USE THE MODULE

01 Enter the Radix and Epoch birth data independently, with each chart's own date, time, place and historical offset. City lookup supplies coordinates; offsets remain explicit inputs.

02 Enter the event date, time and offset. Select an event category for relevant-contact highlighting, or leave All contacts selected. Secondary internal aspects adds progressed-to-progressed contacts in the R/R and E/E panels.

03 Click Calculate all nine. Inspect each panel in orb order. The interaction column includes both R/E and E/R, identified by route labels so the moving source and fixed target stay clear.

04 Use Highlighted only to limit the tiles. All axis equivalents reveals complementary renderings; the grouped view combines equivalent contacts and preserves distinct PSSR variants.

05 Save inputs and Load inputs retain the chart settings. Export CSV uses the displayed event-relevant house references. Review Methods, orbs & chart information for the inherited calculation conventions.

RESULT VIEW

Nine populated panels with revised aspect tiles, a selected event category and clear Radix/Epoch route labels.

READING THE RESULTS

The selected event determines the displayed house-axis end: foreign travel uses the 9th, siblings the 3rd, deaths the 8th, children the 5th, and illness or confinement the 12th. Complementary aspect angles change; the calculated orb is preserved.

Each chart uses its own elapsed time to the event. R/E and E/R target the other fixed chart. PSSR retains its four labelled return variants; this is contact highlighting, with no combined rectification score.

The Mean Node and the supplied orbs are retained: TPD 12′ / 6′, secondary 12′ / 9′, PSSR 12′ with its wider Moon allowances. Required prenatal returns must fit the embedded 1800-2399 coverage.

22 Solar Contacts

SRA.html

Solar Contacts compares four solar-return types: tropical direct/converse and precessed direct/converse. It lists return-chart contacts and contacts from each return to the natal chart, ordered by orb. Precessed returns can use a demi-solar phase; tropical returns remain full annual returns.

USE THE MODULE

01 Enter natal local date/time, birthplace coordinates and historical offset. Longitude is east positive. A named IANA time zone overrides the numeric offset; clear it when using a manual offset.

02 Enter the event date and location. The four returns use that location. Copy birth time, initially checked, uses the natal clock time on the event date, interpreted in the event time zone. Uncheck it to supply a known event time.

03 Set the maximum orb, initially 1°08′. Choose all four returns or one type from Show returns. Keep Keep tightest duplicate enabled for the consolidated view.

04 Click Calculate four returns. Read the return-type and source/target labels carefully to distinguish internal-return aspects, return-to-natal aspects and return-body conjunctions to return cusps.

05 Expand duplicate notes to inspect equivalent expressions or occurrences in other return types. Open chart details for the return dates and positions. The defining Sun-Sun return conjunction/opposition is excluded from the contact report.

06 Save/load inputs, export the report or print/save PDF. The Lennon example and illustrative data provide starting cases, rather than your own saved project.

RESULT VIEW

The four calculated solar-return streams and their angular/contact results. Expand one result's chart details.

READING THE RESULTS

Within a return, planets/mean Nodes/Fortune are checked for conjunctions to cusps and planetary conjunctions/oppositions. Across charts, return planets, points and cusps are compared with natal factors for conjunction/opposition. A cusp opposition can appear as conjunction to its opposite cusp; aliases are grouped by axis. Cross-chart source/target roles remain distinct. The tightest duplicate setting keeps the smallest orb across return types.

Precessed target longitude uses accumulated mean precession from the birth epoch. Converse returns are solved in the prenatal sky, then mapped to the event timeline. Return houses use event coordinates and Topocentric system T; natal houses use the birthplace. Fortune is Ascendant + Moon - Sun for day and night. Mean Nodes are used. Birth/event/converse dates and search margins must fit 1200-2399. This tool’s angular return charts serve a different purpose from PSSR Aspects, which progresses return planets and does not calculate return angles.

23 Studio Hitlists

StudioHitlist.html

Studio Hitlists finds exact contacts across seven predictive systems over a date range. Event-category highlighting and ratings help identify relevant contacts. Use it beside Central Scrutinizer when a chronological list is useful.

USE THE MODULE

01 Enter the birth data, historical UTC offset and west-positive longitude, or import a complete Janus speculum. Set the Node, year-length, Fortune and progressed-to-progressed options before searching.

02 Enter inclusive start/end dates and the Hitlist UTC offset. That offset remains fixed throughout the range; daylight-saving changes are not inferred. Split a range if you need different civil-time offsets in different parts.

03 Select the event category for contact highlighting. Click Build hitlists and allow the seven panels to complete. Cancel stops a search that is longer than needed.

04 Read every row as an exact contact time. Primary-direction results retain their calendar-date Naibod convention. Progressions, arcs and transits show their exact times in the selected fixed offset.

05 Expand a panel and click a result for details. Compare direct/converse labels and progressed-to-natal versus progressed-to-progressed reference frames. Enable separate equivalent-axis results only when you need their alternative expressions.

06 Use the stored reference birthtime and small adjustment buttons to test a nearby time, then rebuild the lists. A change in birthtime changes the exact maturities, not merely the displayed orbs.

07 Export CSV to preserve the hitlists and inspect the natal positions below them. Use a shorter date range when reviewing a specific episode rather than generating an unnecessarily large transit list.

RESULT VIEW

Completed date-range hitlists in several technique panels, with exact dates, motion and highlighted contacts visible.

READING THE RESULTS

The inherited panel captions still show snapshot orb values, but those orbs do not restrict this exact-contact search. The surrounding-directions option is hidden. Primary-direction cusp-to-cusp contacts remain conjunction/opposition only. Progression cusp-to-cusp contacts are omitted, while planetary contacts to/from natal or progressed houses remain included. Solar/lunar arcs use hard aspects and direct motion only. Transits are direct and converse, without moving houses or angles. This pictured edition includes the full transit scope and progressed Moon. Category highlighting identifies relevant exact contacts without assigning a combined rectification score.

24 The New Partner Horoscope

NewPartnerHoroscope.html

The New Partner Horoscope erects two charts from two people’s birth instants and one meeting location. It calculates the prenatal chart of the older person and the companion postnatal chart of the younger person using equal reflected birth intervals. It does not require the date when they met.

USE THE MODULE

01 Enter each person’s name, birth date, local birthtime and actual historical UTC offset in the two person-entry areas. Include seconds when available. Birthplace labels identify the records; birthplace coordinates do not determine these two derived charts.

02 Enter Where they met as latitude and longitude, or use Find city and select the location. Longitude is east positive. Both output charts use these same coordinates.

03 Choose Mean or True Node. Verify the time offsets, because the program compares the converted UTC instants to establish which person is older.

04 Click New Partner Horoscopes. Person 1 and Person 2 are sorted automatically by birth instant; you do not have to enter the older person first.

05 Examine each chart’s calculated UTC date/time, wheel and position table. The charts use tropical apparent geocentric positions and Topocentric houses at the meeting location. Wheel glyphs can be displaced to avoid overlap; their anchor marks identify the actual longitudes.

06 Use Print charts or Export chart data to preserve the output. The Light/Dark control changes the display appearance.

RESULT VIEW

Both generated partner wheels, their derived UTC dates, and the position tables at the common meeting location.

READING THE RESULTS

If O is the older birth instant and Y the younger, the interval is $\Delta = Y - O$. The older prenatal chart is $O - \Delta = 2O - Y$. The younger postnatal chart is $Y + \Delta = 2Y - O$. Changing the meeting coordinates changes the chart houses and angles without changing these derived instants. Historical UTC offsets are not guessed. Output times are shown in UTC, and both derived dates must fall within the embedded 1800-2399 ephemeris span. This tool creates the two charts; it does not supply a separate compatibility score or automatically interpret their contacts.

25 The Sieve

TheSieve.html

The Sieve narrows a birthtime interval using direct/converse secondary-progression contacts from Mercury, Venus and Mars to natal planets and Nodes. It shows each qualifying contact as a birthtime bar. Selected bars become constraints, and their intersection is the surviving range for a later primary-direction scan.

USE THE MODULE

01 Enter the birth date, historical offset, approximate time and original range. Both endpoints must be on the birth date. Place and coordinates can be retained for handoff, but this tool’s planetary calculations do not require them.

02 Set the common event-time convention in UTC, initially 12:00. Add events with their categories/descriptions, paste a table or open CSV/TSV. Optional Use values disable events.

03 Review Event symbolism. The checked progressed planets are tested against the listed natal factors for each category. Assignments are editable adaptations; use Restore supplied assignments to return to the supplied rules.

04 Click Calculate intervals. Inspect the bars against the same original range. Gold markers identify exactness or closest approach. Contacts start unselected, so calculation alone does not reduce the range.

05 Select contacts you want to require. Every selected constraint must hold at a surviving birthtime. Selecting several contacts from one event therefore requires all of them, rather than accepting any one as sufficient.

06 Read surviving width, search-space reduction, active constraints and contributing events. If the overlap disappears, reconsider which contacts you chose or the assumptions behind the event and category. Clear selections returns to the unconstrained view without needing a new biography.

07 Copy the range, download a summary or print the report for use in the rectifier. Download/open a project for a portable record; browser save/load provides a local checkpoint.

RESULT VIEW

Populated progression-contact bars, selected constraints and the surviving range. Include an example with a meaningful reduction.

READING THE RESULTS

The aspect set is conjunction, sextile, square, trine and opposition, with inclusive 11′ conjunction/opposition and 9′ other limits. The progressed Moon, other progressed planets, houses, angles and returns are absent. An internal motion test excludes unsuitable contacts. Each candidate gets its own natal and progressed positions; birthtime is not varied while holding planets fixed. Separate valid intervals remain separate, and boundary marks ≤/≥ indicate continuation beyond the tested range. An event without a useful contact leaves the range unchanged until you deliberately select a constraint. Use this as a planetary pre-stage, then investigate the surviving interval with a tool that includes time-sensitive houses and angles.

26 Timeline

Timeline.html

Timeline places Topocentric Primary Directions, secondary progressions, tertiary progressions and outer-planet transits on one calendar axis. It shows the periods within orb and marks exact passes, making it possible to compare the timing and duration of contacts across systems. Equivalent opposite-cusp and Node contacts share a displayed row.

USE THE MODULE

01 Replace the supplied reference chart with the name, local birth date/time, historical UTC offset, latitude and west-positive longitude of the chart you want. Choose UTC-offset or LMT basis, Node conventions and the secondary year length.

02 Enter Scan start, UTC and Scan end, UTC. The end date is inclusive. Enable the systems to include and decide whether converse transits are required. Click Calculate timeline.

03 Read each row's factor pair, aspect and technique. A line marks a separate within-orb interval; an aspect glyph marks an exact pass. A line without a glyph has no exact pass inside the displayed period. D and C identify direct and converse motion. Displayed times use UTC.

04 Choose an Event Category to add Isaac's points and highlighting to relevant TPD contacts. Check Experimental: Apply Isaac's values overall to extend the same table to secondary and tertiary progressions and transits. This overlay is experimental and does not introduce separate weights for each technique.

05 Check Show highlighted aspects only to retain positive-scoring rows. Select a category first. With the experimental option off, only highlighted TPD rows qualify; with it on, all included systems can qualify. These display changes do not require a new calculation.

06 Use Visible targets, Maximum rows and Row order to adjust the view. The default row count is 24. Drag over the calendar or use the zoom controls to examine a smaller period. Click a row or exact-contact point to keep its details open.

07 Use the hidden/retained-contact inspector to examine contacts outside the visible row limit. Export all contacts preserves the full calculated set, including original expressions grouped in the display. Reset the zoom to return to the complete scan.

RESULT VIEW

A populated calendar showing several techniques, within-orb spans and exact-pass glyphs; open one contact's details.

READING THE RESULTS

Fixed limits are 11′/6′ for TPD, 12′/9′ for secondary and tertiary progressions, and 1°22′ for transits. Secondary moving sources Saturn through Pluto use a 1′ limit for every aspect. Only Jupiter through Pluto are moving transit factors. Tertiaries fill remaining display places after TPD, transits and secondaries; changing the row limit therefore changes what can be seen.

TPD contacts receive a display preference, while short separating tails without an exact pass in view are reduced in priority. These rules change the row selection, not the contact dates or orbs. Intraday TPD timestamps are continuous mathematical maturities derived from a calendar-day key; their displayed seconds are not independent event-timing accuracy. The tool omits solar/lunar arcs, minor progressions and progressed-to-progressed comparisons.

27 Topocentric Birthtime Convergence Matrix

TBCM.html

The Birthtime Convergence Matrix searches a birthtime interval for exact, event-category contacts across multiple events. It groups their birthtime landings into candidate bands and displays the five strongest non-overlapping bands. Each distinct event contributes at most one vote and one selected contact's points within a band.

USE THE MODULE

01 Enter the name, birth date, interval start/end, latitude, west-positive longitude and historical offset or LMT basis. Both endpoints must belong to the entered birth date. Use Search city to fill coordinates online, or enter them directly.

02 Choose Mean or True Node and direct/converse scope. Set Minimum Isaac points, initially 1, and choose all weighted pairs or pairs with at least one house cusp. These controls determine which exact contacts are eligible.

03 Use Import events... to open a Rectifier event file. The recognized columns are Date, Category, Description, Use and Mode. Choose Replace current events or Add to current events before importing. Scoring rows become Find candidates; validation rows become Check candidates. Events can also be entered manually.

04 Assign Find candidates to events used to determine the bands and Check candidates to reserved events. Blank dates are skipped. Keep automatic calculation enabled or click Calculate matrix after preparing the biography.

05 Choose the band width. The current default is 15 seconds, with 15-, 30- and 60-second buttons. Select ranking by Isaac points, then event count or Event count, then Isaac points. Each event's automatic representative is its highest-point qualifying contact in the band.

06 Compare the candidate columns and their Find and Check support. Click a cell to inspect every contact for that event inside the band. A dash means no qualifying contact. Open the representatives to choose between the two leading contacts, or use Use automatic contact choices to restore automatic selection.

07 Save/open the project, export all contacts as CSV, or load the supplied example. View database opens the rectified-record collection. Undo project reset can recover a reset project when available.

RESULT VIEW

The completed candidate-band matrix with Find/Check support and one contact cell opened for inspection.

READING THE RESULTS

Find events determine ranking; Check events report independent support. Identical date/category rows count once, and a Find event cannot also provide an independent Check vote. Band width controls the grouping of exact birthtime landings, rather than the orb of a displayed aspect. The five bands provide candidate regions for further inspection, with the underlying contacts retained for audit and export.

The method uses the calendar-date Naibod key. Online city search requires a connection; calculations are local. Save the project to retain input data and contact choices. Review the contacts supporting a band alongside its point total and reserved-event support.

28 Topocentric Exact Contact Navigator

TPD_ContactNavigator.html

The Exact Contact Navigator finds the nearest earlier and later birthtimes at which a category-relevant primary-direction contact becomes exact for one event. You can jump between those candidate times while inspecting the current primary-direction list. It searches birthtime, rather than searching when an event contact matures.

USE THE MODULE

01 Enter the birth date and starting candidate time in HH:MM:SS, with optional fractional seconds. Enter coordinates and the historical UTC offset or LMT basis. Longitude is west positive. Choose Mean or True Node.

02 Set the search distance on either side: fifteen minutes, one hour, six hours or to each end of the birth date. The search never leaves that date.

03 Enter the event date and category, then choose direct/converse scope. Event time is not used because the method retains the date-only Naibod key.

04 Click Find neighboring exact contacts. The earlier and later cards show the nearest qualifying candidate on each side. A result’s proximity takes priority over the order of factors in the category.

05 Select an earlier/later result to move the candidate time and inspect the associated current primary directions. Repeat the neighbouring search to explore another landing. Equivalent contacts at the same time are presented together.

06 Review Jump history so you can follow the sequence you examined. Return to starting birthtime restores the original point. Save/open inputs as JSON for a repeatable investigation.

RESULT VIEW

The earlier/later exact-contact cards after a search, together with the current candidate's primary-direction list.

READING THE RESULTS

Both listed cusp → planet and planet → cusp orientations qualify. The search includes all nine aspect types and all twelve cusps. Natal positions, houses and direction geometry are recalculated at each tested birthtime. Half-second sampling brackets crossings and millisecond refinement supplies a small residual, which is shown in details. A contact already exact within 0.01 birthtime seconds is treated as current and excluded from the next/previous search.

Use the navigator when examining one event and a nearby candidate; use TBCM when you want exact-contact landings from several events grouped into bands. The nearest partile contact need not be the most persuasive contact or the best overall birthtime. Latitude must be below 66° north/south, and unsupported circumpolar geometry produces an error. Category 19 remains disabled. All calculation data are embedded for offline use.

29 Topocentric Primary Directions

TopocentricPrimaryDirections.html

This is the main Topocentric Primary Directions calculator. It calculates direct and converse directions for one event date, ordered by absolute orb, or exact maturities over a date interval. It includes the Kühr proportional-pole treatment, Topocentric cusps, a Naibod date key and event-category table highlighting.

USE THE MODULE

01 Enter birth date, local time to seconds, historical offset or LMT basis and coordinates. Longitude is west positive. The optional city lookup fills coordinates; save a city for offline reuse. It does not determine the historical offset.

02 Choose the Node and Fortune conventions. Mean Node is the initial setting. Fortune is always a natal target; Also use Part of Fortune as a directed source adds moving Fortune. Use Check natal positions to inspect the speculum and chart constants.

03 Choose Single date and enter the event date for a within-orb list. Alternatively, choose Date range, enter start/end dates and calculate exact maturities. Neither mode needs an event clock time.

04 Select an event category, then click Calculate & sort directions. Direct and converse results are interleaved. Single-date results show forming/separating status and are strictly sorted by absolute orb.

05 Enable Show surrounding directions (+6′) only to broaden a single-date inspection. Normal limits are under 12′ for conjunction/opposition and under 6′ for other aspects; extended results reach the larger limits and are marked nearby.

06 Leave redundant-axis suppression in place for a compact list, or enable all cusps/opposite-angle/Node-axis equivalents to inspect alternate expressions. Click any result row for its calculation trace.

07 Copy the displayed list, export contacts/speculum as CSV or print. Category changes update highlighting and points without changing the calculated orb order.

RESULT VIEW

An orb-sorted calculated direction list with Isaac highlighting and one expanded calculation trace.

READING THE RESULTS

Single-date highlights require at least 4 table points; date-list highlights identify every positive-scoring maturity. The event category can select the displayed end of an intermediate-cusp axis, with a complementary aspect label. Expanded details preserve the original contact. Blank/unidentified table mappings do not receive invented points.

The arc is elapsed calendar days × 0.00269861°. Range mode solves exact crossings and assigns the maturity to the nearest calendar date. Birth seconds affect the natal geometry, but an event clock time does not enter the key. All nine aspects are supported; cusp-to-cusp directions are conjunction/opposition only. The ordinary semi-arc method requires latitude below 66° north/south and non-circumpolar factors. The embedded ephemeris covers 1800-2399.

30 Topocentric Primary Directions: Radix and Epoch

TopocentricPrimaryDirections2.html

This version extends the primary-direction calculator to two charts, Radix and Epoch. It displays four routes: directed Epoch to original Epoch, directed Radix to original Radix, directed Epoch to original Radix and directed Radix to original Epoch. Each source uses its own date and geometry.

USE THE MODULE

01 Enter the Epoch chart in its own entry area: date, local time, time basis/offset, coordinates and optional label. Enter the Radix separately. Longitude is west positive for both. Each chart has a city lookup and natal-position/speculum inspection.

02 Replace either chart's data independently using its time-adjustment and clear controls. Leave one chart empty if you only need the other chart's self-comparison. Both charts are required for cross-comparisons.

03 Choose shared axis-expansion and directed-Fortune options. Select Single date or Date range, enter the event or interval and choose the common event category.

04 Click Calculate & sort directions. Read E, R, E/R and R/E as source/target routes, not direct/converse labels. Direct/converse motion remains a separate property of each contact.

05 Examine the orb-sorted lists and Highlighted only view. Show surrounding directions (+6′) applies to single-date results. Equivalent axis expressions can be expanded when needed.

06 Click a result for its calculation trace and inspect the relevant source chart's speculum. Copy, export CSV or print the displayed results. Changing an Epoch or Radix time requires recalculation of the affected comparisons.

RESULT VIEW

The populated E, R, E/R and R/E direction lists, with their route labels and a selected category visible.

READING THE RESULTS

E/R directs the Epoch chart using its elapsed interval to the event and tests against fixed Radix targets. R/E reverses those chart roles. It does not direct one chart and then compare against a separately directed second chart. The program accepts Epoch as supplied input; it does not find the Epoch date automatically. Use EpochFinder.html first if you need its lunar-crossing candidates.

The underlying calculation retains the main TPD tool's Kühr geometry, Naibod calendar-day key, nine aspects and standard single-date limits. Event-category weights guide highlighting without altering orb order. Each chart has its own historical offset, and the event is a calendar date rather than a timed instant. Check both charts before interpreting interaction contacts, especially if their locations or time conventions differ.

31 TPD Anchor Mapper

TPD_AnchorMapper.html

Find exact birthtimes implied by high-scoring event contacts and compare their convergence in birthtime and RAMC.

USE THE MODULE

01 Enter birth data, historical offset, west-positive longitude and the birthtime range, or open a Polaris2 project. Add or import events, or choose a case through View Database.

02 Set root search step, motion, aspect scope and orb limits. Choose whether to include Mean Node and Fortune, then click Find exact solutions.

03 Filter the solved contacts to 25 points, 20 and 25, or 16, 20 and 25. Choose all cusps or angles only. Set cluster radius in birthtime seconds and minimum distinct scoring events.

04 Inspect diamonds, orb windows, the event-convergence strip and cluster table. Show top 3 separate bands marks distinct leading regions. Click a diamond or Inspect to pin an anchor; Clear anchor removes it.

05 Export solutions or clusters as CSV. Export interval for Polaris2 supplies the selected cluster's centre plus/minus radius, or the selected anchor's orb window, clipped to the search range.

RESULT VIEW

The solved birthtime/RAMC map, event-convergence strip and leading clusters, with one diamond selected as an anchor.

READING THE RESULTS

Only planet/point-to-cusp contacts with 16, 20 or 25 Isaac points are solved. A cluster uses at most one solution per scoring event; validation events do not rank clusters. Month-only dates use the 15th. Weight and cluster filters update without solving again; motion, Node/Fortune, aspects and orb changes require another search.

32 TPD Bi-Wheel

TPD_BiWheel.html

Inspect natal positions on the inner wheel and Topocentric Primary Directions on the outer wheel for a selected date.

USE THE MODULE

01 Enter birth data with historical UTC offset or local mean time. Longitude is west positive. Online city lookup fills coordinates only; saved cities can be reused offline.

02 Choose Mean or True Node and the Fortune formula. Use Check natal positions when verifying the inputs. Small time-adjustment buttons support candidate comparisons.

03 In the bi-wheel view, set Direction date, choose Direct or Converse and click Draw directions. Today supplies the current date. Choose all twelve cusps/both axis ends and Direct Fortune as needed.

04 Inspect the contacts beside the wheel, ordered by absolute orb. Click an aspect in the list to isolate its connection; click again to restore all contact lines. Save wheel SVG exports the chart.

RESULT VIEW

The generated inner natal/outer directed wheel and its contact list. Select one contact to show its isolated connection.

READING THE RESULTS

The bi-wheel uses the Kuehr proportional-pole geometry, Topocentric cusps and the Naibod calendar-day key. Its displayed limits are 11 arcminutes for conjunction/opposition and 6 for other aspects. Cusp-to-cusp contacts use conjunction/opposition only.

Every outer factor has its own directed longitude. Both ends of each house axis are drawn independently; equivalent axis contacts are related geometrically. The wheel does not infer an event category. The embedded calculation engine runs offline.

33 TPD Event Meters

TPD_Event_Meters.html

See weighted Topocentric Primary Direction scores across an entire event list. A compact meter for each event shows the sum of relevant Isaac weights, with the underlying directions available for inspection.

USE THE MODULE

01 Load a rectified chart from the searchable database, use James's example, or enter birth data manually. Online city lookup fills coordinates. Check the birthtime, historical offset and west-positive longitude.

02 Import an event file or database, set the slash-date order when needed, or Add event manually. Review which events are included and their event categories. Month-only events use the 15th with an extra 2.5 arcminutes.

03 Review the conjunction/opposition and other-aspect orbs, then click Calculate meters. The supplied reference scale uses 11 and 6 arcminutes. Direct and converse directions, Mean Node and Pars Fortuna are included.

04 Read the average points per checked event beside the event count. Use the minus/plus one-second controls to recalculate at nearby birthtimes. Selected events only and Extra compact adjust the grid.

05 Choose Direct + converse, Direct only or Converse only. Click a meter to inspect its directions. Export scores saves the event results; event rows can be edited or excluded.

RESULT VIEW

A populated event grid with weighted meters, the average score per event, and one meter's detailed TPD list.

READING THE RESULTS

The meter turns green at 12 points; scores from 0 to 11 remain red. Its needle stops at 75, while the number still shows the full score. The fixed scale supports visual comparison across the event list.

The weighted total sums Isaac values. Equivalent house-axis contacts count once. Mean Node is always used, and Pars Fortuna uses Ascendant + Moon - Sun.

The supplied offline ephemeris span is 1800-2399. The meters provide an event-by-event view of weighted contacts, rather than a cross-system combined score.

34 TPD Event Timeline

TPD_Event_Timeline.html

Place checked life events on a calendar and read their related primary directions below it. This complements TPD Pair Timeline, which follows the possible aspects between two selected factors.

USE THE MODULE

01 Choose a person in the searchable chart database to load birth data and checked events. The date range follows the first and last recorded events.

02 For manual entry, supply the birth date, local time, historical UTC offset and coordinates. Longitude is west positive. Birth options include local mean time, Mean or True Node and the Part of Fortune formula. Online city lookup supplies coordinates; check the offset separately.

03 Import events or a database, load James's events, or edit the selected events. Check the slash-date order for imported dates. Use Fit period to events, Check all, Uncheck all and Vertical category labels as required.

04 Set the period and orb limits, choose Direct and/or Converse, then click Draw timeline. When calculation finishes, the page scrolls to the timeline. The supplied limits are 11 arcminutes for conjunction/opposition and 6 for other aspects.

05 Read Related TPDs at each event. Only in-orb contacts with positive Isaac points appear. Highest points come first; ties use factor names. Equivalent axis contacts appear once, labelled at the event-relevant cusp where appropriate. Hover or select events and contacts to inspect them; zoom or return to the full event period.

RESULT VIEW

A calculated life-event calendar and Related TPDs at each event, ordered by Isaac points and labelled at event-relevant cusps.

READING THE RESULTS

Pre-birth events can appear on the calendar; direction calculations begin after birth. Month-only events use the 15th and carry an asterisk. The embedded database and calculation engine work offline. Exact dates follow the source's calendar-day Naibod convention.

35 TPD Pair Timeline

TPD_Pair_Timeline.html

Follow the primary-direction contacts between two selected factors on one calendar. The two direction tracks show A toward natal B and B toward natal A. A third track above them places checked life events on the same date scale.

USE THE MODULE

01 Choose a chart from the searchable database to load its birth data and checked events. The displayed period runs from its first recorded event to its last.

02 Alternatively, enter birth data and a date range manually. Enter the historical UTC offset at birth. Find city online fills coordinates; check the offset separately. Birth options include local mean time, the lunar node and the Part of Fortune formula.

03 Select Factor A and Factor B, choose Direct and/or Converse, then click Draw timeline. The track label names the directed factor first. Filled dots indicate direct directions; outline dots indicate converse directions.

04 Each dot extends horizontally from orb entry to orb exit at the current calendar scale. The supplied limits are 11 arcminutes for conjunction/opposition and 6 arcminutes for other aspects. Glyphs mark exact contacts. Dimmed glyphs identify spans whose exact contact lies outside the displayed period.

05 Import an event file or database, load James's events, or select another database chart. Check the slash-date order when importing. Fit period to events sets the calendar from the loaded events. Check or uncheck events and enable Vertical category labels as needed.

06 Hover over a contact for its date and direction. Hover over an event for its description. Click an event to open its in-orb primary directions with positive Isaac points. Choose the event category and sort by smallest orb or highest Isaac points.

RESULT VIEW

The two populated A-to-B and B-to-A direction tracks aligned with life events. A detail image can show an event's in-orb contacts.

READING THE RESULTS

Equivalent opposite-cusp and Node contacts share a row in the event-aspect window. A label such as "+1 equivalent" counts another equivalent representation of that contact, rather than an extra Isaac point.

Pre-birth events can be displayed; direction calculations begin after birth. Month-only events use the 15th and carry an asterisk. Calculations use the bundled Kühr/topocentric geometry and Naibod key. City lookup requires internet access; the calculation engine and supplied chart database are embedded.

36 TPD Three Birth Times

TPD_3xCompare.html

TPD Three Birth Times compares three candidate birthtimes side by side for one birth date, place, event and category. Each panel shows that candidate’s direct/converse primary directions, while table weights rank the candidates by total unique contact points or strongest single contact.

USE THE MODULE

01 Enter the common birth date, birthplace, historical offset/time basis and Node/Fortune settings. Longitude is west positive; the optional city search and saved-city list operate as in the main TPD calculator.

02 Enter all three candidate local times in their separate hour/minute/second fields. The small adjustment buttons and natal-position check apply to candidate 1, so edit candidates 2 and 3 directly when testing alternatives.

03 Enter the event date and select the shared category. The three-candidate scoring comparison is intended for one event date. Keep common factor, axis and Fortune options consistent across the panels.

04 Choose Total unique contact points or Strongest single contact under Rank candidates by, then calculate. The best-scoring candidate panel is marked. Read each panel’s aspect list alongside its score rather than comparing only the nearest orb.

05 Click Show only highlighted tiles to show positive table-weight contacts across all three panels. Unlike the main calculator’s four-point single-date highlight threshold, this comparison marks every positive stored weight.

06 Use Show surrounding directions (+6′) to inspect nearby contacts. Out-of-standard-orb directions do not contribute to the comparison score even when visible.

07 Export the comparison CSV for all three candidates, or use the list-copy/CSV/print controls as appropriate. Result rows provide calculation traces; the speculum control concerns candidate 1.

RESULT VIEW

All three populated candidate panels, their scores and the marked best candidate. Keep the chosen ranking method visible.

READING THE RESULTS

Total points count opposite-axis equivalents once. Direct/converse contacts and distinct directed/natal orientations retain their own identities. Strongest single contact measures the best one contact, while Total unique contact points accumulates all qualifying scored contacts for that event. Those ranking choices can favour different times. The event key remains date-only, with standard single-date limits under 12′ for conjunction/opposition and under 6′ otherwise. This is a close comparison of three supplied times, not a scan of all intervening seconds or a multi-event rectification.