

732A54 - Big Data Analytics

BDA2 Spark SQL Exercises

Ashraf Sarhan (ashsa762)

Assignment 1

Questions:

- year, station with the max, maxValue ORDER BY maxValue DESC
- year, station with the min, minValue ORDER BY minValue DESC

Code:

```
#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""
from pyspark import SparkContext
from pyspark.sql import SQLContext, Row

iFile = 'data/temperature-readings.csv'
oFile1 = 'data/sql_max_temperature'
oFile2 = 'data/sql_min_temperature'

sc = SparkContext(appName = "MinMaxTempExtractorSparkSQLJob")

sqlContext = SQLContext(sc)

inFile = sc.textFile(iFile) \
    .map(lambda line: line.split(";")) \
    .map(lambda obs: \
        Row(station = obs[0], date = obs[1], \
            year = obs[1].split("-")[0], time = obs[2], \
            temp = float(obs[3]), quality = obs[4]))

tempSchema = sqlContext.createDataFrame(inFile)

tempSchema.registerTempTable("TempSchema")

"""
Q1. year, station with the max, maxValue ORDER BY maxValue DESC
"""
maxTemp = sqlContext.sql("""
```

```

        SELECT DISTINCT(table1.year) AS year,
            FIRST(table1.station) AS station,
            FIRST(temp) AS temp
        FROM TempSchema AS table1
        INNER JOIN
        (
            SELECT year, MAX(temp) AS max_temp
            FROM TempSchema
            GROUP BY year
        ) AS table2
        ON table1.year = table2.year
        WHERE table1.temp = table2.max_temp
        GROUP BY table1.year
        ORDER BY temp DESC
        """
    )

maxTemp = maxTemp.rdd.repartition(1)\
    .sortBy(ascending = False, keyfunc = lambda \
        (year, station, temp): temp)

maxTemp.saveAsTextFile(oFile1)

"""
Q2. year, station with the min, minValue ORDER BY minValue DESC
"""
minTemp = sqlContext.sql("""
    SELECT DISTINCT(table1.year) AS year,
        FIRST(table1.station) AS station,
        FIRST(temp) AS temp
    FROM TempSchema AS table1
    INNER JOIN
    (
        SELECT year, MIN(temp) AS min_temp
        FROM TempSchema
        GROUP BY year
    ) AS table2
    ON table1.year = table2.year
    WHERE table1.temp = table2.min_temp
    GROUP BY table1.year
    ORDER BY temp DESC
    """
)

minTemp = minTemp.rdd.repartition(1)\
    .sortBy(ascending = False, keyfunc = lambda \
        (year, station, temp): temp)

minTemp.saveAsTextFile(oFile2)

```

Max Temp:

```
print maxTemp.take(10)
[Row(year=u'1975', station=u'86200', temp=36.1),
 Row(year=u'1992', station=u'63600', temp=35.4),
 Row(year=u'1994', station=u'117160', temp=34.7),
 Row(year=u'2014', station=u'96560', temp=34.4),
 Row(year=u'2010', station=u'75250', temp=34.4),
 Row(year=u'1947', station=u'53770', temp=34.3),
 Row(year=u'1989', station=u'63050', temp=33.9),
 Row(year=u'1982', station=u'94050', temp=33.8),
 Row(year=u'1968', station=u'137100', temp=33.7),
 Row(year=u'1966', station=u'151640', temp=33.5)]
```

Min Temp:

```
print minTemp.take(10)
[Row(year=u'1944', station=u'108320', temp=-10.4),
 Row(year=u'1943', station=u'108320', temp=-13.5),
 Row(year=u'1941', station=u'108320', temp=-21.0),
 Row(year=u'1946', station=u'139570', temp=-26.0),
 Row(year=u'1945', station=u'139570', temp=-26.3),
 Row(year=u'1948', station=u'139570', temp=-30.0),
 Row(year=u'1947', station=u'139570', temp=-32.0),
 Row(year=u'1942', station=u'66120', temp=-32.4),
 Row(year=u'1990', station=u'147270', temp=-35.0),
 Row(year=u'1949', station=u'167980', temp=-35.0)]
```

Assignment 2

Questions:

- year, month, value ORDER BY value DESC
- year, month, value ORDER BY value DESC

Code:

```
#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""
from pyspark import SparkContext
from pyspark.sql import SQLContext, Row
```

```

from pyspark.sql import functions as F

iFile = 'data/temperature-readings.csv'
oFile = 'data/sql_over_ten_temp_distinct_counts'

sc = SparkContext(appName = "TempCounterSparkSQLJob")

sqlContext = SQLContext(sc)

inFile = sc.textFile(iFile) \
    .map(lambda line: line.split(";")) \
    .map(lambda obs: \
        Row(station = obs[0], date = obs[1], \
            year = obs[1].split("-")[0], \
            month = obs[1].split("-")[1], time = obs[2], \
            yymm = obs[1][:7], \
            temp = float(obs[3]), quality = obs[4]))

tempSchema = sqlContext.createDataFrame(inFile)

tempSchema.registerTempTable("TempSchema")

"""
Q1. Temperatures readings higher than 10 degrees
"""
overTenTemp = sqlContext.sql(" \
    SELECT FIRST(year), FIRST(month), COUNT(temp) AS counts\
    FROM TempSchema \
    WHERE temp >= 10 AND year >= 1950 AND year <= 2014\
    GROUP BY year, month \
    ORDER BY counts DESC")

"""
Q2. Distinct Temperatures readings higher than 10 degrees
"""
overTenTempDistinct = tempSchema.filter(tempSchema["temp"] > 10) \
    .groupBy("yymm") \
    .agg(F.countDistinct("station").alias("count"))

overTenTempDistinct = overTenTempDistinct.rdd.repartition(1) \
    .sortBy(ascending = False, keyfunc = lambda \
        (yymm, counts): counts)

overTenTempDistinct.saveAsTextFile(oFile)

```

Distinct Temperatures readings counts:

```

print overTenTempDistinct.take(10)
[Row(yymm=u'1972-10', count=378),
 Row(yymm=u'1973-05', count=377),

```

```

Row(yymm=u'1973-06', count=377),
Row(yymm=u'1973-09', count=376),
Row(yymm=u'1972-08', count=376),
Row(yymm=u'1972-05', count=375),
Row(yymm=u'1972-06', count=375),
Row(yymm=u'1972-09', count=375),
Row(yymm=u'1971-08', count=375),
Row(yymm=u'1972-07', count=374)]

```

Assignment 3

Questions:

- year, month, station, avgMonthlyTemperature ORDER BY avgMonthlyTemperature DESC

Code:

```

#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""
from pyspark import SparkContext
from pyspark.sql import SQLContext, Row

iFile = 'data/temperature-readings.csv'
oFile = 'data/sql_station_avg_mth_temp'

sc = SparkContext(appName="AvgTempSparkSQLJob")

sqlContext = SQLContext(sc)

inFile = sc.textFile(iFile) \
    .map(lambda line: line.split(";")) \
    .filter(lambda obs:
        (int(obs[1][:4]) >= 1960 and
         int(obs[1][:4]) <= 2014)) \
    .map(lambda obs: Row(station=int(obs[0]),
                        day=obs[1],
                        month=obs[1][:7],
                        temp=float(obs[3])))

tempSchema = sqlContext.createDataFrame(inFile)

tempSchema.registerTempTable("TempSchema")

avgMonthTemp = sqlContext.sql(

```

```

        """
        SELECT mytbl.month, mytbl.station, AVG(mytbl.max_temp + mytbl.min_temp) / 2 AS avg_temp
        FROM
        (
        SELECT month, station, MIN(temp) AS min_temp, MAX(temp) AS max_temp
        FROM TempSchema
        GROUP BY day, month, station
        ) AS mytbl
        GROUP BY mytbl.month, mytbl.station
        ORDER BY AVG(mytbl.max_temp + mytbl.min_temp) / 2 DESC
        """

    )

avgMonthTemp.rdd.repartition(1).sortBy(ascending=False,
                                       keyfunc=lambda (month, station, temp): temp)

avgMonthTemp.saveAsTextFile(oFile)

```

Average monthly temperatures:

```

print avgMonthTemp.take(10)
[Row(month=u'2014-07', station=96000, avg_temp=26.3),
 Row(month=u'1994-07', station=96550, avg_temp=23.07105263157895),
 Row(month=u'1983-08', station=54550, avg_temp=23.0),
 Row(month=u'1994-07', station=78140, avg_temp=22.970967741935485),
 Row(month=u'1994-07', station=85280, avg_temp=22.872580645161293),
 Row(month=u'1994-07', station=75120, avg_temp=22.858064516129033),
 Row(month=u'1994-07', station=65450, avg_temp=22.856451612903232),
 Row(month=u'1994-07', station=96000, avg_temp=22.808064516129033),
 Row(month=u'1994-07', station=95160, avg_temp=22.764516129032256),
 Row(month=u'1994-07', station=86200, avg_temp=22.711290322580645)]

```

Assignment 4

Questions:

- station, maxTemp, maxDailyPrecipitation ORDER BY station DESC

Code:

```

#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""

```

```

from pyspark import SparkContext
from pyspark.sql import SQLContext, Row

iFile = 'data/temperature-readings.csv'
iFile2 = 'data/precipitation-readings.csv'
oFile = 'data/sql_max_temperature_precipitation'

sc = SparkContext(appName="MaxTempPrecExtractorSparkSQLJob")

sqlContext = SQLContext(sc)

# Temperatures
inFile = sc.textFile(iFile).map(lambda line: line.split(";")) \
    .map(lambda obs: Row(station=int(obs[0]),
                        temp=float(obs[3])))

tempSchema = sqlContext.createDataFrame(inFile)
tempSchema.registerTempTable("TempSchema")

# precipitation
inFile2 = sc.textFile(iFile2).map(lambda line: line.split(";")) \
    .map(lambda obs: Row(station=int(obs[0]),
                        day=obs[1],
                        precip=float(obs[3])))

precSchema = sqlContext.createDataFrame(inFile2)
precSchema.registerTempTable("PrecSchema")

combinedTempPrec = sqlContext.sql(
    """
    SELECT tr.station, MAX(temp) AS max_temp, MAX(precip) AS max_precip
    FROM
    TempSchema AS tr
    INNER JOIN
    (
    SELECT station, SUM(precip) AS precip
    FROM PrecSchema
    GROUP BY day, station
    ) AS pr
    ON tr.station = pr.station
    WHERE temp >= 25 AND temp <= 30
    AND precip >= 100 AND precip <= 200
    GROUP BY tr.station
    ORDER BY tr.station DESC
    """
)

combinedTempPrec.rdd.repartition(1).sortBy(ascending=False,
    keyfunc=lambda (station, temp, precip): station)

combinedTempPrec.saveAsTextFile(oFile)

```

Max daily precipitation:

```
print combinedTempPrec.take(10)
[Row(station=97510, max_temp=30.0, max_precip=103.99999999999999),
Row(station=75250, max_temp=30.0, max_precip=101.8),
Row(station=71420, max_temp=30.0, max_precip=106.3),
Row(station=52350, max_temp=30.0, max_precip=101.6)]
```

Assignment 5

Questions:

- station, maxTemp, maxDailyPrecipitation ORDER BY station DESC

Code:

```
#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""
from pyspark import SparkContext
from pyspark.sql import SQLContext, Row

iFile = 'data/stations-Ostergotland.csv'
iFile2 = 'data/precipitation-readings.csv'
oFile = 'data/OstergotlandAveMonthlyPrec'

sc = SparkContext(appName="OstergotlandAvgMonthlyPrecSparkSQLJob")

sqlContext = SQLContext(sc)

# Ostergotland Stations
ostergotlandStations = sc.textFile(iFile).map(lambda line: line.split(";")) \
    .map(lambda obs: int(obs[0])) \
    .distinct().collect()

ostergotlandStations = sc.broadcast(ostergotlandStations)

ostergotlandStations = {station: True for station in ostergotlandStations.value}

precipitations = sc.textFile(iFile2).map(lambda line: line.split(";")) \
    .filter(lambda obs: ostergotlandStations.get(int(obs[0]), False)) \
    .map(lambda obs: Row(day=obs[1],
                        month=obs[1][:7],
                        station=int(obs[0]),
```



```

precip=float(obs[3]))

precSchema = sqlContext.createDataFrame(precipitations)
precSchema.registerTempTable("PrecSchema")

avgMthPrec = sqlContext.sql(
    """
    SELECT mytbl2.month, AVG(mytbl2.precip) AS avg_precip
    FROM
    (
    SELECT mytbl1.month, mytbl1.station, SUM(mytbl1.precip) AS precip
    FROM
    (
    SELECT month, station, SUM(precip) AS precip
    FROM PrecSchema
    GROUP BY day, month, station
    ) AS mytbl1
    GROUP BY mytbl1.month, mytbl1.station
    ) AS mytbl2
    GROUP BY mytbl2.month
    ORDER BY mytbl2.month DESC
    """
)

avgMthPrec.rdd.repartition(1).sortBy(ascending=False, keyfunc=lambda (month, precip): month)

avgMthPrec.saveAsTextFile(oFile)

```

Östergotland average monthly precipitation:

```

print avgMthPrec.take(10)
[Row(month=u'2016-07', avg_precip=0.0),
 Row(month=u'2016-06', avg_precip=47.6625),
 Row(month=u'2016-05', avg_precip=29.250000000000004),
 Row(month=u'2016-04', avg_precip=26.9),
 Row(month=u'2016-03', avg_precip=19.9625),
 Row(month=u'2016-02', avg_precip=21.5625),
 Row(month=u'2016-01', avg_precip=22.325),
 Row(month=u'2015-12', avg_precip=28.925),
 Row(month=u'2015-11', avg_precip=63.887499999999996),
 Row(month=u'2015-10', avg_precip=2.2625)]

```

Assignment 6

Questions:

- Year, month, difference ORDER BY year DESC, month DESC

Code:

```
#!/usr/bin/env python2
# -*- coding: utf-8 -*-
"""
Created on Mon Dec 12 17:06:24 2016

@author: ashraf
"""
from pyspark import SparkContext
from pyspark.sql import SQLContext, Row

iFile = 'data/stations-Ostergotland.csv'
iFile2 = 'data/temperature-readings.csv'
oFile = 'data/OstergotlandAveMonthlyDiffTemp'

sc = SparkContext(appName="OstergotlandAvgMonthlyTempDiffSparkSQLJob")

sqlContext = SQLContext(sc)

# Ostergotland Stations
ostergotlandStations = sc.textFile(iFile).map(lambda line: line.split(";")) \
    .map(lambda obs: int(obs[0])) \
    .distinct().collect()

ostergotlandStations = sc.broadcast(ostergotlandStations)

ostergotlandStations = {station: True for station in ostergotlandStations.value}

temperatures = sc.textFile(iFile2) \
    .map(lambda line: line.split(";")) \
    .filter(lambda obs: ostergotlandStations.get(int(obs[0]), False)) \
    .map(lambda obs: \
        Row(station = obs[0], \
            date = obs[1], \
            year = obs[1].split("-")[0], \
            month = obs[1].split("-")[1], \
            day = obs[1].split("-")[2], \
            yymm = obs[1][:7], \
            yymmdd = obs[1], \
            time = obs[2], \
            temp = float(obs[3]), \
            quality = obs[4]))

tempSchema = sqlContext.createDataFrame(temperatures)
tempSchema.registerTempTable("TempSchema")

avgMthTemp = sqlContext.sql("""
    SELECT one.yyymm,
           AVG(one.minTemp + one.maxTemp) / 2 AS avgTemp
    FROM
    (
    SELECT yyymm,
```

```

        year,
        yymmdd,
        MIN(temp) AS minTemp,
        MAX(temp) AS maxTemp
    FROM TempSchema
    GROUP BY yymmdd,
            yymm,
            year,
            station
    ) AS one
    WHERE one.year >= 1950 AND one.year <= 2014
    GROUP BY one.yymm
    """)

longTermAvgTemp = avgMthTemp \
    .filter(F.substring(avgMthTemp["yymm"], 1, 4) <= 1980) \
    .groupBy(F.substring(avgMthTemp["yymm"], 6, 7).alias("month")) \
    .agg(F.avg(avgMthTemp["avgTemp"]).alias("longTermAvgTemp"))

diffTemp = avgMthTemp.join(longTermAvgTemp,
    (F.substring(avgMthTemp["yymm"], 6, 7) ==
    longTermAvgTemp["month"]), "inner")

diffTemp = diffTemp.select(diffTemp["yymm"],
    (F.abs(diffTemp["avgTemp"]) -
    F.abs(diffTemp["longTermAvgTemp"])).alias("diffTemp"))

diffTemp = diffTemp.rdd.repartition(1).sortBy(ascending = False,
    keyfunc = lambda (yymm, diff): yymm)

diffTemp.saveAsTextFile(oFile)

```

Östergötland average monthly precipitation temperature difference:

```

print diffTemp.take(10)
[Row(yymm=u'2014-12', diffTemp=-0.7938517834097853),
 Row(yymm=u'2014-11', diffTemp=2.0635396726928987),
 Row(yymm=u'2014-10', diffTemp=1.521957490617976),
 Row(yymm=u'2014-09', diffTemp=0.06105818643722749),
 Row(yymm=u'2014-08', diffTemp=-0.6426470719706963),
 Row(yymm=u'2014-07', diffTemp=2.1059218387139893),
 Row(yymm=u'2014-06', diffTemp=-1.8073686197315233),
 Row(yymm=u'2014-05', diffTemp=0.26719065014070154),
 Row(yymm=u'2014-04', diffTemp=2.0661931589915437),
 Row(yymm=u'2014-03', diffTemp=3.176498950234642)]

```