



INTRODUCTION TO PROGRAMMING LANGUAGE II(JAVA)

Fariha Zahin
Lecturer
CSE, Southeast University

super keyword:

It is used to refer to the immediate **parent class** object.

•Helps access:

- Parent class constructor
- Parent class methods
- Parent class data members

Using super to Access Parent Class Variables

In this code, the Child class has a variable x that hides the x variable from its Parent class. Inside the display method of Child, super.x is used to access the x from the parent class (value 10), rather than the one in the child class (value 20). This shows how super can resolve variable name conflicts in inheritance.

```
class Parent {  
    int x = 10;  
}  
  
class Child extends Parent {  
    int x = 20;  
  
    void display() {  
        System.out.println(super.x); // Outputs 10  
    }  
}
```

Using super to Call Parent Class Method

The Child class overrides the greet method of the Parent class. Inside the child's version of greet, super.greet is used to call the original method from the parent before printing its own message. This demonstrates how to invoke a superclass method when it is overridden in the subclass.

```
class Parent {  
    void greet() {  
        System.out.println("Hello from Parent");  
    }  
}  
  
class Child extends Parent {  
    @Override  
    void greet() {  
        super.greet();  
        System.out.println("Hello from Child");  
    }  
}
```

Using super to Call Parent Constructor

super() must be the first statement in a constructor if used.

Here, the Child class constructor explicitly calls the no-argument constructor of the Parent class using super. This ensures the parent constructor runs first before executing the child constructor's code. It illustrates how constructor chaining works between parent and child classes in Java.

```
class Parent {  
    Parent() {  
        System.out.println("Parent constructor called");  
    }  
}  
  
class Child extends Parent {  
    Child() {  
        super(); // Optional if no-arg constructor  
        System.out.println("Child constructor called");  
    }  
}
```

In this example, the Student class extends Person, and both have constructors that accept parameters. The Student constructor uses super to call the Person constructor and initialize the inherited name field. The main method creates a Student object, showing how both constructors are executed and how values are initialized through inheritance.

```
class Person {  
    String name;  
    Person(String name) {  
        this.name = name;  
        System.out.println("Person constructor called");  
    }  
}  
  
class Student extends Person {  
    int id;  
    Student(String name, int id) {  
        super(name);  
        this.id = id;  
        System.out.println("Student constructor called");  
    }  
}
```

super vs this

super → refers to the immediate parent class object

this → refers to the current object

They can be used together when necessary.

20
20
10

Main.java ×

```
1  class Parent { 1 usage 1 inheritor
2      int x = 10; 1 usage
3  }
4
5  class Child extends Parent { 2 usages
6      int x = 20; 2 usages
7
8      void show() { 1 usage
9          System.out.println(x);           // 20 (Child's x)
10         System.out.println(this.x);       // 20 (explicitly current object's x)
11         System.out.println(super.x);      // 10 (Parent's x)
12     }
13 }
14
15 public class Main {
16     public static void main(String[] args) {
17         Child c = new Child();
18         c.show();
19     }
20 }
```


Constructor Chaining

When constructors call other constructors (in the same class or in the parent class) to avoid code duplication and ensure proper initialization.

Two ways:

1. `this(...)` → calls another constructor **in the same class**
2. `super(...)` → calls a constructor **in the immediate parent class**

```
Main.java x
1  @  class Person { 1 usage 1 inheritor
2      String name; 1 usage
3      int age; 1 usage
4
5      // Constructor 1 (no-arg)
6      Person() { 1 usage
7          this( name: "Unknown", age: 0); // chaining inside sa
8          System.out.println("Person() called");
9      }
10
11     // Constructor 2 (one-arg)
12     Person(String name) { no usages
13         this(name, age: 0); // chaining inside same cla
14         System.out.println("Person(String) called");
15     }
16
17     // Constructor 3 (two-arg) - the "main" one
18     Person(String name, int age) { 3 usages
19         this.name = name; // actual initialization here
20         this.age = age;
21         System.out.println("Person(String, int) called");
22     }
23 }
24
```

Constructor Chaining

Rules:

this(...) or super(...) must be the **first statement** in a constructor.

Only **one** of them can be used (not both).

If you write nothing → compiler automatically inserts super() (no-arg parent constructor).

```
Person(String, int) called
Person() called
Student() called
```

```
Person(String, int) called
Student(full) called
```

```
24
25 class Student extends Person { 4 usages
26     int roll; 1 usage
27
28     Student() { 1 usage
29         super(); // chaining to parent (calls Pe
30         System.out.println("Student() called");
31     }
32
33     Student(String name, int age, int roll) { 1 usage
34         super(name, age); // chaining to parent's 2-arg c
35         this.roll = roll;
36         System.out.println("Student(full) called");
37     }
38 }
39 ▶ public class Main {
40     ▶ public static void main(String[] args)
41     {
42         Student s1 = new Student();
43         System.out.println();
44         Student s2 = new Student( name: "Alice", age: 20, roll: 101);
45     }
46 }
```


Calling Overloaded Parent Constructors

Person(String)

Person(String,int)

Student()

Main.java

```
1  class Person { 1 usage 1 inheritor
2      String name; 1 usage
3      int age; 1 usage
4
5      Person() no usages
6      { System.out.println("Person()"); }
7      Person(String name) 1 usage
8      { this.name = name; System.out.println("Person(String)"); }
9      Person(String name, int age) { 1 usage
10         this(name);
11         this.age = age;
12         System.out.println("Person(String,int)");
13     }
14 }
15 class Student extends Person { 2 usages
16     Student() { 1 usage
17         super( name: "Anonymous", age: 18); // explicitly choosing the 2-arg
18         System.out.println("Student()");
19     }
20 }
21
22 public class Main {
23     public static void main(String[] args) {
24         Student s = new Student();
25     }
26 }
```

**super() is inserted automatically
(only for no-arg)**

Main.java x

```
1  class A { 1 usage 1 inheritor
2      A() { System.out.println("A()"); } 1 usage
3      A(int x) { System.out.println("A(int)"); } no usages
4  }
5  class B extends A { 2 usages
6      B() { 1 usage
7          // compiler inserts super(); here → calls A()
8          System.out.println("B()");
9      }
10 }
11
12 public class Main {
13     public static void main(String[] args) {
14         B s = new B();
15     }
16 }
```

C:\Users\u1904\.jdk\openjdk-25\bin\java

A()

B()

**super() is inserted automatically
(only for no-arg)**

300
200
Parent

```
Main.java x
1  class GrandParent { 1 usage 2 inheritors
2      int x = 100; no usages
3      void show() { System.out.println("Grand"); } 1 usage 1 override
4  }
5  class Parent extends GrandParent { 1 usage 1 inheritor
6      int x = 200; 1 usage
7      void show() { System.out.println("Parent"); } 1 usage
8  }
9  class Child extends Parent { 2 usages
10     int x = 300; 1 usage
11     void display() { 1 usage
12         System.out.println(x); // 300
13         System.out.println(super.x); // 200 ← Parent's x, not GrandParent's
14         super.show(); // "Parent"
15     }
16 }
17 public class Main {
18     public static void main(String[] args)
19     {
20         Child c = new Child();
21         c.display();
22     }
23 }
```