

Lab Sheet: Abstraction in Java

Course: Introduction to Programming Language II (Java)

Topic: Abstraction, Abstract Classes, Interfaces

Level: Beginner to Intermediate

Duration: 3 hours

Prepared by: Ashraful Islam Paran, Dept. of CSE, UIU

1. Objectives

By the end of this lab, students will be able to:

- Use abstract classes and interfaces for abstraction.
- Resolve ambiguities like the diamond problem using interfaces.
- Practice coding with examples and exercises on these topics.

12. Abstraction, Abstract Classes, and Interfaces

Abstraction hides implementation details. Achieved via abstract classes (partial abstraction) or interfaces (full abstraction). **Key Points:**

- **Abstract Class:** Can have abstract (no body) and concrete methods, fields, constructors. Cannot instantiate. Subclasses must implement abstract methods.
- **Interface:** All methods abstract/public by default, variables public static final. Supports multiple inheritance. No constructors/instance fields.
- **Differences:** Interfaces are 100% abstract, abstract classes can have defaults.
- **Diamond Problem:** Java avoids with classes; resolves in interfaces by overriding.
- Multiple inheritance via interfaces is safe due to no implementations.

13. Example 9: Abstract Class Basic Example

```
abstract class Animal {  
    // Abstract method (no body)  
    abstract void sound();  
    // Concrete method  
    void sleep() {  
        System.out.println("Animal is sleeping...");  
    }  
}  
// Concrete subclass  
class Dog extends Animal {  
    @Override  
    void sound() {  
        System.out.println("Dog barks");  
    }  
}  
public static void main(String[] args) {  
    Dog d = new Dog();  
    d.sound(); // Output: Dog barks  
    d.sleep(); // Output: Animal is sleeping...  
}
```

Output:

```
Dog barks  
Animal is sleeping...
```

14. Example 10: Abstract Subclass Example

```
abstract class Animal {  
    abstract void sound();  
    void sleep() {  
        System.out.println("Animal is sleeping...");  
    }  
}  
abstract class Dog extends Animal {  
    void bark() {  
        System.out.println("Dog barking behavior");  
    }  
}  
class Beagle extends Dog {  
    @Override  
    void sound() {  
        System.out.println("Beagle barks");  
    }  
}  
public class MainClass {  
    public static void main(String[] args) {  
        Dog d = new Beagle(); // Dog reference to Beagle object  
        d.sound(); // Output: Beagle barks  
        d.bark(); // Output: Dog barking behavior  
        d.sleep(); // Output: Animal is sleeping...  
    }  
}
```

Output:

```
Beagle barks  
Dog barking behavior  
Animal is sleeping...
```

15. Example 11: Vehicle Abstract Example

```
abstract class Vehicle {  
    abstract void start();  
    abstract void stop();  
    void fuelType() {  
        System.out.println("Uses fuel");  
    }  
}  
  
class Car extends Vehicle {  
    void start() {  
        System.out.println("Car starts with key");  
    }  
    void stop() {  
        System.out.println("Car stops with brakes");  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Vehicle v = new Car();  
        v.start(); // Car starts with key  
        v.stop(); // Car stops with brakes  
        v.fuelType(); // Uses fuel  
    }  
}
```

Output:

```
Car starts with key  
Car stops with brakes  
Uses fuel
```

16. Example 12: Shape Abstract with Constructor

```
abstract class Shape {
    String color;
    Shape(String color) {
        this.color = color;
    }
    abstract double area();
    void displayColor() {
        System.out.println("Color: " + color);
    }
}
class Circle extends Shape {
    double radius;
    Circle(String color, double radius) {
        super(color);
        this.radius = radius;
    }
    double area() {
        return Math.PI * radius * radius;
    }
}
```

17. Example 13: Employee Abstract Example

```
abstract class Employee {
    abstract void calculateSalary();
}
class FullTimeEmployee extends Employee {
    void calculateSalary() {
        System.out.println("Salary: Fixed monthly salary");
    }
}
class PartTimeEmployee extends Employee {
    void calculateSalary() {
        System.out.println("Salary: Hourly based salary");
    }
}
public class Main {
    public static void main(String[] args) {
        Employee e1 = new FullTimeEmployee();
        Employee e2 = new PartTimeEmployee();
        e1.calculateSalary(); // Salary: Fixed monthly salary
        e2.calculateSalary(); // Salary: Hourly based salary
    }
}
```

Output:

```
Salary: Fixed monthly salary
Salary: Hourly based salary
```

18. Example 14: Interface Basic Example

```
interface Flyable {  
    // Variable must be static and final  
    int MAX_ALTITUDE = 10000; // implicitly public static final  
    void fly(); // implicitly public and abstract  
}
```

19. Example 15: Bank Interface Example

```
interface Bank {  
    double INTEREST_RATE = 5.5;  
    void calculateInterest();  
}  
  
class CityBank implements Bank {  
    public void calculateInterest() {  
        System.out.println("Interest Rate: " + INTEREST_RATE + "%");  
    }  
}
```

20. Example 16: Shape Interface Example

```
interface Shape {  
    double pi = 3.1416;  
    double area();  
}  
  
class Circle implements Shape {  
    double r = 2;  
    public double area() {  
        return pi * r * r;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Circle c = new Circle();  
        System.out.println(c.area());  
        System.out.println(Circle.pi);  
        System.out.println(Shape.pi);  
    }  
}
```

21. Example 17: Multiple Interfaces Example

```
interface Printable {  
    void print();  
}  
interface Scannable {  
    void scan();  
}  
class Printer implements Printable, Scannable {  
    public void print() {  
        System.out.println("Printing document");  
    }  
    public void scan() {  
        System.out.println("Scanning document");  
    }  
}
```

22. Example 18: Payment Interface Example

```
interface Payment {  
    void pay();  
}  
class CreditCardPayment implements Payment {  
    public void pay() {  
        System.out.println("Paid using credit card");  
    }  
}  
class MobileBankingPayment implements Payment {  
    public void pay() {  
        System.out.println("Paid using mobile banking");  
    }  
}  
public class Main {  
    public static void main(String[] args) {  
        Payment p1 = new CreditCardPayment();  
        p1.pay(); // Paid using credit card  
        Payment p2 = new MobileBankingPayment();  
        p2.pay(); // Paid using mobile banking  
    }  
}
```

Output:

```
Paid using credit card  
Paid using mobile banking
```

23. Example 19: Abstract Class + Interface Example

```
abstract class Animal {
    abstract void sound();
    void sleep() {
        System.out.println("Sleeping...");
    }
}
// Interface
interface Pet {
    void play();
}
class Dog extends Animal implements Pet {
    public void sound() {
        System.out.println("Bark");
    }
    public void play() {
        System.out.println("Plays fetch");
    }
    public static void main(String[] args) {
        Dog d = new Dog();
        d.sound(); // Output: Bark
        d.play(); // Output: Plays fetch
        d.sleep(); // Output: Sleeping...
    }
}
```

Output:

Bark
Plays fetch
Sleeping...

24. Example 20: Diamond Problem Example (Classes - Error)

```
class A {
    void show() {
        System.out.println("A's show");
    }
}

class C extends A {
    void show() {
        System.out.println("C's show");
    }
}

class B extends A {
    void show() {
        System.out.println("B's show");
    }
}

// class D extends B, C { // Ambiguous: which show() method to inherit? }
// Compile error: Java does not allow multiple inheritance with classes
```


25. Example 21: Diamond Problem Solution (Interfaces)

```
interface A {
    default void show() {
        System.out.println("Interface A");
    }
}
interface B {
    default void show() {
        System.out.println("Interface B");
    }
}
class Demo implements A, B {
    public void show() {
        A.super.show();
    }
}
public class Main {
    public static void main(String[] args) {
        Demo d = new Demo();
        d.show(); // Interface A
    }
}
```

Output:

Interface A

26. Example 22: Multiple Inheritance with Interfaces Example

```
interface Flyable {
    void fly();
}
interface Swimmable {
    void swim();
}
class Duck implements Flyable, Swimmable {
    public void fly() {
        System.out.println("Duck is flying");
    }
    public void swim() {
        System.out.println("Duck is swimming");
    }
    public static void main(String[] args) {
        Duck d = new Duck();
        d.fly(); // Output: Duck is flying
        d.swim(); // Output: Duck is swimming
    }
}
```

Output:

Duck is flying
Duck is swimming

Task 4.1 – Abstract Class Practice (15 min)

- a. Create abstract class `Device` with abstract void `powerOn()` and concrete void `checkBattery()`. Subclass `Phone` implements `powerOn()`.

Sample Code:

```
abstract class Device {
    abstract void powerOn();
    void checkBattery() {
        System.out.println("Battery level: 100%");
    }
}
class Phone extends Device {
    @Override
    void powerOn() {
        System.out.println("Phone powering on");
    }
}
public class DeviceTest {
    public static void main(String[] args) {
        Device d = new Phone();
        d.powerOn(); // Phone powering on
        d.checkBattery(); // Battery level: 100%
    }
}
```

Task 4.2 – Abstract with Constructor (15 min)

- a. Create abstract Fruit with String color (via constructor) and abstract void taste(). Subclass Apple.

Sample Code:

```
abstract class Fruit {
    String color;
    Fruit(String color) {
        this.color = color;
    }
    abstract void taste();
    void displayColor() {
        System.out.println("Color: " + color);
    }
}

class Apple extends Fruit {
    Apple(String color) {
        super(color);
    }
    @Override
    void taste() {
        System.out.println("Sweet");
    }
}

public class FruitTest {
    public static void main(String[] args) {
        Apple a = new Apple("Red");
        a.taste(); // Sweet
        a.displayColor(); // Color: Red
    }
}
```

Task 4.3 – Interface Practice (15 min)

- a. Create interface `Drawable` with `void draw()` and constant `int SIZE = 10`. Implement in class `Square`.

Sample Code:

```
interface Drawable {  
    int SIZE = 10;  
    void draw();  
}  
class Square implements Drawable {  
    public void draw() {  
        System.out.println("Drawing square of size " + SIZE);  
    }  
}  
public class DrawTest {  
    public static void main(String[] args) {  
        Square s = new Square();  
        s.draw(); // Drawing square of size 10  
    }  
}
```

Task 4.4 – Multiple Interfaces (15 min)

- a. Create interfaces Readable (void read()) and Writable (void write()). Class Book implements both.

Sample Code:

```
interface Readable {
    void read();
}
interface Writable {
    void write();
}
class Book implements Readable, Writable {
    public void read() {
        System.out.println("Reading book");
    }
    public void write() {
        System.out.println("Writing book");
    }
}
public class BookTest {
    public static void main(String[] args) {
        Book b = new Book();
        b.read(); // Reading book
        b.write(); // Writing book
    }
}
```

Task 4.5 – Abstract Class + Interface (15 min)

- a. Abstract class `Gadget` (abstract void `operate()`) + interface `Chargeable` (void `charge()`). Class `Laptop` extends/implements both.

Sample Code:

```
abstract class Gadget {
    abstract void operate();
}
interface Chargeable {
    void charge();
}
class Laptop extends Gadget implements Chargeable {
    @Override
    void operate() {
        System.out.println("Laptop operating");
    }
    @Override
    void charge() {
        System.out.println("Laptop charging");
    }
}
public class GadgetTest {
    public static void main(String[] args) {
        Laptop l = new Laptop();
        l.operate(); // Laptop operating
        l.charge(); // Laptop charging
    }
}
```

Task 4.6 – Diamond Problem Resolution (15 min)

- a. Interfaces SoundA and SoundB both with default void makeSound(). Class Speaker implements both and overrides.

Sample Code:

```
interface SoundA {
    default void makeSound() {
        System.out.println("Sound A");
    }
}
interface SoundB {
    default void makeSound() {
        System.out.println("Sound B");
    }
}
class Speaker implements SoundA, SoundB {
    @Override
    public void makeSound() {
        SoundA.super.makeSound(); // Choose A
    }
}
public class SoundTest {
    public static void main(String[] args) {
        Speaker s = new Speaker();
        s.makeSound(); // Sound A
    }
}
```

27. Key Differences: Abstract Class vs Interface

Interface	Abstract Class
Java interface are implicitly abstract and cannot have implementations	A Java abstract class can have implementations
Variables declared in a Java interface is by default final	An abstract class may contain variables
Members of a Java interface are public by default	A Java abstract class can have protected and private members
Java interface should be implemented using keyword “implements”	A Java abstract class should be extended using keyword “extends”
An interface can extend another Java interface only	an abstract class can extend another class
Interface is absolutely abstract and cannot be instantiated	A Java abstract class also can be instantiated
java interfaces are slow as it requires extra indirection	Comparatively fast

28. Summary Table

Concept	Description	Example
Abstract Class	Partial abstraction	abstract class Animal
Interface	Full abstraction	interface Flyable
Diamond Problem	Ambiguity in multiple inheritance	Resolved by overriding in interfaces

29. Final Task

Design a system using abstraction and polymorphism:

- Abstract class Shape with abstract `area()` and `perimeter()`.
- Concrete classes Circle and Rectangle.
- Interface Resizable with `resize(double factor)`.
- Make Rectangle implement Resizable.
- Use polymorphism to compute areas in a list of shapes.

Use `final` where appropriate.

30. Practice Questions

1. Explain the difference between reference type and object type.
2. What is dynamic dispatch, and when does it occur?
3. Why can't abstract classes be instantiated?
4. How does Java handle multiple inheritance?
5. Write a program using an interface with default methods and resolve a diamond problem.
6. What happens if a subclass doesn't implement an abstract method?

Keep Coding!