



Underwater Image Enhancements

by

Ashray Adhikari

Bachelor Thesis in Computer Science

Submission: April 11, 2021

Supervisor: Prof. Andreas Birk

Jacobs University Bremen | Department of Computer Science and Electrical Engineering

English: Declaration of Authorship

I hereby declare that the thesis submitted was created and written solely by myself without any external support. Any sources, direct or indirect, are marked as such. I am aware of the fact that the contents of the thesis in digital form may be revised with regard to usage of unauthorized aid as well as whether the whole or parts of it may be identified as plagiarism. I do agree my work to be entered into a database for it to be compared with existing sources, where it will remain in order to enable further comparisons with future theses. This does not grant any rights of reproduction and usage, however.

This document was neither presented to any other examination board nor has it been published.

German: Erklärung der Autorenschaft (Urheberschaft)

Ich erkläre hiermit, dass die vorliegende Arbeit ohne fremde Hilfe ausschließlich von mir erstellt und geschrieben worden ist. Jedwede verwendeten Quellen, direkter oder indirekter Art, sind als solche kenntlich gemacht worden. Mir ist die Tatsache bewusst, dass der Inhalt der Thesis in digitaler Form geprüft werden kann im Hinblick darauf, ob es sich ganz oder in Teilen um ein Plagiat handelt. Ich bin damit einverstanden, dass meine Arbeit in einer Datenbank eingegeben werden kann, um mit bereits bestehenden Quellen verglichen zu werden und dort auch verbleibt, um mit zukünftigen Arbeiten verglichen werden zu können. Dies berechtigt jedoch nicht zur Verwendung oder Vervielfältigung.

Diese Arbeit wurde noch keiner anderen Prüfungsbehörde vorgelegt noch wurde sie bisher veröffentlicht.

Date, Signature

Contents

1	Introduction	1
2	Discussion of Related Work	2
3	Methodology	6
4	Evaluation of the Investigation	6
5	Conclusions	6

1 Introduction

Researchers today strive to capture high-quality underwater images for various Underwater activities [20] but, Underwater imaging is a challenging field in computer vision research as opposed to land photography. Many physical and chemical characteristics of Underwater conditions raise issues that we can easily overcome in land photography [20].

Underwater imaging raises new challenges and problems due to the absorption and scattering effects of light underwater. This generates low-contrast images and causes distant objects to appear blurry and misty [17]. As light moves from air to water, it is partly reflected, and the amount of light entering reduces as we start going deeper. So, Underwater images appear dark as depth increases and the colors drop off one by one depending on the wavelength [8]. Due to the varying degrees of attenuation encountered by the light traveling in water with different wavelengths, the ambient underwater environment is dominated by a bluish tone [23].

The light received by the camera is mainly generated by a direct component that reflects light from the object, forward scattering that randomly deviates light on its way to the camera, and the backscattering component that reflects light toward the camera before the light reaches the objects [11]. In an underwater scene light accepted through a camera can be represented as a linear superposition of all three components. So, forward scattering causes the blurring on the image, and the backscattering masks the details of the scene [11].

Besides the absorption and scattering effects of light by the water, the quality of water also influences the quality of underwater images. The presence of suspended particles with significant size and density in the medium also causes light to be scattered and absorbed [22]. Haze is caused by the suspended particles such as sand, minerals, and plankton that exist in the water body. Some portion of the light meets these suspended particles as light reflected from the object propagates towards the camera [3].

Due to certain challenging underwater conditions, traditional enhancing techniques appear to be strongly limited for Underwater Images. Traditional image restoration methods use an atmospheric scattering model to restore underwater images[15] and underwater conditions are considered similar to dense fog on land, but unlike fog, underwater illumination is spectrally deprived as water attenuates different wavelengths of light to different degrees [4]. Applying conventional color correction methods designed for terrestrial environments on Underwater images will lead to undesired artifacts since the red component of the Underwater image is much weaker than the green and blue components [6].

In this document, we test the effects and analyze both quantitatively and qualitatively the result of different machine vision methods for Underwater Image Enhancement on images extracted from Underwater videos of the Valentine memorial. The rest of the document is structured as follows. Section 2 gives an overview of Underwater Image Enhancement methods and discusses related works. Section 3 goes in-depth on some Underwater Image Enhancement methods. Section 4 showcases the results and analysis of the effects of different methods on the extracted images. Section 5 provides the summary of the project and further discussions.

2 Discussion of Related Work

Over the years several methods have been specifically designed according to the characteristics of underwater images eg, hazing, color casts and low contrast [20]. In this section, we will discuss different physics-based, color correction, haze removal, fusion-based, and CNN-based Underwater Image Enhancements and Restoration methods.

In a Physics-based approach for recovery of visibility in Underwater scenes, raw images are taken through different stages of a polarizing filter. In 2004 Schechner [19] proposed a physics-based approach that inverts the image formation process, to recover a good visibility image of the object. The algorithm presented were based on images taken through a polarizer at different orientations. But, the physics-based methods require high computing resources and long execution time and the polarizer used in the approach is expensive [22]. We will not consider the physics-based method for our analysis.

In recent years many studies have proved the effectiveness of deep-learning methods for various computer vision tasks. But, very few of them have been effective in underwater image enhancement. In 2017, Perez [18] proposed a CNN-based Underwater Image Enhancement method, that uses a convolution neural network to learn the transformation from raw acquired images to enhanced images using a pair of degraded and recovered underwater images [20]. Then in 2018 Li [12] proposed WaterGAN, a generative adversarial network for generating synthetic realistic underwater images from in-air image and depth maps, where the raw underwater, true color-in air, and the depth data were used to feed a deep learning network for correcting color casts in underwater images [20]. To relax the need for paired underwater images for network training and allow the use of unknown underwater images Li [10] proposed an Underwater Image Correction model based on a Weakly Supervised Color Transfer [20]. In this method first, a color correction algorithm is applied to correct the color cast and produce a natural appearance of the sub-sea image and then a pair of dictionaries based on sparse representation are applied to sharpen the image and enhance the details [10]. Even though the Deep Learning-based Underwater Enhancement methods has in some extent proven to be effective in enhancing underwater images, we will not use the CNN-based model to enhance the extracted images from the Valentine memorial due to the lack of data required to train the model.

Most enhancement methods are scene-dependent and need prior knowledge. Farhadi-fard [5] in 2015 proposed an image enhancement method that combines learning-based de-blurring and adaptive color correction. First, the degraded image is white balanced using an adaptive gain factor to compensate color cast which produces a natural appearance of the underwater medium. Then, the partially restored version is enhanced by a learning-based de-blurring algorithm [5]. Two global dictionaries are trained based on sparse representation. One from a clear and high-quality underwater image set and the second one, using the corresponding blurred version. Blur free and sharpened image is obtained based on basic principle between the high and low patches [5].

Classic Retinex theory assumes that the images can be decomposed into two components, reflectance, and illumination. But, the classic Retinex model is not suited for the low-light image enhancement problem, as intensive noise exists in low-light images [13]. In 2018 Li [13] proposed a Structural Revealing Image Enhancement Algorithm Using a Robust Retinex Model. This method proposed a Robust Retinex, which additionally

considers a noise map compared to the conventional Retinex model to improve the performance of enhancing low-light images accompanied by intense noise [13]. Even though this method was not made for underwater conditions it can be generalized to handle Underwater Image Enhancements [13].

In 2019 Gao [6] proposed an Underwater Image Enhancement model inspired by the morphology and function of the teleost fish retina to solve the blurring and non-uniform color biasing problem of underwater images. The motivation behind this approach is that the visual system of the oceanic creatures has evolved to adapt to the natural statistics of aquatic scenes [6]. So, modeling the perception and imaging mechanisms of the oceanic creatures will give us new insights into processing Underwater images [6].

Wavelet decomposition algorithm decomposes an original image into a sequence of new images of decreasing size [16], and in a fusion-based approach weight maps are computed and fused to enhance the image [7]. In 2016 A. Khan [9] proposed a wavelet-based fusion method to enhance hazy underwater images by addressing low contrast and color attenuation issues. Two input images are generated from the hazy image by color correction using histogram stretching and contrast enhancement using contrast limited adaptive histogram equalization (CLAHE). Both input images are decomposed into wavelet coefficient and the coefficient is fused using an algorithm that eliminates unwanted low and high frequency present in the image. Finally, the inverse composition is applied to the fused coefficient to get a synthesized enhanced image. [9]

In 2017 Wang [21] proposed a different fusion-based model applied to a frequency domain. It involves 2 inputs represented as color corrected and contrast enhanced images extracted from the original image. The input images are decomposed into low frequency and high-frequency components using a three-scale wavelet operator. Then, Multi-scale fusion principles are applied to the low and high-frequency components. Fusion principle for of Low-frequency component involves a weighted average of the components and high-frequency component involves local variance of components. The fused image is obtained by reconstructing the new fused low frequency and high-frequency components [21].

As the weight maps computed in a fusion-based approach may introduce artifacts in the image, P. Honnutagi in 2018 [7] proposed a method to overcome this problem by using an optimized fusion method of weight maps, where multi-step fusion is used to perform a fusion of weight maps computed from illumination estimation and contrast-enhanced inputs of the original image. First illumination estimation is applied on the image to improve visibility, then contrast limited adaptive histogram equalization (CLAHE) is used to derive the second input which improves the contrast of the image [7]. Saliency, luminance, and chromatic weight maps are computed for each derived inputs. After computing each weight map, the final weight map is produced by multiplying all three weight maps. Finally, an enhanced image is generated from multi-step fusion technique by using the Gaussian and mean operators on both weight maps [7].

The Dark Channel Prior method is based on the observation that in a clear day image there exists some pixels which have a very low intensity in at least one color channel [20]. Due to the similarity between hazed outdoor image and underwater image Dark Channel-based hazing method is used in underwater image enhancement. Chao and Wang in 2010 [14] used the Dark Channel Prior method directly to enhance the clarity of the image. Using dark channel prior depth of the Underwater Image is estimated but this

method does not solve the problem of absorption [14].

In 2011 Yang [22] proposed a DCP-based fast Underwater Image Enhancement method that can effectively enhance Underwater Image and reduce execution time. This method used a median filter instead of a soft matting procedure to estimate the depth map of the image. The Dark Channel Prior is calculated to estimate air-light, and the depth map is generated using a median filter. A color correction method is employed to enhance the color contrast of the image.[22]

As larger scene depth causes more object blurriness in Underwater images, Y. Peng in 2015 [17] proposed a method that measures scene depth from image blurriness to estimate depth map for Underwater Image enhancement. The method is based on the observation that objects farther from the camera are more blurry for Underwater Images. To overcome the limitation of DCP the depth estimation method first calculates the difference between the original and the multi-scale Gaussian filter to estimate the pixel blurriness map. Then, by assuming that the depth in the small local patch is uniform the max filter is applied to the pixel blurriness map. Finally, closing by morphological reconstruction (CMR) and the guided filter are used to refine the depth map [17].

Most existing methods based on the DCP method convert information from three RGB channels to one dark channel, but those methods are inadequate in cases where chromatic information is essential for restoration [24]. Zhou in 2019 [24] proposed a method to handle the scattering and absorption problems of light with different wavelengths base on the color-line model. The color line is a regularity in images, which shows that the pixel values of small patches are distributed along a one-dimensional line in the RGB space [24]. First, the image patches that exhibit the characteristics of the color-line prior are filtered out and the color line of the patches are recovered [24]. "Then, the local transmission for each patch is estimated based on the offsets of the color lines along the background-light vector from the origin" [24]. An alternating iterative algorithm is also presented here, to solve the non-linear optimization problem for transmission in an Underwater environment [24]. Finally, a wavelength-compensation method is also proposed to correct the color cast caused by water depth [24].

The transmission map is reducing exponentially with scene depth, which is difficult to estimate in Underwater Environment. So, Mi in 2018 [15] proposed an enhancement method using a multi-scale gradient-domain contrast enhancement strategy to increase visibility and compensate the attenuation of color saturation according to the estimated transmission. Before applying the enhancement method first white balance the image to remove the color casts while producing a natural appearance of the Underwater image [15]. Then, a multi-scale gradient enhancement strategy is used to prevent halo artifacts. Gradient enhancement is processed on multiple residual images produced by edge-decomposition [15]. By compensating color saturation according to the estimated transmission we get the enhanced image [15].

Several other methods have been proposed to remove the haze and increase the contrast of Underwater images. Ancutti in 2018 [1] proposed a method that uses color balance and fusion methods to enhance Underwater Images. The White Balanced version of the original image is decomposed into 2 input images to enhance the color contrast and edge sharpness. Then, the weight maps are defined to preserve the qualities and reject the defaults of the inputs [1]. Finally, the multi-scale fusion method decomposes the image into a sum of bandpass images. The method is motivated by the human visual system,

which is very sensitive to sharp transition appearing in smooth image [1].

Since most Underwater dehazing methods are for still underwater images, Emberton [4] in 2018 proposed a dehazing method that improves visibility in images and videos by detecting and segmenting image regions that contain only water. The spectral distortion problem is addressed in the method by automatically selecting the most appropriate white balancing method based on the most dominant color of the water [4]. Varying patch sizes are used for the estimation of light that is scattered from underwater particles into the line of sight of the camera [4]. Entropy-based segmentation is used to localize pure haze region that informs the features to select for the scattered light [4]. Image-specific transmission value is allocated to pure haze regions to avoid generating artifacts [4].

The presence of an artificial light source in Underwater Image increases the scattering of light underwater. So, Chiang in 2012 [3] proposed a method to enhance underwater images by dehazing algorithm to compensate the attenuation difference along the propagation path, and to take the influence of the possible presence of an artificial light source into consideration. Dark channel prior is first used to estimate the distances of scene objects to the camera. Based on the depth map, the foreground and background areas within the image are segmented. The light intensity of the foreground and background are compared to determine whether artificial is used. Dehazing algorithm and wavelength compensation are used to remove the haze effect and color change along the Underwater propagation path to the camera [3].

Histogram equalization involves the transfer of the histogram of an original image to an evenly distributed form [2]. For an Underwater image histogram equalization method is mostly used for color correction of the degraded image. Beilei Hu [2] in 2013 proposed a method that uses inhomogeneous illumination to get a clearer image, and then processes it to use color image histogram equalization to get more color information which gives out true color correction. Inhomogeneous intensity can compensate for the loss of light intensity due to light attenuation and decrease backscattering effect caused by the scattering of light Underwater [2]. As the light in Underwater is heavily attenuated, so if the light source is not strong enough, the intensity of the target object in the image is very weak. So, it is necessary to use inhomogeneous illumination as the light source [2]. During color histogram equalization each channel of the image is histogram equalized by monotonically increasing grey level transform, and then these images of different color channels combined to form a high contrast image [2].

Underwater Images are used for many different computer vision applications, and different kinds of images are required. So, Li in 2016 [11] proposed an Underwater Enhancement algorithm, which includes both image dehazing and contrast enhancement algorithm that is built on minimum information loss principle to restore the visibility, color, and natural appearance of Underwater images. Two different versions of the output image can be produced for different applications using this method. The first version with relatively genuine color and natural appearance that is suitable for displaying the image and the second version with high contrast and brightness that is used for extracting more valuable information and revealing more details [11]. For the image dehazing algorithm first, the global background light is estimated using a hierarchical searching technique based on quad-tree subdivision followed by the removal of suspended particles using the dark channel prior algorithm. The disturbance of bright objects is removed and the global

background light is determined according to the properties of light traveling in water [11]. Then, to minimize information loss, the medium transmission map of the color channels is defined. Underwater images with high contrast and brightness play a really important role in object detection, classification, etc [11]. The contrast enhancement algorithm proposed in this method is based on statistics of histogram distribution of visually appealing natural-scene images [11]. The histogram distribution prior is counted for five natural-scene image datasets. Then, the average histogram distributions of natural scenes are regarded as a template, and is followed by the approximate histogram matching to adjust the histogram distributions of haze-free underwater images obtained by the dehazing algorithm [11].

Most Underwater images are degraded by light absorption and scattering, which causes a single color to dominate the image. Iqbal in 2007 [8] proposed a method based on slide stretching. First, contrast stretching of the RGB algorithm is used to equalize color contrast in the image. Then, the RGB image is transformed into HSI color space, using the saturation and intensity transfer function to increase the true color and brightness of Underwater images [8]. Using side two stretching models helps equalize the color contrast in images and address the problem of lighting [8].

3 Methodology

This is the technical core of the thesis. Here you lay out your how you answered your research question, you specify your design of experiments or simulations, point out difficulties that you encountered, etc.

(target size: 5-10 pages)

4 Evaluation of the Investigation

This section discusses criteria that are used to evaluate the research results. Make sure your results can be used to published research results, i.e., to the already known state-of-the-art.

(target size: 5-10 pages)

5 Conclusions

Summarize the main aspects and results of the research project. Provide an answer to the research questions stated earlier.

(target size: 1/2 page)

References

- [1] C. O. Ancuti et al. "Color Balance and Fusion for Underwater Image Enhancement". In: *IEEE Transactions on Image Processing* 27.1 (2018), pp. 379–393. DOI: [10.1109/TIP.2017.2759252](https://doi.org/10.1109/TIP.2017.2759252).
- [2] Beilei Hu et al. "Underwater image color correct in extremely poor visibility". In: *2013 OCEANS - San Diego*. 2013, pp. 1–4. DOI: [10.23919/OCEANS.2013.6741113](https://doi.org/10.23919/OCEANS.2013.6741113).
- [3] J. Y. Chiang and Y. Chen. "Underwater Image Enhancement by Wavelength Compensation and Dehazing". In: *IEEE Transactions on Image Processing* 21.4 (2012), pp. 1756–1769. DOI: [10.1109/TIP.2011.2179666](https://doi.org/10.1109/TIP.2011.2179666).
- [4] Simon Emberton, Lars Chittka, and Andrea Cavallaro. "Underwater image and video dehazing with pure haze region segmentation". In: *Computer Vision and Image Understanding* 168 (2018), pp. 145–156. ISSN: 1077-3142. DOI: [10.1016/j.cviu.2017.08.003](https://doi.org/10.1016/j.cviu.2017.08.003). URL: <https://uwe-repository.worktribe.com/output/862635>.
- [5] F. Farhadifard, Z. Zhou, and U. F. von Lukas. "Learning-based underwater image enhancement with adaptive color mapping". In: *2015 9th International Symposium on Image and Signal Processing and Analysis (ISPA)*. 2015, pp. 48–53. DOI: [10.1109/ISPA.2015.7306031](https://doi.org/10.1109/ISPA.2015.7306031).
- [6] S. B. Gao et al. "Underwater Image Enhancement Using Adaptive Retinal Mechanisms". In: *IEEE Transactions on Image Processing* 28.11 (2019), pp. 5580–5595. DOI: [10.1109/TIP.2019.2919947](https://doi.org/10.1109/TIP.2019.2919947).
- [7] P. Honnutagi, V. D. Mytri, and Y. S. Lalitha. "Optimized Weight Maps and Fusion for Underwater Image Enhancement". In: *2018 International Conference on Electrical, Electronics, Communication, Computer, and Optimization Techniques (ICEEC-COT)*. 2018, pp. 1654–1658. DOI: [10.1109/ICEECOT43722.2018.9001568](https://doi.org/10.1109/ICEECOT43722.2018.9001568).
- [8] Kashif Iqbal et al. "Underwater image enhancement using an integrated colour model". In: *International Journal Of Computer Science* (2007), pp. 239–244.
- [9] A. Khan et al. "Underwater image enhancement by wavelet based fusion". In: *2016 IEEE International Conference on Underwater System Technology: Theory and Applications (USYS)*. 2016, pp. 83–88. DOI: [10.1109/USYS.2016.7893927](https://doi.org/10.1109/USYS.2016.7893927).
- [10] C. Li, J. Guo, and C. Guo. "Emerging From Water: Underwater Image Color Correction Based on Weakly Supervised Color Transfer". In: *IEEE Signal Processing Letters* 25.3 (2018), pp. 323–327. DOI: [10.1109/LSP.2018.2792050](https://doi.org/10.1109/LSP.2018.2792050).
- [11] C. Li et al. "Underwater Image Enhancement by Dehazing With Minimum Information Loss and Histogram Distribution Prior". In: *IEEE Transactions on Image Processing* 25.12 (2016), pp. 5664–5677. DOI: [10.1109/TIP.2016.2612882](https://doi.org/10.1109/TIP.2016.2612882).
- [12] J. Li et al. "WaterGAN: Unsupervised Generative Network to Enable Real-Time Color Correction of Monocular Underwater Images". In: *IEEE Robotics and Automation Letters* 3.1 (2018), pp. 387–394. DOI: [10.1109/LRA.2017.2730363](https://doi.org/10.1109/LRA.2017.2730363).
- [13] M. Li et al. "Structure-Revealing Low-Light Image Enhancement Via Robust Retinex Model". In: *IEEE Transactions on Image Processing* 27.6 (2018), pp. 2828–2841. DOI: [10.1109/TIP.2018.2810539](https://doi.org/10.1109/TIP.2018.2810539).
- [14] Liu Chao and Meng Wang. "Removal of water scattering". In: *2010 2nd International Conference on Computer Engineering and Technology*. Vol. 2. 2010, pp. V2–35–V2–39. DOI: [10.1109/ICCET.2010.5485339](https://doi.org/10.1109/ICCET.2010.5485339).

- [15] Z. Mi et al. "Multi-Scale Gradient Domain Underwater Image Enhancement". In: *2018 OCEANS - MTS/IEEE Kobe Techno-Oceans (OTO)*. 2018, pp. 1–5. DOI: [10.1109/OCEANSKOB.2018.8559180](https://doi.org/10.1109/OCEANSKOB.2018.8559180).
- [16] Xavier Otazu. "6 - Theory and implementation of image fusion methods based on the á trous algorithm". In: *Image Fusion*. Ed. by Tania Stathaki. Oxford: Academic Press, 2008, pp. 139–155. ISBN: 978-0-12-372529-5. DOI: <https://doi.org/10.1016/B978-0-12-372529-5.00014-7>. URL: <https://www.sciencedirect.com/science/article/pii/B9780123725295000147>.
- [17] Y. Peng, X. Zhao, and P. C. Cosman. "Single underwater image enhancement using depth estimation based on blurriness". In: *2015 IEEE International Conference on Image Processing (ICIP)*. 2015, pp. 4952–4956. DOI: [10.1109/ICIP.2015.7351749](https://doi.org/10.1109/ICIP.2015.7351749).
- [18] Javier Perez et al. "A Deep Learning Approach for Underwater Image Enhancement". In: *Biomedical Applications Based on Natural and Artificial Computing*. Ed. by José Manuel Ferrández Vicente et al. Cham: Springer International Publishing, 2017, pp. 183–192. ISBN: 978-3-319-59773-7.
- [19] Y. Y. Schechner and N. Karpel. "Clear underwater vision". In: *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2004. CVPR 2004*. Vol. 1. 2004, pp. I–I. DOI: [10.1109/CVPR.2004.1315078](https://doi.org/10.1109/CVPR.2004.1315078).
- [20] Y. Wang et al. "An Experimental-Based Review of Image Enhancement and Image Restoration Methods for Underwater Imaging". In: *IEEE Access* 7 (2019), pp. 140233–140251. DOI: [10.1109/ACCESS.2019.2932130](https://doi.org/10.1109/ACCESS.2019.2932130).
- [21] Y. Wang et al. "Fusion-based underwater image enhancement by wavelet decomposition". In: *2017 IEEE International Conference on Industrial Technology (ICIT)*. 2017, pp. 1013–1018. DOI: [10.1109/ICIT.2017.7915500](https://doi.org/10.1109/ICIT.2017.7915500).
- [22] H. Yang et al. "Low Complexity Underwater Image Enhancement Based on Dark Channel Prior". In: *2011 Second International Conference on Innovations in Bio-inspired Computing and Applications*. 2011, pp. 17–20. DOI: [10.1109/IBICA.2011.9](https://doi.org/10.1109/IBICA.2011.9).
- [23] Y. Yang and X. Xu. "A Underwater Image Enhanced Algorithm combined MSR and Channel Energy". In: *2020 22nd International Conference on Advanced Communication Technology (ICACT)*. 2020, pp. 348–349. DOI: [10.23919/ICACT48636.2020.9061370](https://doi.org/10.23919/ICACT48636.2020.9061370).
- [24] Y. Zhou et al. "Underwater Image Restoration Using Color-Line Model". In: *IEEE Transactions on Circuits and Systems for Video Technology* 29.3 (2019), pp. 907–911. DOI: [10.1109/TCSVT.2018.2884615](https://doi.org/10.1109/TCSVT.2018.2884615).