My Static Website on S3

"

"

Amazon S3 > Buckets > ashritsbucket > Edit bucket policy

Bucket ARN

arn:aws:s3:::ashritsbucket

Policy

```
 1 ▼ {
 2     "Version": "2012-10-17",
 3 ▼   "Statement": [
 4 ▼     {
 5         "Effect": "Allow",
 6         "Principal": "*",
 7         "Action": "s3:GetObject",
 8         "Resource": "arn:aws:s3:::ashritsbucket/*"
 9       }
10     ]
11 }
```

Edit statement

Select a statement

Select an existing statement in the policy or add a new statement.

+ Add new statement

☰

✓ **Upload succeeded**
For more information, see the **Files and folders** table.   ✕

Summary

Destination
s3://ashritsbucket

Succeeded
⊘ 1 file, 67.0 B (100.00%)

Failed
⊙ 0 files, 0 B (0%)

Files and folders | Configuration

Files and folders (1 total, 67.0 B)

🔍 Find by name   < 1 >

Name	Folder	▽	Type	▽	Size	▽	Status	▽	Error	▽
index.html ⎘	-		text/html		67.0 B		⊘ Succeeded		-	

Add the files and folders you want to upload to S3. To upload a file larger than 160GB, use the AWS CLI, AWS SDKs or Amazon S3 REST API. Learn more ⧉

Drag and drop files and folders you want to upload here, or choose **Add files** or **Add folder**.

Files and folders (1 total, 67.0 B)

Remove | Add files | Add folder

All files and folders in this table will be uploaded.

🔍 Find by name   ‹ 1 ›

☐	Name ▽	Folder ▽	Type ▽	Size ▽
☐	index.html	-	text/html	67.0 B

Destination Info

Destination

s3://ashritsbucket ⧉

▶ **Destination details**
Bucket settings that impact new objects stored in the specified destination.

⊘ Successfully edited static website hosting.   ✕

ashritsbucket Info

| Objects | **Properties** | Permissions | Metrics | Management | Access Points |

Bucket overview

AWS Region	**Amazon Resource Name (ARN)**	**Creation date**
Asia Pacific (Mumbai) ap-south-1	📋 arn:aws:s3:::ashritsbucket	March 11, 2025, 15:06:50 (UTC+05:30)

Bucket Versioning

Edit

Versioning is a means of keeping multiple variants of an object in the same bucket. You can use versioning to preserve, retrieve, and restore every version of every object stored in your Amazon S3 bucket. With versioning, you can easily recover from both unintended user actions and application failures. Learn more ⧉

Bucket Versioning
Enabled

Multi-factor authentication (MFA) delete
An additional layer of security that requires multi-factor authentication for changing Bucket Versioning settings and permanently deleting object versions. To modify MFA delete settings, use the AWS CLI, AWS SDK, or the Amazon S3 REST API. Learn more ⧉

☰ Amazon S3 › Buckets ⓘ ⊡ ⊕

✓ **Successfully created bucket "ashritsbucket"**
To upload files and folders, or to configure additional bucket settings, choose **View details**.

View details ✕

▶ **Account snapshot -** *updated every 24 hours* `All AWS Regions`

View Storage Lens dashboard

Storage lens provides visibility into storage usage and activity trends. Metrics don't include directory buckets. Learn more ⧉

General purpose buckets | Directory buckets

General purpose buckets (1) Info `All AWS Regions`
Buckets are containers for data stored in S3.

🔄 Copy ARN Empty Delete Create bucket

🔍 Find buckets by name

< 1 > ⚙

☐	**Name** ▲	**AWS Region** ▽	**IAM Access Analyzer**	**Creation date** ▽
○	ashritsbucket	Asia Pacific (Mumbai) ap-south-1	View analyzer for ap-south-1	March 11, 2025, 15:06:49 (UTC+05:30)