



BETA INNOVATION GROUP USA SRL
San José, Costa Rica
Mata Redonda, Sabana Oeste
3-102-742818

BETA TECH®

INSTALACIÓN SERVER ARS
CON SUSE LINUX ENTERPRISE
SERVER 15 SP2
(32 BITS)

WALMART

MARZO 2021





BETA INNOVATION GROUP USA SRL
San José, Costa Rica
Mata Redonda, Sabana Oeste
3-102-742818

ÍNDICE


ÍNDICE	2
Instalación server ARS con SUSE Linux Enterprise Server 15 SP2	3
RECURSOS DE BETA TECH	15

Instalación server ARS con SUSE Linux Enterprise Server 15 SP2

Una vez se haya seleccionado el idioma (Inglés) y la versión de Suse como se muestra en la imagen adjunta seleccionar siguiente y aceptar el acuerdo de licencia




En la ventana de registro omitir el registro y seleccionar el cuadro en la esquina superior derecha “Network Configuration”




The screenshot shows the SUSE Linux Enterprise Server 15 SP2 Registration window. The title bar includes the SUSE logo and a 'Network Configuration...' button. The main content area is titled 'Registration' and prompts the user to 'Please select your preferred method of registration.' There are three radio button options: 'Register System via scc.suse.com' (with fields for 'Email Address' and 'Registration Code'), 'Register System via local RMT Server' (with a 'Local Registration Server URL' dropdown menu showing 'https://rmt.example.com'), and 'Skip Registration' (which is selected). At the bottom, there are 'Help', 'Abort', 'Back', and 'Next' buttons.

En la ventana de “Network Settings” seleccionar el botón de “Add” para agregar la ip estática




The screenshot shows the SUSE Linux Enterprise Server 15 SP2 Network Settings window. The title bar includes the SUSE logo. The main content area is titled 'Network Settings' and has three tabs: 'Overview' (selected), 'Hostname/DNS', and 'Routing'. The 'Overview' tab displays a table with columns 'Name', 'IP Address', 'Device', and 'Note'. The table contains one entry: '82540EM Gigabit Ethernet Controller' with 'DHCP' in the 'IP Address' column and 'eth0' in the 'Device' column. Below the table, there is a detailed view of the selected network interface, showing its name, MAC address, and BSSID, along with a list of properties: 'Device Name: eth0', 'Configured with dhcp', and 'Started automatically at boot'. At the bottom, there are 'Add', 'Edit', and 'Delete' buttons, and a 'Help' button. On the right side, there are 'Abort', 'Back', and 'Next' buttons.

Seleccionar la opción “Statically Assigned IP Address”, ingresar la ip del servidor a crear, la máscara de la red y el hostname del servidor




The screenshot shows the 'Network Card Setup' window with the 'Address' tab selected. The 'General' tab is also visible. The 'Statically Assigned IP Address' option is selected. The 'IP Address' field contains '10.20.11.35', the 'Subnet Mask' field contains '255.255.255.0', and the 'Hostname' field contains 'SRVARS'. There is a section for 'Additional Addresses' with columns for 'Address Label', 'IP Address', and 'Netmask'. At the bottom, there are buttons for 'Add', 'Edit', 'Delete', 'Help', 'Cancel', and 'Next'.

Luego seleccionar la pestaña “HostnameDNS” y colocar el nombre del servidor de ARS




The screenshot shows the 'Network Settings' window with the 'Hostname/DNS' tab selected. The 'Static Hostname' field contains 'SRVARS'. The 'Set Hostname via DHCP' dropdown is set to 'yes: any'. The 'Modify DNS Configuration' dropdown is set to 'Use Default Policy'. There are fields for 'Name Server 1', 'Name Server 2', and 'Name Server 3', and a 'Domain Search' field. At the bottom, there are buttons for 'Help', 'Abort', 'Back', and 'Next'.

De ahí seleccionar la pestaña “Routing” y configurar el gateway de la red, además de la tarjeta de red correcta (eth0), ok y después Next.




Se seleccionan los siguientes 6 módulos para su instalación:


- Basesystem Module
- Desktop Applications Module
- Development Application Module
- Legacy Module
- Python 2 Module
- Server Application Module




En la ventana de System Role seleccionar el “text Mode”



Se añade la zona horaria




Se omite la creación de usuario





The image shows the 'Local User' creation screen in the SUSE installer. The SUSE logo is in the top left. The title 'Local User' is on the left. On the right, there are two radio buttons: 'Create New User' (selected) and 'Skip User Creation'. Under 'Create New User', there are input fields for 'User's Full Name', 'Username', 'Password', and 'Confirm Password'. Below these are two checkboxes: 'Use this password for system administrator' and 'Automatic Login'. At the bottom, there are buttons for 'Help', 'Release Notes...', 'Abort', 'Back', and 'Next'.

Se agrega la contraseña de root



The image shows the 'Authentication for the System Administrator' screen in the SUSE installer. The SUSE logo is in the top left. The title 'Authentication for the System Administrator' is on the left, with '"root"' below it. On the right, there are two input fields for 'Password for root User' and 'Confirm Password', both masked with dots. Below these is a 'Test Keyboard Layout' input field. Further down, there is an 'Import Public SSH Key' section with a dropdown menu showing 'CD-ROM (/dev/sr0)' and a 'Refresh' button. Below that is a 'Browse...' button. At the bottom, there are buttons for 'Help', 'Release Notes...', 'Abort', 'Back', and 'Next'.


Se validan las configuraciones del sistema operativo e inicia la instalación



Una vez ingresado al servidor correr los siguientes comandos para bajar el firewall y así habilitar el acceso por ssh:

```
root # systemctl stop firewalld.service
root # systemctl disable firewalld.service
Removed /etc/systemd/system/multi-user.target.wants/firewalld.service
Removed /etc/systemd/system/dbus-org.fedoraproject.FirewallD1.service
root # systemctl status firewalld.service
• firewalld.service - firewalld- dynamic firewall daemon
  Loaded: loaded (/usr/lib/systemd/system/firewalld.service;
  disabled; vendor preset: disabled)
  Active: inactive (dead)
  Docs: man:firewalld(1)
```

En la terminal poner el comando yast2 para ingresar a la consola, una vez dentro seleccionar la opción “Software Repositories”



[illegible]

```

YaST2 - menu @ SROARS

```

YaST Control Center	
Software System Hardware Network Services Security and Users Virtualization Support Miscellaneous	Online Update Software Management Add-On Products Media Check Online Migration Product Registration Software Repositories System Extensions

[Help]

[Run][Quit]

F1 Help F9 Quit

En la opción search colocar pam, presionar enter y seleccionar todas las opciones de pam en 32 bits como lo indican las siguientes imágenes:

```
YaST2 - sw_single @ localhost

lqqqqqqqqqqqqqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
xFilter                xx          xName                xSummary
xSearchaaaaaaaaaaaaaa↓xx      i    xpam                xA Secux
xlqqqqqqqqqqqqqqqqqqqqqqqqkxx  i    xpam-32bit          xA Secuw
xxSearch Phrase        xxx      i    xpam-config          xModifyx
xxpamaaaaaaaaaaaaaaaaxxx      i    xpam-devel          xIncludv
xx[x] Ignore Case      xxx      i    xpam-devel-32bit      xIncludx
xx                      xxx      xpam-doc                xDocumex
xxSearch Mode          xxx      xpam-extra          xPAM mox
xxContainsaaaaaa↓      xxx      i    xpam-extra-32bit      xPAM mox
xx                      xxx      xpam-modules          xAdditix
xmqqqqqqqqqqqqqqqqqqqqqqqqjxx  i    xpam-modules-32bit    xAdditix
mqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
36 packages found      Package: pam-devel-32bit          [Actions↓]
lSearch in qqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
x[x] Name of the Package qx    pam-devel-32bit - Include Files and Libraries for q
x[x] Summary            xx    PAM-Development          x
x[ ] Keywords           xx
mtqqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
[Help↓]                [Cancel] [Accept]

F1 Help  F9 Cancel  F10 Accept
```

```
YaST2 - sw_single @ localhost

lqqqqqqqqqqqqqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
xFilter                xx          xName                xSummary
xSearchaaaaaaaaaaaaaa↓xx      i    xpam_apparmor-32bit    xPAM mox
xlqqqqqqqqqqqqqqqqqqqqqqqqkxx  xpam_krb5          xA Plugx
xxSearch Phrase        xxx      i    xpam_krb5-32bit      xA Plugx
xxpamaaaaaaaaaaaaaaaaxxx      xpam_ldap          xA PAM x
xx[x] Ignore Case      xxx      i    xpam_ldap-32bit      xA PAM w
xx                      xxx      xpam_mount          xA PAM x
xxSearch Mode          xxx      i    xpam_mount-32bit      xA PAM v
xxContainsaaaaaa↓      xxx      xpam_pkcs11          xPKCS #x
xx                      xxx      i    xpam_pkcs11-32bit      xPKCS #x
xmqqqqqqqqqqqqqqqqqqqqqqqqjxx  xpam_radius        xA PAM x
mqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
36 packages found      Package: pam_ldap-32bit          [Actions↓]
lSearch in qqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
x[x] Name of the Package qx    pam_ldap-32bit - A PAM Module for LDAP q
x[x] Summary            xx    Authentication          x
x[ ] Keywords           xx
mtqqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
[Help↓]                [Cancel] [Accept]

F1 Help  F9 Cancel  F10 Accept
```



```
YaST2 - sw_single @ localhost

lqqqqqqqqqqqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
xFilter                xx      xName                                xSummary
xSearchaaaaaaaaaaaaaa↓xx i  x pam_pkcs11-32bit                xPKCS #x
xlqqqqqqqqqqqqqqqqqqqqqqqqkxx      x pam_radius                xA PAM x
xxSearch Phrase        xxx      x pam_snapper                xPAM mox
xxpamaaaaaaaaaaaaaaaaaaaaaaaxxx      x pam_ssh                  xPAM Mox
xx[x] Ignore Case      xxx i  x pam_ssh-32bit                xPAM Mox
xx                        xxx      x pam_u2f                    xU2F aux
xxSearch Mode          xxx      x pam_yubico                xYubicow
xxContainsaaaaaa↓      xxx      x perl-Mail-SpamAssassin    xPerl Mx
xx                        xxx      x perl-Mail-SpamAssassin-Plugin-iXhash2xThe iXv
xmqqqqqqqqqqqqqqqqqqqqqqqqjxx      x spamassassin            xExtensx
mqqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
36 packages found      Package: pam_ssh-32bit                [Actions↓]
lSearch in qqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
x[x] Name of the Package qx pam_ssh-32bit - PAM Module for SSH Authentication q
x[x] Summary           xx
x[ ] Keywords          xxVersion: 2.1-2.27 Installed: 2.1-2.27 x
mtqqqqqqqqqqqqqqqqqqqqqqqqjmqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
[Help↓]                [Cancel] [Accept]

F1 Help  F9 Cancel  F10 Accept
```



Luego de instalar el modulo de pam, se procede a instalar la libreria de gcc en 32bits como se refleja en la imagen adjunto:

```
YaST2 - sw_single @ localhost

lqqqqqqqqqqqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
xFilter                xx      xName                                xSummary w
xSearchaaaaaaaaaaaaaa↓xx i  x cpp7                      xThe GCC Preproce
xlqqqqqqqqqqqqqqqqqqqqqqqqkxx      x cpp9                      xThe GCC Preproce
xxSearch Phrase        xxx      x cross-nvptx-gcc7          xThe GNU Compiler
xxgccaaaaaaaaaaaaaaaaaaaaaaxxx i  x gcc                        xThe system GNU C
xx[x] Ignore Case      xxx i  x gcc-32bit                xThe system GNU C
xx                        xxx      x gcc-ada                  xThe system GNU A
xxSearch Mode          xxx i  x gcc-c++                  xThe system GNU C
xxContainsaaaaaa↓      xxx i  x gcc-c++-32bit            xThe system GNU C
xx                        xxx i  x gcc-fortran                  xThe system GNU F
xmqqqqqqqqqqqqqqqqqqqqqqqqjxx i  x gcc-fortran-32bit        xThe system GNU F
mqqqqqqqqqqqqqqqqqqqqqqqqjmtqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
44 packages found      Package: gcc-32bit                [Actions↓]
lSearch in qqqqqqqqqqqqqqqkllqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqk
x[x] Name of the Package qx gcc-32bit - The system GNU C Compiler q
x[x] Summary           xx
x[ ] Keywords          xxVersion: 7-3.3.22 Installed: 7-3.3.22 x
mtqqqqqqqqqqqqqqqqqqqqqqqqjmqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj
[Help↓]                [Cancel] [Accept]

F1 Help  F9 Cancel  F10 Accept
```

Una vez ingresado colocar el la ventana de “Search Phrase”: **net-tools**, una vez reflejado en el cuadro de la derecha se selecciona el paquete **net-tools-deprecated**, presionamos enter y luego F10.



Validamos la instalación del paquete utilizando el comando **ifconfig**



BETA INNOVATION GROUP USA SRL
San José, Costa Rica
Mata Redonda, Sabana Oeste
3-102-742818

```
root # ifconfig
```

Luego en la misma terminal proceder a correr el siguiente comando para habilitar la carga de librerías en 32 bits:

```
root # zypper in -t pattern 32bit
```

RECURSOS DE BETA TECH

Allen Alfonso Hernández Fuentes

Consultor

ahernandez@betasolutions.tech

Ing. Josué R. Quirós Mora

Gerente PMO

jquiros@betasolutions.tech